

Betagard Miniature Circuit Breakers 5SL7, with C characteristics



- Standards: IS/IEC 60898-1:2015
- Voltage: Un 240/415V, 50...60Hz
- Breaking capacity: 15kA¹⁾ as per IS/IEC 60898-1
- With ISI marking: CM/L No. 2255548

	Rated Current I_n (A)	MW [#]	Reference No	Unit MRP* ₹	Std. Pkg.** (Nos.)
	0.5	1	5SL71057RC	925.-	1/12
	1		5SL71017RC	925.-	1/12
	2		5SL71027RC	910.-	1/12
	4		5SL71047RC	910.-	1/12
	6		5SL71067RC	780.-	1/12
	10		5SL71107RC	780.-	1/12
	16		5SL71167RC	780.-	1/12
	20		5SL71207RC	780.-	1/12
	25		5SL71257RC	780.-	1/12
	32		5SL71327RC	780.-	1/12
	40		5SL71407RC	1230.-	1/12
	50		5SL71507RC	1240.-	1/12
	63		5SL71637RC	1240.-	1/12
	0.5	2	5SL72057RC	2630.-	1/6
	1		5SL72017RC	2630.-	1/6
	2		5SL72027RC	2575.-	1/6
	4		5SL72047RC	2575.-	1/6
	6		5SL72067RC	1875.-	1/6
	10		5SL72107RC	1875.-	1/6
	16		5SL72167RC	1875.-	1/6
	20		5SL72207RC	1875.-	1/6
	25		5SL72257RC	1875.-	1/6
	32		5SL72327RC	1875.-	1/6
	40		5SL72407RC	2825.-	1/6
	50		5SL72507RC	2825.-	1/6
	63		5SL72637RC	2825.-	1/6
	0.5	3	5SL73057RC	4025.-	1/4
	1		5SL73017RC	4025.-	1/4
	2		5SL73027RC	3955.-	1/4
	4		5SL73047RC	3955.-	1/4
	6		5SL73067RC	2985.-	1/4
	10		5SL73107RC	2985.-	1/4
	16		5SL73167RC	2985.-	1/4
	20		5SL73207RC	2985.-	1/4
	25		5SL73257RC	2985.-	1/4
	32		5SL73327RC	2985.-	1/4
	40		5SL73407RC	4450.-	1/4
	50		5SL73507RC	4450.-	1/4
	63		5SL73637RC	4450.-	1/4
	0.5	4	5SL74057RC	5075.-	1/3
	1		5SL74017RC	5075.-	1/3
	2		5SL74027RC	4985.-	1/3
	4		5SL74047RC	4985.-	1/3
	6		5SL74067RC	3990.-	1/3
	10		5SL74107RC	3990.-	1/3
	16		5SL74167RC	3990.-	1/3
	20		5SL74207RC	3990.-	1/3
	25		5SL74257RC	3990.-	1/3
	32		5SL74327RC	3990.-	1/3
	40		5SL74407RC	5595.-	1/3
	50		5SL74507RC	5595.-	1/3
	63		5SL74637RC	5595.-	1/3

Note:

* MRP - Maximum Retail Price # 1MW (Module Width) = 18mm

** Purchase MOQ for our authorized dealers is in multiples of standard packing, contact Siemens Sales Office for further details

¹⁾ Breaking capacity 63A - 10kA