

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 1_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 15

Section 1 : MCQ

1. What is the output of the below expression?

```
print(3*1**3)
```

Answer

3

Status : Correct

Marks : 1/1

2. What is the value of the following expression?

```
float(22//3+3/3)
```

Answer

8.0

Status : Correct

Marks : 1/1

3. What will the following code output?

```
z = 3 + 4j  
print(abs(z))
```

Answer

5.0

Status : Correct

Marks : 1/1

4. What will be the output of the following code?

```
X = 2+9*((3*12)-8)/10  
print(X)
```

Answer

27.2

Status : Correct

Marks : 1/1

5. Which of these is not a core data type?

Answer

Class

Status : Correct

Marks : 1/1

6. Which of the following is an example of the type casting?

Answer

All of the above

Status : Correct

Marks : 1/1

7. Which of the following can convert the string to a float number?

Answer

float(str)

Status : Correct

Marks : 1/1

8. The value of the expressions $4/(3*(2-1))$ and $4/3*(2-1)$ is the same. True or False?

Answer

True

Status : Correct

Marks : 1/1

9. Which of the following operators has its associativity from right to left?

Answer

**

Status : Correct

Marks : 1/1

10. What is used to concatenate two strings in Python?

Answer

+ operator

Status : Correct

Marks : 1/1

11. Evaluate the expression given below if $A = 16$ and $B = 15$

$A \% B // A$

Answer

0

Status : Correct

Marks : 1/1

12. Which of the following expressions results in an error?

Answer

```
int('10.8')&nbsp;
```

Status : Correct

Marks : 1/1

13. What will be the output of the following code?

```
x = int(34.56 - 2 * 2)
print(x)
```

Answer

30

Status : Correct

Marks : 1/1

14. What is the output of the following number conversion?

```
z = complex(1.25)
print(z)
```

Answer

(1.25+0j)

Status : Correct

Marks : 1/1

15. What is the value of x in the following program?

```
x = int(43.55+2/2)
print(x)
```

Answer

44

Status : Correct

Marks : 1/1

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 1_COD

Attempt : 1
Total Mark : 5
Marks Obtained : 5

Section 1 : Coding

1. Problem Statement

A science experiment produces a decimal value as the result. However, the scientist needs to convert this value into an integer so that it can be used in further calculations.

Write a Python program that takes a floating-point number as input and converts it into an integer.

Input Format

The input consists of a floating point number, F.

Output Format

The output prints "The integer value of F is: {result}", followed by the integer number equivalent to the floating point number.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 10.36

Output: The integer value of 10.36 is: 10

Answer

```
F=float(input())  
print("The integer value of ",F,"is:",int(F))
```

Status : Correct

Marks : 1/1

2. Problem Statement

In a family, two children receive allowances based on the gardening tasks they complete. The older child receives an allowance rate of Rs.5 for each task, with a base allowance of Rs.50. The younger child receives an allowance rate of Rs.3 for each task, with a base allowance of Rs.30.

Your task is to calculate and display the allowances for the older and younger children based on the number of gardening tasks they complete, along with the total allowance for both children combined.

Input Format

The first line of input consists of an integer n , representing the number of chores completed by the older child.

The second line consists of an integer m , representing the number of chores completed by the youngest child.

Output Format

The first line of output displays "Older child allowance: Rs." followed by an integer representing the allowance calculated for the older sibling.

The second line displays "Younger child allowance: Rs." followed by an integer

representing the allowance calculated for the youngest sibling.

The third line displays "Total allowance: Rs." followed by an integer representing the sum of both siblings' allowances.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 10

5

Output: Older child allowance: Rs.100

Younger child allowance: Rs.45

Total allowance: Rs.145

Answer

You are using Python

```
n=int(input())
```

```
m=int(input())
```

```
older_base=50
```

```
older_rate=5
```

```
younger_base=30
```

```
younger_rate=3
```

```
older_allowance=older_base+(n*older_rate)
```

```
younger_allowance=younger_base+(m*younger_rate)
```

```
total_allowance=older_allowance+younger_allowance
```

```
print(f"Older child allowance:Rs.{older_allowance}")
```

```
print(f"Younger child allowance:Rs.{younger_allowance}")
```

```
print(f"Total allowance:Rs.{total_allowance}")
```

Status : Correct

Marks : 1/1

3. Problem Statement

Bob, the owner of a popular bakery, wants to create a special offer code for his customers. To generate the code, he plans to combine the day of the month with the number of items left in stock.

Help Bob to encode these two values into a unique offer code.

Note: Use the bitwise operator to calculate the offer code.

Example

Input:

15

9

Output:

Offer code: 6

Explanation:

Given the day of the month 15th day (binary 1111) and there are 9 items left (binary 1001), the offer code is calculated as 0110 which is 6.

Input Format

The first line of input consists of an integer D, representing the day of the month.

The second line consists of an integer S, representing the number of items left in stock.

Output Format

The output displays "Offer code: " followed by an integer representing the encoded offer code.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 15

9

Output: Offer code: 6

Answer


```
# You are using Python
d=int(input())
s=int(input())
offer_code=d^s
print(f"offer code:{offer_code}")
```

Status : Correct

Marks : 1/1

4. Problem Statement

A company has hired two employees, Alice and Bob. The company wants to swap the salaries of both employees. Alice's salary is an integer value and Bob's salary is a floating-point value.

Write a program to swap their salaries and print the new salary of each employee.

Input Format

The first line of input consists of an integer N, representing Alice's salary.

The second line consists of a float value F, representing Bob's salary.

Output Format

The first line of output displays "Initial salaries:"

The second line displays "Alice's salary = N", where N is Alice's salary.

The third line of output displays "Bob's salary = F", where F is Bob's salary.

After a new line space, the following line displays "New salaries after swapping:"

The next line displays "Alice's salary = X", where X is the swapped salary.

The last line displays "Bob's salary = Y", where Y is the swapped salary.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 10000

15400.55

Output: Initial salaries:

Alice's salary = 10000

Bob's salary = 15400.55

New salaries after swapping:

Alice's salary = 15400.55

Bob's salary = 10000

Answer

You are using Python

```
print("Initial salaries:")
```

```
N=int(input())
```

```
F=float(input())
```

```
print("Alice's salary = ",N)
```

```
print("Bob's salary = ",F)
```

```
print("New salaries after swapping:")
```

```
X=F
```

```
Y=N
```

```
print("Alice's salary = ",X)
```

```
print("Bob's salary = ",Y)
```

Status : Correct

Marks : 1/1

5. Problem Statement

Quentin, a mathematics enthusiast, is exploring the properties of numbers. He believes that for any set of four consecutive integers, calculating the average of their fourth powers and then subtracting the product of the first and last numbers yields a constant value.

To validate his hypothesis, check if the result is indeed constant and display.

Example:

Input:

5

Output:

Constant value: 2064.5

Explanation:

Find the Average:

Average: $(625 + 1296 + 2401 + 4096)/4 = 2104.5$

Now, we calculate the product of a and (a + 3):

Product = $5 \times (5 + 3) = 5 \times 8 = 40$

Final result: $2104.5 - 40 = 2064.5$

Input Format

The input consists of an integer a, representing the first of four consecutive integers.

Output Format

The output displays "Constant value: " followed by the computed result based on Quentin's formula.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

Output: Constant value: 2064.5

Answer

```
# You are using Python
n=int(input())
```

```
a=n  
b=n+1  
c=n+2  
d=n+3
```

```
a4=a**4  
b4=b**4  
c4=c**4  
d4=d**4
```

```
average_value=(a4+b4+c4+d4)/4  
product_value=a*d  
constant_value=average_value-product_value  
print(f"Constant value:{constant_value}")
```

Status : Correct

Marks : 1/1

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 1_PAH

Attempt : 1
Total Mark : 6
Marks Obtained : 6

Section 1 : Coding

1. Problem Statement

Oliver is planning a movie night with his friends and wants to download a high-definition movie. He knows the file size of the movie in megabytes (MB) and his internet speed in megabits per second (Mbps). To ensure the movie is ready in time, Oliver needs to calculate the download time.

Your task is to write a program that calculates the download time and displays it in hours, minutes, and seconds.

Example

Input:

MB = 800

mbps = 40

Output:

Download Time: 0 hours, 2 minutes, and 40 seconds

Explanation:

Convert the file size to bits ($800 \text{ MB} * 8 \text{ bits/byte} = 6400 \text{ megabits}$) and divide it by the download speed ($6400 \text{ Mbps} / 40 \text{ Mbps} = 160 \text{ seconds}$). Now, convert the download time in seconds to hours, minutes, and seconds: 160 seconds is equal to 2 minutes and 40 seconds. So, the download time is 0 hours, 2 minutes and 40 seconds.

Input Format

The first line of input consists of an integer N, representing the file size in megabytes (MB).

The second line consists of an integer S, representing the network speed in megabits per second (mbps).

Output Format

The output prints "Download Time: X hours, Y minutes, and Z seconds", where X, Y, and Z are integers representing the hours, minutes, and seconds respectively.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 180

3

Output: Download Time: 0 hours, 8 minutes, and 0 seconds

Answer

You are using Python

N = int(input())

S = int(input())

total_bits = N * 8 # Convert MB to megabits (since 1 MB = 8 Mb)

total_seconds = total_bits / S

```
# Round to nearest whole second, since time can be a float
total_seconds = int(round(total_seconds))
```

```
hours = total_seconds // 3600
remaining = total_seconds % 3600
minutes = remaining // 60
seconds = remaining % 60
```

```
print(f"Download Time: {hours} hours, {minutes} minutes, and {seconds}
seconds")
```

Status : Correct

Marks : 1/1

2. Problem Statement

Shawn, a passionate baker, is planning to bake cookies for a large party. His original recipe makes 15 cookies, with the following ingredient quantities: 2.5 cups of flour, 1 cup of sugar, and 0.5 cups of butter.

Write a program to calculate the amounts of flour, sugar, and butter needed for a different number of cookies. Provide the ingredient quantities for a specified number of cookies, maintaining the original proportions of the recipe.

Input Format

The input consists of an integer n , representing the number of cookies.

Output Format

The first line prints "Flour: X cups" where X represents the amount of flour required for n cookies, as a double value rounded to two decimal places.

The second line prints "Sugar: Y cups" where Y represents the amount of Sugar required for n , as a double value rounded to two decimal places.

The third line prints "Butter: Z cups" where Z represents the amount of flour required for n , as a double value rounded to two decimal places.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 15

Output: Flour: 2.50 cups

Sugar: 1.00 cups

Butter: 0.50 cups

Answer

You are using Python

```
n = int(input())
```

```
flour = 2.5 * n / 15
```

```
sugar = 1.0 * n / 15
```

```
butter = 0.5 * n / 15
```

```
print(f"Flour: {flour:.2f} cups")
```

```
print(f"Sugar: {sugar:.2f} cups")
```

```
print(f"Butter: {butter:.2f} cups")
```

Status : Correct

Marks : 1/1

3. Problem Statement

Mandy is debating with her friend Rachel about an interesting mathematical claim. Rachel asserts that for any positive integer n , the ratio of the sum of n and its triple to the integer itself is always 4. Mandy, intrigued by this statement, decides to validate it using logical operators and basic arithmetic.

She wants to confirm if the statement holds true for any positive integer n .

Input Format

The input consists of a positive integer n , representing the integer to be tested.

Output Format

The first line of output displays "Sum:" followed by an integer representing the calculated sum.

The second line displays "Rachel's statement is: " followed by a Boolean value indicating whether Rachel's statement is correct.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 12

Output: Sum: 48

Rachel's statement is: True

Answer

```
# You are using Python
```

```
n = int(input())
```

```
sum_n = n + 3 * n # or sum_n = 4 * n
```

```
ratio = sum_n / n
```

```
print(f"Sum: {sum_n}")
```

```
print(f"Rachel's statement is: {ratio == 4}")
```

Status : Correct

Marks : 1/1

4. Problem Statement

Ella, an avid TV show enthusiast, is planning a binge-watching marathon for a new series. She has a specific routine: after watching a set number of episodes, she takes a short break.

She is provided with the following information:

Each episode of the series has a fixed duration of 45 minutes. After a certain number of episodes, there is a break of 15 minutes.

Ella wants to know the total time she will need to watch the entire series, including the breaks. Your task is to help Ella by calculating the total viewing time.

Input Format

The first line of input consists of an integer E, representing the total number of episodes in the series.

The second line consists of an integer B, representing the number of episodes watched before taking a break.

Output Format

The output prints an integer representing the total viewing time required to watch the entire series, including the breaks.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

2

Output: 255 minutes

Answer

You are using Python

```
E = int(input())
```

```
B = int(input())
```

```
episode_time = E * 45
```

```
number_of_breaks = (E - 1) // B
```

```
break_time = number_of_breaks * 15
```

```
total_time = episode_time + break_time
```

```
print(total_time, "minutes")
```

Status : Correct

Marks : 1/1

5. Problem Statement

A smart home system tracks the temperature and humidity of each room. Create a program that takes the room name (string), temperature (float), and humidity (float).

Display the room's climate details.

Input Format

The first line of input consists of a string, representing the room name.

The second line consists of a float value, representing the temperature.

The third line consists of a float value, representing the humidity.

Output Format

The first line of output prints "Room: " followed by the room name (string).

The second line prints "Temperature: " followed by the temperature (float) formatted to two decimal places.

The third line prints "Humidity: " followed by the humidity (float) formatted to two decimal places and a percentage sign (%).

Refer to the sample output for formatting specifications.

Sample Test Case

Input: Living Room

23.45

45.78

Output: Room: Living Room

Temperature: 23.45

Humidity: 45.78%

Answer

```
# You are using Python
```

```
room = input().strip()
```

```
temperature = input().strip()
```

```
humidity = float(input().strip())
```

```
print(f"Room: {room}")
```

```
print(f"Temperature: {float(temperature):.2f}" if '.' in temperature else
```

```
f"Temperature: {temperature}.00")
```

```
print(f"Humidity: {humidity:.2f}%")
```

Status : Correct

Marks : 1/1

6. Problem Statement

Liam works at a car dealership and is responsible for recording the details of cars that arrive at the showroom. To make his job easier, he wants a program that can take the car's make, model, and price, and display the information in a formatted summary.

Assist him in the program.

Input Format

The first line of input contains a string, representing the car make.

The second line contains a string, representing the car model.

The third line contains a float value, representing the car price.

Output Format

The first line of output prints "Car Make: ", followed by the car make.

The second line prints "Car Model: ", followed by the car model.

The third line prints "Price: ", followed by the car price, formatted to two decimal places.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: Toyota
Camry
23450.75

Output: Car Make: Toyota
Car Model: Camry

Price: Rs.23450.75

Answer

```
# You are using Python
make = input().strip()
model = input().strip()
price = float(input().strip())

print(f"Car Make: {make}")
print(f"Car Model: {model}")
print(f"Price: Rs.{price:.2f}")
```

Status : Correct

Marks : 1/1

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 1_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Mandy is working on a mathematical research project involving complex numbers. For her calculations, she often needs to swap the real and imaginary parts of two complex numbers.

Mandy needs a Python program that takes two complex numbers as input and swaps their real and imaginary values.

Input Format

The first line of input consists of a complex number in the format $a+bj$, representing the first complex number.

The second line consists of a complex number in the format $a+bj$, representing the second complex number.

Output Format

The first line of output displays "New first complex number: " followed by the swapped complex number.

The second line of output displays "New second complex number: " followed by the swapped complex number.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 10+8j

7-9j

Output: New first complex number: (8+10j)

New second complex number: (-9+7j)

Answer

```
# You are using Python
```

```
c1 = eval(input())
```

```
c2 = eval(input())
```

```
# Swap real and imaginary parts
```

```
new_c1 = complex(c1.imag, c1.real)
```

```
new_c2 = complex(c2.imag, c2.real)
```

```
print(f"New first complex number: {new_c1}")
```

```
print(f"New second complex number: {new_c2}")
```

Status : Correct

Marks : 10/10

2. Problem Statement

Alex is an air traffic controller who needs to record and manage flight delays efficiently. Given a flight number, the delay in minutes (as a string), and the coordinates of the flight's current position (as a complex number),

Help Alex convert and store this information in a structured format.

Input Format

The first line of input consists of an integer N, representing the flight number.

The second line consists of a string representing the delay in minutes.

The third line consists of two floats separated by a space, representing the real and imaginary parts of the complex number for the flight's position.

Output Format

The first line of output displays the complex number.

The second line displays a string with the flight number, delay, and the real and imaginary parts of the complex number, separated by commas.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 12345

30.5

12.3 45.6

Output: (12.3+45.6j)

12345, 30.5, 12.3, 45.6

Answer

```
# You are using Python
# Read inputs
flight_num = input().strip()
delay = input().strip()
real, imag = map(float, input().split())

# Construct complex number
pos = complex(real, imag)

# Print complex number
print(pos)

# Print formatted string
print(f"{flight_num}, {delay}, {real}, {imag}")
```


Status : Correct

Marks : 10/10

3. Problem Statement

John is developing a financial application to help users manage their investment portfolios. As part of the application, he needs to write a program that receives the portfolio's main value and the values of two specific investments as inputs. The program should then display these values in reverse order for clear visualization.

Help John achieve this functionality by writing the required program.

Input Format

The first line of input consists of a float, representing the first investment value.

The second line of input consists of a float, representing the second investment value.

The third line of input consists of an integer, representing the portfolio ID.

Output Format

The first line of output prints "The values in the reverse order:".

The second line prints the integer, representing the portfolio ID.

The third line prints the second float, representing the second investment value.

The fourth line prints the first float, representing the first investment value.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 35.29

9374.11

48

Output: The values in the reverse order:

48
9374.11
35.29

Answer

```
# You are using Python
first_investment = float(input())
second_investment = float(input())
portfolio_id = input() # Kept as string to preserve formatting; could be int but
output matches string
```

```
print("The values in the reverse order:")
print(portfolio_id)
print(second_investment)
print(first_investment)
```

Status : Correct

Marks : 10/10

4. Problem Statement

Nina is working on a project involving multiple sensors. Each sensor provides a data point that needs to be processed to compute an aggregated value.

Given data points from three sensors, write a program to calculate the aggregated value using specific bitwise operations and arithmetic manipulations. The final result should be the aggregated value modulo 1000.

Example:

Input:

```
1 //sensor 1 data
2 //sensor 2 data
3 //sensor 3 data
```

Output

9

Explanation

Calculate the bitwise AND of sensor 1 data and sensor 2 data: 0

Calculate the XOR of the result from step 1 and sensor 3 data: 3

Multiply the result from step 2 by 3: 9

Compute the final aggregated value by taking the result from step 3 modulo 1000: 9

So, the aggregated value is 9.

Input Format

The first line of input consists of an integer S1, representing sensor1 data.

The second line of input consists of an integer S2, representing sensor2 data.

The third line of input consists of an integer S3, representing sensor3 data.

Output Format

The output displays an integer representing the aggregated value.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1

2

3

Output: 9

Answer

You are using Python

```
s1 = int(input())
```

```
s2 = int(input())
```

```
s3 = int(input())
```

```
result = ((s1 & s2) ^ s3) * 3
```

```
result = result % 1000
```

```
print(result)
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 2_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 10

Section 1 : MCQ

1. When does the else statement written after the loop execute?

Answer

When loop condition becomes false

Status : Correct

Marks : 1/1

2. What will be the output of the following Python code?

```
i = 1
while True:
    if i%3 == 0:
        break
    print(i)
    i += 1
```

Answer

12

Status : Correct

Marks : 1/1

3. What is the purpose of the pass statement in Python?

Answer

To do nothing and act as a placeholder.

Status : Correct

Marks : 1/1

4. What will be the output of the following Python code?

```
i = 1
while True:
    if i % 2 == 0:
        i += 1
        continue
    if i > 10:
        break
    print(i, end = " ")
    i += 2
```

Answer

1 3 5 7 9

Status : Correct

Marks : 1/1

5. What will be the output for the following code snippet?

```
i = 0
for i in range(10):
    break
print(i)
```

Answer

0

Status : Correct

Marks : 1/1

6. What will be the output of the following code snippet?

```
balloon_inflated = False
while not balloon_inflated:
    if not balloon_inflated:
        balloon_inflated = True
        print("inflate-", end="")
    print("done")
```

Answer

inflate-done

Status : Correct

Marks : 1/1

7. What is the output of the following code?

```
i = 5
while True:
    if i%009 == 0:
        break
    print(i)
    i += 1
```

Answer

5 6 7 8 9 10 11 12 13 14 15

Status : Wrong

Marks : 0/1

8. What will be the output of the following Python code?

```
i = 1
while True:
    if i % 2 == 0:
        i += 1
        continue
    if i > 10:
```

```
break
print(i)
i += 2
```

Answer

1 3 5 7 9

Status : Correct

Marks : 1/1

9. What will be the output of the following code?

```
i = 1
while True:
    if i%007 == 0:
        break
    print(i)
    i += 1
```

Answer

1 2 3 4 5 6 7

Status : Wrong

Marks : 0/1

10. What is the output of the following code?

```
for i in range(5):
    if i == 5:
        break
    else:
        print(i)
else:
    print("Here")
```

Answer

0 1 2 3 4 Here

Status : Correct

Marks : 1/1

11. What will be the output of the following code snippet?


```
i = 0
while i < 5:
    if i % 2 == 0:
        i += 1
        continue
    print(i, end=" ")
    i += 1
```

Answer

1 3

Status : Correct

Marks : 1/1

12. What is the output of the following?

```
i = 2
while True:
    if i%3 == 0:
        break
    print(i)
    i += 2
```

Answer

2 4

Status : Correct

Marks : 1/1

13. What is the output of the following?

```
for i in range(10):
    if i == 5:
        break
    else:
        print(i, end=' ')
else:
    print("Here")
```

Answer

0 1 2 3 4 Here

Status : Wrong

Marks : 0/1

14. How many times will the inner for loop be executed in the below code?

```
i=0
while(True):
    for j in range(4,0,-2):
        print(i*j)
        print("")
        i=i+1
    if(i%2==0):
        break
```

Answer

2

Status : Wrong

Marks : 0/1

15. What will be the output of the following Python code?

```
i = 5
while True:
    if i%0011 == 0:
        break
    print(i)
    i += 1
```

Answer

5 6 7 8 9 10

Status : Wrong

Marks : 0/1

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 2_COD_Updated

Attempt : 1
Total Mark : 50
Marks Obtained : 50

Section 1 : Coding

1. Problem Statement

You work as an instructor at a math enrichment program, and your goal is to develop a program that showcases the concept of using control statements to manipulate loops. Your task is to create a program that takes an integer 'n' as input and prints the squares of even numbers from 1 to 'n', while skipping odd numbers.

Input Format

The input consists of a single integer, which represents the upper limit of the range.

Output Format

The output displays the square of even numbers from 1 to 'n' separated by lines.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 10

Output: 4

16

36

64

100

Answer

```
# You are using Python
def squares_of_evens(n):
    for i in range(1,n+1):
        if i%2==0:
            print(i*i)
n=int(input())
squares_of_evens(n)
```

Status : Correct

Marks : 10/10

2. Problem Statement

John, a software developer, is analyzing a sequence of numbers within a given range to calculate their digit sum. However, to simplify his task, he excludes all numbers that are palindromes (numbers that read the same backward as forward).

Help John find the total sum of the digits of non-palindromic numbers in the range [start, end] (both inclusive).

Example:

Input:

10

20

Output:

55

Explanation:

Range [10, 20]: Non-palindromic numbers are 10, 12, 13, 14, 15, 16, 17, 18, 19 and 20.

Digit sums: $1+0 + 1+2 + 1+3 + 1+4 + 1+5 + 1+6 + 1+7 + 1+8 + 1+9 + 2+0 = 55$.

Output: 55

Input Format

The first line of input consists of an integer, representing the starting number of the range.

The second line of input consists of an integer, representing the ending number of the range.

Output Format

The output prints a single integer, representing the total sum of the digits of all non-palindromic numbers in the range.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 10

20

Output: 55

Answer

```
# You are using Python
def is_palindrome(n):
    return str(n)==str(n)[::-1]
def digit_sum(n):
    return sum(int(digit) for digit in str(n))
def total_digit_sum(start,end):
```

```
    return sum(digit_sum(n) for n in range(start,end+1) if not is_palindrome(n))
start=int(input())
end=int(input())
print(total_digit_sum(start,end))
```

Status : Correct

Marks : 10/10

3. Problem Statement

Emma, a mathematics enthusiast, is exploring a range of numbers and wants to count how many of them are not Fibonacci numbers.

Help Emma determine the count of non-Fibonacci numbers within the given range [start, end] using the continue statement.

Input Format

The first line of input consists of an integer, representing the starting number of the range.

The second line consists of an integer, representing the ending number of the range.

Output Format

The output prints a single integer, representing the count of numbers in the range that are not Fibonacci numbers.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1
10

Output: 5

Answer

```
# You are using Python
def is_fibonacci(n):
    if n<=1:
```

```
    return True
    a,b=0,1
    while b<n:
        a,b=b,a+b
    return b==n
def count_non_fibonacci(start,end):
    count=0
    for num in range(start,end+1):
        if not is_fibonacci(num):
            count+=1
    return count
start=int(input())
end=int(input())
result=count_non_fibonacci(start,end)
print(result)
```

Status : Correct

Marks : 10/10

4. Problem Statement

As a junior developer working on a text analysis project, your task is to create a program that displays the consonants in a sentence provided by the user, separated by spaces.

You need to implement a program that takes a sentence as input and prints the consonants while skipping vowels and non-alphabetic characters using only control statements.

Input Format

The input consists of a string representing the sentence.

Output Format

The output displays space-separated consonants present in the sentence.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: Hello World!

Output: H l l W r l d

Answer

```
# You are using Python
def extract_consonants(sentence):
    vowels="aeiouAEIOU"
    result=[]
    for char in sentence:
        if char.isalpha() and char not in vowels:
            result.append(char)
    print(" ".join(result))
sentence=input()
extract_consonants(sentence)
```

Status : Correct

Marks : 10/10

5. Problem Statement

Ethan, a curious mathematician, is fascinated by perfect numbers. A perfect number is a number that equals the sum of its proper divisors (excluding itself). Ethan wants to identify all perfect numbers within a given range.

Help him write a program to list these numbers.

Input Format

The first line of input consists of an integer start, representing the starting number of the range.

The second line consists of an integer end, representing the ending number of the range.

Output Format

The output prints all perfect numbers in the range, separated by a space.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

100

Output: 6 28

Answer

You are using Python

```
def is_perfect(n):
```

```
    return n>1 and sum(i for i in range(1,n) if n%i==0)==n
```

```
def find_perfect_numbers(start,end):
```

```
    perfect_numbers=[n for n in range(start,end+1) if is_perfect(n)]
```

```
    print(" ".join(map(str,perfect_numbers)))
```

```
start=int(input())
```

```
end=int(input())
```

```
find_perfect_numbers(start,end)
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 2_PAH_Updated

Attempt : 1
Total Mark : 60
Marks Obtained : 60

Section 1 : Coding

1. Problem Statement

Rajesh wants to design a program that simulates a real-time scenario based on a mathematical concept known as the Collatz Conjecture. This concept involves the repeated application of rules to a given starting number until the number becomes 1. The rules are as follows:

If the number is even, divide it by 2. If the number is odd, multiply it by 3 and add 1.

Your task is to write a program that takes a positive integer as input, applies the Collatz Conjecture rules to it, counts the number of steps taken to reach 1, and provides an output accordingly. If the process exceeds 100 steps, the program should print a message indicating so and use break to exit.

Input Format

The input consists of a single integer, n.

Output Format

The output displays the total number of steps taken to reach 1 if it's under 100.

If it's more than 100, it displays "Exceeded 100 steps. Exiting...".

Refer to sample output for the formatting specifications.

Sample Test Case

Input: 6

Output: Steps taken to reach 1: 8

Answer

You are using Python

```
def collatz_steps(n):
```

```
    steps=0
```

```
    while n!=1 and steps<100:
```

```
        if n%2==0:
```

```
            n//=2
```

```
        else:
```

```
            n=3*n+1
```

```
        steps+=1
```

```
    if n==1:
```

```
        print(f"Steps taken to reach 1: {steps}")
```

```
    else:
```

```
        print("Exceeded 100 steps. Exiting...")
```

```
n=int(input())
```

```
collatz_steps(n)
```

Status : Correct

Marks : 10/10

2. Problem Statement

Kamali recently received her electricity bill and wants to calculate the amount she needs to pay based on her usage. The electricity company

charges different rates based on the number of units consumed.

For the first 100 units, there is no charge. For units consumed beyond 100 and up to 200, there is a charge of Rs. 5 per unit. For units consumed beyond 200, there is a charge of Rs. 10 per unit.

Write a program to help Kamali calculate the amount she needs to pay for her electricity bill based on the units consumed.

Input Format

The input consists of an integer, representing the number of units.

Output Format

The output prints the total amount of the electricity bill, an integer indicating the amount Kamali needs to pay in the format "Rs. amount".

Refer to the sample output for the exact format.

Sample Test Case

Input: 350

Output: Rs. 2000

Answer

```
# You are using Python
units=int(input())
if units<=100:
    bill=0
elif units<=200:
    bill=(units-100)*5
else:
    bill=(100*5)+(units-200)*10
print(f"Rs.{bill: d}")
```

Status : Correct

Marks : 10/10

3. Problem Statement

Sophia, a primary school teacher, wants to calculate the sum of numbers within a given range, excluding those that are multiples of 3.

Write a program to help Sophia compute the sum of all numbers between start and end (inclusive) that are not divisible by 3 using the continue statement.

Input Format

The first line of input consists of an integer, representing the starting number of the range.

The second line of input consists of an integer, representing the ending number of the range.

Output Format

The output prints a single integer, representing the sum of numbers in the range that are not multiples of 3.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

10

Output: 37

Answer

```
# You are using Python
start=int(input())
end=int(input())
total=0
for num in range(start,end+1):
    if num%3==0:
        continue
    total+=num
print(total)
```

Status : Correct

Marks : 10/10

4. Problem Statement

Aarav is fascinated by the concept of summing numbers separately based on their properties. He plans to write a program that calculates the sum of even numbers and odd numbers separately from 1 to a given positive integer.

Aarav wants to input an integer value to represent the upper limit of the range. Help Aarav by developing a program that computes and displays the sum of even and odd numbers separately.

Input Format

The input consists of a single integer N, where N is the upper limit of the range.

Output Format

The output consists of two lines:

- The first line displays the sum of even numbers from 1 to N.
- The second line displays the sum of odd numbers from 1 to N.

Refer to the sample output for the exact format.

Sample Test Case

Input: 10

Output: Sum of even numbers from 1 to 10 is 30
Sum of odd numbers from 1 to 10 is 25

Answer

```
# You are using Python
n=int(input())
even_sum=sum(i for i in range(2,n+1,2))
odd_sum=sum(i for i in range(1,n+1,2))
print(f"Sum of even numbers from 1 to {n} is{even_sum}")
print(f"Sum of odd numbers from 1 to {n} is{odd_sum}")
```

Status : Correct

Marks : 10/10

5. Problem Statement

Imagine being entrusted with the responsibility of creating a program that simulates a math workshop for students. Your task is to develop an interactive program that not only calculates but also showcases the charm of factorial values. Your program should efficiently compute and present the sum of digits for factorial values of only odd numbers within a designated range. This approach will ingeniously keep even factorials at bay, allowing students to delve into the intriguing world of mathematics with enthusiasm and clarity.

Input Format

The input consists of a single integer, n .

Output Format

The output displays the factorial and sum of digits of the factorial of odd numbers within the given range.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 6

Output: $1! = 1$, sum of digits = 1

$3! = 6$, sum of digits = 6

$5! = 120$, sum of digits = 3

Answer

You are using Python

```
import math
```

```
def factorial_sum_of_digits(n):
```

```
    for i in range(1,n+1,2):
```

```
        fact=math.factorial(i)
```

```
        sum_digits=sum(int(digit) for digit in str(fact))
```

```
        print(f"{i}!={fact}, Sum of digits={sum_digits}")
```

```
n=int(input())
```

```
factorial_sum_of_digits(n)
```

Status : Correct

Marks : 10/10

6. Problem Statement

As a software engineer, your goal is to develop a program that facilitates the identification of leap years in a specified range. Your task is to create a program that takes two integer inputs, representing the start and end years of the range and then prints all the leap years within that range.

Input Format

The first line of the input consists of an integer, which represents the start year.

The second line consists of an integer, which represents the end year.

Output Format

The output displays the leap years within the given range, separated by lines.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 2000

2053

Output: 2000

2004

2008

2012

2016

2020

2024

2028

2032

2036

2040

2044

2048

2052

Answer

You are using Python

```
def is_leap_year(year):  
    if(year%4==0 and year%100!=0) or(year%400==0):  
        return True
```

```
def print_leap_years(start_year,end_year):  
    for year in range(start_year,end_year +1):  
        if is_leap_year(year):  
            print(year)  
start_year=int(input())  
end_year=int(input())  
print_leap_years(start_year,end_year)
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 2_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Rohith is a data analyst who needs to categorize countries based on their population growth rates. Each country is assigned a unique code. Rohith will receive a code and corresponding data based on the code. If the data falls within specific thresholds, he needs to classify the country's priority level.

Your task is to write a program that reads a country code and its associated data, and then determines if the priority is "High" or "Low."

Thresholds: France: Priority is "High" if the percentage < 50, else "Low". Japan: Priority is "High" if life expectancy > 80, else "Low". Brazil: Priority is "High" if the urban population > 80, else "Low".

Input Format

The first line of input consists of an integer, representing the country code (1 for France, 2 for Japan, 3 for Brazil).

If the country code is 1,

- The second line consists of a floating-point value N , representing the percentage of the English-speaking population.

If the country code is 2,

- The second line consists of a floating-point value A , representing the average life expectancy in years.

If the country code is 3,

- The second line consists of a floating-point value P , representing the percentage of the urban population.

Output Format

The first line of output displays "Priority: High" or "Priority: Low" based on the input data.

If the country code is invalid, print "Invalid".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

30.0

Output: Priority: High

Answer

You are using Python

```
a=int(input())
```

```
if a==1:
```

```
    m=float(input())
```

```
    if m<50:
```

```
        print("Priority: High")
```

```
    else:
```

```
print("Priority: Low")
elif a==2:
    n=float(input())
    if n>80:
        print("Priority: High")
    else:
        print("Priority: Low")
elif a==3:
    p=float(input())
    if p>80:
        print("Priority: High")
    else:
        print("Priority: Low")
else:
    print("Invalid")
```

Status : Correct

Marks : 10/10

2. Problem Statement

Taylor is tasked with a mathematical challenge that requires finding the smallest positive number divisible by all integers from 1 to n.

Help Taylor to determine the smallest positive number that is divisible by all integers from 1 to n. Make sure to employ the break statement to ensure efficiency in the program.

Input Format

The input consists of a single integer, n.

Output Format

The output displays the smallest positive number that is divisible by all integers from 1 to n.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 10
Output: 2520

Answer

```
# You are using
import math
n=int(input().strip())
lcm=1
for i in range(1,n+1):
    lcm=(lcm*i) // math.gcd(lcm,i)
print(lcm)
```

Status : Correct

Marks : 10/10

3. Problem Statement

Alex is practicing programming and is curious about prime and non-prime digits. He wants to write a program that calculates the sum of the non-prime digits in a given integer using loops.

Help Alex to complete his task.

Example:

Input:
845

output:
12

Explanation:

Digits: 8 (non-prime), 4 (non-prime), 5 (prime)

The sum of Non-Prime Digits: $8 + 4 = 12$

Output: 12

Input Format

The input consists of a single integer X.

Output Format

The output prints an integer representing the sum of non-prime digits in X.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 845

Output: 12

Answer

```
# You are using Python
n=input()
np={0,1,4,6,8,9}
t=0
for i in n:
    if int(i) in np:
        t+=int(i)
print(t)
```

Status : Correct

Marks : 10/10

4. Problem Statement

John is tasked with configuring the lighting for a high-profile event, where different lighting modes affect the ambiance of the venue. He can choose from three distinct lighting modes, each requiring a specific adjustment to the initial light intensity:

Ambient Lighting (Mode 1): The intensity level is multiplied by 1.5.

Stage Lighting (Mode 2): The intensity level is multiplied by 2.0.

Spotlight (Mode 3): The intensity level is multiplied by 1.8.

In the event that an invalid mode is provided, the program should output an error message indicating the invalid selection.

Your task is to write a program that reads the selected lighting mode and the initial intensity level, applies the appropriate adjustment, and prints the

final intensity.

Input Format

The first line of input is an integer n, representing the lighting mode.

The second line is a floating value m, representing the initial intensity level of the light.

Output Format

The output displays "Intensity: " followed by a float representing the adjusted intensity level, formatted to two decimal places, if the mode is valid.

If the mode is invalid, the output should display "Invalid".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1

10.0

Output: Intensity: 15.00

Answer

You are using Python

```
n=int(input())
```

```
m=float(input())
```

```
if(n==1):
```

```
    a=m*1.5
```

```
    print(f"Intensity: {a:.2f}")
```

```
elif(n==2):
```

```
    b=m*2.0
```

```
    print(f"Intensity: {b:.2f}")
```

```
elif(n==3):
```

```
    c=m*1.8
```

```
    print(f"Intensity: {c:.2f}")
```

```
else:
```

```
    print("Invalid")
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 3_MCQ

Attempt : 1
Total Mark : 25
Marks Obtained : 8

Section 1 : MCQ

1. What is the output of the following Python code?

```
text = "Python"  
result = text.center(10, "*")  
print(result)
```

Answer

"Python"

Status : Wrong

Marks : 0/1

2. What is the output of the following Python code?

```
txt = "My Classroom"  
print(txt.find("o"))
```

```
print(txt.index("o"))
```

Answer

99

Status : Correct

Marks : 1/1

3. What is the output of the following code?

```
my_list = [3, 6, 1, 2, 5, 4]
print(sorted(my_list) == my_list.sort())
```

Answer

False

Status : Correct

Marks : 1/1

4. What does the following code output?

```
lst = [10, 20, 30, 40, 50]
print(lst[-4:-1])
```

Answer

[20, 30, 40]

Status : Correct

Marks : 1/1

5. What is the output of the following Python code?

```
word = "programming"
answer = word.index("gram")
print(answer)
```

Answer

5

Status : Wrong

Marks : 0/1

6. What is the output of the following Python code?

```
a = "Hello"  
b = "World"  
c = a + " " + b  
print(c)
```

Answer

Hello World

Status : Correct

Marks : 1/1

7. Suppose list1 is [2, 33, 222, 14, 25], What is list1[::-1]?

Answer

[25, 14, 222, 33, 2]

Status : Wrong

Marks : 0/1

8. What does negative indexing in Python lists allow you to do?

Answer

Access elements in the list from the end

Status : Correct

Marks : 1/1

9. What will be the output of the following code?

```
my_list = [1, 2, 2, 3]  
print(my_list.count(2))
```

Answer

2

Status : Correct

Marks : 1/1

10. Which of the following is a valid way to use the '%' operator to concatenate strings in Python?

Answer

`"%s %s" % (string1, string2)`

Status : Correct

Marks : 1/1

11. Suppose list1 is [2, 33, 222, 14, 25], What is list1[-1]?

Answer

25

Status : Correct

Marks : 1/1

12. Which method is used to add multiple items to the end of a list?

Answer

-

Status : -

Marks : 0/1

13. What is the result of the slicing operation `lst[-5:-2]` on the list `lst = [1, 2, 3, 4, 5, 6]`?

Answer

-

Status : -

Marks : 0/1

14. What will be the output of the following program?

```
numbers = [1, 2, 3, 4, 5]
```

```
numbers.append(6, 7)
```

```
print(numbers)
```

Answer

-

Status : -

Marks : 0/1

15. What will be the output of the following code?

```
numbers = [1, 2, 3, 4, 5]  
numbers.remove(6)  
print(numbers)
```

Answer

-

Status : -

Marks : 0/1

16. If you have a list `lst = [1, 2, 3, 4, 5, 6]`, what does the slicing operation `lst[-3:]` return?

Answer

-

Status : -

Marks : 0/1

17. What does the `append()` method do in Python?

Answer

-

Status : -

Marks : 0/1

18. What is the output of the following code?

```
my_list = [1, 2, 3]  
my_list *= 2  
print(len(my_list))
```

Answer

-

Status : -

Marks : 0/1

19. What is the output of the following Python code?

```
word = "Python"
result = word[::-1]
print(result)
```

Answer

-

Status : -

Marks : 0/1

20. What is the output of the following Python code?

```
string1 = "Hello"
string2 = "World"
result = string1 + string2
print(result)
```

Answer

-

Status : -

Marks : 0/1

21. What is the output of the following Python code?

```
name = "John"
age = 25
message = "My name is %s and I am %d years old." % (name, age)
print(message)
```

Answer

-

Status : -

Marks : 0/1

22. What is the output of the following Python code?

```
text = " Python "
answer = text.strip()
print(answer)
```

Answer

-

Status : -

Marks : 0/1

23. Suppose list1 is [4, 2, 2, 4, 5, 2, 1, 0], Which of the following is the correct syntax for slicing operation?

Answer

-

Status : -

Marks : 0/1

24. Which method in Python is used to create an empty list?

Answer

-

Status : -

Marks : 0/1

25. What is the output of the following Python code?

```
b = "Projects!"  
print(b[2:5])
```

Answer

-

Status : -

Marks : 0/1

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 3_COD

Attempt : 1
Total Mark : 50
Marks Obtained : 50

Section 1 : Coding

1. Problem Statement

You have a string containing a phone number in the format "(XXX) XXX-XXXX". You need to extract the area code from the phone number and create a new string that contains only the area code.

Write a Python program for the same.

Note

(XXX) - Area code

XXX-XXXX - Phone number

Input Format

The input consists of a string, representing the phone number in the format

"(XXX) XXX-XXXX".

Output Format

The output displays "Area code: " followed by a string representing the area code for the given phone number.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: (123) 456-7890

Output: Area code: 123

Answer

```
# You are using Pyth
p=input()
a=p[1:4]
print("Area code:",a)
```

Status : Correct

Marks : 10/10

2. Problem Statement

Given a list of positive and negative numbers, arrange them such that all negative integers appear before all the positive integers in the array. The order of appearance should be maintained.

Example

Input:

[12, 11, -13, -5, 6, -7, 5, -3, -6]

Output:

List = [-13, -5, -7, -3, -6, 12, 11, 6, 5]

Explanation:

The output is the arranged list where all the negative integers appear before the positive integers while maintaining the original order of appearance.

Input Format

The input consists of a single line containing a list of integers enclosed in square brackets separated by commas.

Output Format

The output displays "List = " followed by an arranged list of integers as required, separated by commas and enclosed in square brackets.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: [12, 11, -13, -5, 6, -7, 5, -3, -6]

Output: List = [-13, -5, -7, -3, -6, 12, 11, 6, 5]

Answer

```
# You are using Python
input_list=eval(input().strip())
n=[]
p=[]
for num in input_list:
    if num<0:
        n.append(num)
    else:
        p.append(num)
result=n+p
print("List=",result)
```

Status : Correct

Marks : 10/10

3. Problem Statement

Dhruv wants to write a program to slice a given string based on user-defined start and end positions.

The program should check whether the provided positions are valid and then return the sliced portion of the string if the positions are within the string's length.

Input Format

The first line consists of the input string as a string.

The second line consists of the start position (0-based index) as an integer.

The third line consists of the end position (0-based index) as an integer.

Output Format

The output displays the following format:

If the start and end positions are valid, print the sliced string.

If the start and end positions are invalid, print "Invalid start and end positions".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: pythonprogramming

0

5

Output: python

Answer

```
# You are using Python
n=input()
s=int(input())
e=int(input())
if 0<=s<=e<len(n):
    print(n[s:e+1])
else:
    print("Invalid start and end positions")
```

Status : Correct

Marks : 10/10

4. Problem Statement

Alex is working on a Python program to manage a list of elements. He needs to append multiple elements to the list and then remove an element from the list at a specified index.

Your task is to create a program that helps Alex manage the list. The program should allow Alex to input a list of elements, append them to the existing list, and then remove an element at a specified index.

Input Format

The first line contains an integer n , representing the number of elements to be appended to the list.

The next n lines contain integers, representing the elements to be appended to the list.

The third line of input consists of an integer M , representing the index of the element to be popped from the list.

Output Format

The first line of output displays the original list.

The second line of output displays the list after popping the element of the index M .

The third line of output displays the popped element.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5

64

98

-1

5

26

3

Output: List after appending elements: [64, 98, -1, 5, 26]
List after popping last element: [64, 98, -1, 26]
Popped element: 5

Answer

```
# You are using Python
n=int(input())
l=[]
for i in range(1,n+1):
    a=int(input())
    l.append(a)
print("List after appending elements:",l)
m=int(input())
b=l.pop(m)
print("List after popping last element:",l)
print("Popped element:",b)
```

Status : Correct

Marks : 10/10

5. Problem Statement

Ram is working on a program to manipulate strings. He wants to create a program that takes two strings as input, reverses the second string, and then concatenates it with the first string.

Ram needs your help to design a program.

Input Format

The input consists of two strings in separate lines.

Output Format

The output displays a single line containing the concatenated string of the first string and the reversed second string.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: hello
word
Output: hellodrow

Answer

```
# You are using Python
a=input()
b=input()
c=b[::-1]
print(a+c)
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 3_PAH

Attempt : 1
Total Mark : 60
Marks Obtained : 57.5

Section 1 : Coding

1. Problem Statement

Accept an unsorted list of length n with both positive and negative integers, including 0. The task is to find the smallest positive number missing from the array. Assume the n value is always greater than zero.

Input Format

The first line consists of n , which means the number of elements in the array.

The second line consists of the values in the list as space-separated integers.

Output Format

The output displays the smallest positive number, which is missing from the array.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 6
-5 2 0 -1 -10 2

Output: 1

Answer

```
# You are using Python
n=int(input())
a=list(map(int,input().split()))
positive_nums=set(x for x in a if x>0)
i=1
while i in positive_nums:
    i+=1
print(i)
```

Status : Correct

Marks : 10/10

2. Problem Statement

Neha is learning string operations in Python and wants to practice using built-in functions. She is given a string A, and her task is to:

Find the length of the string using a built-in function. Copy the content of A into another string B using built-in functionality.

Help Neha implement a program that efficiently performs these operations.

Input Format

The input consists of a single line containing the string A (without spaces).

Output Format

The first line of output prints the length of the given string.

The second line prints the copied string without an extra newline at the end.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: technology-23

Output: Length of the string: 13

Copied string: technology-23

Answer

You are using Python

```
a=input()
```

```
length=len(a)
```

```
b=a
```

```
print("Length of the string:",length)
```

```
print("Copied string:",b,end="")
```

Status : Correct

Marks : 10/10

3. Problem Statement

You are tasked with writing a program that takes n integers as input from the user and stores them in a list. After this, you need to transform the list according to the following rules:

The element at index 0 should be replaced with 0. For elements at even indices (excluding index 0), replace the element with its cube. For elements at odd indices, replace the element with its square.

Additionally, you should sort the list in ascending order before applying these transformations.

Input Format

The first line of input represents the size of the list, N .

The elements of the list are represented by the next N lines.

Output Format

The first line of output displays "Original List: " followed by the original list.

The second line displays "Replaced List: " followed by the replacement list as per the given condition.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5

5

1

2

3

4

Output: Original List: [1, 2, 3, 4, 5]

Replaced List: [0, 4, 27, 16, 125]

Answer

You are using Python

```
n=int(input())
```

```
o=[int(input()) for _ in range(n)]
```

```
o.sort()
```

```
print("Original List:",o)
```

```
replaced_list=[]
```

```
for i in range(n):
```

```
    if i==0:
```

```
        replaced_list.append(0)
```

```
    elif i%2==0:
```

```
        replaced_list.append(o[i]**3)
```

```
    else:
```

```
        replaced_list.append(o[i]**2)
```

```
print("Replaced List:",replaced_list)
```

Status : Correct

Marks : 10/10

4. Problem Statement

Gowri was doing her homework. She needed to write a paragraph about modern history. During that time, she noticed that some words were

repeated repeatedly. She started counting the number of times a particular word was repeated.

Your task is to help Gowri to write a program to get a string from the user. Count the number of times a word is repeated in the string.

Note: Case-sensitive

Input Format

The first line of input consists of a string, str1.

The second line consists of a single word that needs to be counted, str2.

Output Format

The output displays the number of times the given word is in the string.

If the second string str2 is not present in the first string str1, it prints 0.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: I felt happy because I saw the others were happy and because I knew I
should feel happy
happy

Output: 3

Answer

```
# You are using Python
import string
s1=input()
s2=input()
t=str.maketrans("",string.punctuation)
cleaned_s1=s1.translate(t)
words=cleaned_s1.split()
count=words.count(s2)
#count=words.count(s2)
print(count)
```

Status : Partially correct

Marks : 7.5/10

5. Problem Statement

Imagine you are developing a text analysis tool for a cybersecurity company. Your task is to analyze input strings to categorize and count the characters into four categories: uppercase letters, lowercase letters, digits, and special characters. The company needs this tool to process log files and identify potential security threats.

Input Format

The input consists of the log entry provided as a single string.

Output Format

The output consists of four lines:

The first line contains an integer representing the count of uppercase letters in the format "Uppercase letters: {uppercase count}".

The second line contains an integer representing the count of lowercase letters in the format "Lowercase letters: {lowercase count}".

The third line contains an integer representing the count of digits in the format "Digits: {digits count}".

The fourth line contains an integer representing the count of special characters in the format "Special characters: {special characters count}".

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: Hello123

Output: Uppercase letters: 1

Lowercase letters: 4

Digits: 3

Special characters: 0

Answer

You are using Python

```
l=input()
u=0
lo=0
d=0
s=0
for char in l:
    if char.isupper():
        u+=1
    elif char.islower():
        lo+=1
    elif char.isdigit():
        d+=1
    else:
        s+=1
print(f"Uppercase letters: {u}")
print(f"Lowercase letters: {lo}")
print(f"Digits: {d}")
print(f"Special characters: {s}")
```

Status : Correct

Marks : 10/10

6. Problem Statement

Kyara is analyzing a series of measurements taken over time. She needs to identify all the "peaks" in this list of integers.

A peak is defined as an element that is greater than its immediate neighbors. Boundary elements are considered peaks if they are greater than their single neighbor.

Your task is to find and list all such peaks using list comprehension.

Example

Input

1 3 2 4 1 5 7 6 10 2 8

Output

Peaks: [3, 4, 7, 10, 8]

Explanation

3 is a peak because it's greater than 1 and 2.

4 is a peak because it's greater than 2 and 1.

7 is a peak because it's greater than 5 and 6.

10 is a peak because it's greater than 6 and 2.

8 is a peak because it is an boundary element and it is greater than 2.

Input Format

The input consists of several integers separated by spaces, representing the measurements.

Output Format

The output displays "Peaks: " followed by a list of integers, representing the peak elements in the list.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1 3 2 4 1 5 7 6 10 2 8

Output: Peaks: [3, 4, 7, 10, 8]

Answer

You are using Python

```
m=list(map(int,input().split()))
```

```
p=[]
```

```
for i in range(len(m)):
```

```
    if i==0 and m[i]>m[i+1]:
```

```
        p.append(m[i])
```

```
    elif i==len(m)-1 and m[i]>m[i-1]:
```

```
        p.append(m[i])
```

```
    elif 0<i<len(m) -1 and m[i]>m[i-1] and m[i]>m[i+1]:
```

```
p.append(m[i])  
print("Peaks:",p)
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 3_CY

Attempt : 1
Total Mark : 30
Marks Obtained : 25

Section 1 : Coding

1. Problem Statement

Emily is a data analyst working for a company that collects feedback from customers in the form of text messages. As part of her data validation tasks, Emily needs to perform two operations on each message:

Calculate the sum of all the digits mentioned in the message. If the sum of the digits is greater than 9, check whether the sum forms a palindrome number.

Your task is to help Emily automate this process by writing a program that extracts all digits from a given message, calculates their sum, and checks if the sum is a palindrome if it is greater than 9.

Input Format

The input consists of a string *s*, representing the customer message, which may

contain letters, digits, spaces, and other characters.

Output Format

The output prints an integer representing the sum of all digits in the string, followed by a space.

If the sum is greater than 9, print "Palindrome" if the sum is a palindrome, otherwise print "Not palindrome".

If the sum is less than or equal to 9, no palindrome check is required.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 12 books 4 pen

Output: 7

Answer

```
# You are using Pyth
s=input()
t=sum(int (c) for c in s if c.isdigit())
print(t,end=")
if t>9:
    if str(t)==str(t)[::-1]:
        print("Palindrome")
    else:
        print("Not Palindrome")
else:
    print()
```

Status : Correct

Marks : 10/10

2. Problem Statement

Raja needs a program that helps him manage his shopping list efficiently. The program should allow him to perform the following operations:

Add Items: Raja should be able to add multiple items to his shopping list at once. He will input a space-separated list of items, each item being a string.

Remove Item: Raja should be able to remove a specific item from his shopping list. He will input the item he wants to remove, and if it exists in the list, it will be removed. If the item is not found, the program should notify him.

Update List: Raja might realize he forgot to add some items initially. After removing unnecessary items, he should be able to update his list by adding more items. Similar to the initial input, he will provide a space-separated list of new items.

Input Format

The first line consists of the initial list of integers should be entered as space-separated values.

The second line consists of the element to be removed should be entered as a single integer value.

The third line consists of the new elements to be appended should be entered as space-separated values.

Output Format

The output displays the current state of Raja's shopping list after each operation. After adding items, removing items, and updating the list, the program prints the updated shopping list in the following format:

"List1: [element1, element2, ... ,element_n]

List after removal: [element1, element2, ... ,element_n]

Final list: [element1, element2, ... ,element_n]".

If the item is not found in the removing item process, print the message "Element not found in the list".

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1 2 3 4 5

3

6 7 8

Output: List1: [1, 2, 3, 4, 5]

List after removal: [1, 2, 4, 5]

Final list: [1, 2, 4, 5, 6, 7, 8]

Answer

You are using Python

```
i=input()
```

```
ir=int(input())
```

```
new=input()
```

```
shop=[int(item) for item in i.split()]
```

```
print(f"List1: {shop}")
```

```
if ir in shop:
```

```
    shop.remove(ir)
```

```
    print(f"List after removal: {shop}")
```

```
else:
```

```
    print("Element not found in the list")
```

```
    # print(f"List after removal: {shop}")
```

```
new=[int(item) for item in new.split()]
```

```
shop.extend(new)
```

```
print(f"Final list: {shop}")
```

Status : Correct

Marks : 10/10

3. Problem Statement

Write a program to check if a given string is perfect.

A perfect string must satisfy the following conditions:

The string starts with a consonant. The string alternates between consonants and vowels. Each consonant appears exactly once. Vowels can occur consecutively multiple times but should not be followed immediately by a consonant.

If the string satisfies all these conditions, print "True"; otherwise, print "False".

Input Format

The input consists of a string.

Output Format

The output prints "True" if the string is perfect. Otherwise, print "False".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: capacitor

Output: True

Answer

```
# You are using Python
def is_perfect(s):
    vowels='aeiou'
    consonants='bcdfghjklmnpqrstvwxyz'

    if s[0] not in consonants:
        return False

    ex_con=True
    seen_consonants=set()
```

```
for i in range(len(s)):
    if s[i] in consonants:
        if s[i] in seen_consonants:
            return False
        seen_consonants.add(s[i])

    if not ex_con:
        return False
    ex_con=False

    #if i+1<len(s) and s[i+1] not in vowels:
    # return False

elif s[i] in vowels:
    if ex_con:
        #if i+1 < len(s) and s[i+1] in consonants:
        return False
    ex_con=True
return True

s=input().strip()

if is_perfect(s):
    print("True")
else:
    print("False")
```

Status : Partially correct

Marks : 5/10

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 4_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 15

Section 1 : MCQ

1. What is the main advantage of using lambda functions in Python?

Answer

They allow you to write shorter code than regular functions

Status : Correct

Marks : 1/1

2. What will be the output of the following code?

```
num1 = 10  
num2 = -10  
result = abs(num1) + abs(num2)  
print(result)
```

Answer

20

Status : Correct

Marks : 1/1

3. What is the output of the following code?

```
x=12
def f1(a,b=x):
    print(a,b)
x=15
f1(4)
```

Answer

4 12

Status : Correct

Marks : 1/1

4. What will be the output of the following Python code?

```
def maximum(x, y):
    if x > y:
        return x
    elif x == y:
        return 'The numbers are equal'
    else:
        return y

print(maximum(2, 3))
```

Answer

3

Status : Correct

Marks : 1/1

5. What is the output of the following code snippet?

```
def fun(x, y=2, z=3):
    return x + y + z
```

```
result = fun(1, z=4)
print(result)
```

Answer

7

Status : Correct

Marks : 1/1

6. What will be the output of the following Python code?

```
def is_even(number):
    if number % 2 == 0:
        return True
```

```
result = is_even(6)
print(result)
```

Answer

True

Status : Correct

Marks : 1/1

7. What will be the output of the following code?

```
num = -5
result = abs(num)
print(result)
```

Answer

5

Status : Correct

Marks : 1/1

8. What will be the output of the following Python code?

```
def C2F(c):
    return c * 9/5 + 32
print(C2F(100))
print(C2F(0))
```


Answer

212.032.0

Status : Correct

Marks : 1/1

9. What is the output of the code shown?

```
def f1():  
    global x  
    x+=1  
    print(x)  
x=12  
print("x")
```

Answer

x

Status : Correct

Marks : 1/1

10. What is the output of the following code snippet?

```
def add(a, b=2):  
    return a - b  
  
result = add(3)  
print(result)
```

Answer

1

Status : Correct

Marks : 1/1

11. What is the output of the code shown below?

```
def f1(x):  
    x += 1  
    print(x)
```

```
global_variable = 15  
f1(global_variable)  
print("hello")
```

Answer

16hello

Status : Correct

Marks : 1/1

12. What will be the output of the following code?

```
number = 7  
result = abs(number) + pow(number, 2)  
print(result)
```

Answer

56

Status : Correct

Marks : 1/1

13. What will be the output of the following Python code?

```
def cube(x):  
    return x * x * x  
x = cube(3)  
print(x)
```

Answer

27

Status : Correct

Marks : 1/1

14. Which of the following functions can take a lambda function as a parameter in Python?

Answer

map()

Status : Correct

Marks : 1/1

15. What will be the output of the following Python code?

```
def absolute_value(x):  
    if x < 0:  
        return -x  
    return x  
  
result = absolute_value(-9)  
print(result, absolute_value(5))
```

Answer

9 5

Status : Correct

Marks : 1/1

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 4_COD_Updated

Attempt : 1
Total Mark : 50
Marks Obtained : 50

Section 1 : Coding

1. Problem Statement

Imagine you are developing a text analysis tool for a cybersecurity company. Your task is to create a function that analyzes input strings to categorize and count the characters into four categories: uppercase letters, lowercase letters, digits, and special characters. The company needs this tool to process log files and identify potential security threats.

Function Signature: `analyze_string(input_string)`

Input Format

The input consists of a single string (without space), which may include uppercase letters, lowercase letters, digits, and special characters.

Output Format

The first line contains an integer representing the count of uppercase letters in the format "Uppercase letters: [count]".

The second line contains an integer representing the count of lowercase letters in the format "Lowercase letters: [count]".

The third line contains an integer representing the count of digits in the format "Digits: [count]".

The fourth line contains an integer representing the count of special characters in the format "Special characters: [count]".

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: Hello123

Output: Uppercase letters: 1

Lowercase letters: 4

Digits: 3

Special characters: 0

Answer

```
def analyze_string(input_string):
    uppercase_count=0
    lowercase_count=0
    digit_count=0
    special_count=0
    for char in input_string:
        if char.isupper():
            uppercase_count+=1
        elif char.islower():
            lowercase_count+=1
        elif char.isdigit():
            digit_count+=1
        else:
            special_count+=1
    return(uppercase_count,lowercase_count,digit_count,special_count)
input_string = input()
```

```
uppercase_count, lowercase_count, digit_count, special_count =  
analyze_string(input_string)
```

```
print("Uppercase letters:", uppercase_count)  
print("Lowercase letters:", lowercase_count)  
print("Digits:", digit_count)  
print("Special characters:", special_count)
```

Status : Correct

Marks : 10/10

2. Problem Statement

Sara is developing a text-processing tool that checks if a given string starts with a specific character or substring. She needs to implement a function that accepts a string and a character (or substring), and returns True if the string starts with the provided character/substring, or False otherwise.

Write a program that uses a lambda function to help Sara perform this check.

Input Format

The first line contains a string `str` representing the main string to be checked.

The second line contains a string `n`, which is the character or substring to check if the main string starts with it.

Output Format

The first line of output prints "True" if the string starts with the given character/substring, otherwise prints "False".

Refer to the sample for the formatting specifications.

Sample Test Case

Input: Examly
e

Output: False

Answer

```
# Whitelist  
# Set 1:  
#Lambda
```

```
main=input()  
check=input()
```

```
st=lambda s, sub: s[:len(sub)] == sub
```

```
print(st(main,check))
```

Status : Correct**Marks : 10/10****3. Problem Statement**

Sneha is building a more advanced exponential calculator. She wants to implement a program that does the following:

Calculates the result of raising a given base to a specific exponent using Python's built-in pow() function. Displays all intermediate powers from base¹ to base^{exponent} as a list. Calculates and displays the sum of these intermediate powers.

Help her build this program to automate her calculations.

Input Format

The input consists of line-separated two integer values representing base and exponent.

Output Format

The first line of the output prints the calculated result of raising the base to the exponent.

The second line prints a list of all powers from base¹ to base^{exponent}.

The third line prints the sum of all these powers.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 2

3

Output: 8

[2, 4, 8]

14

Answer

```
# Whitelist
```

```
# Set 1:
```

```
#Pow
```

```
#Sum
```

```
# list
```

```
b=int(input())
```

```
ex=int(input())
```

```
res=pow(b,ex)
```

```
inter=list(pow(b,i) for i in range(1,ex+1))
```

```
tot=sum(inter)
```

```
print(res)
```

```
print(inter)
```

```
print(tot)
```

Status : Correct

Marks : 10/10

4. Problem Statement

Imagine you are building a messaging application, and you want to know the length of the messages sent by the users. You need to create a program that calculates the length of a message using the built-in function `len()`.

Input Format

The input consists of a string representing the message.

Output Format

The output prints an integer representing the length of the entered message.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: hello!!

Output: 7

Answer

```
# You are using Python
def message(string):
    str2=len(string)
    return str2
user_input=input()
print(message(user_input))
```

Status : Correct

Marks : 10/10

5. Problem Statement

Implement a program that needs to identify Armstrong numbers.

Armstrong numbers are special numbers that are equal to the sum of their digits, each raised to the power of the number of digits in the number.

Write a function `is_armstrong_number(number)` that checks if a given number is an Armstrong number or not.

Function Signature: `armstrong_number(number)`

Input Format

The first line of the input consists of a single integer, `n`, representing the number to be checked.

Output Format

The output should consist of a single line that displays a message indicating whether the input number is an Armstrong number or not.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 153

Output: 153 is an Armstrong number.

Answer

You are using Python

```
def is_armstrong_number(number):
```

```
    m=number
```

```
    length=len(str(m))
```

```
    count=0
```

```
    while m>0:
```

```
        rem=m%10
```

```
        count+=pow(rem,length)
```

```
        m=m//10
```

```
    if count==number:
```

```
        print(f"{number} is an Armstrong number.")
```

```
    else:
```

```
        print(f"{number} is not an Armstrong number.")
```

```
n=int(input())
```

```
is_armstrong_number(n)
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 4_PAH_Updated

Attempt : 1
Total Mark : 60
Marks Obtained : 60

Section 1 : Coding

1. Problem Statement

Hussain wants to create a program to calculate a person's BMI (Body Mass Index) based on their weight in kilograms and height in meters. The BMI is a measure of a person's body fat relative to their height.

Your program should take user input for weight and height, calculate the BMI, and display the result.

Function Signature: calculate_bmi(weight, height)

Formula: $BMI = \text{Weight} / (\text{Height})^2$

Input Format

The first line of input consists of a positive floating-point number, the person's

weight in kilograms.

The second line of input consists of a positive floating-point number, the person's height in meters.

Output Format

The output displays "Your BMI is: [BM]" followed by a float value representing the calculated BMI, rounded off two decimal points.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 70.0

1.75

Output: Your BMI is: 22.86

Answer

```
weight = float(input())
```

```
height = float(input())
```

```
# You are using Py
```

```
def calculate_bmi(weight,height):
```

```
    bmi=weight/(height**2)
```

```
    return round(bmi,2)
```

```
bmi_result=calculate_bmi(weight,height)
```

```
print(f"Your BMI is: {bmi_result}")
```

```
calculate_bmi(weight, height)
```

Status : Correct

Marks : 10/10

2. Problem Statement

Ella is designing a messaging application that needs to handle long text messages efficiently. To optimize storage and transmission, she plans to implement a text compression feature that replaces consecutive repeated characters with the character followed by its count, while leaving non-repeated characters unchanged.

Help Ella create a recursive function to achieve this compression without altering the original message's meaning.

Function Specification: def compress_string(*args)

Input Format

The input consists of a single line containing the string to be compressed.

Output Format

The output consists of a single line containing the compressed string.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: aaaBBBccc

Output: a3B3c3

Answer

You are using Python

```
def string(a):
    result=""
    count=1
    for i in range(1,len(a)):
        if a[i]==a[i-1]:
            count+=1
        else:
            result+=a[i-1]+(str(count) if count>1 else "")
            count=1
    result+=a[-1]+(str(count) if count>1 else "")
    print(result)
a=input()
string(a)
```

Status : Correct

Marks : 10/10

3. Problem Statement

Create a Python program to monitor temperatures in a greenhouse using two sensors. Calculate and display the absolute temperature difference between the two sensor readings to ensure proper temperature control.

Note: Use the `abs()` built-in function.

Input Format

The first line consists of a floating-point number, representing the temperature reading from Sensor 1.

The second line consists of a floating-point number, representing the temperature reading from Sensor 2.

Output Format

The output displays the absolute temperature difference between Sensor 1 and Sensor 2, rounded to two decimal places.

Refer to the sample output for the exact format.

Sample Test Case

Input: 33.2

26.7

Output: Temperature difference: 6.50 °C

Answer

```
# You are using Python
```

```
a=float(input())
```

```
b=float(input())
```

```
diff=abs(a-b)
```

```
print(f"Temperature difference:{diff:.2f}\u00B0 C")
```

Status : Correct

Marks : 10/10

4. Problem Statement

Alice works at a digital marketing company, where she analyzes large datasets. One day, she's tasked with processing customer ID numbers, which are long numeric sequences.

To simplify her task, Alice needs to calculate the digital root of each ID. The digital root is obtained by repeatedly summing the digits of a number until a single digit remains.

Help Alice write a program that reads a customer ID number, calculates its digital root, and prints the result using a loop-based approach.

For example, the sum of the digits of 98675 is $9 + 8 + 6 + 7 + 5 = 35$, then $3 + 5 = 8$, which is the digital root.

Function prototype: `def digital_root(num)`

Input Format

The input consists of an integer num.

Output Format

The output prints an integer representing the sum of digits for a given number until a single digit is obtained.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 451110

Output: 3

Answer

```
num = int(input())
```

```
# You are using Python
```

```
def digital_root(num):
```

```
    while num >= 10:
```

```
        sum = 0
```

```
        while num > 0:
```

```
    sum+=num%10
    num=num//10
    num=sum
    return num

print(digital_root(num))
```

Status : Correct

Marks : 10/10

5. Problem Statement

Ravi is working on analyzing a set of integers to determine how many of them are divisible by 3 and how many are divisible by 5. He decides to use lambda functions to filter and count the numbers based on their divisibility.

Write a program that takes a list of integers, calculates how many numbers are divisible by 3, and how many are divisible by 5, and then prints the results.

Additionally, the program should calculate the total sum of all numbers divisible by 3 and divisible by 5 separately.

Input Format

The first line contains an integer n , representing the number of integers in the list.

The second line contains n space-separated integers.

Output Format

The first line should print the count of numbers divisible by 3.

The second line should print the count of numbers divisible by 5.

The third line should print the sum of numbers divisible by 3.

The fourth line should print the sum of numbers divisible by 5.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 6
3 5 6 10 15 20

Output: 3
4
24
50

Answer

```
def digit(num):  
    div_3=[]  
    div_5=[]  
    is_div_3=lambda x:x%3==0  
    is_div_5=lambda x:x%5==0  
    for i in num:  
        if is_div_3(i):  
            div_3.append(i)  
        if is_div_5(i):  
            div_5.append(i)  
    print(len(div_3))  
    print(len(div_5))  
    print(sum(div_3))  
    print(sum(div_5))  
  
n=int(input())  
num=list(map(int,input().split()))  
digit(num)
```

Status : Correct

Marks : 10/10

6. Problem Statement

Sophia is developing a feature for her online banking application that calculates the total sum of digits in customers' account numbers. This sum is used to generate unique verification codes for secure transactions. She needs a program that takes an account number as input and outputs the sum of its digits.

Help Sophia to complete her task.

Function Specification: def sum_digits(num)

Input Format

The input consists of an integer, representing the customer's account number.

Output Format

The output prints an integer representing the sum of the digits of the account number.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 123245

Output: 17

Answer

```
num = int(input())  
# You are using Python  
def sum_digits(num):  
    return sum(int(digit) for digit in str(num))  
sum = sum_digits(num)  
print(sum)
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 4_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Develop a text analysis tool that needs to count the occurrences of a specific substring within a given text string.

Write a function `count_substrings(text, substring)` that takes two inputs: the text string and the substring to be counted. The function should count how many times the substring appears in the text string and return the count.

Function Signature: `count_substrings(text, substring)`

Input Format

The first line of the input consists of a string representing the text.

The second line consists of a string representing the substring.

Output Format

The output should display a single line of output containing the count of occurrences of the substring in the text string.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: programming is fun and programming is cool
programming

Output: The substring 'programming' appears 2 times in the text.

Answer

```
# You are using Python
def count_ss(text,ss):
    count=text.count(ss)
    return count
def main():
    text=input().strip()
    ss=input().strip()

    count=count_ss(text,ss)
    print(f"The substring '{ss}' appears {count} times in the text.")
main()
```

Status : Correct

Marks : 10/10

2. Problem Statement

You are tasked with designing a shipping cost calculator program that calculates the shipping cost for packages based on their weight and destination. The program utilizes different shipping rates for domestic, international, and remote destinations. The rates for each destination type are provided as global constants.

Constant Values:

DOMESTIC_RATE = 5.0

INTERNATIONAL_RATE = 10.0

REMOTE_RATE = 15.0

Function Signature: calculate_shipping(weight, destination)

Formula: shipping cost = weight * destination rate

Input Format

The first line of the input consists of a float representing the weight of the package.

The second line consists of a string representing the destinations(Domestic or International or Remote).

Output Format

The program outputs any one of the following:

1. If the input is valid and the destination is recognized, the output should consist of a single line stating the calculated shipping cost for the given weight and destination in the format: "Shipping cost to [destination] for a [weight] kg package: \$[calculated cost]" with two decimal places.
2. If the input weight is not a positive float, print "Invalid weight. Weight must be greater than 0."
3. If the input destination is not one of the valid options, print "Invalid destination."

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5.5

Domestic

Output: Shipping cost to Domestic for a 5.5 kg package: \$27.50

Answer

#

```
# You are using Pyth
dom=5.0
inter=10.0
r=15.0
```

```
def calculate_shipping(weight,destination):
    if weight<0:
        print("Invalid weight. Weight must be greater than 0.")
        return None
    elif destination.lower()=="domestic":
        rate=dom
    elif destination.lower()=="international":
        rate=inter
    elif destination.lower()=="remote":
        rate=r
    else:
        print("Invalid destination.")
        return None
    return weight*rate
weight=float(input())
destination=input()
shipping_cost=calculate_shipping(weight,destination)

if shipping_cost is not None:
    print(f"Shipping cost to {destination} for a {weight} kg package:
    ${shipping_cost:.2f}")
```

Status : Correct

Marks : 10/10

3. Problem Statement

Create a program for a mathematics competition where participants need to find the smallest positive divisor of a given integer n. Your program should efficiently determine this divisor using the min() function and display the result.

Input Format

The input consists of a single positive integer n, representing the number for which the smallest positive divisor needs to be found.

Output Format

The output prints the smallest positive divisor of the input integer in the format:
"The smallest positive divisor of [n] is: [smallest divisor]".

Refer to the sample output for the exact format.

Sample Test Case

Input: 24

Output: The smallest positive divisor of 24 is: 2

Answer

```
# You are using Python
def small(n):
    div=[i for i in range(2,n+1) if n%i==0]
    return min(div)
def main():
    n=int(input())
    res=small(n)
    print(f"The smallest positive divisor of {n} is: {res}")
main()
```

Status : Correct

Marks : 10/10

4. Problem Statement

Arjun is working on a mathematical tool to manipulate lists of numbers. He needs a program that reads a list of integers and generates two lists: one containing the squares of the input numbers, and another containing the cubes. Arjun wants to use lambda functions for both tasks.

Write a program that computes the square and cube of each number in the input list using lambda functions.

Input Format

The input consists of a single line of space-separated integers representing the list of input numbers.

Output Format

The first line contains a list of the squared values of the input numbers.

The second line contains a list of the cubed values of the input numbers.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1 2 3

Output: [1, 4, 9]

[1, 8, 27]

Answer

```
# You are using Python
num=list(map(int,input().split()))
```

```
sq=list(map(lambda x: x**2,num))
cub=list(map(lambda x: x**3,num))
```

```
print(sq)
print(cub)
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 5_MCQ

Attempt : 1
Total Mark : 20
Marks Obtained : 19

Section 1 : MCQ

1. Fill in the code in order to get the following output.

Output:

Tuple: (1, 3, 4)

Max value: 4

t=(1,)

```
_____  
print("Tuple:",t)  
print("Max value:",_____)
```

Answer

1) t=t+(3,4)2) max(t)

Status : Correct

Marks : 1/1

2. What is the output of the following?

```
set1 = {10, 20, 30, 40, 50}
set2 = {60, 70, 10, 30, 40, 80, 20, 50}
print(set1.issubset(set2))
print(set2.issuperset(set1))
```

Answer

TrueTrue

Status : Correct

Marks : 1/1

3. What will be the output of the following code?

```
a=(1,2,3,4)
print(sum(a,3))
```

Answer

12

Status : Wrong

Marks : 0/1

4. Which of the statements about dictionary values is false?

Answer

Values of a dictionary must be unique

Status : Correct

Marks : 1/1

5. Predict the output of the following Python program

```
init_tuple_a = 1, 2, 8
init_tuple_b = (1, 2, 7)
set1=set(init_tuple_b)
set2=set(init_tuple_a)
print (set1 | set2)
print (init_tuple_a | init_tuple_b)
```

Answer

{1, 2, 7, 8}TypeError: unsupported operand type

Status : Correct

Marks : 1/1

6. What is the result of print(type({}) is set)?

Answer

False

Status : Correct

Marks : 1/1

7. What will be the output for the following code?

```
t1 = (1, 2, 4, 3)
t2 = (1, 2, 3, 4)
print(t1 < t2)
```

Answer

False

Status : Correct

Marks : 1/1

8. Which of the following statements is used to create an empty tuple?

Answer

()

Status : Correct

Marks : 1/1

9. Which of the following isn't true about dictionary keys?

Answer

Keys must be integers

Status : Correct

Marks : 1/1

10. What is the output of the below Python code?

```
list1 = [1, 2, 3]
list2 = [5, 6, 7]
list3 = [10, 11, 12]
set1 = set(list2)
set2 = set(list1)
set1.update(set2)
set1.update(list3)
print(set1)
```

Answer

{1, 2, 3, 5, 6, 7, 10, 11, 12}

Status : Correct

Marks : 1/1

11. Suppose t = (1, 2, 4, 3), which of the following is incorrect?

Answer

t[3] = 45

Status : Correct

Marks : 1/1

12. Which of the following is a Python tuple?

Answer

(1, 2, 3)

Status : Correct

Marks : 1/1

13. If 'a' is a dictionary with some key-value pairs, what does a.popitem() do?

Answer

Removes an arbitrary element

Status : Correct

Marks : 1/1

14. What will be the output of the following program?

```
set1 = {1, 2, 3}
set2 = set1.copy()
set2.add(4)
print(set1)
```

Answer

{1, 2, 3}

Status : Correct

Marks : 1/1

15. What will be the output for the following code?

```
a=(1,2,3)
b=('A','B','C')
c=zip(a,b)
```

```
print(c)
print(tuple(c))
```

Answer

((1, 'A'), (2, 'B'), (3, 'C'))

Status : Correct

Marks : 1/1

16. What is the output of the following code?

```
a={1:"A",2:"B",3:"C"}
b=a.copy()
b[2]="D"
print(a)
```

Answer

{1: 'A', 2: 'B', 3: 'C'}

Status : Correct

Marks : 1/1

17. Set $s1 = \{1, 2, 4, 3\}$ and $s2 = \{1, 5, 4, 6\}$, find $s1 \& s2$, $s1 - s2$, $s1 \cup s2$ and $s1 \Delta s2$.

Answer

$s1 \& s2 = \{1, 4\}$ $s1 - s2 = \{2, 3\}$ $s1 \wedge s2 = \{2, 3, 5, 6\}$ $s1 | s2 = \{1, 2, 3, 4, 5, 6\}$

Status : Correct

Marks : 1/1

18. What is the output of the following code?

```
a={"a":1,"b":2,"c":3}
b=dict(zip(a.values(),a.keys()))
print(b)
```

Answer

{1: 'a', 2: 'b', 3: 'c'}

Status : Correct

Marks : 1/1

19. What will be the output?

```
a={'B':5,'A':9,'C':7}
print(sorted(a))
```

Answer

['A', 'B', 'C'].

Status : Correct

Marks : 1/1

20. What is the output of the following code?

```
a=(1,2,(4,5))
b=(1,2,(3,4))
print(a<b)
```

Answer

False

Status : Correct

Marks : 1/1

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 5_COD

Attempt : 1
Total Mark : 50
Marks Obtained : 50

Section 1 : Coding

1. Problem Statement

Ella is analyzing the sales data for a new online shopping platform. She has a record of customer transactions where each customer's data includes their ID and a list of amounts spent on different items. Ella needs to determine the total amount spent by each customer and identify the highest single expenditure for each customer.

Your task is to write a program that computes these details and displays them in a dictionary.

Input Format

The first line of input consists of an integer n , representing the number of customers.

Each of the next n lines contains a numerical customer ID followed by integers representing the amounts spent on different items.

Output Format

The output displays a dictionary where the keys are customer IDs and the values are lists containing two integers: the total expenditure and the maximum single expenditure.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 2

101 100 150 200

102 50 75 100

Output: {101: [450, 200], 102: [225, 100]}

Answer

You are using Python

```
n=int(input())
```

```
customer={}
```

```
for _ in range(n):
```

```
    line=list(map(int,input().split()))
```

```
    customer_id=line[0]
```

```
    expenditures=line[1:]
```

```
    tot=sum(expenditures)
```

```
    maxi=max(expenditures)
```

```
    customer[customer_id]=[tot,maxi]
```

```
print(customer)
```

Status : Correct

Marks : 10/10

2. Problem Statement

Professor Adams needs to analyze student participation in three recent academic workshops. She has three sets of student IDs: the first set contains students who registered for the workshops, the second set contains students who actually attended, and the third set contains

students who dropped out.

Professor Adams needs to determine which students who registered also attended, and then identify which of these students did not drop out.

Help Professor Adams identify the students who registered, attended, and did not drop out of the workshops.

Input Format

The first line of input consists of integers, representing the student IDs who registered for the workshops.

The second line consists of integers, representing the student IDs who attended the workshops.

The third line consists of integers, representing the student IDs who dropped out of the workshops.

Output Format

The first line of output displays the intersection of the first two sets, which shows the IDs of students who registered and attended.

The second line displays the result after removing student IDs that are in the third set (dropped out), showing the IDs of students who both attended and did not drop out.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1 2 3

2 3 4

3 4 5

Output: {2, 3}

{2}

Answer

You are using Python

```
reg=set(map(int,input().split()))
```

```
attend=set(map(int,input().split()))
drop_out=set(map(int,input().split()))

regg_and_att=reg & attend
final=regg_and_att-drop_out
print(regg_and_att)
print(final)
```

Status : Correct

Marks : 10/10

3. Problem Statement

Gowshik is working on a task that involves taking two lists of integers as input, finding the element-wise sum of the corresponding elements, and then creating a tuple containing the sum values.

Write a program to help Gowshik with this task.

Example:

Given list:

[1, 2, 3, 4]

[3, 5, 2, 1]

An element-wise sum of the said tuples: (4, 7, 5, 5)

Input Format

The first line of input consists of a single integer n , representing the length of the input lists.

The second line of input consists of n integers separated by commas, representing the elements of the first list.

The third line of input consists of n integers separated by commas, representing the elements of the second list.

Output Format

The output is a single line containing a tuple of integers separated by commas.

representing the element-wise sum of the corresponding elements from the two input lists.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4

1, 2, 3, 4

3, 5, 2, 1

Output: (4, 7, 5, 5)

Answer

```
# You are using Python
```

```
n = int(input())
```

```
list1 = list(map(int, input().split(';')))
```

```
list2 = list(map(int, input().split(';')))
```

```
result = tuple(a + b for a,b in zip(list1, list2))
```

```
print(result)
```

Status : Correct

Marks : 10/10

4. Problem Statement

Liam is analyzing a list of product IDs from a recent sales report. He needs to determine how frequently each product ID appears and calculate the following metrics:

Frequency of each product ID: A dictionary where the key is the product ID and the value is the number of times it appears. Total number of unique product IDs. Average frequency of product IDs: The average count of all product IDs.

Write a program to read the product IDs, compute these metrics, and output the results.

Example

Input:

6 //number of product ID

101

102

101

103

101

102 //product IDs

Output:

{101: 3, 102: 2, 103: 1}

Total Unique IDs: 3

Average Frequency: 2.00

Explanation:

Input 6 indicates that you will enter 6 product IDs.

A dictionary is created to track the frequency of each product ID.

Input 101: Added with a frequency of 1.

Input 102: Added with a frequency of 1.

Input 101: Frequency of 101 increased to 2.

Input 103: Added with a frequency of 1.

Input 101: Frequency of 101 increased to 3.

Input 102: Frequency of 102 increased to 2.

The dictionary now contains 3 unique IDs: 101, 102, and 103.

Total Unique is 3.

The average frequency is 2.00.

Input Format

The first line of input consists of an integer n , representing the number of product IDs.

The next n lines each contain a single integer, each representing a product ID.

Output Format

The first line of output displays the frequency dictionary, which maps each product ID to its count.

The second line displays the total number of unique product IDs, preceded by "Total Unique IDs: ".

The third line displays the average frequency of the product IDs. This is calculated by dividing the total number of occurrences of all product IDs by the total number of unique product IDs, rounded to two decimal places. It is preceded by "Average Frequency: ".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 6

101

102

101

103

101

102

Output: {101: 3, 102: 2, 103: 1}

Total Unique IDs: 3

Average Frequency: 2.00

Answer

You are using Python

```
n = int(input())
```

```
product_ids = [int(input()) for _ in range(n)]
```

```
freq = {}
```

```
for pid in product_ids:
```

```
    freq[pid] = freq.get(pid, 0) + 1
```

```
total_unique = len(freq)
average_freq = sum(freq.values()) / total_unique

print(freq)
print(f"Total Unique IDs: {total_unique}")
print(f"Average Frequency: {average_freq:.2f}")
```

Status : Correct

Marks : 10/10

5. Problem Statement

James is managing a list of inventory items in a warehouse. Each item is recorded as a tuple, where the first element is the item ID and the second element is a list of quantities available for that item. James needs to filter out all quantities that are above a certain threshold to find items that have a stock level above this limit.

Help James by writing a program to process these tuples, filter the quantities from all the available items, and display the results.

Note:

Use the filter() function to filter out the quantities greater than the specified threshold for each item's stock list.

Input Format

The first line of input consists of an integer N, representing the number of tuples.

The next N lines each contain a tuple in the format (ID, [quantity1, quantity2, ...]), where ID is an integer and the list contains integers.

The final line consists of an integer threshold, representing the quantity threshold.

Output Format

The output should be a single line displaying the filtered quantities, space-

separated. Each quantity is strictly greater than the given threshold.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 2

(1, [1, 2])

(2, [3, 4])

2

Output: 3 4

Answer

```
# You are using Python
```

```
N = int(input())
```

```
filtered_quantities = []
```

```
for _ in range(N):
```

```
    item = eval(input())
```

```
    item_id, quantities = item
```

```
    filtered_quantities.append(quantities)
```

```
threshold = int(input())
```

```
result = [q for sublist in filtered_quantities for q in filter(lambda x: x > threshold,  
sublist)]
```

```
print(*result)
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 5_PAH

Attempt : 1
Total Mark : 60
Marks Obtained : 60

Section 1 : Coding

1. Problem Statement

Sophia is organizing a list of event IDs representing consecutive days of an event. She needs to group these IDs into consecutive sequences. For example, if the IDs 3, 4, and 5 appear consecutively, they should be grouped.

Write a program that helps Sophia by reading the total number of event IDs and the IDs themselves, then display each group of consecutive IDs in tuple format.

Input Format

The first line of input consists of an integer n , representing the number of event IDs.

The next n lines contain integers representing the event IDs, where each integer corresponds to an event ID.

Output Format

The output should display each group of consecutive event IDs in a tuple format. Each group should be printed on a new line, and single event IDs should be displayed as a single-element tuple.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3

1
2
3

Output: (1, 2, 3)

Answer

You are using Python

```
n=int(input())
```

```
event_ids=[int(input()) for _ in range(n)]
```

```
event_ids.sort()
```

```
result=[]
```

```
group=[event_ids[0]]
```

```
for i in range(1,n):
```

```
    if event_ids[i]==event_ids[i-1]+1:
```

```
        group.append(event_ids[i])
```

```
    else:
```

```
        result.append(group)
```

```
        group=[event_ids[i]]
```

```
result.append(group)
```

```
for grp in result:
```

```
    if len(grp)==1:
```

```
        print(f"({grp[0]})")
```

```
    else:
```

```
        print(tuple(grp))
```

Status : Correct

Marks : 10/10

2. Problem Statement

Tom wants to create a dictionary that lists the first n prime numbers, where each key represents the position of the prime number, and the value is the prime number itself.

Help Tom generate this dictionary based on the input she provides.

Input Format

The input consists of an integer n , representing the number of prime numbers Tom wants to generate.

Output Format

The output displays the generated dictionary where each key is an integer from 1 to n , and the corresponding value is the prime number.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4

Output: {1: 2, 2: 3, 3: 5, 4: 7}

Answer

```
# You are using Python
def is_prime(num):
    if num<2:
        return False
    for i in range(2,int(num**0.5)+1):
        if num%i==0:
            return False
    return True
n=int(input().strip())
primes={}
count=0
candidate=2
```

```
while count<n:
    if is_prime(candidate):
        count+=1
        primes[count]=candidate
        candidate+=1
print (primes)
```

Status : Correct

Marks : 10/10

3. Problem Statement

Rishi is working on a program to manipulate a set of integers. The program should allow users to perform the following operations:

Find the maximum value in the set. Find the minimum value in the set. Remove a specific number from the set.

The program should handle these operations based on user input. If the user inputs an invalid operation choice, the program should indicate that the choice is invalid.

Input Format

The first line contains space-separated integers that will form the initial set. Each integer x is separated by a space.

The second line contains an integer ch , representing the user's choice:

- 1 to find the maximum value
- 2 to find the minimum value
- 3 to remove a specific number from the set

If ch is 3, the third line contains an integer $n1$, which is the number to be removed from the set.

Output Format

The first line of output prints the original set in descending order.

For choice 1: Print the maximum value from the set.

For choice 2: Print the minimum value from the set.

For choice 3: Print the set after removing the specified number, in descending order.

For invalid choices: Print "Invalid choice".

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1 2 3 4 5

1

Output: {5, 4, 3, 2, 1}

5

Answer

You are using Python

```
input_set=set(map(int,input().strip().split()))
```

```
try:
```

```
    ch=int(input().strip())
```

```
except ValueError:
```

```
    ch=0
```

```
sorted_original=sorted(input_set,reverse=True)
```

```
print("{ " + ",".join(map(str,sorted_original)) + "}")
```

```
if ch==1:
```

```
    print(max(input_set))
```

```
elif ch==2:
```

```
    print(min(input_set))
```

```
elif ch==3:
```

```
    try:
```

```
        n1=int(input().strip())
```

```
        input_set.discard(n1)
```

```
        sorted_updated=sorted(input_set,reverse=True)
```

```
        print("{ " + ",".join(map(str,sorted_updated)) + "}")
```

```
    except ValueError:
```

```
        print("Invalid number to remove")
```

```
else:
```

```
    print("Invalid choice")
```

Status : Correct

Marks : 10/10

4. Problem Statement

Maya wants to create a dictionary that maps each integer from 1 to a given number n to its square. She will use this dictionary to quickly reference the square of any number up to n .

Help Maya generate this dictionary based on the input she provides.

Input Format

The input consists of an integer n , representing the highest number for which Maya wants to calculate the square.

Output Format

The output displays the generated dictionary where each key is an integer from 1 to n , and the corresponding value is its square.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

Output: {1: 1, 2: 4, 3: 9, 4: 16, 5: 25}

Answer

```
# You are using Python
n=int(input().strip())
squares_dict={i:i**2 for i in range(1,n+1)}
print(squares_dict)
```

Status : Correct

Marks : 10/10

5. Problem Statement

Mia is organizing a list of integers into a series of pairs for his new project. She wants to create pairs of consecutive integers from the list. The last integer should be paired with None to complete the series. The pairing happens as follows: ((Element 1, Element 2), (Element 2, Element 3).....

(Element n, None)).

Your task is to help Henry by writing a Python program that reads a list of integers, forms these pairs, and displays the result in tuple format.

Input Format

The first line of input consists of an integer n, representing the number of elements in the tuple.

The second line of input contains n space-separated integers, representing the elements of the tuple.

Output Format

The output displays a tuple containing pairs of consecutive integers from the input. The last integer in the tuple is paired with 'None'.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3

5 10 15

Output: ((5, 10), (10, 15), (15, None))

Answer

```
# You are using Python
n=int(input().strip())
```

```
elements=list(map(int,input().strip().split()))
```

```
result=tuple((elements[i],elements[i+1]) for i in range(n-1))
+((elements[-1],None),)
```

```
print(result)
```

Status : Correct

Marks : 10/10

Jordan is creating a program to process a list of integers. The program should take a list of integers as input, remove any duplicate integers while preserving their original order, concatenate the remaining unique integers into a single string, and then print the result.

Help Jordan in implementing the same.

Input Format

The input consists of space-separated integers representing the elements of the set.

Output Format

The output prints a single integer formed by concatenating the unique integers from the input in the order they appeared.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 11 11 33 50

Output: 113350

Answer

```
# You are using Python
numb=input().strip().split()
```

```
seen=set()
unique_num=[]
```

```
for num in numb:
    if num not in seen:
        unique_num.append(num)
        seen.add(num)
result="".join(unique_num)
print(result)
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 5_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

James is an engineer working on designing a new rocket propulsion system. He needs to solve a quadratic equation to determine the optimal launch trajectory. The equation is of the form $ax^2 + bx + c = 0$.

Your task is to help James find the roots of this quadratic equation. Depending on the discriminant, the roots might be real and distinct, real and equal, or complex. Implement a program to determine and display the roots of the equation based on the given coefficients.

Input Format

The first line of input consists of an integer N, representing the number of coefficients.

The second line contains three space-separated integers a,b, and c representing the coefficients of the quadratic equation.

Output Format

The output displays:

1. If the discriminant is positive, display the two real roots.
2. If the discriminant is zero, display the repeated real root.
3. If the discriminant is negative, display the complex roots as a tuple with real and imaginary parts.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3

1 5 6

Output: (-2.0, -3.0)

Answer

You are using Python

```
import math
```

```
N = int(input())
```

```
a, b, c = map(int, input().split())
```

```
D = b**2 - 4*a*c
```

```
if D > 0:
```

```
    root1 = (-b + math.sqrt(D)) / (2*a)
```

```
    root2 = (-b - math.sqrt(D)) / (2*a)
```

```
    print((round(root1, 1), round(root2, 1)))
```

```
elif D == 0:
```

```
    root = -b / (2*a)
```

```
    print((round(root, 1), round(root, 1)))
```

```
else:
```

```
    real = -b / (2*a)
```

```
    imag = math.sqrt(-D) / (2*a)
```

```
    root1 = (round(real, 1), round(imag, 1))
```

```
    root2 = (round(real, 1), round(-imag, 1))
```

```
    print((root1, root2))
```

Status : Correct

Marks : 10/10

2. Problem Statement

Samantha is working on a text analysis tool that compares two words to find common and unique letters. She wants a program that reads two words, w_1 , and w_2 , and performs the following operations:

Print the letters common to both words, in alphabetical order. Print the letters that are unique to each word, in alphabetical order. Determine if the set of letters in the first word is a superset of the letters in the second word. Check if there are no common letters between the two words and print the result as a Boolean value.

Ensure the program ignores case differences and leading/trailing spaces in the input words.

Your task is to help Samantha in implementing the same.

Input Format

The first line of input consists of a string representing the first word, w_1 .

The second line consists of a string representing the second word, w_2 .

Output Format

The first line of output should display the sorted letters common to both words, printed as a list.

The second line should display the sorted letters that are unique to each word, printed as a list.

The third line should display a Boolean value indicating if the set of letters in w_1 is a superset of the set of letters in w_2 .

The fourth line should display a Boolean value indicating if there are no common letters between w_1 and w_2 .

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: program

Peace

Output: ['a', 'p']

['c', 'e', 'g', 'm', 'o', 'r']

False

False

Answer

You are using Python

```
w1 = input().strip().lower()
```

```
w2 = input().strip().lower()
```

```
set1 = set(w1)
```

```
set2 = set(w2)
```

```
common_letters = sorted(set1 & set2)
```

```
print(common_letters)
```

```
unique_letters = sorted(set1 ^ set2)
```

```
print(unique_letters)
```

```
is_superset = set1.issuperset(set2)
```

```
print(is_superset)
```

```
no_common = set1.isdisjoint(set2)
```

```
print(no_common)
```

Status : Correct

Marks : 10/10

3. Problem Statement

Noah, a global analyst at a demographic research firm, has been tasked with identifying which country experienced the largest population growth over a two-year period. He has a dataset where each entry consists of a country code and its population figures for two consecutive years. Noah needs to determine which country had the highest increase in population and present the result in a specific format.

Help Noah by writing a program that outputs the country code with the largest population increase, along with the increase itself.

Input Format

The first line of input consists of an integer N, representing the number of countries.

Each of the following N blocks contains three lines:

1. The first line is a country code.
2. The second line is an integer representing the population of the country in the first year.
3. The third line is an integer representing the population of the country in the second year.

Output Format

The output displays the country code and the population increase in the format {code: difference}, where code is the country code and difference is the increase in population.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3

01

1000

1500

02

2000

2430

03

1500

3000

Output: {03:1500}

Answer

```
# You are using Python
```

```
N = int(input())
```

```
max_increase = -1
```

```
max_country_code = ""
```

```
for _ in range(N):
```

```
    code = input().strip()
```

```
    pop1 = int(input())
```

```
    pop2 = int(input())
```

```
    increase = pop2 - pop1
```

```
if increase > max_increase:
    max_increase = increase
    max_country_code = code
print(f"{{{max_country_code}:{max_increase}}}")
```

Status : Correct

Marks : 10/10

4. Problem Statement

Emily is a librarian who keeps track of books borrowed and returned by her patrons. She maintains four sets of book IDs: the first set represents books borrowed, the second set represents books returned, the third set represents books added to the collection, and the fourth set represents books that are now missing. Emily wants to determine which books are still borrowed but not returned, as well as those that were added but are now missing. Finally, she needs to find all unique book IDs from both results.

Help Emily by writing a program that performs the following operations on four sets of integers:

Compute the difference between the borrowed books (first set) and the returned books (second set). Compute the difference between the added books (third set) and the missing books (fourth set). Find the union of the results from the previous two steps, and sort the final result in descending order.

Input Format

The first line of input consists of a list of integers representing borrowed books.

The second line of input consists of a list of integers representing returned books.

The third line of input consists of a list of integers representing added books.

The fourth line of input consists of a list of integers representing missing books.

Output Format

The first line of output displays the difference between sets P and Q, sorted in descending order.

The second line of output displays the difference between sets R and S, sorted in descending order.

The third line of output displays the union of the differences from the previous two steps, sorted in descending order.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1 2 3

2 3 4

5 6 7

6 7 8

Output: [1]

[5]

[5, 1]

Answer

You are using Python

```
P = set(map(int, input().split()))
```

```
Q = set(map(int, input().split()))
```

```
R = set(map(int, input().split()))
```

```
S = set(map(int, input().split()))
```

```
borrowed_not_returned = sorted(P - Q, reverse=True)
```

```
added_but_missing = sorted(R - S, reverse=True)
```

```
final_result = sorted(set(borrowed_not_returned + added_but_missing),  
reverse=True)
```

```
print(borrowed_not_returned)
```

```
print(added_but_missing)
```

```
print(final_result)
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 6_MCQ

Attempt : 1
Total Mark : 20
Marks Obtained : 18

Section 1 : MCQ

1. What is the correct way to raise an exception in Python?

Answer

raise Exception()

Status : Correct

Marks : 1/1

2. Match the following:

- a) f.seek(5,1) i) Move file pointer five characters behind from the current position
- b) f.seek(-5,1) ii) Move file pointer to the end of a file
- c) f.seek(0,2) iii) Move file pointer five characters ahead from the current position

d) f.seek(0) iv) Move file pointer to the beginning of a file

Answer

a-iii, b-i, c-ii, d-iv

Status : Correct

Marks : 1/1

3. What happens if an exception is not caught in the except clause?

Answer

The program will display a traceback error and stop execution

Status : Correct

Marks : 1/1

4. Fill the code to in order to read file from the current position.

Assuming exp.txt file has following 3 lines, consider current file position is beginning of 2nd line

Meri,25

John,21

Raj,20

Ouput:

['John,21\n','Raj,20\n']

```
f = open("exp.txt", "w+")
```

```
_____ (1)
```

```
print _____ (2)
```

Answer

1) f.seek(0, 1) 2) f.readlines()

Status : Correct

Marks : 1/1

5. What is the default value of reference_point in the following code?


```
file_object.seek(offset [,reference_point])
```

Answer

0

Status : Correct

Marks : 1/1

6. What will be the output of the following Python code?

```
f = None
for i in range (5):
    with open("data.txt", "w") as f:
        if i > 2:
            break
print(f.closed)
```

Answer

True

Status : Correct

Marks : 1/1

7. What is the output of the following code?

```
try:
    x = "hello" + 5
except TypeError:
    print("Type Error occurred")
finally:
    print("This will always execute")
```

Answer

Type Error occurredThis will always execute

Status : Correct

Marks : 1/1

8. What is the output of the following code?

```
try:
    x = 1 / 0
except ZeroDivisionError:
    print("Caught division by zero error")
finally:
    print("Executed")
```

Answer

Caught division by zero errorExecuted

Status : Correct

Marks : 1/1

9. Which of the following is true about the finally block in Python?

Answer

The finally block is always executed, regardless of whether an exception occurs or not

Status : Correct

Marks : 1/1

10. Which of the following is true about
fp.seek(10,1)

Answer

Move file pointer ten characters ahead from the current position

Status : Correct

Marks : 1/1

11. What happens if no arguments are passed to the seek function?

Answer

error

Status : Wrong

Marks : 0/1

12. What is the output of the following code?

```
class MyError(Exception):  
    pass
```

```
try:  
    raise MyError("Something went wrong")  
except MyError as e:  
    print(e)
```

Answer

Something went wrong

Status : Correct

Marks : 1/1

13. What is the purpose of the except clause in Python?

Answer

To handle exceptions during code execution

Status : Correct

Marks : 1/1

14. How do you create a user-defined exception in Python?

Answer

By creating a new class that inherits from the Exception class

Status : Correct

Marks : 1/1

15. What is the difference between r+ and w+ modes?

Answer

in r+ the pointer is initially placed at the beginning of the file and the pointer is at the end for w+

Status : Correct

Marks : 1/1

16. Which clause is used to clean up resources, such as closing files in

Python?

Answer

finally

Status : Correct

Marks : 1/1

17. What will be the output of the following Python code?

```
# Predefined lines to simulate the file content
lines = [
    "This is 1st line",
    "This is 2nd line",
    "This is 3rd line",
    "This is 4th line",
    "This is 5th line"
]

print("Name of the file: foo.txt")

# Print the first 5 lines from the predefined list
for index in range(5):
    line = lines[index]
    print("Line No %d - %s" % (index + 1, line.strip()))
```

Answer

Displays Output

Status : Correct

Marks : 1/1

18. Fill in the blanks in the following code of writing data in binary files.

```
import _____ (1)
rec=[]
while True:
    rn=int(input("Enter"))
    nm=input("Enter")
    temp=[rn, nm]
```

```
rec.append(temp)
ch=input("Enter choice (y/N)")
if ch.upper=="N":
    break
f.open("stud.dat","_____")(2)
_____.dump(rec,f)(3)
_____.close()(4)
```

Answer

(pickle,wb,pickle,f)

Status : Correct

Marks : 1/1

19. How do you rename a file?

Answer

os.rename(existing_name, new_name)

Status : Correct

Marks : 1/1

20. Fill in the code in order to get the following output:

Output:

Name of the file: ex.txt

```
fo = open(_____(1), "wb")
print("Name of the file: ",_____(2))
```

Answer

1) ex.txt2) fo.name

Status : Wrong

Marks : 0/1

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 6_COD

Attempt : 1
Total Mark : 50
Marks Obtained : 50

Section 1 : Coding

1. Problem Statement

A retail store requires a program to calculate the total cost of purchasing a product based on its price and quantity. The program performs validation to ensure valid inputs and handles specific error conditions using exceptions:

Price Validation: If the price is zero or less, raise a ValueError with the message: "Invalid Price". Quantity Validation: If the quantity is zero or less, raise a ValueError with the message: "Invalid Quantity". Cost Threshold: If the total cost exceeds 1000, raise RuntimeError with the message: "Excessive Cost".

Input Format

The first line of input consists of a double value, representing the price of a product.

The second line consists of an integer, representing the quantity of the product.

Output Format

If the calculation is successful, print the total cost rounded to one decimal place.

If the price is zero or less prints "Invalid Price".

If the quantity is zero or less prints "Invalid Quantity".

If the total cost exceeds 1000, prints "Excessive Cost".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 20.0

5

Output: 100.0

Answer

You are using Python

```
n=float(input())
```

```
m=int(input())
```

```
try:
```

```
    if(n<=0):
```

```
        print("Invalid Price")
```

```
    elif(m<=0):
```

```
        print("Invalid Quantity")
```

```
        #pass ValueError
```

```
    elif(m*n>1000):
```

```
        print("Excessive Cost")
```

```
        #pass RuntimeError
```

```
    else:
```

```
        print(m*n)
```

```
except ValueError:
```

```
    pass
```

```
except RuntimeError:
```

```
    pass
```

Status : Correct

Marks : 10/10

2. Problem Statement

Write a program that calculates the average of a list of integers. The program prompts the user to enter the length of the list (n) and each element of the list. It performs error handling to ensure that the length of the list is a non-negative integer and that each input element is a numeric value.

Input Format

The first line of the input is an integer n, representing the length of the list as a positive integer.

The second line of the input consists of an element of the list as an integer, separated by a new line.

Output Format

If the length of the list is not a positive integer or zero, the output displays "Error: The length of the list must be a non-negative integer."

If a non-numeric value is entered for the length of the list, the output displays "Error: You must enter a numeric value."

If a non-numeric value is entered for a list element, the output displays "Error: You must enter a numeric value."

If the inputs are valid, the program calculates and prints the average of the provided list of integers with two decimal places: "The average is: [average]".

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: -2

1

2

Output: Error: The length of the list must be a non-negative integer.

Answer

You are using Python

try:

```
k=int(input())
```

```
if k<=0:
```

```
    raise Exception
```

```
else:
```

```
    l=[]
```

```
    for i in range(k):
```

```
        n=input().strip()
```

```
        if(not n.isdigit()):
```

```
            raise ValueError
```

```
        l.append(int(n))
```

```
    t=sum(l)
```

```
    m=t/k
```

```
    print(f"The average is:{m:.2f}")
```

```
except ValueError:
```

```
    print("Error: You must enter a numeric value.")
```

```
except Exception:
```

```
    print("Error: The length of the list must be a non-negative integer.")
```

Status : Correct

Marks : 10/10

3. Problem Statement

Tara is a content manager who needs to perform case conversions for various pieces of text and save the results in a structured manner.

She requires a program to take a user's input string, save it in a file, and then retrieve and display the string in both upper-case and lower-case versions. Help her achieve this task efficiently.

File Name: text_file.txt

Input Format

The input consists of a single line containing a string provided by the user.

Output Format

The first line displays the original string read from the file in the format: "Original String: {original_string}".

The second line displays the upper-case version of the original string in the format: "Upper-Case String: {upper_case_string}".

The third line displays the lower-case version of the original string in the format: "Lower-Case String: {lower_case_string}".

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: #SpecialSymBoLs1234

Output: Original String: #SpecialSymBoLs1234

Upper-Case String: #SPECIALSYMBOLS1234

Lower-Case String: #specialsymbols1234

Answer

You are using Python

```
s=input()
```

```
with open("text_file.txt","w") as f:
```

```
    f.write(s)
```

```
with open("text_file.txt","r") as f:
```

```
    c=f.read()
```

```
    print("Original String:",c)
```

```
    print("Upper-Case String:",c.upper())
```

```
    print("Lower-Case String:",c.lower())
```

Status : Correct

Marks : 10/10

4. Problem Statement

In a voting system, a person must be at least 18 years old to be eligible to vote. If a user enters an age below 18, the system should raise a user-

defined exception indicating that they are not eligible to vote.

Input Format

The input contains a positive integer representing age.

Output Format

If the age is less than 18, the output displays "Not eligible to vote".

Otherwise, the output displays "Eligible to vote".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 18

Output: Eligible to vote

Answer

You are using Python

```
k=int(input())
```

```
try:
```

```
    if(k>=18):
```

```
        print("Eligible to vote")
```

```
    else:
```

```
        raise ValueError
```

```
except ValueError:
```

```
    print("Not eligible to vote")
```

Status : Correct

Marks : 10/10

5. Problem Statement

Sophie enjoys playing with words and wants to count the number of words in a sentence. She inputs a sentence, saves it to a file, and then reads it from the file to count the words.

Write a program to determine the number of words in the input sentence.

File Name: sentence_file.txt

Input Format

The input consists of a single line of text containing words separated by spaces.

Output Format

The output displays the count of words in the sentence.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: Four Words In This Sentence

Output: 5

Answer

```
# You are using Python
s=input()
with open("sentence_file.txt","w") as f:
    f.write(s)
with open("sentence_file.txt","r") as f:
    c=f.read()
    print(len(c.split()))
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 6_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Alice is developing a program called "Name Sorter" that helps users organize and sort names alphabetically.

The program takes names as input from the user, saves them in a file, and then displays the names in sorted order.

File Name: sorted_names.txt.

Input Format

The input consists of multiple lines, each containing a name represented as a string.

To end the input and proceed with sorting, the user can enter 'q'.

Output Format

The output displays the names in alphabetical order, each name on a new line.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: Alice Smith
John Doe
Emma Johnson

q

Output: Alice Smith
Emma Johnson
John Doe

Answer

```
# You are using Python
def name_sorter():
    names = []
    while True:
        name = input()
        if name == 'q':
            break
        names.append(name)
    names.sort()
    with open("sorted_names.txt", "w") as f:
        for name in names:
            f.write(name + "\n")
    for name in names:
        print(name)
name_sorter()
```

Status : Correct

Marks : 10/10

2. Problem Statement

Write a program to obtain the start time and end time for the stage event show. If the user enters a different format other than specified, an

exception occurs and the program is interrupted. To avoid that, handle the exception and prompt the user to enter the right format as specified.

Start time and end time should be in the format 'YYYY-MM-DD HH:MM:SS'. If the input is in the above format, print the start time and end time. If the input does not follow the above format, print "Event time is not in the format "

Input Format

The first line of input consists of the start time of the event.

The second line of the input consists of the end time of the event.

Output Format

If the input is in the given format, print the start time and end time.

If the input does not follow the given format, print "Event time is not in the format".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 2022-01-12 06:10:00

2022-02-12 10:10:12

Output: 2022-01-12 06:10:00

2022-02-12 10:10:12

Answer

You are using Python

from datetime import datetime

def get_event_times():

try:

start_time = input().strip()

end_time = input().strip()

start_dt = datetime.strptime(start_time, '%Y-%m-%d %H:%M:%S')

end_dt = datetime.strptime(end_time, '%Y-%m-%d %H:%M:%S')

print(start_time)

print(end_time)

```
except ValueError:  
    print("Event time is not in the format")  
get_event_times()
```

Status : Correct

Marks : 10/10

3. Problem Statement

A shopkeeper is recording the daily sales of an item for N days, where the price of the item remains the same for all days. Write a program to calculate the total sales for each day and save them in a file named sales.txt that can store the data for a maximum of 30 days. Then, read the file and display the total earnings for each day.

Note: Total Earnings for each day = Number of Items sold in that day × Price of the item.

Input Format

The first line of input consists of an integer N, representing the number of days.

The second line of input consists of N space-separated integers representing the number of items sold each day.

The third line of input consists of an integer M, representing the price of the item that is common for all N days.

Output Format

If the number of days entered exceeds 30 ($N > 30$), the output prints "Exceeding limit!" and terminates.

Otherwise, the code reads the contents of the file and displays the total earnings for each day on separate lines.

Contents of the file: The total earnings for N days, with each day's earnings appearing on a separate line.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4
5 10 5 0
20
Output: 100
200
100
0

Answer

```
# You are using Python
n=int(input())
if n>30:
    print("Exceeding limit!")
else:
    instr=input().strip()
    price=int(input())
    with open ("sales.txt",'w') as f:
        f.write(instr)
    with open ("sales.txt",'r') as f:
        l=f.read().split()
    for i in l:
        print(int(i)*price)
```

Status : Correct

Marks : 10/10

4. Problem Statement

Implement a program that checks whether a set of three input values can form the sides of a valid triangle. The program defines a function `is_valid_triangle` that takes three side lengths as arguments and raises a `ValueError` if any side length is not a positive value. It then checks whether the sum of any two sides is greater than the third side to determine the validity of the triangle.

Input Format

The first line of input consists of an integer A, representing side1.

The second line of input consists of an integer B, representing side2.

The third line of input consists of an integer C, representing side3.

Output Format

The output prints either "It's a valid triangle" if the input side lengths form a valid triangle,

or "It's not a valid triangle" if they do not.

If there is a ValueError, it should print "ValueError: <error_message>".

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 3

4

5

Output: It's a valid triangle

Answer

You are using Python

```
def is_valid_triangle(a, b, c):
```

```
    if a <= 0 or b <= 0 or c <= 0:
```

```
        raise ValueError("Side lengths must be positive")
```

```
    if (a + b > c) and (a + c > b) and (b + c > a):
```

```
        return True
```

```
    else:
```

```
        return False
```

```
try:
```

```
    A = int(input().strip())
```

```
    B = int(input().strip())
```

```
    C = int(input().strip())
```

```
    if is_valid_triangle(A, B, C):
```

```
        print("It's a valid triangle")
```

```
    else:
```

```
        print("It's not a valid triangle")
```

```
except ValueError as e:  
    print(f"ValueError: {e}")
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 7_MCQ

Attempt : 1
Total Mark : 20
Marks Obtained : 18

Section 1 : MCQ

1. What will be the output of the following code?

```
import pandas as pnd  
pnd.Series([1,2], index= ['a','b','c'])
```

Answer

Value Error

Status : Correct

Marks : 1/1

2. Which NumPy function is used to create an identity matrix?

Answer

```
numpy.identity()
```

Status : Correct

Marks : 1/1

3. What is the result of the following NumPy operation?

```
import numpy as np
arr = np.array([1, 2, 3])
r = arr + 5
print(r)
```

Answer

[6 7 8]

Status : Correct

Marks : 1/1

4. What is the primary purpose of Pandas DataFrame?

Answer

To store data in tabular form for analysis and manipulation

Status : Correct

Marks : 1/1

5. Minimum number of argument we require to pass in pandas series ?

Answer

0

Status : Wrong

Marks : 0/1

6. In the DataFrame created in the code, what is the index for the row containing the data for 'Jack'?

```
import pandas as pd
```

```
data = {'Name': ['Tom', 'Jack', 'nick', 'juli'],
        'marks': [99, 98, 95, 90]}
```

```
df = pd.DataFrame(data, index=['rank1',
                                'rank2',
                                'rank3',
                                'rank4'])
```

```
print(df)
```

Answer

```
rank2
```

Status : Correct

Marks : 1/1

7. What is the output of the following NumPy code snippet?

```
import numpy as np
arr = np.array([1, 2, 3, 4, 5])
r = arr[arr > 2]
print(r)
```

Answer

```
[3 4 5]
```

Status : Correct

Marks : 1/1

8. Which of the following is a valid way to import NumPy in Python?

Answer

```
import numpy as np
```

Status : Correct

Marks : 1/1

9. Which function is used to create a Pandas DataFrame?

Answer

```
pd.DataFrame()
```

Status : Correct

Marks : 1/1

10. What does NumPy stand for?

Answer

```
Numerical Python
```

Status : Correct

Marks : 1/1

11. What does the np.arange(10) function in NumPy do?

Answer

Creates an array with values from 0 to 10

Status : Wrong

Marks : 0/1

12. Which NumPy function is used to calculate the standard deviation of an array?

Answer

numpy.std()

Status : Correct

Marks : 1/1

13. What will be the output of the following code snippet?

```
import numpy as np
arr = np.array([1, 2, 3])
result = np.concatenate((arr, arr))
print(result)
```

Answer

[1 2 3 1 2 3]

Status : Correct

Marks : 1/1

14. Which NumPy function is used to find the indices of the maximum and minimum values in an array?

Answer

argmax() and argmin()

Status : Correct

Marks : 1/1

15. The important data structure of pandas is/are ____.

Answer

Both Series and Data Frame

Status : Correct

Marks : 1/1

16. What is the output of the following NumPy code?

```
import numpy as np
arr = np.array([1, 2, 3, 4, 5])
r = arr[2:4]
print(r)
```

Answer

[3 4]

Status : Correct

Marks : 1/1

17. What is the output of the following code?

```
import numpy as np
a = np.arange(10)
print(a[2:5])
```

Answer

[2, 3, 4]

Status : Correct

Marks : 1/1

18. What is the primary data structure used in NumPy for numerical computations?

Answer

Array

Status : Correct

Marks : 1/1

19. In NumPy, how do you access the first element of a one-dimensional array arr?

Answer

arr[0]

Status : Correct

Marks : 1/1

20. What is the purpose of the following NumPy code snippet?

```
import numpy as np
arr = np.zeros((3, 4))
print(arr)
```

Answer

Displays a 3x4 matrix filled with zeros

Status : Correct

Marks : 1/1

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 6_PAH

Attempt : 1
Total Mark : 30
Marks Obtained : 30

Section 1 : Coding

1. Problem Statement

Peter manages a student database and needs a program to add students. For each student, Alex inputs their ID and name. The program checks for duplicate IDs and ensures the database isn't full.

If a duplicate or a full database is detected, an appropriate error message is displayed. Otherwise, the student is added, and a confirmation message is shown. The database has a maximum capacity of 30 students, and each student must have a unique ID.

Input Format

The first line contains an integer n, representing the number of students to be added to the school database.

The next n lines each contain two space-separated values, representing the student's ID (integer) and the student's name (string).

Output Format

The output will depend on the actions performed in the code.

If a student is added to the database, the output will display: "Student with ID [ID number] added to the database."

If there is an exception due to a duplicate student ID, the output will display: "Exception caught. Error: Student ID already exists."

If there is an exception due to the database being full, the output will display: "Exception caught. Error: Student database is full."

Refer to the sample outputs for the formatting specifications.

Sample Test Case

Input: 3
16 Sam
87 Sabari
43 Dani

Output: Student with ID 16 added to the database.
Student with ID 87 added to the database.
Student with ID 43 added to the database.

Answer

```
# You are using Python
MAX=30
students={}
n=int(input())
for _ in range(n):
    try:
        line=input().strip()
        sid,sname=line.split()
        sid=int(sid)
```

```
if len(students) >= MAX:
    raise OverflowError(" Student database is full.")
if sid in students:
    raise ValueError(" Student ID already exists.")
students[sid]=sname
print(f"Student with ID {sid} added to the database.")
except ValueError as ve:
    print(f"Exception caught. Error:{ve}")
    break
except OverflowError as oe:
    print(f"Exception caught. Error:{oe}")
    break
```

Status : Correct

Marks : 10/10

2. Problem Statement

John is a data analyst who often works with text files. He needs a program that can analyze the contents of a text file and count the number of times a specific character appears in the file.

John wants a simple program that allows him to specify a file and a character to count within that file.

Input Format

The first line of input consists of the file's name to be analyzed.

The second line of the input consists of the string they want to write within the file.

The third line of the input consists of a character to count within the file.

Output Format

If the character is found, the output displays "The character 'X' appears {Y} times in the file." where X is the character and Y is the count,

If the character does not appear in the file, the output displays "Character not found."

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: test.txt

This is a test file to check the character count.

e

Output: The character 'e' appears 5 times in the file.

Answer

```
# You are using Python
fname=input().strip()
s=input().lower()
fc=input().lower()
with open (fname,"w") as f:
    f.write(s)
with open (fname,"r") as f:
    c=f.read()
ct=c.count(fc)
if ct>0:
    print(f"The character '{fc}' appears {ct} times in the file.")
else:
    print("Character not found in the file.")
```

Status : Correct

Marks : 10/10

3. Problem Statement

Reeta is playing with numbers. Reeta wants to have a file containing a list of numbers, and she needs to find the average of those numbers. Write a program to read the numbers from the file, calculate the average, and display it.

File Name: user_input.txt

Input Format

The input file will contain a single line of space-separated numbers (as a string).

These numbers may be integers or decimals.

Output Format

If all inputs are valid numbers, the output should print: "Average of the numbers is: X.XX" (where X.XX is the computed average rounded to two decimal places)

If the input contains invalid data, print: "Invalid data in the input."

Refer to the sample output for format specifications.

Sample Test Case

Input: 1 2 3 4 5

Output: Average of the numbers is: 3.00

Answer

```
# You are using Python
fname='user_input.txt'
inputstr=input()
with open(fname,'w') as f:
    f.write(inputstr)
with open(fname,'r') as f:
    line=f.readline().strip()
    num_str=line.split()
try:
    num=[float(i) for i in num_str]
    avg=sum(num)/len(num)
    print(f"Average of the numbers is: {avg:.2f}")
except ValueError:
    print("Invalid data in the input.")
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 7_COD

Attempt : 1
Total Mark : 50
Marks Obtained : 47.5

Section 1 : Coding

1. Problem Statement

Alex is a data scientist analyzing the relationship between two financial indicators over time. He has collected two time series datasets representing daily values of these indicators over several months. Alex wants to understand how these two indicators correlate at different time lags to identify possible leading or lagging behaviors.

Your task is to help Alex compute the cross-correlation of these two time series using numpy, so he can analyze the similarity between the two signals at various time shifts.

Input Format

The first line of input consists of space-separated float values representing the first time series, array1.

The second line of input consists of space-separated float values representing the second time series, array2.

Output Format

The first line of output prints: "Cross-correlation of the two time series:"

The second line of output prints: the 1D numpy array cross_corr representing the cross-correlation of array1 and array2 across different lags.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1.0 2.0 3.0
4.0 5.0 6.0

Output: Cross-correlation of the two time series:
[6. 17. 32. 23. 12.]

Answer

```
# You are using Python
import numpy as np
a1=np.array(list(map(float,input().split()))))
a2=np.array(list(map(float,input().split()))))
c=np.correlate(a1,a2,mode='full')
print("Cross-correlation of the two time series:")
print(c)
```

Status : Correct

Marks : 10/10

2. Problem Statement

Sita is analyzing her company's daily sales data to find all sales values that are multiples of 5 and exceed 100. She wants to filter these specific sales values from the list.

Help her to implement the task using the numpy package.

Formula:

To filter sales values:

Select all values s from sales such that $(s \% 5 == 0)$ and $(s > 100)$

Input Format

The first line of input consists of an integer value, n , representing the number of sales entries.

The second line of input consists of n floating-point values, sales, separated by spaces, representing daily sales figures.

Output Format

The output prints: filtered_sales

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5

50.0 100.0 105.0 150.0 99.0

Output: [105. 150.]

Answer

```
# You are using Python
import numpy as np
n=int(input())
sales=np.array(list(map(float,input().split()))))
f=sales[(sales%5==0) & (sales>100)]
print(f)
```

Status : Correct

Marks : 10/10

3. Problem Statement

A company tracks the monthly sales data of various products. You are given a table where each row represents a product and each column

represents its monthly sales in sequential months.

Your task is to compute the cumulative monthly sales for each product using numpy, where the cumulative sales for a month is the total sales from month 1 up to that month.

Input Format

The first line of input consists of two integer values, products and months, separated by a space.

Each of the next products lines consists of months integer values representing the monthly sales data of a product.

Output Format

The first line of output prints: "Cumulative Monthly Sales:"

The second line of output prints: the 2D numpy array `cumulative_array` that contains the cumulative sales data for each product.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 2 4
10 20 30 40
5 15 25 35

Output: Cumulative Monthly Sales:
[[10 30 60 100]
[5 20 45 80]]

Answer

```
# You are using Python
import numpy as np
p,m=map(int,input().split())
s_d=[list(map(int,input().split())) for i in range(p)]
s_a=np.array(s_d)
c_a=np.cumsum(s_a,axis=1)
print("Cumulative Monthly Sales:")
print(c_a)
```

Status : Correct

Marks : 10/10

4. Problem Statement

Sita works as a sales analyst and needs to analyze monthly sales data for different cities. She receives lists of cities, months, and corresponding sales values and wants to create a pandas DataFrame using a MultiIndex of cities and months.

Help her to implement this task and calculate total sales for each city.

Input Format

The first line of input consists of an integer value, n , representing the number of records.

The second line of input consists of n space-separated city names.

The third line of input consists of n space-separated month names.

The fourth line of input consists of n space-separated float values representing sales for each city-month combination.

Output Format

The first line of output prints: "Monthly Sales Data with MultiIndex:"

The next lines print the DataFrame with MultiIndex (City, Month) and their corresponding sales values.

The following line prints: "\nTotal Sales Per City:"

The final lines print the total sales per city, computed by grouping the sales data on city names.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4

NYC NYC LA LA
Jan Feb Jan Feb
100 200 300 400

Output: Monthly Sales Data with MultiIndex:

Sales
City Month
NYC Jan 100.0
Feb 200.0
LA Jan 300.0
Feb 400.0

Total Sales Per City:

Sales
City
LA 700.0
NYC 300.0

Answer

```
# You are using Python
import pandas as pd
n=int(input())
c=input().split()
m=input().split()
s=list(map(float,input().split()))
ind=pd.MultiIndex.from_arrays([c,m],names=['City','Month'])
df=pd.DataFrame({'Sales': s},index=ind)
print("Monthly Sales Data with MultiIndex:")
print(df)
tot=df.groupby(level='City').sum()
print("\nTotal Sales Per City:")
print(tot)
```

Status : Partially correct

Marks : 7.5/10

5. Problem Statement

Rekha works in hospital data management and receives patient records with missing or incomplete data. She needs to clean the records by performing the following tasks:

Calculate the mean of the available Age values. Replace any missing (NaN) values in the Age column with this mean age. Remove any rows where the Diagnosis value is missing (NaN). Reset the DataFrame index after removing these rows.

Implement this data cleaning task using the pandas package.

Input Format

The first line of input contains an integer n representing the number of patient records.

The second line contains the CSV header – comma-separated column names (e.g., "Name, Age, Diagnosis, Gender").

The next n lines each contain one patient record in comma-separated format.

Output Format

The first line of output is the text:

Cleaned Hospital Records:

The next lines print the cleaned pandas DataFrame (as produced by `print(cleaned_df)`).

This will include the updated values of the Age column (with missing ages filled by the mean age), and any rows with missing Diagnosis removed.

The DataFrame will be displayed using the default pandas `print()` representation.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5

PatientID, Name, Age, Diagnosis

1, John Doe, 45, Flu

2, Jane Smith, , Cold

3, Bob Lee, 50,

4, Alice Green, 38, Fever

5,Tom Brown,,Infection

Output: Cleaned Hospital Records:

	PatientID	Name	Age	Diagnosis
0	1	John Doe	45.000000	Flu
1	2	Jane Smith	44.333333	Cold
2	4	Alice Green	38.000000	Fever
3	5	Tom Brown	44.333333	Infection

Answer

```
# You are using Python
import pandas as pd
import sys
from io import StringIO
input_data=sys.stdin.read().splitlines()
n=int(input_data[0])
head=input_data[1]
row=input_data[2:n+2]
csv='\n'.join([head]+row)
df=pd.read_csv(StringIO(csv))
df['Age']=pd.to_numeric(df['Age'],errors='coerce')
mean=df['Age'].mean()
df['Age']=df['Age'].fillna(mean)
df_cleaned=df.dropna(subset=['Diagnosis'])
df_cleaned=df_cleaned.reset_index(drop=True)
print("cleaned Hospital Records:")
print(df_cleaned)
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 7_CY

Attempt : 1
Total Mark : 50
Marks Obtained : 47.5

Section 1 : Coding

1. Problem Statement

You are working as a data analyst for a small retail store that wants to track the stock levels of its products. Each product has a unique Name (such as "Toothpaste", "Shampoo", "Soap") and an associated Quantity in stock. Management wants to identify which products have zero stock so they can be restocked.

Write a Python program using the pandas library to help with this task. The program should:

Read the number of products, n. Read n lines, each containing the Name of the product and its Quantity, separated by a space. Convert this data into a pandas DataFrame. Identify and display the Name and Quantity of products with zero stock. If no products have zero stock, display: No products with zero stock.

Input Format

The first line contains an integer n , the number of products.

The next n lines each contain:

`<Product_ID> <Quantity>`

where `<Product_ID>` is a single word (e.g., "Shampoo") and `<Quantity>` is a non-negative integer (e.g., 5).

Output Format

The first line of output prints:

Products with Zero Stock:

If there are any products with zero stock, the following lines print the pandas DataFrame showing those products with two columns: Product_ID and Quantity.

The column headers Product_ID and Quantity are printed in the second line.

Each subsequent line shows the product's name and quantity, aligned under the respective headers, with no index column.

The output formatting (spacing and alignment) follows the default pandas `to_string(index=False)` style.

If no products have zero stock, print:

No products with zero stock.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 3

P101 10

P102 0

P103 5

Output: Products with Zero Stock:

Product_ID	Quantity
------------	----------

P102	0
------	---

Answer

```
# You are using Python
```

```
import pandas as pd
```

```
def identify_zero_stock():
```

```
    n = int(input().strip())
```

```
    data = []
```

```
    for _ in range(n):
```

```
        line = input().strip().split()
```

```
        product_id = line[0]
```

```
        quantity = int(line[1])
```

```
        data.append([product_id, quantity])
```

```
    df = pd.DataFrame(data, columns=["Product_ID", "Quantity"])
```

```
    zero_stock_df = df[df["Quantity"] == 0]
```

```
    print("Products with Zero Stock:")
```

```
    if zero_stock_df.empty:
```

```
        print("No products with zero stock.")
```

```
    else:
```

```
        print(zero_stock_df.to_string(index=False))
```

```
identify_zero_stock()
```

Status : Partially correct

Marks : 7.5/10

2. Problem Statement

Rekha works as an e-commerce data analyst. She receives transaction

data containing purchase dates and needs to extract the month and day from these dates using the pandas package.

Help her implement this task by performing the following steps:

Convert the Purchase Date column to datetime format, treating invalid date entries as NaT (missing).

Create two new columns:

Purchase Month, containing the month (as an integer) extracted from the Purchase Date.

Purchase Day, containing the day (as an integer) extracted from the Purchase Date. Keep the rest of the data as is.

Input Format

The first line of input contains an integer n , representing the number of records.

The second line contains the CSV header — comma-separated column names.

The next n lines each contain a transaction record in comma-separated format.

Output Format

The first line of output is the text:

Transformed E-commerce Transaction Data:

The next lines print the pandas DataFrame with:

The original columns (including Purchase Date, which is now in datetime format or NaT if invalid).

Two additional columns: Purchase Month and Purchase Day.

The output uses the default pandas DataFrame string representation as produced by `print(transformed_df)`.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 3

Customer,Purchase Date

Alice,2023-05-15

Bob,2023-06-20

Charlie,2023-07-01

Output: Transformed E-commerce Transaction Data:

	Customer	Purchase Date	Purchase Month	Purchase Day
0	Alice	2023-05-15	5	15
1	Bob	2023-06-20	6	20
2	Charlie	2023-07-01	7	1

Answer

You are using Python

```
import pandas as pd
```

```
import sys
```

```
def transform_transaction_data():
```

```
    n = int(input().strip())
```

```
    header = input().strip().split(',')
```

```
    data = [input().strip().split(',') for _ in range(n)]
```

```
    df = pd.DataFrame(data, columns=header)
```

```
    df['Purchase Date'] = pd.to_datetime(df['Purchase Date'], errors='coerce')
```

```
    df['Purchase Month'] = df['Purchase Date'].dt.month
```

```
    df['Purchase Day'] = df['Purchase Date'].dt.day
```

```
    print("Transformed E-commerce Transaction Data:")
```

```
    print(df)
```

```
transform_transaction_data()
```

Status : Correct

Marks : 10/10

3. Problem Statement

Arjun is developing a system to monitor environmental sensors installed in different rooms of a smart building. Each sensor records multiple temperature readings throughout the day. To compare sensor data fairly despite differing scales, Arjun needs to normalize each sensor's readings so that they have a mean of zero and standard deviation of one.

Help him implement this normalization using numpy.

Normalization Formula:

Input Format

The first line of input consists of two integers: sensors (number of sensors) and samples (number of readings per sensor).

The next sensors lines each contain samples space-separated floats representing the sensor readings.

Output Format

The first line of output prints: "Normalized Sensor Data:"

The next lines print the normalized readings as a numpy array, where each row corresponds to a sensor's normalized values.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 3 3
1.0 2.0 3.0
4.0 5.0 6.0
7.0 8.0 9.0

Output: Normalized Sensor Data:
[[-1.22474487 0. 1.22474487]
 [-1.22474487 0. 1.22474487]
 [-1.22474487 0. 1.22474487]]

Answer

```
# You are using Python
import numpy as np
def normalize_sensor_data():
    sensors,samples=map(int,input().strip().split())
    data=[]
    for _ in range(sensors):
        readings=list(map(float,input().strip().split()))
        data.append(readings)
```

```
sensor_array=np.array(data)
means=np.mean(sensor_array,axis=1,keepdims=True)
stds=np.std(sensor_array,axis=1, keepdims=True)
normalized=(sensor_array-means)/stds
print("Normalized Sensor Data:")
print(normalized)
normalize_sensor_data()
```

Status : Correct

Marks : 10/10

4. Problem Statement

Arjun is monitoring hourly temperature data recorded continuously for multiple days. He needs to calculate the average temperature for each day based on 24 hourly readings.

Help him to implement the task using the numpy package.

Formula:

Reshape the temperature readings into rows where each row has 24 readings (one day).

Average temperature per day = mean of 24 hourly readings in each row.

Input Format

The first line of input consists of an integer value, n, representing the total number of temperature readings.

The second line of input consists of n floating-point values separated by spaces, representing hourly temperature readings.

Output Format

The output prints: avg_per_day

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 30

30.0 30.0 30.0 30.0 30.0 30.0 30.0 30.0 30.0 30.0 30.0 30.0 30.0 30.0 30.0
30.0 30.0 30.0 30.0 30.0 30.0 30.0 30.0

Output: [30.]

Answer

You are using Python

```
import numpy as np
```

```
def calculate_daily_averages():
```

```
    n=int(input().strip())
```

```
    temp=list(map(float,input().strip().split()))
```

```
    temp_arr=np.array(temp)
```

```
    da=temp_arr.reshape(-1,24)
```

```
    avg=np.mean(da,axis=1)
```

```
    print(avg)
```

```
calculate_daily_averages()
```

Status : Correct

Marks : 10/10

5. Problem Statement

Rekha is a meteorologist analyzing rainfall data collected over 5 years, with monthly rainfall recorded for each year. She wants to find the total rainfall each year and also identify the month with the maximum rainfall for every year.

Help her to implement the task using the numpy package.

Formula:

Yearly total rainfall = sum of all 12 months' rainfall for each year

Month with max rainfall = index of the maximum rainfall value within the 12 months for each year (0-based index)

Input Format

The input consists of 5 lines.

Each line contains 12 floating-point values separated by spaces, representing the rainfall data (in mm) for each month of that year.

Output Format

The first line of output prints: yearly_totals

The second line of output prints: max_rainfall_months

Refer to the sample output for the formatting specifications.

Sample Test Case

```
Input: 1.0 2.0 3.0 4.0 5.0 6.0 7.0 8.0 9.0 10.0 11.0 12.0
2.0 3.0 4.0 5.0 6.0 7.0 8.0 9.0 10.0 11.0 12.0 13.0
3.0 4.0 5.0 6.0 7.0 8.0 9.0 10.0 11.0 12.0 13.0 14.0
4.0 5.0 6.0 7.0 8.0 9.0 10.0 11.0 12.0 13.0 14.0 15.0
5.0 6.0 7.0 8.0 9.0 10.0 11.0 12.0 13.0 14.0 15.0 16.0
Output: [ 78.  90. 102. 114. 126.]
[11 11 11 11 11]
```

Answer

```
# You are using Python
import numpy as np
```

```
def rain():
    rdata=[]
    for _ in range(5):
        month=list(map(float,input().strip().split()))
        rdata.append(month)
    array=np.array(rdata)
    year=np.sum(array,axis=1)
    m=np.argmax(array,axis=1)
    print(year)
    print(m)
rain()
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Dhana Sri S
Email: 240701110@rajalakshmi.edu.in
Roll no: 240701110
Phone: 7904020218
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 7_PAH

Attempt : 1
Total Mark : 50
Marks Obtained : 43.5

Section 1 : Coding

1. Problem Statement

Arjun is a data scientist working on an image processing task. He needs to normalize the pixel values of a grayscale image matrix to scale between 0 and 1. The input image data is provided as a matrix of integers.

Help him to implement the task using the numpy package.

Formula:

To normalize each pixel value in the image matrix:

$$\text{normalized_pixel} = (\text{pixel} - \text{min_pixel}) / (\text{max_pixel} - \text{min_pixel})$$

where min_pixel and max_pixel are the minimum and maximum pixel values in the image matrix, respectively. If all pixel values are the same, the normalized image matrix should be filled with zeros.

Input Format

The first line of input consists of an integer value, rows, representing the number of rows in the image matrix.

The second line of input consists of an integer value, cols, representing the number of columns in the image matrix.

The next rows lines each consist of cols integer values separated by a space, representing the pixel values of the image matrix.

Output Format

The output prints: normalized_image

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 2

3

1 2 3

4 5 6

Output: [[0. 0.2 0.4]

[0.6 0.8 1.]]

Answer

```
# You are using Python
import numpy as np
def n():
    row=int(input().strip())
    col=int(input().strip())
    p=[]
    for _ in range(row):
        rv=list(map(int,input().strip().split()))
        p.append(rv)
    image=np.array(p)
    mi=np.min(image)
    ma=np.max(image)
    if mi==ma:
        nor=np.zeros_like(image,dtype=float)
```

```
else:  
    nor=(image-mi)/(ma-mi)  
    print(nor)  
n()
```

Status : Correct

Marks : 10/10

2. Problem Statement

A company conducted a customer satisfaction survey where each respondent provides their RespondentID and an optional textual Feedback. Sometimes, respondents submit their ID without any feedback or with empty feedback.

Your task is to process the survey responses using pandas to replace any missing or empty feedback with the phrase "No Response". Finally, print the cleaned survey responses exactly as shown in the sample output.

Input Format

The first line contains an integer n , the number of survey responses.

Each of the next n lines contains:

A RespondentID (a single alphanumeric string without spaces),

Followed optionally by a Feedback string, which may be empty or missing.

If no feedback is provided after the RespondentID, treat it as missing.

Output Format

Print the line:

Survey Responses with Missing Feedback Filled:

Then print the cleaned survey data as a table with two columns: RespondentID and Feedback.

The table should have the headers exactly as:

RespondentID Feedback

Print each respondent's data on a new line, aligned to match the output produced by `pandas.DataFrame.to_string(index=False)`.

For any missing or empty feedback, print "No Response" in the Feedback column.

Maintain the spacing and alignment exactly as shown in the sample outputs.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4

101 Great service

102

103 Loved it

104

Output: Survey Responses with Missing Feedback Filled:

RespondentID	Feedback
--------------	----------

101	Great service
-----	---------------

102	No Response
-----	-------------

103	Loved it
-----	----------

104	No Response
-----	-------------

Answer

```
# You are using Python
```

```
import pandas as pd
```

```
def pr():
```

```
    n=int(input().strip())
```

```
    data=[]
```

```
    for _ in range(n):
```

```
        l=input().strip()
```

```
        p=l.split(' ',1)
```

```

r=p[0]
f=p[1] if len(p)>1 else""
data.append((r,f))
df=pd.DataFrame(data,columns=['RespondentID','Feedback'])
df['Feedback']=df['Feedback'].replace(",','No Response'")
print("Survey Responses with Missing FeedBack Filled:")
print(df.to_string(index=False))
pr()

```

Status : Partially correct

Marks : 7.5/10

3. Problem Statement

A software development company wants to classify its employees based on their years of service at the company. They want to categorize employees into three experience levels: Junior (less than 3 years), Mid (3 to 6 years, inclusive), and Senior (more than 6 years).

Experience Level Classification:

Junior: Years at Company < 3

Mid: $3 \leq$ Years at Company < 6

Senior: Years at Company > 5

You need to create a Python program using the pandas library that reads employee data, processes it into a DataFrame, and adds a new column "Experience Level" to display the appropriate classification for each employee.

Input Format

First line: an integer n representing the number of employees.

Next n lines: each line has a string Name and a floating-point number Years at Company (space-separated).

Output Format

First line: "Employee Data with Experience Level:"

The employee data table printed with no index column, and with columns: Name,

Years at Company, Experience Level.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5

Alice 2

Bob 4

Charlie 7

Diana 3

Evan 6

Output: Employee Data with Experience Level:

Name	Years at Company	Experience Level
Alice	2.0	Junior
Bob	4.0	Mid
Charlie	7.0	Senior
Diana	3.0	Mid
Evan	6.0	Senior

Answer

You are using Python

```
import pandas as pd
```

```
def classify(years):
```

```
    if years<3:
```

```
        return "Junior"
```

```
    elif 3<=years<6:
```

```
        return "Mid"
```

```
    else:
```

```
        return "Senior"
```

```
def main():
```

```
    n=int(input())
```

```
    names=[]
```

```
    y=[]
```

```
    for _ in range(n):
```

```
        e=input().strip().split(" ")
```

```
        name=e[0]
```

```
        ye=float(e[1])
```

```
        names.append(name)
```

```
        y.append(ye)
```

```
df=pd.DataFrame({
    'Name':names,
    'Years at Company': y
})
df['Experience Level']=df['Years at Company'].apply(classify)
print("Employee Data with Experience Level:")
print(df.to_string(index=False))
if __name__ == "__main__":
    main()
```

Status : Correct

Marks : 10/10

4. Problem Statement

You're analyzing the daily returns of a set of financial assets over a period of time. Each day is represented as a row in a 2D array, where each column represents the return of a specific asset on that day.

Your task is to identify which days had all positive returns across every asset using numpy, and output a boolean array indicating these days.

Input Format

The first line of input consists of two integer values, rows and cols, separated by a space.

Each of the next rows lines consists of cols float values representing the returns of the assets for that day.

Output Format

The first line of output prints: "Days where all asset returns were positive:"

The second line of output prints: the boolean array positive_days, indicating True for days where all asset returns were positive and False otherwise.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 3 4

0.01 0.02 0.03 0.04

0.05 0.06 0.07 0.08

-0.01 0.02 0.03 0.04

Output: Days where all asset returns were positive:

[True True False]

Answer

You are using Python

import numpy as np

def main():

rows,cols=map(int,input().strip().split())

data=[]

for _ in range(rows):

r=list(map(float,input().strip().split()))

data.append(r)

arr=np.array(data)

p=np.all(arr>0,axis=1)

print("Days where all asset returns were positive:")

print(p)

if __name__=="__main__":

main()

Status : Correct

Marks : 10/10

5. Problem Statement

Arjun manages a busy customer service center and wants to analyze the distribution of customer wait times to improve service efficiency. He decides to group the wait times into intervals of 5 minutes each and count how many customers fall into each interval bucket.

Help him implement this bucketing and counting task using NumPy.

Bucketing Logic:

Divide the wait times into intervals (buckets) of size 5 minutes, e.g.:

[0-5), [5-10), [10-15), ...

Use NumPy's digitize function to determine which bucket each wait time

falls into.

Count the number of wait times in each bucket and generate bucket labels.

Input Format

The first line contains an integer n , the number of customer wait times recorded.

The second line contains n space-separated floating-point numbers representing the wait times (in minutes).

Output Format

The first line of output is the text:

Wait Time Buckets and Counts:

Each subsequent line prints the bucket range and the number of wait times in that bucket, formatted as:

<bucket_range>: <count>

where <bucket_range> is the lower and upper bound of the bucket (inclusive lower bound, exclusive upper bound), for example:

0-5: 3

5-10: 2

10-15: 1

The output uses the default string formatting of Python's `print()` function (no extra spaces, no special formatting beyond the specified lines).

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 10

2.0 3.0 7.0 8.0 12.0 14.0 18.0 19.0 21.0 25.0

Output: Wait Time Buckets and Counts:

0-5: 2

5-10: 2

10-15: 2

15-20: 2

20-25: 1

Answer

You are using Python

```
import numpy as np
```

```
import math
```

```
n=int(input())
```

```
w=list(map(float,input().split()))
```

```
m=max(w)
```

```
u=math.ceil(m/5)*5
```

```
b=np.arange(0,u+5,5)
```

```
buck=np.digitize(w,b,right=False)
```

```
counts=np.bincount(buck,minlength=len(b))
```

```
o=["Wait Time Buckets and Counts:"]
```

```
for i in range(len(b)-1):
```

```
    l=b[i]
```

```
    up=b[i+1]
```

```
    c=counts[i+1]
```

```
    if c>0:
```

```
        o.append(f"{l}-{up}:{c}")
```

```
print(" ".join(o))
```

Status : Partially correct

Marks : 6/10