

HTTP PUSH API

Private & Confidential



Connectivity



Security



Collaboration



Cloud & SaaS



Marketing & IoT

Revision History

Version	Change Type	Description	Date
1.0	Initial Draft	Updated TLV Parameter for DLT/UCC guidelines in SMPP Interface.	17 th Nov 2020
1.1	Updated Error Codes	Updated Scrubbing Error Codes list	27 th Jan 2020
1.2	Updated Error Codes	Updated Scrubbing Error Codes list	29 th Jul 2021

SMS Push HTTP Query String (QS) Interface

Contents

1 Document Overview

1.1 Scope

1.2 Audience

2 SMS Push HTTP Query String

2.1 Usage

2.1.1 DR on HTTP interface

2.2 Example

2.2.1 Test Bed HTTP connection details

2.3 Interface Response Error Codes

2.4 HTTP interface Delivery Report Example

1 Document Overview

1.1 Scope

This document provides a guide for using the SMS (Short Message Service) URL (Uniform Resource Locator) interface. It describes the usage of HTTP (Hyper Text Transport Protocol) interface over GET method. The parameters mentioned in this document are used to submit and query requests.

1.2 Audience

It is intended for designers and implementers of push Query String (QS) interface using Ngage.

2 SMS Push HTTP Query String

The API is used to push a single SMS to handset (non-bulk AO-MT flow) over http query string. This API is mainly invoked from CP who wants to push non-bulk SMS

2.1 Usage

The interface supports only GET method. URL can be over either http or https. Sample Submit Request:

```
https://host:port/campaignService/campaigns/qs?channel=2.1&recipient=919900244982&contentType=3.1&dr=false&msg=Welcome&user=ecpDemoUser&pswd=ecpDemo&sender=AM-12&isDrReqInJson=1
```

The following are the QUERY_STRING parameters.

Table 2-1: Request Parameters

S. No.	Field Name	Details	
1	User	Description	User name of the Ngage user
		Presence	Conditional: ▪ Optional when authtoken is set
		Default	NA
		Data Type	String
		Remarks	In absence of user name & password, a validated authtoken can be set from API testing tool like Postman in the headers or any other third Party Integrated software
2	Pswd	Description	Encrypted Password of the Ngage user
		Presence	Conditional: ▪ Optional when authtoken is set
		Default	NA
		Data Type	string
		Remarks	In absence of user name & password, a validated authtoken can be set from API testing tool like Postman in the headers or any other third Party Integrated software
3	Msg	Description	Contents of the message
		Presence	Mandatory
		Default	NA
		Data Type	String
		Remarks	If the message has special characters, it should be URL encoded (Maximum URL length is 2000 chars)
4	Recipient	Description	Recipient Mobile Number (MSISDN)
		Presence	Mandatory
		Default	NA
		Data Type	String
		Remarks	Mobile number given should include the national calling code. Example: 919823456789 In the above example, "91" is India's calling code followed by actual mobile number of the recipient
5	Sender	Description	Originator address (or default MSISDN)
		Presence	Mandatory
		Default	Sender's contact number (or default MSISDN) as stored in Ngage
		Data Type	String
		Remarks	Content provider sends the sender id

6	contentType	Description	Content type of message. Only following contentType are valid through queryString interface: "3.1" for Text "3.3" for Text Flash (Not Supported in GUI) "3.3.1" for Unicode Flash (Not Supported in GUI) "3.7" for Unicode
		Presence	Optional
		Default	NA
		Data Type	String
		Remarks	This is deprecated and moved out of this table. It will be auto detected in the application.
7	Dr	Description	Flag to enable or disable the delivery report Value: 1 or true for enable 0 or false for disable
		Presence	Optional
		Default	0 or false for disable
		Data Type	Boolean
		Remarks	-
		Presence	Optional
		Default	Current time
		Data Type	String
		Remarks	In case past date and time is sent then the request is rejected and bad request
8	Channel	Description	Request type supported by Ngage. Currently Ngage supports SMS and USSD for QS interface: ▪ "2.1" for SMS Channel ▪ "2.3" for USSD Channel
		Presence	Optional
		Default	2.1
		Data Type	String
		Remarks	
9	PE_ID	Description	PE_ID is optional and is send for customization of DLT integration
		Presence	Mandatory
		Default	Not sent
		Data Type	String
		Remarks	DLT parameter
10	Template_ID	Description	Template_ID is optional and is send for customization of DLT integration
		Presence	Option , even when DLT integration is enabled

		Default	Not sent
		Data Type	String
		Remarks	DLT parameter
11	drUri	Description	drUri is an optional parameter to specify the callback DR URL to be used
		Presence	Optional
		Default	Not sent
		Data Type	String
		Remarks	Use to send DR call back
12	recipients	Description	List of Recipient Mobile Number (MSISDN)
		Presence	Mandatory if recipient field is not present
		Default	NA
		Data Type	String
		Remarks	Mobile number given should include the national calling code. Example: 919823456789 In the above example, “91” is India’s calling code followed by actual mobile number of the recipient Recipient should be a comma-separated list of numbers. Note – Max number of recipients allowed is 250.
13	campaign Name	Description	Name given for the campaign
		Presence	Conditional: ▪ Mandatory for bulk campaign
		Default	NA
		Data Type	String
		Remarks	-
14	isDrReqInJson	Description	Enable the flag to send the DR request in JSON format.
		Presence	Optional
		Default	0
		Data Type	Boolean
		Remarks	isDrReqInJson = 1 – DR request goes in json format isDrReqInJson = 0 – DR request goes in default format If the key is not there in the request – DR request goes in default format

The following mandatory parameters are required for pushing the content for submit request.

Mandatory

- msg
- recipient

- recipients (Bulk)
- campaignName (Bulk)
- user
- pswd
- sender

Optional

- channel
- contentType
- dr
- PE_ID (For DLT integration)
- Template_ID(For DLT integration)
- drUri(non-bulk only)
- isDrReqInJson

2.1.1 User Name and Password

A valid authorized account must exist on Ngage to push the message. Thus, the same user name and password must be mentioned to use this interface. In absence of user name & password, a validated authtoken should be set in the header of the HTTP request.

2.1.2 Recipient

The mobile number given should be in international format. Example: 919823456789

2.1.3 Sender

User can use one of the sender addresses approved by administrator to the interface for pushing the SMS message.

2.1.4 DR on HTTP interface

To enable a HTTP DR for the user on QS interface the enterprise user first needs to define a HTTP DR URL in the user's profile section:

Once the highlighted section defined user needs to pass another additional parameter in the existing QS URL:

S. No.	Field Name	Details	
1	Dr	Description	This is the dr required flag for the interface
		Presence	Conditional: - Optional when DR is required 1 – If DR is required 0 – If DR is not required (Default if not sent DR is set to 0)
		Default	0
		Data Type	Integer

Example is provided in the below section

2.2 Example

Submit Request for Promo message:

```
https://host:port/campaignService/campaigns/qs?channel=2.1&recipient=919900244982&contentType=3.1&dr=false&msg=Welcome&user=ecpDemoUser&pswd=ecpDemo&sender=AM-12
```

Submit Request for Transactional message:

```
https://host:port/campaignService/campaigns/qs?channel=2.1&recipient=919900244982&contentType=3.1&dr=false&msg=Welcome&user=ecpDemoUser&pswd=ecpDemo&sender=AM-12
```

Submit request with DLT parameters:

```
https://host:port/campaignService/campaigns/qs?channel=2.1&recipient=919900244982&contentType=3.1&dr=false&msg=Welcome&user=ecpDemoUser&pswd=ecpDemo&sender=AM-12
```


pDemoUser&pswd=ecpDemo&sender=AM-
12&PE_ID=123456789012&TemplateID=883312345678

Submit request in case dr URL is sent along the request:

https://host:port/campaignService/campaigns/qs?channel=2.1&recipient=919900244982&contentType=3.1&dr=false&msg=Welcme&user=ecpDemoUser&pswd=ecpDemo&sender=AM-12&PE_ID=123456789012&TemplateID=883312345678&drUri=http%3A%2F%2Ftest.exmpale.com%3A7777%2Fcallback%2Fdr

2.2.1 Test Bed HTTP connection details

Test Bed:

Host: 10.163.3.13

Port: 9095

2.3 Interface Response Error Codes

Table 2-2: Response Error Codes

Error Code	Error Description
401	CP User does not exist in the database/Invalid Authorization
400	Bad request (one of the mandatory fields is missing except username/password)
500	Internal server error
402	Payment required
504	Gateway timeout

Response Format:

response body|Response code|Submission ID Description

Example

```
"Invalid authorization"|401
{"jobId":"760685587926"}|201
{
  jobId: "2111571224187625",
  requireApproval: false,
  jobCost: "1.50",
  recipientCnt: 1,
  totalCnt:1,
  campaignId:"2111571224187625"
}
```

For Success

Table 2-3: Success Code

Response	Submission ID	Status Code	Description
"jobId": "391576903710"	391576903710	201	Accepted

2.4 Example for DR of HTTP interface

In case CP wants dr request back then the push request should be with dr=1

Submit Request

```
https://host:port/campaignService/campaigns/qs?channel=2.1&recipient=919900244982&contentType=3.1&dr=false&msg=Welcome&user=ecpDemoUser&pswd=ecpDemo&sender=AM-12&dr=1
```

DR request:

```
url: "http://<CP IP>:<CP_PORT>",
method: POST,
headers: {Authorization=Basic SW50ZWdyYWNpb246U3lub3BzaXMyMDE4,
Content-Type=application/json},
body:
DRType: Nonbulk
SubmissionID: 312111605529927798
Recipient: 916543217890
DeliveryStatusCode: 2
DeliveryStatus: DELIVERED
DeliveryTimestamp: 1605529928957
```

- **CP-IP:** Content provider application IP address
- **CP-PORT:** Content provider application port

Submit Request:

https://host:port/campaignService/campaigns/qs?channel=2.1&recipient=919900244982&contentType=3.1&dr=false&msg=Welcome&user=ecpDemoUser&pswd=ecpDemo&sender=AM-12&dr=1&isDrReqInJson=1

DR Request:

```
"http:// <CP IP>:<CP Port>",
method: POST,
headers : {Authorization=Basic SW50ZWdyYWNpb246U3lub3BzaXMyMDE4,
ContentType=application/json}
body : {
"DRType":"Nonbulk",
"SubmissionID":"312131626262740537",
"Recipient":"917073157574",
"DeliveryStatusCode":"2",
"DeliveryStatus":"DELIVERED",
"DeliveryTimestamp":"1626262743160"
```

}

Table 2-4: DR request description

S. No.	Field Name	Details	
1	DRType	Description	Delivery request type either Bulk or Nonbulk
		Presence	Mandatory
		Default	NA
		Data Type	String
		Remarks	Value represents the DR is for non-bulk or bulk requests
2	SubmissionID	Description	Message submission id created in middleware
		Presence	Mandatory
		Default	NA
		Data Type	String
		Remarks	Sample id looks like 312111605529927798
3	Recipient	Description	Destination address
		Presence	Mandatory
		Default	NA
		Data Type	String
		Remarks	Destination MSISDN with country code
4	DeliveryStatusCode	Description	Predefined status code for different delivery status
		Presence	Mandatory
		Default	NA
		Data Type	String
		Remarks	Please refer to Table 2-4-1 and 2-4-2 (DLT error codes)
5	DeliveryStatus	Description	Status of the message if it is delivered to end subscriber or not
		Presence	Mandatory
		Default	NA

		Data Type	String
		Remarks	Please refer to Table 2-4-1
6	DeliveryTimestamp	Description	Timestamp at which DR is received
		Presence	Mandatory
		Default	NA
		Data Type	String [UNIX timestamp]
		Remarks	Sample value - 1605529928957

Table 2-4-1: Delivery Status and Delivery Status Code

DeliveryStatus	DeliveryStatusCode
SCHEDULED	0
DELIVERED	2
EXPIRED	3
UNDELIVERABLE	5
ACCEPTED	6
UNKNOWN	7
REJECTED	8
FAILED	10
DELIVERY_FAILED	11
Delivery-Timeout	912

DR for DLT Error Codes:

In case of DLT error codes on DLT request, middleware sends the DR with Delivery Status as UNDELIVERABLE and Delivery Status Code with below error codes. Descriptions of each error code mentioned in the below table

Table 2-4-2: Delivery Status and Delivery Status Code for DLT error codes

Delivery Status Code	Delivery Status Description
74	Category has been Blocked
75	Mode is blocked
76	Mandatory fields are missing

79	Entity is blacklisted
80	Entity is not active
81	RTM is blacklisted
82	RTM is not active
83	Header is not active
84	Header is blacklisted
85	Header is not owned by Entity
86	Temple ID not registered in DLT system
87	Content template is not owned by Entity
88	Input file format is not valid
89	RTM is unauthorized
90	Template ID status in DLT is in Inactive or Blocked state
91	Invalid MSISDN number
92	Template dynamic variable exceeded max length
93	Invalid API Key
94	Invalid Template ID - NULL or Alpha or Length not valid
95	Header is not mapped with template
96	Consent Template is not mapped with template
97	SMS content is not mapped with template
98	No Available Time to Deliver
99	Days are Blocked
100	HTTP Client errors(4xx)
101	HTTP Server Errors(5xx)
600	Native Error from SMSC
601	Internal Module Timeout,
604	Message Timedout
602	Submit Failed - EXPIRED
603	Message Expired
605	UDH missing fragment
702	Submit Failed - SUBMIT_FAILED
703	Message Expired
704	Message Expired
705	UDH missing fragment