Lead Integration & Distribution Middleware — Full API List

All HTTP endpoints exposed by the NestJS API · source: `apps/api/src/modules/**/*.controller.ts` · 84 endpoints in 16 controllers

BASE URL
`http://localhost:4000/api/v1`

VERSIONING
URI (`/api/v1` prefix)

AUTH
Bearer JWT (900 s) or `x-api-key`

ENVELOPE
`{ success, data | error }`

PAGINATION
cursor + limit (default 25, max 100)

STATUS CODES
POST → 201, others → 200

Notes. The CSV error download (`GET /imports/:id/errors`) is the only endpoint that bypasses the response envelope (`@SkipTransform`, returns `text/csv`). Public routes (marked `public`) need no token. Permissions are re-loaded from the role on every request; UI visibility is UX-only — the API enforces every permission. Rate limits: 300 req/min global, 20/min on login/refresh, 600/min on inbound webhooks.

Legend: GET read · POST create / action · PUT replace · PATCH update · DELETE remove · `public` unauthenticated

1. Health

#	METHOD	PATH	PERMISSION	DESCRIPTION
1	GET	/health	public	Liveness/readiness probe with real dependency checks (Postgres `SELECT 1`, Redis PING)

2. Authentication

#	METHOD	PATH	PERMISSION	DESCRIPTION
2	POST	/auth/login	public	Exchange credentials for access + refresh tokens (rate-limited, audited)
3	POST	/auth/refresh	public	Rotate the refresh token and mint a new access token (reuse detection revokes all sessions)
4	POST	/auth/logout	public	Revoke the current session (refresh token rotation guard)
5	GET	/auth/me	authenticated	Current user, role and permissions

3. Users

#	METHOD	PATH	PERMISSION	DESCRIPTION
6	GET	/users	users:read	List users (cursor paginated)
7	POST	/users	users:write	Create a user (bcrypt cost 12, audited)
8	PATCH	/users/:id	users:write	Update a user's name, role or status

4. Roles

#	METHOD	PATH	PERMISSION	DESCRIPTION
9	GET	/roles	roles:read	List application roles (with user counts)
10	GET	/roles/permissions	roles:read	Static permission catalog and role templates (fixed reference data)
11	POST	/roles	roles:write	Create a custom role
12	PATCH	/roles/:id	roles:write	Update a custom role (system roles are immutable)
13	DELETE	/roles/:id	roles:write	Delete a custom role (fails while users are assigned)

5. API Keys

#	METHOD	PATH	PERMISSION	DESCRIPTION
14	GET	/api-keys	apikeys:read	List API keys (never exposes the key or its hash)
15	POST	/api-keys	apikeys:write	Create an API key — the raw key is returned only once
16	DELETE	/api-keys/:id	apikeys:write	Revoke an API key (idempotent)

6. Sources (lead sources & inbound accounts)

#	METHOD	PATH	PERMISSION	DESCRIPTION
17	GET	/sources	sources:read	List lead sources with account/lead counts
18	POST	/sources	sources:write	Create a lead source
19	GET	/sources/:id	sources:read	Source detail with its inbound accounts
20	PATCH	/sources/:id	sources:write	Update a lead source
21	DELETE	/sources/:id	sources:write	Delete a source (blocked while leads exist)
22	GET	/sources/:id/accounts	sources:read	List inbound accounts (with webhook URLs)
23	POST	/sources/:id/accounts	sources:write	Create an inbound account and public webhook URL
24	PATCH	/sources/accounts/:accountId	sources:write	Update an inbound account
25	DELETE	/sources/accounts/:accountId	sources:write	Delete an inbound account (blocked while leads exist)
26	POST	/sources/accounts/:accountId/rotate-secret	sources:write	Rotate the webhook signing secret (returned ONCE)

7. Destinations (CRM / endpoints)

#	METHOD	PATH	PERMISSION	DESCRIPTION
27	GET	/destinations/types	destinations:read	Supported destination types + required config keys (from adapters)
28	GET	/destinations	destinations:read	List destinations with health and delivery counts
29	POST	/destinations	destinations:write	Create a destination
30	GET	/destinations/:id	destinations:read	Destination detail (credential metadata only, never the secret)
31	PATCH	/destinations/:id	destinations:write	Update a destination
32	DELETE	/destinations/:id	destinations:write	Delete a destination (blocked while deliveries exist)
33	PUT	/destinations/:id/credential	destinations:write	Set/replace the destination credential (write-only; never returned)
34	DELETE	/destinations/:id/credential	destinations:write	Remove the destination credential
35	GET	/destinations/:id/health	destinations:read	Last known destination health (real probe results)
36	POST	/destinations/:id/test	destinations:test	Run a REAL connectivity/auth probe against the destination

8. Webhooks (inbound)

#	METHOD	PATH	PERMISSION	DESCRIPTION
37	POST	/webhooks/inbound/:publicId	public	Inbound lead webhook (idempotent, fast-ack; rate-limited 600/min)
38	GET	/webhooks/events	sources:read	Inbound webhook event log (status, duplicates, errors)
39	GET	/webhooks/events/:id	sources:read	Webhook event detail (sanitized payload)

9. Leads

#	METHOD	PATH	PERMISSION	DESCRIPTION
40	GET	`/leads`	`leads:read`	List leads (cursor pagination, filters, exact-match search, filtered `total`, server-side date/time ranges in APP_TIMEZONE)
41	POST	`/leads`	`leads:write`	Create a lead manually (enqueued for processing; 409 on duplicate external id)
42	POST	`/leads/selection`	`leads:read`	Resolve every lead matching the filters into an expiring server-side selection token (≤ LEAD_SELECTION_MAX)
43	POST	`/leads/manual-send/preview`	`leads:replay`	Authoritative eligibility counts before a manual send (combinations, skipped, limits)
44	POST	`/leads/manual-send`	`leads:replay`	Queue deliveries for the selected leads (bounded batches, audited, idempotent)
45	GET	`/leads/:id`	`leads:read`	Lead detail with processing, scores and deliveries
46	GET	`/leads/:id/timeline`	`leads:read`	Immutable pipeline timeline (stage events, scores, routing)
47	GET	`/leads/:id/payloads`	`leads:read`	Raw inbound payloads + canonical data
48	POST	`/leads/:id/replay`	`leads:replay`	Re-run the processing pipeline for a lead (audited)
49	DELETE	`/leads/:id`	`leads:delete`	Delete a lead and its processing history (audited with before-snapshot)

10. Routing Rules

#	METHOD	PATH	PERMISSION	DESCRIPTION
50	GET	`/routing-rules`	`routing:read`	List routing rules ordered by priority
51	POST	`/routing-rules`	`routing:write`	Create a routing rule with its ordered destinations
52	POST	`/routing-rules/preview`	`routing:read`	Dry-run rule evaluation for a sample lead (same engine as the worker; nothing persisted)
53	PATCH	`/routing-rules/:id`	`routing:write`	Update a routing rule (bumps its version)
54	DELETE	`/routing-rules/:id`	`routing:write`	Delete a routing rule

11. Field Mappings

#	METHOD	PATH	PERMISSION	DESCRIPTION
55	GET	`/field-mappings`	`mappings:read`	List field mappings (optionally filtered by destination)
56	GET	`/field-mappings/:id`	`mappings:read`	Get a field mapping with all of its versions (newest first)
57	POST	`/field-mappings`	`mappings:write`	Create a field mapping with version 1
58	POST	`/field-mappings/:id/versions`	`mappings:write`	Append a new version to a field mapping
59	POST	`/field-mappings/:id/activate`	`mappings:write`	Activate an existing version of a field mapping
60	DELETE	`/field-mappings/:id`	`mappings:write`	Delete a field mapping

12. Deliveries

#	METHOD	PATH	PERMISSION	DESCRIPTION
61	GET	`/deliveries/queue-stats`	`deliveries:read`	Real BullMQ queue + dead-letter counts (errors reported verbatim)
62	GET	`/deliveries/dead-letter`	`deliveries:read`	Dead-lettered jobs with failure reasons (e.g. `?queue=delivery`)
63	GET	`/deliveries/failed`	`deliveries:read`	Failed jobs awaiting retry/dead-lettering
64	GET	`/deliveries/stats`	`deliveries:read`	Live status counts for one operation (`?correlationId=` manual-send progress)

#	METHOD	PATH	PERMISSION	DESCRIPTION
65	GET	`/deliveries`	`deliveries:read`	List deliveries (cursor pagination + filters)
66	GET	`/deliveries/:id`	`deliveries:read`	Delivery detail with the full attempt history
67	POST	`/deliveries/:id/replay`	`deliveries:retry`	Replay a FAILED/DEAD delivery (audited; attempt history preserved)

13. Imports (CSV)

#	METHOD	PATH	PERMISSION	DESCRIPTION
68	POST	`/imports`	`imports:write`	Upload a CSV file and queue it for import (multipart, 10 MB / 100k rows / 200 cols)
69	GET	`/imports`	`imports:read`	List import jobs (cursor paginated)
70	GET	`/imports/:id`	`imports:read`	Get a single import job (full row)
71	GET	`/imports/:id/row-errors`	`imports:read`	List failed rows (row number + reason), cursor paginated
72	GET	`/imports/:id/errors`	`imports:read`	Download the CSV error report (text/csv, bypasses envelope)

14. Audit Logs

#	METHOD	PATH	PERMISSION	DESCRIPTION
73	GET	`/audit-logs`	`audit:read`	List application audit log entries (cursor paginated)

15. Analytics

#	METHOD	PATH	PERMISSION	DESCRIPTION
74	GET	`/analytics/overview`	`analytics:read`	Dashboard overview — real aggregates over PostgreSQL
75	GET	`/analytics/timeseries`	`analytics:read`	Daily lead intake + delivery outcomes (1–90 days)
76	GET	`/analytics/sources`	`analytics:read`	Per-source lead counts by status
77	GET	`/analytics/destinations`	`analytics:read`	Per-destination delivery success rate + latency
78	GET	`/analytics/pipeline`	`analytics:read`	Pipeline funnel — leads by current stage

16. Automation (scoring / dedup / enrichment)

#	METHOD	PATH	PERMISSION	DESCRIPTION
79	GET	`/automation/scoring`	`scoring:read`	List all scoring rule set versions
80	POST	`/automation/scoring`	`scoring:write`	Create the next scoring rule set version
81	PATCH	`/automation/scoring/:id`	`scoring:write`	Enable or disable a scoring rule set
82	GET	`/automation/dedup`	`dedup:read`	Get the deduplication config (created with defaults on first read)
83	PUT	`/automation/dedup`	`dedup:write`	Replace the deduplication config
84	GET	`/automation/enrichment`	`enrichment:read`	Enrichment provider status (not configured in this phase)

Permission summary (34 codes)

- `leads:read`, `leads:write`, `leads:replay`, `leads:delete`
- `sources:read`, `sources:write` · `destinations:read`, `destinations:write`, `destinations:test`
- `routing:read`, `routing:write` · `mappings:read`, `mappings:write`

- `scoring:read`, `scoring:write` · `dedup:read`, `dedup:write` · `enrichment:read`, `enrichment:write`
- `deliveries:read`, `deliveries:retry` · `imports:read`, `imports:write`
- `analytics:read` · `audit:read`
- `users:read`, `users:write` · `roles:read`, `roles:write` · `apikeys:read`, `apikeys:write`
- `settings:read`, `settings:write`

System roles

- **admin** — all permissions
- **manager** — all reads + operational writes + `deliveries:retry`
- **developer** — all reads + integration writes + `apikeys:write`
- **viewer** — read-only

Generated from source on 2026-10-14 · Lead Integration & Distribution Middleware · 84 endpoints · 16 controllers · OpenAPI spec also available at `docs/openapi.yaml`