S.B. J AIN INSTITUTE OF TECHNOLOGY MANAGEMENT & RESEARCH, NAGPUR

Practical 05

Aim: Write a program to implement Shortest Job First (SJF) Preemptive Scheduling for three processes and calculate the total context switches and average waiting time. The processes have burst times 10 ns, 20 ns, and 30 ns, arriving at 0ns, 2ns, and 6ns, respectively.

Name: Dhanshri Gaurkhede

USN: CM24013

Semester / Year: 4th /2nd

Academic Session: 2025-26

Date of Performance:

Date of Submission:

❖ **Aim:** Writeaprogram to implement Shortest Job First (SJF) Preemptive Schedulingfor three processes and calculate the total context switches and average waiting time. The processes have burst times 10ns, 20ns, and 30ns, arriving at0ns, 2ns, and 6ns, respectively.

❖ **Objectives:**

Understand SJF Preemptive Scheduling: Implement the **Shortest Job First (SJF) Preemptive Scheduling** algorithm to manage CPU execution efficiently.

Calculate Con text Switches: Determinethetotalnumberofcontextswitches required forthegivenset ofprocesses.

Evaluate Waiting Time: Computethe **average waiting time** forall processes beforegetting CPUexecution.

❖ **Requirements:**

✓ **HardwareRequirements:**

- Processor: Minimum 1 GHz
- RAM: 512 MB or higher
- Storage: 100 MB free space

✓ **Software Requirements:**

- Operating System: Linux/Unix-based
- Shell:Bash 4.0 or higher
- TextEditor: Nano, Vim, or any preferred editor

❖ **Theory:**

CPU Scheduling in Operating Systems

Introduction

Scheduling isthe method by which processes are given accessto the CPU. Efficient scheduling is essential for optimal system performance and user experience. There are two primary types of CPU scheduling:**Preemptive Scheduling** and **Non-Preemptive Scheduling**. Understanding the differences between these scheduling typeshelps in designing and choosing the right scheduling algorithms for different operating systems.

1. Preemptive Scheduling

In **Preemptive Scheduling** ,the operating system can interrupt or preempt a runningprocesstoallocateCPU time to another process, typically based on priorityor time-sharingpolicies.Aprocess canbe switched fromthe **running state to the ready state**at any time.

Algorithms BasedonPreemptiveScheduling:

- **Round Robin (RR)**
- **Shortest Remaining Time First (SRTF)**
- **Priority Scheduling (Preemptive version) Example:**

Inthefollowing case, **P2 is preempted at time 1** duetothearrivalofahigher- priority process.

Advantages of Preemptive Scheduling:

✓ Prevents a process from monopolizing the CPU, improving system reliability.

✓ Enhances **average response time**, making it beneficial for multi- programming environments.

✓ Used in modern operating systems like **Windows, Linux, and macOS**.

Disadvantages of Preemptive Scheduling:

Morecomplex toimplement.

Involves **overhead** forsuspendingarunningprocessandswitchingcontexts.

May cause starvation iflow-priorityprocessesarefrequentlypreempted.

Cancreate **concurrency issues**,especiallywhenaccessingsharedresources.

---

2. **Non-Preemptive Scheduling**

In **Non-Preemptive Scheduling**,a running process cannot be interrupted by the operating system. It continues executing until **itterminates**or **enters a waiting state** voluntarily.

Algorithms Based on Non-Preemptive Scheduling:

- **First Come First Serve (FCFS)**
- **Shortest Job First (SJF - Non-Preemptive)**
- **Priority Scheduling (Non-Preemptive version) Example:**

Belowisa **Gantt Chart** based onthe **FCFS algorithm**,whereeachprocessexecutes fullybefore the nextonestarts.

Advantages of Non-Preemptive Scheduling:

✓ **Easy to implement** in an operating system (used in older versions like Windows 3.11 and early macOS).

✓ **Minimal scheduling overhead** due to fewer context switches.

✓ **Less computational resource usage**, making it more efficient for simpler systems.

Disadvantages of Non-Preemptive Scheduling:

Risk of Denial of Service (DoS) attacks, asaprocesscanmonopolizethe CPU.

Poor response time, especially in multi-user systems.

---

3. **Differences Between Preemptive and Non-Preemptive Scheduling**

Parameter	Preemptive Scheduling	Non-Preemptive Scheduling
Basic Concept	CPU time is allocated for a **limitedtime**.	CPUishoerlednutnetrislwpraoictiensg **terminates** state.
Interrupts	Process **can be interrupted**.	Process **cannot be interrupted**.
Starvation	Frequent high-priority processes may starve low-priority ones.	A long-running process can starve later-arriving shorter processes.
Overhead	Higher overhead due to frequent **context switching**.	Minimal overhead.
Flexibility	More flexible (critical processes getpriority).	Rigidschedulingapproach.
Response Time	Fasterresponsetime.	Slowerresponsetime.
Process Control	**OS has more control** over scheduling.	OShas **less control** over scheduling.
Concurrency Issues	**H ig her** rerseoeumrpceteadcdceusrsin.gsl**ow**er p ,asprocessesrunto completion.	**Lower**,asprocessesrunto completion.
Examples	Round Robin, SRTF, FCFS,Non-Preemptive SJF.	

4.**Frequently Asked Questions (FAQs)**

a. How is priority determined in Preemptive scheduling?

Ans: Preemptive scheduling systems assign priority based on**task importance, deadlines, or urgency**. Higher-priority tasks execute before lower-priority ones.

b. What happens in non-preemptive scheduling if a process does not yield the CPU?

Ans: If a process does not voluntarily yield the CPU, it can lead to **starvation or deadlock**, where other tasks are unable to execute.

c. Whichscheduling method is better for real-time systems?

Ans:Preemptive schedulingisbetterfor **real-time systems**,asitallows high-prioritytasksto executeimmediately .

❖ **CODE:**

```
#include<stdio.h>

int main(){
int n =3;
int at[3]={0,2,6};
int bt[3]={10,20, 30};
int rt[3];
int wt[3];
int ct[3];

    int t =0,completed = 0;
    int min,shortest;
    int context_switches = 0;
    int prev=-1;
    for (inti=0;i< n; i++) {

        rt[i] = bt[i];
        wt[i] = 0;
    }

    while (completed < n) {
        min = 100000;
        shortest = -1;

        for (int i = 0; i < n; i++) {
            if (at[i] <= t && rt[i] > 0 && rt[i] < min) {
                min = rt[i];
                shortest = i;
            }
        }

        if (shortest == -1) {
            t++;
            continue;
```

```
        }

        if(prev!=-1&&prev!= shortest)
            context_switches++;

        prev = shortest;
        rt[shortest]--;
        t++;

        if (rt[shortest] == 0) {
            completed++;
            ct[shortest] =t;
            wt[shortest]=ct[shortest] - bt[shortest] - at[shortest];
        }
    }

    float avg_wt = 0;
    for (int i = 0; i < n; i++)
        avg_wt += wt[i];
    avg_wt /= n;


    printf("\nSJFPREEMPTIVE SCHEDULING OUTPUT\n");
    printf("-------------------------------------------------------------\n");
    printf("|Process|ArrivalTime | Burst Time | Completion Time | Waiting
Time |\n");
    printf("-------------------------------------------------------------\n");

    for (int i = 0; i < n; i++) {
        printf("|P%d      |     %2d      |    %2d     |     %2d      | %2d |\n",
                i+1,at[i],bt[i],ct[i], wt[i]);
    }

    printf("-------------------------------------------------------------\n");
    printf("\nTotalContextSwitches = %d\n", context_switches);
    printf("AverageWaitingTime = %.2f ns\n", avg_wt);

    return 0;
}
```

❖ **Output:**

```
-------------------------------------------------------------
| Process | Arrival Time | Burst Time | Completion | Waiting |
-------------------------------------------------------------
|   P1    |       0      |     10     |     10     |    0    |
|   P2    |       2      |     20     |     30     |    8    |
|   P3    |       6      |     30     |     60     |   24    |
-------------------------------------------------------------

Total Context Switches = 2
Average Waiting Time   = 10.67 ns


=== Code Execution Successful ===
```

Conclusion: Preemptive scheduling offers better responsiveness but adds complexity, while non-preemptive scheduling is simpler but may cause inefficiencies. The choice depends on system needs, with preemptive suited for multitasking and non-preemptive for low-overhead scenarios.

❖ **Discussion Questions:**

1. **What is the key difference between preemptive and non-preemptive scheduling?**
2. **Why does preemptive scheduling require context switching?**
3. **Which CPU scheduling algorithm is most suitable for real-time systems and why?**
4. **What is starvation in CPU scheduling, and how can it be prevented?**
5. **Why is the Round Robin scheduling algorithm preferred in time-sharing systems?**

❖ **References:**

https://www.geeksforgeeks.org/preemptive-and-non-preemptive-scheduling/

Date: /___/2026

Signature
Course Coordinator
B.Tech CSE(AIML)
Sem: 4/2025-26