

SMART CONTRACT SECURITY AUDIT OF





SMART CONTRACT AUDIT | SOLIDITY DEVELOPMENT & TESTING | PROJECT EVALUATION

RELENTLESSLY SECURING THE PUBLIC BLOCKCHAIN

Audit Introduction

Auditing Firm InterFi Network

Audit Architecture InterFi Echelon Auditing Standard

Language Solidity

Client Firm META AIR

Website https://metaaircoin.com/

Telegram https://t.me/metaair/

Twitter https://twitter.com/metaaircoin?s=21/

Report Date January 24, 2022

About META AIR

MetaAir is a decentralized all in one ecosystem built on Binance Blockchain which is one of the largest and safest Blockchain protocols. MetaAir is revolutionizing the METAVERSE industry by offering their unique marketplace for NFTs, play to earn gaming ecosystem with staking of NFT facility to earn passive income.

Key Features: P2E games, Metaverse platform for >, NFTs, Buying/selling of Virtual land in Space



Audit Summary

InterFi team has performed a line-by-line manual analysis and automated review of the smart contract. The smart contract was analyzed mainly for common smart contract vulnerabilities, exploits, and manipulation hacks. According to the smart contract audit:

- META AIR's solidity source code has LOW RISK SEVERITY
- ❖ META AIR's smart contract has an ACTIVE OWNERSHIP
- Important owner privileges BUYBACK, MAX BUY & SELL LIMIT, MAX WALLET LIMIT SET BUY & SELL TAXES, SET COOLDOWN TIMER, SET BOT
- META AIR's smart contract owner has multiple "Write Contract" privileges. Centralization risk correlated to the active owner is MEDIUM

Be aware that smart contracts deployed on the blockchain aren't resistant to internal exploit, external vulnerability, or hack. For a detailed understanding of risk severity, source code vulnerability, functional hack, and audit disclaimer, kindly refer to the audit.

- Token Contract address: 0x1828e38E7271c44e4BeC6810dC5279223cCd14ff
- Blockchain: **Binance Smart Chain**
- Verify the authenticity of this report on InterFi's GitHub: https://github.com/interfinetwork



Table Of Contents

Audit Information

Audit Scope	5
Echelon Audit Standard	
Audit Methodology	6
Risk Classification	8
Smart Contract Risk Assessment	
Static Analysis	g
Software Analysis	13
Manual Analysis	17
SWC Attacks	21
Risk Status & Radar Chart	
<u>Audit Summary</u>	
Auditor's Verdict	24
<u>Legal Advisory</u>	
Important Disclaimer	25
About InterFi Network	26



Audit Scope

InterFi was consulted by META AIR to conduct the smart contract security audit of their solidity source code. The audit scope of work is strictly limited to the mentioned solidity file(s) only:

❖ METAAIR.sol

Solidity Source Code On Blockchain (Verified Contract Source Code)

https://bscscan.com/address/0x1828e38e7271c44e4bec6810dc5279223ccd14ff#code

Contract Name: METAAIR

Compiler Version: v0.8.6

Optimization Enabled: Yes with 200 runs

Solidity Source Code On InterFi GitHub

https://github.com/interfinetwork/audited-codes/blob/main/METAAIR.sol

SHA-1 Hash

Solidity source code is audited at hash #d22e17505de20e573724c19b8183e8d69de9f9d8



Audit Methodology

The scope of this report is to audit the smart contract source code of META AIR. InterFi has scanned the contract and reviewed the project for common vulnerabilities, exploits, hacks, and back-doors. Below is the list of commonly known smart contract vulnerabilities, exploits, and hacks:

Category

***	Re-entrancy
-----	-------------

- Unhandled Exceptions
- Transaction Order Dependency
- Integer Overflow
- Unrestricted Action
- Incorrect Inheritance Order
- Typographical Errors
- Requirement Violation
- Ownership Takeover
- Gas Limit and Loops
- Deployment Consistency
- Repository Consistency
- Data Consistency
- Token Supply Manipulation
- Access Control and Authorization
- Operations Trail and Event Generation
- Assets Manipulation
- Liquidity Access

Smart Contract Vulnerabilities

Source Code Review

Functional Assessment



InterFi's Echelon Audit Standard

The aim of InterFi's "Echelon" standard is to analyze the smart contract and identify the vulnerabilities and the hacks in the smart contract. Mentioned are the steps used by ECHELON-1 to assess the smart contract:

- Solidity smart contract source code reviewal:
 - Review of the specifications, sources, and instructions provided to InterFi to make sure we understand the size, scope, and functionality of the smart contract.
 - Manual review of code, which is the process of reading source code line-by-line to identify potential vulnerabilities.
- 2. Static, Manual, and Software analysis:
 - * Test coverage analysis is the process of determining whether the test cases are covering the code and how much code is exercised when we run those test cases.
 - Symbolic execution is analyzing a program to determine what inputs cause each part of a program to execute.
- 3. Best practices review, which is a review of the smart contracts to improve efficiency, effectiveness, clarify, maintainability, security, and control based on the established industry and academic practices, recommendations, and research.
- 4. Specific, itemized, actionable recommendations to help you take steps to secure your smart contracts

Automated 3P frameworks used to assess the smart contract vulnerabilities

- Slither
- Consensys MythX, Mythril
- SWC Registry
- Solidity Coverage
- Open Zeppelin Code Analyzer
- Solidity Code Complier



Risk Classification

Smart contracts are generally designed to manipulate and hold funds denominated in ETH/BNB. This makes them very tempting attack targets, as a successful attack may allow the attacker to directly steal funds from the contract. Below are the typical risk levels of a smart contract:

Vulnerable: A contract is vulnerable if it has been flagged by a static analysis tool as such. As we will see later, this means that some contracts may be vulnerable because of a false positive.

Exploitable: A contract is exploitable if it is vulnerable and the vulnerability could be exploited by an external attacker. For example, if the "vulnerability" flagged by a tool is in a function that requires owning the contract, it would be vulnerable but not exploitable.

Exploited: A contract is exploited if it received a transaction on the main network which triggered one of its vulnerabilities. Therefore, a contract can be vulnerable or even exploitable without having been exploited.

of the state of th	
Risk severity	Meaning Security Audit
! High	This level vulnerabilities could be exploited easily and can lead to asset loss,
	data loss, asset, or data manipulation. They should be fixed right away.
! Medium	This level vulnerabilities are hard to exploit but very important to fix, they carry
	an elevated risk of smart contract manipulation, which can lead to high-risk
	severity
! Low	This level vulnerabilities should be fixed, as they carry an inherent risk of future
	exploits, and hacks which may or may not impact the smart contract execution.
! Informational	This level vulnerabilities can be ignored. They are code style violations and
	informational statements in the code. They may not affect the smart contract
	execution



Static Analysis

Symbol Meaning Function can be modified Function is payable S Function is locked Function can be accessed Important functionality | **Address** | Library | ||| | L | sendValue | Internal 🗎 | 🛑 | | 111111 | **METAAIR** | Implementation | ERC20, Ownable ||| | └ | <Constructor> | Public ! | ● | ERC20 | | L | <Receive Ether> | External ! | 🙉 |NO! | | L | updateDividendTracker | Public ! | • | onlyOwner | | L | processDividendTracker | External ! | • | NO! | └ | claim | External ! | ● |NO! | | L | rescueBEP20Tokens | External ! | • | only0wner | | L | forceSend | External ! | P | NO! | | L | updateRouter | External ! | | onlyOwner | └ | excludeFromFees | Public ! | ● | onlyOwner | | └ | excludeMultipleAccountsFromFees | Public ! | ● | onlyOwner | | L | excludeFromDividends | External ! | • | onlyOwner | | L | setMarketingWallet | External ! | ● | onlyOwner | | └ | setBuybackWallet | External ! | ● | onlyOwner | | └ | setOperationsWallet | External ! | ● | onlyOwner | | L | setMaxWallet | External ! | • | onlyOwner | | L | setDevWallet | External ! | 🔎 | onlyOwner | | L | setSwapTokensAtAmount | External ! | Particle | onlyOwner | | L | setBuyTaxes | External ! | Page | onlyOwner | | L | setSellTaxes | External ! | onlyOwner | | └ | setRewardToken | External ! | ● | onlyOwner | | L | setMaxBuyAndSellLimits | External ! | • | onlyOwner | | └ | setSwapEnabled | External ! | ● | onlyOwner | | L | setCooldownTime | External ! | • | onlyOwner | | L | setBot | External ! | • | onlyOwner | | └ | setBulkBot | External ! | ● | onlyOwner |



```
| L | setAutomatedMarketMakerPair | External ! | 🔴 | onlyOwner |
 └ | setMinBalanceForDividends | External ! | ● | onlyOwner |
| └ | _setAutomatedMarketMakerPair | Private 🔐 | 🛑 | |
| L | setGasForProcessing | External ! | • | onlyOwner |
 └ | setClaimWait | External ! | ● | onlyOwner |
 L | getClaimWait | External ! | NO! |
| L | getTotalDividendsDistributed | External ! | NO! |
 L | isExcludedFromFees | Public ! | NO! |
| L | withdrawableDividendOf | Public ! | NO! |
| L | getCurrentRewardToken | External ! | NO! |
| L | dividendTokenBalanceOf | Public ! |
                                       INO!
| L | getAccountDividendsInfo | External ! | NO! | | | |
| L | getAccountDividendsInfoAtIndex | External ! |
| L | getLastProcessedIndex | External ! | NO! |
| L | getNumberOfDividendTokenHolders | External ! |
| L | _transfer | Internal | L | | | L |
| └ | swapAndLiquify | Private 🔐 | 🛑 | |
| └ | swapTokensForBNB | Private 🗳 | ● | |
| └ | addLiquidity | Private 🔐 | 🛑 | |
IIIIIII
| **MetaAirDividendTracker** | Implementation | Ownable, DividendPayingToken |||
| └ | _transfer | Internal 🗎 | | |
| L | setMinBalanceForDividends | External ! | • | onlyOwner |
| L | excludeFromDividends | External ! | • | onlyOwner |
| L | updateClaimWait | External ! | • | onlyOwner |
| L | getLastProcessedIndex | External ! | NO! |
| L | getNumberOfTokenHolders | External ! | NO! |
| L | getAccount | Public ! | NO! |
| L | getAccountAtIndex | Public ! | NO! |
| └ | canAutoClaim | Private 🔐 | | |
| L | setBalance | Public ! | 🔴 | onlyOwner |
| L | process | Public ! | O | NO! |
| L | processAccount | Public ! | • | onlyOwner |
| **Context** | Implementation | |||
| L | _msgSender | Internal 🗎 | | |
| **DividendPayingToken** | Implementation | ERC20, DividendPayingTokenInterface, Ownable |||
| └ | <Constructor> | Public ! | ● | ERC20 |
| L | <Receive Ether> | External ! | MO! |
| L | distributeDividends | Public ! | 💹 |NO! |
| L | _withdrawDividendOfUser | Internal 🗎 | 🛑 | |
| L | setRewardToken | External ! | • | onlyOwner |
| └ | swapBnbForCustomToken | Internal 🗎 | ● | |
| L | dividendOf | Public ! | NO! |
| L | withdrawableDividendOf | Public ! | NO! |
| L | withdrawnDividendOf | Public ! | NO! |
```



```
| L | accumulativeDividendOf | Public ! |
                                       |N0 ! |
| └ | _transfer | Internal 🏻 | ● | |
| L | _mint | Internal 🗎 | 🔴 | |
| <sup>L</sup> | _burn | Internal 🗎 | 🛑 | |
| L | _setBalance | Internal 🗎 | 🛑 | |
111111
| **DividendPayingTokenInterface** | Interface | |||
| L | dividendOf | External ! | NO! |
| L | distributeDividends | External ! | 🙉 |NO! |
| L | withdrawableDividendOf | External ! | NO! |
| L | withdrawnDividendOf | External ! | NO! |
| L | accumulativeDividendOf | External ! | NO! |
| **ERC20** | Implementation | Context, IERC20, IERC20Metadata |||
 L | <Constructor> | Public ! | 🛑 |NO! |
| L | name | Public ! | NO! | | |
| L | symbol | Public ! | NO! |
| L | decimals | Public ! | NO! |
| L | totalSupply | Public ! | NO! |
| L | balanceOf | Public ! | NO! |
| L | transfer | Public ! | 🛑 |NO! |
| L | allowance | Public ! | NO! |
| L | approve | Public ! | Public ! | | NO! |
| L | transferFrom | Public ! | 🔴 |NO! |
| L | increaseAllowance | Public ! | •
                                    |NO ! |
| L | decreaseAllowance | Public ! | •
| L | _transfer | Internal 🗎 | 🛑 | |
| L | _approve | Internal 🗎 | 🔴 | |
| └ | _beforeTokenTransfer | Internal 🗎 | ● | |
| **IPair** | Interface | |||
| **IFactory** | Interface | |||
| L | createPair | External ! | 📦 |NO! |
| L | getPair | External ! | NO! |
| **IRouter** | Interface | |||
| L | factory | External ! | NO! |
| L | WETH | External ! | NO! |
| L | addLiquidityETH | External ! | 💹 |NO! |
| L | swapExactTokensForTokensSupportingFeeOnTransferTokens | External ! | 🛑 | NO! |
| L | swapExactETHForTokens | External ! | 💹 |NO! |
| └ | swapExactTokensForETHSupportingFeeOnTransferTokens | External ! | ● |NO! |
| **IERC20** | Interface | |||
| L | totalSupply | External ! | NO! |
| L | balanceOf | External ! | NO! |
```



```
| L | transfer | External ! | 🛑 |NO! |
| L | allowance | External ! | NO! |
| L | approve | External ! | P | NO! |
| L | transferFrom | External ! | P | NO! |
\Pi\Pi\Pi\Pi
| **IERC20Metadata** | Interface | IERC20 |||
| L | name | External ! | NO! |
| L | symbol | External ! | NO! |
| L | decimals | External ! | NO! |
| **IterableMapping** | Library | |||
| L | get | Public ! | | NO! |
| L | getIndexOfKey | Public ! |
                                    INO! I
| L | getKeyAtIndex | Public ! |
                                    |NO ! |
| L | set | Public ! | • | NO! |
| L | remove | Public ! | • | NO! |
| **Ownable** | Implementation | Context | | |
| L | <Constructor> | Public ! | ● |NO! |
| L | owner | Public ! | NO! |
| L | renounceOwnership | Public ! | • | onlyOwner |
| L | transferOwnership | Public ! | 🔴 | onlyOwner |
| **<mark>SafeMath</mark>** | Library |
| L | add | Internal 🗎 |
| <sup>L</sup> | sub | Internal 🔒 |
| <sup>L</sup> | sub | Internal <sup>@</sup> |
| L | mul | Internal 🔒 |
| <sup>L</sup> | div | Internal <sup>@</sup> |
| L | div | Internal 🗎 |
| <sup>L</sup> | mod | Internal 🗎 |
                            III
| L | mod | Internal 🔒 | | |
| **SafeMathInt** | Library | |||
| <sup>L</sup> | mul | Internal 🗎 |
| L | div | Internal 🔒 |
| L | sub | Internal 🗎 |
| <sup>L</sup> | add | Internal 🗎 |
| L | abs | Internal 🔒 |
                            | |
| └ | toUint256Safe | Internal 🗎 |
111111
| **SafeMathUint** | Library | |||
| └ | toInt256Safe | Internal 🗎 | | |
```



Software Analysis

Function Signatures

```
39509351 => increaseAllowance(address,uint256)
43509138 \Rightarrow div(int256,int256)
24a084df => sendValue(address,uint256)
88bdd9be => updateDividendTracker(address)
700bb191 => processDividendTracker(uint256)
4e71d92d \Rightarrow claim()
042cfb51 => rescueBEP20Tokens(address)
12b77e8a => forceSend()
c851cc32 => updateRouter(address)
c0246668 => excludeFromFees(address,bool)
c492f046 => excludeMultipleAccountsFromFees(address[],bool)
0483f7a0 => excludeFromDividends(address,bool)
5d098b38 => setMarketingWallet(address)
1d0adc07 => setBuybackWallet(address)
ee5ecc89 => setOperationsWallet(address)
5d0044ca => setMaxWallet(uint256)
1f53ac02 => setDevWallet(address)
afa4f3b2 => setSwapTokensAtAmount(uint256)
87921b1e => setBuyTaxes(uint256,uint256,uint256,uint256,uint256,uint256)
5bdbb0f9 => setSellTaxes(uint256,uint256,uint256,uint256,uint256)
8aee8127 => setRewardToken(address)
78ce296a => setMaxBuyAndSellLimits(uint256,uint256)
e01af92c => setSwapEnabled(bool)
397843c7 => setCooldownTime(uint256,uint256)
c2e5ec04 => setTradingEnabled(bool)
342aa8b5 => setBot(address,bool)
b83b297f => setBulkBot(address[],bool)
8a0bc8e3 => setAntiBotBlocks(uint256)
9a7a23d6 => setAutomatedMarketMakerPair(address,bool)
9d7ceafb => setMinBalanceForDividends(uint256)
a7f7b36f => setAutomatedMarketMakerPair(address,bool)
5960e46d => setGasForProcessing(uint256)
0bc22944 => setClaimWait(uint256)
a26579ad => getClaimWait()
30bb4cff => getTotalDividendsDistributed()
4fbee193 => isExcludedFromFees(address)
a8b9d240 => withdrawableDividendOf(address)
854c84dc => getCurrentRewardToken()
6843cd84 => dividendTokenBalanceOf(address)
ad56c13c =>
             getAccountDividendsInfo(address)
f27fd254 => getAccountDividendsInfoAtIndex(uint256)
e7841ec0 => getLastProcessedIndex()
64b0f653 => getNumberOfDividendTokenHolders()
30e0789e => _transfer(address,address,uint256)
b4d03198 => swapAndLiquify(uint256,uint256)
```



```
56c3726b => swapTokensForBNB(uint256)
9cd441da =>
             addLiquidity(uint256,uint256)
e98030c7 =>
             updateClaimWait(uint256)
09bbedde =>
             getNumberOfTokenHolders()
fbcbc0f1 => getAccount(address)
5183d6fd =>
             getAccountAtIndex(uint256)
77fdb837 => canAutoClaim(uint256)
e30443bc => setBalance(address,uint256)
ffb2c479 => process(uint256)
bc4c4b37 => processAccount(address,bool)
119df25f => _msgSender()
8b49d47e => _msgData()
03c83302 => distributeDividends()
373de4aa => _withdrawDividendOfUser(address)
81b37964 => swapBnbForCustomToken(address,uint256)
91b89fba => dividend0f(address)
aafd847a => withdrawnDividendOf(address)
27ce0147 => accumulativeDividendOf(address)
4e6ec247 => mint(address,uint256)
6161eb18 => _burn(address,uint256)
ab86e0a6 => _setBalance(address,uint256)
06fdde03 => name()
95d89b41 => symbol()
313ce567 => decimals()
18160ddd => totalSupply()
70a08231 => balanceOf(address)
a9059cbb => transfer(address,uint256)
dd62ed3e => allowance(address,address)
095ea7b3 => approve(address,uint256)
23b872dd => transferFrom(address,address,uint256)
a457c2d7 => decreaseAllowance(address,uint256)
104e81ff => _approve(address,address,uint256)
cad3be83 => beforeTokenTransfer(address,address,uint256)
fff6cae9 => sync()
c9c65396 => createPair(address,address)
e6a43905 => getPair(address,address)
c45a0155 => factory()
ad5c4648 \Rightarrow WETH()
             addLiquidityETH(address,uint256,uint256,uint256,address,uint256)
f305d719 =>
5c11d795 =>
swapExactTokensForTokensSupportingFeeOnTransferTokens(uint256, uint256, address[], address, uint256)
7ff36ab5 => swapExactETHForTokens(uint256,address[],address,uint256)
791ac947 =>
swapExactTokensForETHSupportingFeeOnTransferTokens(uint256, uint256, address[], address, uint256)
268d8e2e =>
             get(Map,address)
b45dad3d => getIndexOfKey(Map,address)
7596720f => getKeyAtIndex(Map,uint256)
b1b533f3 => size(Map)
6b06f325 => set(Map,address,uint256)
0eac8729 => remove(Map,address)
```



```
8da5cb5b => owner()
715018a6 => renounceOwnership()
f2fde38b => transferOwnership(address)
771602f7 => add(uint256,uint256)
b67d77c5 => sub(uint256,uint256)
e31bdc0a => sub(uint256,uint256,string)
c8a4ac9c => mul(uint256,uint256)
a391c15b => div(uint256,uint256)
b745d336 => div(uint256,uint256)
b745d336 => mod(uint256,uint256)
71af23e8 => mod(uint256,uint256)
71af23e8 => mod(uint256,uint256)
adefc37b => sub(int256,int256)
```

a5f3c23b => add(int256,int256)

1b5ac4b5 => abs(int256)


744f7c7d => toUint256Safe(int256) e823b9bf => toInt256Safe(uint256)



Smart Contract Security Audit



<u>Inheritance Graph</u>



Interfi

Smart Contract Security Audit



Manual Analysis

Function	Description	Tested	Verdict
Total Supply	provides information about the total token		Passed
Total Supply	supply	Yes	
Dalamas Of	provides account balance of the owner's	Yes	Passed
Balance Of	account		
T	executes transfers of a specified number of		Passed
Transfer	tokens to a specified address	Yes	
	allow a spender to withdraw a set number of		Passed
Approve	tokens from a specified account	Yes	
	returns a set number of tokens from a spender to		
Allowance	the owner	Yes	Passed
	is an action in which the project buys back its		
Buy Back	tokens from the existing holders usually at a	Yes	Passed
	market price Contract		
	executes transfers of a specified number of	NA	NA
Burn	tokens to a burn address		
	executes the creation of a specified number of		
Mint	tokens and adds it to the total supply	NA	NA
	circulating token supply adjusts (increases or		
Rebase	decreases) automatically according to a token's	NA	NA
	price fluctuations	•	
	stops specified wallets from interacting with the		
Blacklist	smart contract function modules	Yes	! Low
	stops or locks all function modules of the smart		
Lock	contract	NA	NA



Function	Description	Tested	Verdict
Dividend	executes transfers of a specified dividend token to a specified address	Yes	Passed
Airdrop	executes transfers of a specified number of tokens to a specified address	NA	NA
Max Transaction	a non-whitelisted wallet can only transfer a specified number of tokens	Yes	! Low
Max Wallet	a non-whitelisted wallet can only hold a specified number of tokens	Yes	! Low
Cooldown Timer	functionality to limit the number of transactions that a wallet can make within 24-hours	NA	NA
Anti Bot	stops some or all bot wallets from interacting with the smart contract	Yes	Passed
Anti Snipe	prevents bots from making transaction at "addLiquidity" block	NA	NA
Transfer Ownership	executes transfer of contract ownership to a specified wallet	Yes	Passed
Renounce Ownership	executes transfer of contract ownership to a dead address	Yes	Passed



Best Practices V

- Owner cannot stop or pause the smart contract.
- Owner cannot lock or burn the user assets.
- Owner cannot mint tokens after initial contract creation/deployment.
- The smart contract utilizes "SafeMath" function to avoid common smart contract vulnerabilities.

```
string private _name = "METAAIR";
library SafeMath {
function add(uint256 a, uint256 b) internal pure returns (uint256) {
    uint256 c = a + b;
    require(c >= a, "SafeMath: addition overflow");

function sub(uint256 a, uint256 b) internal pure returns (uint256) {
    return sub(a, b, "SafeMath: subtraction overflow");

    uint256 c = a * b;
    require(c / a == b, "SafeMath: multiplication overflow");

    return c;

function div(uint256 a, uint256 b) internal pure returns (uint256) {
        return div(a, b, "SafeMath: division by zero");

function mod(uint256 a, uint256 b) internal pure returns (uint256) {
        return mod(a, b, "SafeMath: modulo by zero");
}
```

Note 4

- Active smart contract owner: 0xda0ebed9a4539f81c2d0cd5aae5e32cfaf36cfc6
- Be aware that active smart contract owner privileges constitute an elevated impact to smart contract safety and security.
- Smart contract can **buyback** tokens from the total supply.
- Smart contract owner can blacklist (set bulk bot) certain wallets from interacting with the contract function modules.



- Smart contract owner can change transaction fees. This function module can be used to impose extraordinary transaction fees. No arbitrary limit set.
- Smart contract owner can change max buy and sell %. The smart contract owner can change the value to "zero". No arbitrary limit set.
- Smart contract owner can change max wallet limit %. The smart contract owner can change the value to "zero". No arbitrary limit set.
- Smart contract has a low severity issue which may or may not create any functional vulnerability.

```
"resource": "/METAAIR.sol",

"owner": "_generated_diagnostic_collection_name_#0",

"severity": 8, (! Low Severity)

"Expected token Comma got 'Payable'",

"source": "solc",

Security Audit
```



SWC Attacks

SWC ID	Description	Verdict
SWC-101	Integer Overflow and Underflow	Passed
SWC-102	Outdated Compiler Version	! Low
SWC-103	Floating Pragma	Passed
SWC-104	Unchecked Call Return Value	Passed
SWC-105	Unprotected Ether Withdrawal	Passed
SWC-106	Unprotected SELF-DESTRUCT Instruction	Passed
SWC-107	Re-entrancy	Passed
SWC-108	State Variable Default Visibility	Passed
SWC-109	Uninitialized Storage Pointer	Passed
SWC-110	Assert Violation Smort Contract	Passed
swc-111	Use of Deprecated Solidity Functions	Passed
SWC-112	Delegate Call to Untrusted Callee	Passed
SWC-113	DoS with Failed Call	Passed
SWC-114	Transaction Order Dependence	Passed
SWC-115	Authorization through tx.origin	Passed
SWC-116	Block values as a proxy for time	Passed
SWC-117	Signature Malleability	Passed
SWC-118	Incorrect Constructor Name	Passed



SWC-119	Shadowing State Variables	Passed
SWC-120	Weak Sources of Randomness from Chain Attributes	Passed
SWC-121	Missing Protection against Signature Replay Attacks	Passed
SWC-122	Lack of Proper Signature Verification	Passed
SWC-123	Requirement Violation	Passed
SWC-124	Write to Arbitrary Storage Location	Passed
SWC-125	Incorrect Inheritance Order	Passed
SWC-126	Insufficient Gas Griefing	Passed
SWC-127	Arbitrary Jump with Function Type Variable	Passed
SWC-128	DoS With Block Gas Limit	Passed
SWC-129	Typographical Error	Passed
SWC-130	Right-To-Left-Override control character (U+202E)	Passed
SWC-131	Presence of unused variables	Passed
SWC-132	Unexpected Ether balance	Passed
SWC-133	Hash Collisions With Multiple Variable Length Arguments	Passed
SWC-134	Message call with the hardcoded gas amount	Passed
SWC-135	Code With No Effects (Irrelevant/Dead Code)	! Low
SWC-136	Unencrypted Private Data On-Chain	Passed



Risk Status & Radar Chart

Risk Severity	Status
!!! High	No high severity issues identified
!! Medium	No medium severity issues identified
! Low	4 low severity issues identified
	Please Review Report
Informational	2 informational severity issues identified
	 Active Ownership
	 Outdated Compiler
Verified	54 functions and instances verified and checked
	SIN OF Score out of 100 CT
	Se Compiler Check
	95
	Interface Safety 85 Static Analysis 80 75

Manual Analysis

Software Analysis



Auditor's Verdict

InterFi team has performed a line-by-line manual analysis and automated review of the smart contract. The smart contract was analyzed mainly for common smart contract vulnerabilities, exploits, and manipulation hacks.

- ❖ META AIR's smart contract source code has LOW RISK SEVERITY
- ❖ META AIR's smart contract has an ACTIVE OWNERSHIP
- META AIR's smart contract owner has multiple "Write Contract" privileges. Centralization risk correlated to the active owner is MEDIUM



Note for stakeholders

- Be aware that active smart contract owner privileges constitute an elevated impact on smart contract safety and security.
- Make sure that the project team's KYC/identity is verified by an independent firm.
- Always check if the contract's liquidity is locked. A longer liquidity lock plays an important role in the project's longevity. It is recommended to have multiple liquidity providers.
- Examine the unlocked token supply in the owner, developer, or team's private wallets. Understand the project's tokenomics, and make sure the tokens outside of the LP Pair are vested or locked for a longer period.
- Ensure that the project's official website is hosted on a trusted platform, and is using an active SSL certificate. The website's domain should be registered for a longer period.



Important Disclaimer

InterFi Network provides contract development, testing, auditing and project evaluation services for blockchain projects. The purpose of the audit is to analyze the on-chain smart contract source code and to provide a basic overview of the project. **This report should not be transmitted, disclosed, referred to, or relied upon by any person for any purpose without InterFi's prior written consent.**

InterFi provides the easy-to-understand assessment of the project, and the smart contract (otherwise known as the source code). The audit makes no statements or warranties on the security of the code. It also cannot be considered as enough assessment regarding the utility and safety of the code, bug-free status, or any other statements of the contract. While we have used all the data at our disposal to provide the transparent analysis, it is important to note that you should not rely on this report only — we recommend proceeding with several independent audits and a public bug bounty program to ensure the security of smart contracts. Be aware that smart contracts deployed on a blockchain aren't resistant to external vulnerability, or a hack. Be aware that active smart contract owner privileges constitute an elevated impact on smart contract safety and security. Therefore, InterFi does not guarantee the explicit security of the audited smart contract.

The analysis of the security is purely based on the smart contracts alone. No applications or operations were reviewed for security. No product code has been reviewed.

This report should not be considered as an endorsement or disapproval of any project or team.

The information provided in this report does not constitute investment advice, financial advice, trading advice, or any other sort of advice and you should not treat any of the report's content as such. Do conduct your due diligence and consult your financial advisor before making any investment decisions.



About InterFi Network

InterFi Network provides intelligent blockchain solutions. InterFi is developing an ecosystem that is seamless and responsive. Some of our services: Blockchain Security, Token Launchpad, NFT Marketplace, etc. InterFi's mission is to interconnect multiple services like Blockchain Security, DeFi, Gaming, and Marketplace under one ecosystem that is seamless, multi-chain compatible, scalable, secure, fast, responsive, and easy to use.

InterFi is built by a decentralized team of UI experts, contributors, engineers, and enthusiasts from all over the world. Our team currently consists of 6+ core team members, and 10+ casual contributors. InterFi provides manual, static, and automatic smart contract analysis, to ensure that project is checked against known attacks and potential vulnerabilities.

To learn more, visit https://interfi.network

To view our audit portfolio, visit https://github.com/interfinetwork

To book an audit, message https://t.me/interfiaudits



