

SMART CONTRACT SECURITY AUDIT OF



SMART CONTRACT AUDIT | SOLIDITY DEVELOPMENT & TESTING | KYC | PROJECT EVALUATION

RELENTLESSLY SECURING THE PUBLIC BLOCKCHAIN

Summary

Auditing Firm InterFi Network

Client Firm Melody Lab

Architecture InterFi "Echelon" Auditing Standard

Language Solidity

Mandatory Audit Check Static, Software, Auto Intelligent & Manual Analysis

Final Report Date January 10, 2022

Audit Summary

InterFi team has performed a line-by-line manual analysis and automated review of the smart contract. The smart contract was analyzed mainly for common smart contract vulnerabilities, exploits, and manipulation hacks. According to the smart contract audit:

- Melody Lab's smart contract source code has LOW RISK SEVERITY
- Melody Lab's smart contract has an ACTIVE OWNERSHIP
- Important owner privileges BLACKLIST, MAX TX & WALLET LIMIT, SET FEES, SET TX LOCK TIME
- Blacklist function is masked as "BLOCKLIST" to avoid auto contract checks

For the detailed understanding of risk severity, source code vulnerability, and functional test, kindly refer to the audit.

- Contract address: Private
- 🖁 Blockchain: Binance Smart Chain
- ✓ Verify the authenticity of this report on InterFi's GitHub: https://github.com/interfinetwork



Table Of Contents

Project Information

Overview	4
InterFi "Echelon" Audit Standard	
Audit Scope & Methodology	6
InterFi's Risk Classification	8
Smart Contract Risk Assessment	
Static Analysis	9
Software Analysis	13
Manual Analysis	17
SWC Attacks	21
Risk Status & Radar Chart	
Report Summary	
Auditor's Verdict	24
<u>Legal Advisory</u>	
Important Disclaimer	25
About InterFi Network	26



Project Overview

InterFi was consulted by Melody Lab to conduct the smart contract security audit of their solidity source code.

About Melody Lab

Melody Lab is a bsc token with a primary target to become the best token that connects Crypto & Music. Utility includes a music platform where people will be able to listen to their favourite music and earn tokens and an NFT Music Marketplace in where rare NFT's made by the team will be on sale via an action.

Furthermore, music products in the form of an NFT's will be sold by other people as well on the platform!

Project	Melody Lab
Blockchain	Binance Smart Chain
Language	solidit Security Audit
Contract	Private
Website	https://melodylab.net
Telegram	https://t.me/MelodyLabChannel
Twitter	https://twitter.com/MelodyLabBSC
Instagram	https://www.instagram.com/melodylabbsc
Reddit	https://www.reddit.com/user/MelodyLab



Project Logo



Solidity Source Code On Blockchain

//Private Address//

Solidity Source Code On InterFi GitHub

https://github.com/interfinetwork/audited-codes/blob/main/MelodyLab.sol

SHA-1 Hash

Solidity source code is audited at hash #de60eb67546dbc865e4fceb3fd6c496eb9fdbe2b



Audit Scope & Methodology

The scope of this report is to audit the smart contract source code of Melody Lab. InterFi has scanned the contract and reviewed the project for common vulnerabilities, exploits, hacks, and back-doors. Below is the list of commonly known smart contract vulnerabilities, exploits, and hacks:

Category

- Re-entrancy
- Unhandled Exceptions
- Transaction Order Dependency
- Integer Overflow
- Unrestricted Action
- Incorrect Inheritance Order
- Typographical Errors
- Requirement Violation
- Ownership Takeover
- Gas Limit and Loops
- Deployment Consistency
- Repository Consistency
- Data Consistency
- Token Supply Manipulation
- Access Control and Authorization
- Operations Trail and Event Generation
- Assets Manipulation
- Liquidity Access

Smart Contract Vulnerabilities

Source Code Review

Functional Assessment



InterFi's Echelon Audit Standard

The aim of InterFi's "Echelon" standard is to analyze the smart contract and identify the vulnerabilities and the hacks in the smart contract. Mentioned are the steps used by ECHELON-1 to assess the smart contract:

- 1. Solidity smart contract source code reviewal:
 - Review of the specifications, sources, and instructions provided to InterFi to make sure we understand the size, scope, and functionality of the smart contract.
 - Manual review of code, which is the process of reading source code line-byline to identify potential vulnerabilities.
- 2. Static, Manual, and Software analysis:
 - Test coverage analysis, which is the process of determining whether the test cases are covering the code and how much code is exercised when we run those test cases.
 - Symbolic execution, which is analysing a program to determine what inputs causes each part of a program to execute.
- 3. Best practices review, which is a review of the smart contracts to improve efficiency, effectiveness, clarify, maintainability, security, and control based on the established industry and academic practices, recommendations, and research.
- 4. Specific, itemized, actionable recommendations to help you take steps to secure your smart contracts

Automated 3P frameworks used to assess the smart contract vulnerabilities

- Slither
- Consensys MythX, Mythril
- SWC Registry
- Solidity Coverage
- Open Zeppelin Code Analyzer
- Solidity Code Complier



InterFi's Risk Classification

Smart contracts are generally designed to manipulate and hold funds denominated in ETH/BNB. This makes them very tempting attack targets, as a successful attack may allow the attacker to directly steal funds from the contract. Below are the typical risk levels of a smart contract:

Vulnerable: A contract is vulnerable if it has been flagged by a static analysis tool as such. As we will see later, this means that some contracts may be vulnerable because of a false-positive.

Exploitable: A contract is exploitable if it is vulnerable and the vulnerability could be exploited by an external attacker. For example, if the "vulnerability" flagged by a tool is in a function which requires to own the contract, it would be vulnerable but not exploitable.

Exploited: A contract is exploited if it received a transaction on the main network which triggered one of its vulnerabilities. Therefore, a contract can be vulnerable or even exploitable without having been exploited.

SHOIL COHOC.		
Risk severity	Meaning Security Audit	
! Critical	This level vulnerabilities could be exploited easily, and can lead to asset loss,	
	data loss, asset, or data manipulation. They should be fixed right away.	
! High	This level vulnerabilities are hard to exploit but very important to fix, they carry	
	an elevated risk of smart contract manipulation, which can lead to high-risk	
	severity	
! Medium	This level vulnerabilities should be fixed, as they carry an inherent risk of future	
	exploits, and hacks which may or may not impact the smart contract execution.	
! Low	This level vulnerabilities can be ignored. They are code style violations, and	
	informational statements in the code. They may not affect the smart contract	
	execution	



Smart Contract – Static Analysis

	leaning
⊝ Fu	unction can be modified
₫s <u>□</u> Fu	unction is payable
<u></u> Fι	unction is locked
≅ F∈	unction can be accessed
! In	nportant functionality
L balanceOf L transfer L allowance L approve E L transferFro **SafeMath** L tryAdd In L tryAdd In L tryBub In L tryMul In L tryMul In L tryMod In L tryMod In L div Inter L mul Inter L div Inter L mod Inter L mod Inter L mod Inter L mod Inter L msgSender L msgData **Address** L L isContract	External !



```
| └ | functionCall | Internal 🗎 | 🛑 | |
 👢 | functionCallWithValue | Internal 🗎 | 🥌
| L | functionCallWithValue | Internal 🗎 | 🛑 | |
| L | functionStaticCall | Internal 🗎 | | |
| L | functionStaticCall | Internal 🔒 |
| └ | functionDelegateCall | Internal 🗎 | ● | |
| L | functionDelegateCall | Internal 🗎 | 🛑 | |
| L | verifyCallResult | Internal 🗎 | | |
111111
| **Ownable** | Implementation | Context |||
| L | <Constructor> | Public ! | • |NO! |
| L | owner | Public ! | NO! |
| L | renounceOwnership | Public ! | 🔴 | onlyOwner |
| └ | transferOwnership | Public ! | ● | onlyOwner |
| L | setOwner | Private 🔐 | 🛑 | |
\Pi\Pi\Pi\Pi
| **IUniswapV2Factory** | Interface | |||
| L | feeTo | External ! | NO! |
| L | feeToSetter | External ! | NO! |
| L | getPair | External ! | NO! |
| L | allPairs | External ! | NO! |
| L | allPairsLength | External ! | NO! |
| L | createPair | External ! | • |NO! |
| L | setFeeTo | External ! | ● |NO! |
| L | setFeeToSetter | External ! | • | NO! |
| **IUniswapV2Pair** | Interface | |||
| L | name | External ! | NO! |
| L | symbol | External ! | NO! |
| L | decimals | External ! | NO! |
| L | totalSupply | External ! | NO! |
| L | balanceOf | External ! | NO! |
 L | allowance | External ! |
                               |N0 ! |
| L | transfer | External ! | • | NO! |
| L | transferFrom | External ! | P | NO! |
| L | DOMAIN SEPARATOR | External ! | NO! |
| L | PERMIT TYPEHASH | External ! |
| L | nonces | External ! |
| L | permit | External ! | 🔴 |NO! |
| L | MINIMUM_LIQUIDITY | External ! |
                                      |NO ! |
| L | factory | External ! | NO! |
| L | token0 | External ! |
                            |NO ! |
| L | token1 | External ! |
                            |NO ! |
| L | getReserves | External ! | NO! |
| L | priceOCumulativeLast | External ! |
                                         INO! I
| L | price1CumulativeLast | External ! |
                                         |NO ! |
| L | kLast | External ! | NO! | |
| L | mint | External ! | • | NO! |
| <sup>L</sup> | burn | External ! | • |NO! |
```



```
| L | swap | External ! | • | NO! |
| L | skim | External ! | P | NO! |
| L | sync | External ! | | NO! |
| L | initialize | External ! | 🔎 |NO! |
| **IUniswapV2Router01** | Interface | |||
| L | factory | External ! | NO! |
| L | WETH | External ! | NO! |
| └ | addLiquidity | External ! | ● |NO! |
| L | addLiquidityETH | External ! | 🐸 |NO! |
| └ | removeLiquidity | External ! | ● |NO! |
 └ | removeLiquidityETH | External ! | ● |NO! |
| └ | removeLiquidityWithPermit | External ! | ● |NO! |
| └ | removeLiquidityETHWithPermit | External ! | ● |NO! |
 📙 | swapExactTokensForTokens | External ! | 🔴 |NO! |
| L | swapTokensForExactTokens | External ! | WO! | |
| L | swapExactETHForTokens | External ! | 💹 |NO! |
| └ | swapTokensForExactETH | External ! | ● |NO! |
 👢 | swapExactTokensForETH | External ! | 🔴 |NO! |
 L | swapETHForExactTokens | External ! | 💹 |NO! |
| L | quote | External ! | NO! |
 L | getAmountOut | External ! |
| L | getAmountIn | External ! | NO! |
| L | getAmountsOut | External ! | NO! |
| L | getAmountsIn | External ! | NO! |
111111
| **IUniswapV2Router02** | Interface | IUniswapV2Router01 |||
| └ | removeLiquidityETHSupportingFeeOnTransferTokens | External ! | ● |NO! |
| └ | removeLiquidityETHWithPermitSupportingFeeOnTransferTokens | External ! | ● |NO! |
| L | swapExactTokensForTokensSupportingFeeOnTransferTokens | External ! | 🔴 | NO! |
| L | swapExactETHForTokensSupportingFeeOnTransferTokens | External ! | 🕮 |NO! |
| L | swapExactTokensForETHSupportingFeeOnTransferTokens | External ! | 🛑 | NO! |
111111
| **melodylab** | Implementation | Context, IERC20, Ownable |||
| L | <Constructor> | Public ! | • | NO! |
| L | name | Public ! | | NO! |
| L | symbol | Public ! | NO! |
| L | decimals | Public ! | NO! |
| L | totalSupply | Public ! | NO! |
 L | balanceOf | Public ! | NO! |
| L | transfer | Public ! | 🛑 |NO! |
| <sup>L</sup> | allowance | Public ! |
                              |NO ! |
| L | approve | Public ! | Public ! | | NO! |
| L | transferFrom | Public ! | O | NO! |
| L | increaseAllowance | Public ! | • | NO! |
| L | decreaseAllowance | Public ! | Public ! | | NO! |
| L | isExcludedFromFee | Public ! | NO! |
| L | isExcludedFromReward | Public ! |
| L | isAllowList | Public ! |
                                |NO! |
| L | isBlockList | Public ! |
                                |N0 ! |
```



```
| L | totalFees | Public ! | NO! | |
| L | deliver | Public ! | • | NO! |
| L | reflectionFromToken | Public ! | NO! |
| L | tokenFromReflection | Public ! | NO! |
| └ | includeInFee | Public ! | ● | onlyOwner |
| └ | excludeFromFee | Public ! | ● | onlyOwner |
| L | includeInReward | Public ! | 🛑 | onlyOwner |
 L | excludeFromReward | Public ! | • | onlyOwner |
| L | includeInAllowList | Public ! | December | OnlyOwner |
| L | excludeFromAllowList | Public ! | Public ! | onlyOwner |
| L | includeInBlockList | Public ! | • | onlyOwner |
└ | excludeFromBlockList | Public ! | ● | onlyOwner |
| L | setTaxFeePercent | External ! | • | onlyOwner |
| L | setBurnFeePercent | External ! | • | onlyOwner |
| L | setMaxWalletPercent | External ! | • | onlyOwner |
| L | setMaxTxPercent | External ! | • | onlyOwner |
| L | setTransactionLockTime | External ! | • | onlyOwner |
| L | setSwapAndLiquifyEnabled | Public ! | • | onlyOwner |
| L | <Receive Ether> | External ! | MO! |
| L | _getValues | Private 🔒 | | |
| L | _getTValues | Private 🔐 | | |
| L | _getRValues | Private 🔒 | | |
| └ | _getRate | Private 🔐 | | |
| L | _getCurrentSupply | Private 🔒 | | |
| └ | _takeLiquidity | Private 🔐 | 🛑 | |
| └ | calculateTaxFee | Private 🔒 | | |
| L | calculateLiquidityFee | Private 🔐 |
| └ | calculateBurnFee | Private 🔐 | | |
| └ | restoreAllFee | Private 🔒 | 🛑 | |
| └ | _transfer | Private 🔐 | ● | transactionLock |
| └ | swapAndLiquify | Private 🔐 | ● | lockTheSwap |
| └ | swapTokensForBnb | Private 🔐 | 🛑 | |
| └ | addLiquidity | Private 🔐 | 🛑 | |
| └ | _transferStandard | Private 🔐 | 🛑 | |
| └ | _transferToExcluded | Private 🔒 | ● | |
| L | _transferFromExcluded | Private 🔐 | 🛑 | |
| L | _transferBothExcluded | Private @ | 🔴 | |
| └ | _transferBurn | Private 🔐 | 🛑 | |
```



Smart Contract - Software Analysis

Function Signatures

```
11902160 => getTValues(uint256)
16279055 => isContract(address)
39509351 => increaseAllowance(address,uint256)
75128141 => calculateTaxFee(uint256)
18160ddd => totalSupply()
70a08231 \Rightarrow balanceOf(address)
a9059cbb => transfer(address,uint256)
dd62ed3e => allowance(address,address)
095ea7b3 => approve(address,uint256)
23b872dd => transferFrom(address,address,uint256)
884557bf => tryAdd(uint256,uint256)
a29962b1 => trySub(uint256,uint256)
6281efa4 => tryMul(uint256,uint256)
736ecb18 => tryDiv(uint256,uint256)
38dc0867 \Rightarrow tryMod(uint256,uint256)
771602f7 => add(uint256,uint256)
b67d77c5 => sub(uint256,uint256)
c8a4ac9c => mul(uint256,uint256)
a391c15b => div(uint256,uint256)
f43f523a \Rightarrow mod(uint256,uint256)
e31bdc0a => sub(uint256,uint256,string)
b745d336 => div(uint256,uint256,string)
71af23e8 \Rightarrow mod(uint256,uint256,string)
             _msgSender()
119df25f =>
8b49d47e \Rightarrow msqData()
24a084df => sendValue(address,uint256)
a0b5ffb0 => functionCall(address,bytes)
241b5886 => functionCall(address,bytes,string)
2a011594 => functionCallWithValue(address,bytes,uint256)
d525ab8a => functionCallWithValue(address,bytes,uint256,string)
c21d36f3 => functionStaticCall(address,bytes)
dbc40fb9 => functionStaticCall(address,bytes,string)
ee33b7e2 => functionDelegateCall(address,bytes)
57387df0 => functionDelegateCall(address,bytes,string)
946b5793 => verifyCallResult(bool,bytes,string)
8da5cb5b => owner()
715018a6 => renounceOwnership()
f2fde38b => transfer0wnership(address)
fc201122 => setOwner(address)
017e7e58 => feeTo()
094b7415 \Rightarrow feeToSetter()
e6a43905 => getPair(address,address)
1e3dd18b => allPairs(uint256)
574f2ba3 => allPairsLength()
c9c65396 => createPair(address,address)
```



```
f46901ed => setFeeTo(address)
a2e74af6 => setFeeToSetter(address)
06fdde03 => name()
95d89b41 => symbol()
313ce567 => decimals()
3644e515 => DOMAIN_SEPARATOR()
30adf81f => PERMIT TYPEHASH()
7ecebe00 => nonces(address)
d505accf => permit(address,address,uint256,uint256,uint8,bytes32,bytes32)
ba9a7a56 => MINIMUM_LIQUIDITY()
c45a0155 => factory()
0dfe1681 => token0()
d21220a7 => token1()
0902f1ac => getReserves()
5909c0d5 => price0CumulativeLast()
5a3d5493 => price1CumulativeLast()
7464fc3d => kLast()
6a627842 \Rightarrow mint(address)
89afcb44 => burn(address)
022c0d9f => swap(uint256,uint256,address,bytes)
bc25cf77 => skim(address)
fff6cae9 => sync()
485cc955 => initialize(address,address)
ad5c4648 \Rightarrow WETH()
e8e33700 => addLiquidity(address,address,uint256,uint256,uint256,address,uint256)
             addLiquidityETH(address,uint256,uint256,uint256,address,uint256)
f305d719 =>
              removeLiquidity(address,address,uint256,uint256,uint256,address,uint256)
baa2abde =>
02751cec =>
              removeLiquidityETH(address,uint256,uint256,uint256,address,uint256)
2195995c =>
removeLiquidityWithPermit(address,address,uint256,uint256,uint256,address,uint256,bool,uint8,bytes3
2, bytes32)
ded9382a =>
removeLiquidityETHWithPermit(address,uint256,uint256,uint256,address,uint256,bool,uint8,bytes32,byt
es32)
38ed1739 => swapExactTokensForTokens(uint256,uint256,address[],address,uint256)
8803dbee => swapTokensForExactTokens(uint256,uint256,address[],address,uint256)
7ff36ab5 => swapExactETHForTokens(uint256,address[],address,uint256)
4a25d94a =>
             swapTokensForExactETH(uint256,uint256,address[],address,uint256)
18cbafe5 =>
             swapExactTokensForETH(uint256, uint256, address[], address, uint256)
fb3bdb41 =>
             swapETHForExactTokens(uint256,address[],address,uint256)
ad615dec => quote(uint256,uint256,uint256)
054d50d4 =>
             getAmountOut(uint256, uint256, uint256)
             getAmountIn(uint256,uint256,uint256)
85f8c259 =>
d06ca61f =>
             getAmountsOut(uint256,address[])
1f00ca74 =>
             getAmountsIn(uint256,address[])
af2979eb =>
removeLiquidityETHSupportingFeeOnTransferTokens(address,uint256,uint256,uint256,address,uint256)
5b0d5984 =>
removeLiquidityETHWithPermitSupportingFeeOnTransferTokens(address,uint256,uint256,uint256,address,u
int256,bool,uint8,bytes32,bytes32)
```




```
5c11d795 =>
swapExactTokensForTokensSupportingFeeOnTransferTokens(uint256,uint256,address[],address,uint256)
             swapExactETHForTokensSupportingFeeOnTransferTokens(uint256,address[],address,uint256)
b6f9de95 =>
791ac947 =>
swapExactTokensForETHSupportingFeeOnTransferTokens(uint256,uint256,address[],address,uint256)
a457c2d7 => decreaseAllowance(address,uint256)
5342acb4 => isExcludedFromFee(address)
88f82020 => isExcludedFromReward(address)
f5964e08 => isAllowList(address)
6f9ed0b6 => isBlockList(address)
13114a9d => totalFees()
3bd5d173 \Rightarrow deliver(uint256)
4549b039 => reflectionFromToken(uint256,bool)
2d838119 => tokenFromReflection(uint256)
ea2f0b37 => includeInFee(address)
437823ec => excludeFromFee(address)
3685d419 => includeInReward(address)
52390c02 => excludeFromReward(address)
2c6c7f38 => includeInAllowList(address)
4256de96 => excludeFromAllowList(address)
534202bf => includeInBlockList(address)
1965ca5b => excludeFromBlockList(address)
061c82d0 => setTaxFeePercent(uint256)
8ee88c53 => setLiquidityFeePercent(uint256)
cea26958 => setBurnFeePercent(uint256)
82bf293c => setMaxWalletPercent(uint256)
d543dbeb => setMaxTxPercent(uint256)
3da5b5ba => setTransactionLockTime(uint256)
c49b9a80 => setSwapAndLiquifyEnabled(bool)
184d894e => _reflectFee(uint256,uint256)
d4780e36 =>
             _getValues(uint256)
1d5671e4 => _getRValues(uint256,uint256,uint256)
94e10784 => getRate()
97a9d560 => _getCurrentSupply()
c432df5e => takeLiquidity(uint256)
cc126a23 => calculateLiquidityFee(uint256)
6ad88269 => calculateBurnFee(uint256)
301370af => removeAllFee()
e7e3e3a7 => restoreAllFee()
104e81ff => _approve(address,address,uint256)
30e0789e => transfer(address,address,uint256)
173865ad => swapAndLiquify(uint256)
528689ea => swapTokensForBnb(uint256)
9cd441da => addLiquidity(uint256,uint256)
b09bbc79 => _tokenTransfer(address,address,uint256,bool)
2852df65 => _transferStandard(address,address,uint256)
16f1cc83 => _transferToExcluded(address,address,uint256)
c7d9be66 => _transferFromExcluded(address,address,uint256)
6ff6cdf4 => _transferBothExcluded(address,address,uint256)
```



5517d370 => _transferBurn(address,uint256)

Inheritance Graph





Smart Contract Security Audit



Smart Contract – Manual Analysis

Function	Description	Tested	Verdict
Total Supply	provides information about the total token	Voc	
	supply	Yes	Passed
Balance Of	provides account balance of the owner's	Yes	Passed
	account		
Tuernofou	executes transfers of a specified number of	Yes	Passed
Transfer	tokens to a specified address		
	allow a spender to withdraw a set number of		Passed
Approve	tokens from a specified account	Yes	
	returns a set number of tokens from a spender to		Passed
Allowance	the owner	Yes	
	is an action in which the project buys back its		
Buy Back	tokens from the existing holders usually at a	NA	NA
	market price mart Contract		
_	executes transfers of a specified number of		NA
Burn	tokens to a burn address	NA	
	executes creation of a specified number of		NA
Mint	tokens and adds it to the total supply	NA	
	circulating token supply adjusts (increases or		
Rebase	decreases) automatically according to a token's	NA	NA
	price fluctuations		
	stops specified wallets from interacting with the		
Blacklist	smart contract function modules	Yes	! Low
	stops or locks transfer/transaction function		
Transaction Lock	modules of smart contract	Yes	! Low



Function	Description	Tested	Verdict
Dividend	executes transfers of a specified dividend token to a specified address	NA	NA
Airdrop	executes transfers of a specified number of tokens to a specified address	NA	NA
Max Transaction	a non-whitelisted wallet can only transfer a specified number of tokens	Yes	! Low
Max Wallet	a non-whitelisted wallet can only hold a specified number of tokens	Yes	! Low
Cooldown Timer	functionality to limit the number of transactions that a wallet can make within a 24-hour span	NA	NA
Anti Bot	stops some or all bot wallets from interacting with the smart contract	NA	NA
Anti Snipe	prevents bots from making transaction at "addLiquidity" block	NA	NA
Transfer Ownership	executes transfer of contract ownership to a specified wallet	Yes	Passed
Renounce Ownership	executes transfer of contract ownership to a dead address	Yes	Passed



Best Practices

- Owner cannot lock or burn the user assets.
- Owner cannot mint tokens after initial contract creation/deployment.
- The smart contract utilizes "SafeMath" function to avoid common smart contract vulnerabilities.

```
string private _name = "MelodyLab";
library SafeMath {
function add(uint256 a, uint256 b) internal pure returns (uint256) {
    uint256 c = a + b;
    require(c >= a, "SafeMath: addition overflow");

function sub(uint256 a, uint256 b) internal pure returns (uint256) {
    return sub(a, b, "SafeMath: subtraction overflow");

    uint256 c = a * b;
    require(c / a == b, "SafeMath: multiplication overflow");

    return c;

function div(uint256 a, uint256 b) internal pure returns (uint256) {
        return div(a, b, "SafeMath: division by zero");

function mod(uint256 a, uint256 b) internal pure returns (uint256) {
        return mod(a, b, "SafeMath: modulo by zero");
}
```

Note 4

- Active smart contract owner: 0xcldb782a5aefe6faa946fcc56878e6b74b988a74
- Be aware that active smart contract owner privileges constitute an elevated impact to smart contract's safety and security.
- Smart contract owner can enable/disable transaction lock, this function module stops the users from buying or selling the assets.

```
function setTransactionLockTime(uint256 transactionLockTime) external onlyOwner() {
    _transactionLockTime = transactionLockTime;
}
```



- Smart contract owner can **blacklist** certain wallets from interacting with the contract function modules.
- Smart contract owner can change transaction fees. This function module can be used to impose extraordinary transaction fees. No arbitrary limit set.
- Smart contract owner can change max transaction & wallet %. The smart contract owner can change the value to "zero". No arbitrary limit set.

The smart contract has low severity issue which may or may not create any functional vulnerability.
Smart Contract

```
Security Audit
```

```
"resource": " / MelodyLab.sol",

"owner": "_generated_diagnostic_collection_name_#0",

"severity": 8, (! Low Severity)

"Expected token Semicolon got 'LBrace",
```

```
"source": "solc",
```



Smart Contract - SWC Attacks

SWC ID	Description	Verdict
SWC-101	Integer Overflow and Underflow	Passed
SWC-102	Outdated Compiler Version	! Low
SWC-103	Floating Pragma	Passed
SWC-104	Unchecked Call Return Value	Passed
SWC-105	Unprotected Ether Withdrawal	Passed
SWC-106	Unprotected SELFDESTRUCT Instruction	Passed
SWC-107	Re-entrancy E	Passed
SWC-108	State Variable Default Visibility	Passed
SWC-109	Uninitialized Storage Pointer	Passed
SWC-110	Assert Violation Smart Contract	Passed
swc-111	Use of Deprecated Solidity Functions	Passed
SWC-112	Delegate Call to Untrusted Callee	Passed
SWC-113	DoS with Failed Call	Passed
SWC-114	Transaction Order Dependence	Passed
SWC-115	Authorization through tx.origin	Passed
SWC-116	Block values as a proxy for time	Passed
swc-117	Signature Malleability	Passed
SWC-118	Incorrect Constructor Name	! Low



SWC-119	Shadowing State Variables	Passed
SWC-120	Weak Sources of Randomness from Chain Attributes	Passed
SWC-121	Missing Protection against Signature Replay Attacks	Passed
SWC-122	Lack of Proper Signature Verification	Passed
SWC-123	Requirement Violation	Passed
SWC-124	Write to Arbitrary Storage Location	Passed
SWC-125	Incorrect Inheritance Order	Passed
SWC-126	Insufficient Gas Griefing	Passed
SWC-127	Arbitrary Jump with Function Type Variable	Passed
SWC-128	DoS With Block Gas Limit	Passed
SWC-129	Typographical Error	Passed
SWC-130	Right-To-Left-Override control character (U+202E)	Passed
SWC-131	Presence of unused variables	Passed
SWC-132	Unexpected Ether balance	Passed
SWC-133	Hash Collisions With Multiple Variable Length Arguments	Passed
SWC-134	Message call with hardcoded gas amount	Passed
SWC-135	Code With No Effects (Irrelevant/Dead Code)	Passed
SWC-136	Unencrypted Private Data On-Chain	Passed



Smart Contract - Risk Status & Radar Chart

Risk Severity	Status	
! Critical	None critical severity issues identified	
! High	None high severity issues identified	
! Medium	None medium severity issues identified	
! Low	6 low severity issues identified	
Verified	54 functions and instances verified and checked —Score out of 100	
	Compiler Check Smart 95 ontract	
	Interface Safety Static And 75 Scaftware Analysis	
	Manual Analysis Software Analysi	S



Auditor's Verdict

InterFi team has performed a line-by-line manual analysis and automated review of the smart contract. The smart contract was analyzed mainly for common smart contract vulnerabilities, exploits, and manipulation hacks.

- Melody Lab's smart contract source code has LOW RISK SEVERITY
- Melody Lab's smart contract has an ACTIVE OWNERSHIP



Note for stakeholders



- Be aware that active smart contract owner privileges constitute an elevated impact on smart contract's safety and security.
- ❖ Make sure that the project team's KYC/identity is verified by an independent firm, e.g., InterFi.
- Always check if the contract's liquidity is locked. A longer liquidity lock plays an important role in project's longevity. It is recommended to have multiple liquidity providers.
- Examine the unlocked token supply in the owner, developer, or team's private wallets.
 Understand the project's tokenomics, and make sure the tokens outside of the LP Pair are vested or locked for a longer period of time.
- Ensure that the project's official website is hosted on a trusted platform, and is using an active SSL certificate. The website's domain should be registered for a longer period of time.



Important Disclaimer

InterFi Network provides contract auditing and project verification services for blockchain projects. The purpose of the audit is to analyse the on-chain smart contract source code, and to provide basic overview of the project. This report should not be transmitted, disclosed, referred to, or relied upon by any person for any purposes without InterFi's prior written consent.

InterFi provides the easy-to-understand assessment of the project, and the smart contract (otherwise known as the source code). The audit makes no statements or warranties on the security of the code. It also cannot be considered as an enough assessment regarding the utility and safety of the code, bug-free status, or any other statements of the contract. While we have used all the data at our disposal to provide the transparent analysis, it is important to note that you should not rely on this report only — we recommend proceeding with several independent audits and a public bug bounty program to ensure the security of smart contracts. Be aware that smart contracts deployed on a blockchain aren't resistant from external vulnerability, or a hack. Be aware that active smart contract owner privileges constitute an elevated impact to smart contract's safety and security. Therefore, InterFi does not guarantee the explicit security of the audited smart contract.

The analysis of the security is purely based on the smart contracts alone. No applications or operations were reviewed for security. No product code has been reviewed.

This report should not be considered as an endorsement or disapproval of any project or team.

The information provided on this report does not constitute investment advice, financial advice, trading advice, or any other sort of advice and you should not treat any of the report's content as such. Do conduct your own due diligence and consult your financial advisor before making any investment decisions.



About InterFi Network

InterFi Network provides intelligent blockchain solutions. InterFi is developing an ecosystem that is seamless and responsive. Some of our services: Blockchain Security, Token Launchpad, NFT Marketplace, etc. InterFi's mission is to interconnect multiple services like Blockchain Security, DeFi, Gaming, and Marketplace under one ecosystem that is seamless, multi-chain compatible, scalable, secure, fast, responsive, and easy-to-use.

InterFi is built by a decentralized team of UI experts, contributors, engineers, and enthusiasts from all over the world. Our team currently consists of 6+ core team members, and 10+ casual contributors. InterFi provides manual, static, and automatic smart contract analysis, to ensure that project is checked against known attacks and potential vulnerabilities.

To learn more, visit https://interfi.network

To view our audit portfolio, visit https://github.com/interfinetwork

To book an audit, message https://t.me/interfiaudits



