```
#include <stdio.h>

struct Customer
{
    int bankNo;
    char name[50];
    char address[100];
    char phoneNo[15];
    float openingBalance;
    float deposit;
    float withdrawal;
    float utrPayment;
    float remainingBalance;
};

int main()
{
    struct Customer c[100];
    int n, i, choice;

    printf("Enter number of customers: ");
    scanf("%d", &n);

    for (i = 0; i < n; i++)
    {
        printf("\nEnter details of Customer %d\n", i + 1);
```

```
printf("Enter Bank No: ");
scanf("%d", &c[i].bankNo);

printf("Enter Name: ");
scanf(" %49[^\n]", c[i].name);

printf("Enter Address: ");
scanf(" %99[^\n]", c[i].address);

printf("Enter Phone No: ");
scanf("%14s", c[i].phoneNo);

printf("Enter Opening Balance: ");
scanf("%f", &c[i].openingBalance);

printf("Enter Deposit: ");
scanf("%f", &c[i].deposit);

printf("Enter Withdrawal: ");
scanf("%f", &c[i].withdrawal);

printf("Enter UTR Payment: ");
scanf("%f", &c[i].utrPayment);

c[i].remainingBalance =
   c[i].openingBalance +
   c[i].deposit +
```

```
        c[i].utrPayment -
        c[i].withdrawal;
}

while (1)
{
    printf("\n\n===== CUSTOMER DETAILS MENU =====");
    printf("\n1. Display All Customers");
    printf("\n2. Display Customer by Bank No");
    printf("\n3. Exit");

    printf("\nEnter your choice: ");
    scanf("%d", &choice);

    switch (choice)
    {
        case 1:
            for (i = 0; i < n; i++)
            {
                printf("\n\n===== CUSTOMER %d =====", i + 1);
                printf("\nBank No: %d", c[i].bankNo);
                printf("\nName: %s", c[i].name);
                printf("\nAddress: %s", c[i].address);
                printf("\nPhone No: %s", c[i].phoneNo);
                printf("\nOpening Balance: %.2f",
                      c[i].openingBalance);
                printf("\nDeposit: %.2f", c[i].deposit);
```

```
        printf("\nWithdrawal: %.2f", c[i].withdrawal);
        printf("\nUTR Payment: %.2f", c[i].utrPayment);
        printf("\nRemaining Balance: %.2f",
              c[i].remainingBalance);
    }
    break;

case 2:
{
    int searchNo, found = 0;

    printf("Enter Bank No to search: ");
    scanf("%d", &searchNo);

    for (i = 0; i < n; i++)
    {
        if (c[i].bankNo == searchNo)
        {
            printf("\nCustomer Name: %s", c[i].name);
            printf("\nAddress: %s", c[i].address);
            printf("\nPhone No: %s", c[i].phoneNo);
            printf("\nRemaining Balance: %.2f",
                  c[i].remainingBalance);

            found = 1;
            break;
        }
```

```
            }

            if (found == 0)
                printf("\nCustomer not found!");

            break;
        }
        case 3:
            printf("\nThank you!");
            return 0;

        default:
            printf("\nInvalid choice!");
      }
   }
   return 0;
}
```