

Date: 16/03/2026
Name: Dhanya S

I am Dhanya S from Kakunje Software working as an Intern. Today I had my 37 session it was an interesting session and mam had taught us about MongoDB. Today I learned about the mongoDB, difference between SQL and NoSQL, how to store the data in NoSQL had seen today, creating the folders and files and installing some prompts in VS code, and how to insert the json documents in postman and displaying it in mongoDB compass.

config > JS db.js > default

```
1  import mongoose from "mongoose";
2
3  const connectDB = async ()=>{
4      try{
5          await mongoose.connect(process.env.MONGO_URI);
6          console.log("mongodb connected");
7      }catch(error){
8          console.log("database connection failed",error);
9          process.exit(1);
10     }
11 };
12 export default connectDB;
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS POSTMAN CONSOLE

○ Node.js v24.13.1

PS C:\Users\Dhanya\OneDrive\Desktop\mongodb> node server.js

[dotenv@17.3.1] injecting env (2) from .env -- tip: 🔒 prevent building .env in docker: <https://dotenvx.com>

server in running on port 5000

mongodb connected

█

models > JS Product.js > ...

```
1  import mongoose from "mongoose";
2
3  const productSchema = new mongoose.Schema({
4    name:{
5      type:String,
6      required:true
7    },
8    price:{
9      type:Number
10   },
11   category:{
12     type:String,
13     required:true
14   },
15   stock:{
16     type:Number
17   }
18 },{timestamps:true});
19 const Product = mongoose.model("Product",productSchema);
20 export default Product;
21
```

PROBLEMS

OUTPUT

DEBUG CONSOLE

TERMINAL

PORTS

POSTMAN CONSOLE

○ Node.js v24.13.1

PS C:\Users\Dhanya\OneDrive\Desktop\mongodb> node server.js

[dotenv@17.3.1] injecting env (2) from .env -- tip:  prevent building .env in doc

server in running on port 5000

mongodb connected

□

routes > JS productroutes.js > ...

```
1  import express from "express";
2  import Product from "../models/Product.js";
3
4  const router = express.Router();
5  router.post("/products", async(req, res)=>{
6      try{
7          const product = new Product(req.body);
8          await product.save();
9          res.status(201).json(product);
10     }catch(error){
11         res.status(500).json({message:error.message});
12     }
13 })
14 router.get("/products", async(req, res)=>{
15     try{
16         const products = await Product.find();
17         res.json(products);
18     }catch(error){
19         res.status(500).json({message:error.message});
20     }
21 })
22 export default router;
23
```

PROBLEMS

OUTPUT

DEBUG CONSOLE

TERMINAL

PORTS

POSTMAN CONSOLE

○ Node.js v24.13.1

PS C:\Users\Dhanya\OneDrive\Desktop\mongodb> node server.js

[dotenv@17.3.1] injecting env (2) from .env -- tip:  prevent building .env in doc

server in running on port 5000

mongodb connected

█

JS server.js > ...

```
1  import express from "express";
2  import dotenv from "dotenv";
3  import connectDB from "../config/db.js";
4  import productRoutes from "../routes/productroutes.js";
5
6  dotenv.config();
7  connectDB();
8  const app = express();
9  app.use(express.json());
10 app.use("/api", productRoutes);
11 const PORT = process.env.PORT;
12 app.listen(PORT, () => {
13   console.log(`server in running on port ${PORT}`)
14 })
```

PROBLEMS

OUTPUT

DEBUG CONSOLE

TERMINAL

PORTS

POSTMAN CONSOLE

○ Node.js v24.13.1

PS C:\Users\Dhanya\OneDrive\Desktop\mongodb> node server.js

[dotenv@17.3.1] injecting env (2) from .env -- tip: 🗝 prevent building .env in docker: h

server in running on port 5000

mongodb connected

□

⚙️ .env

Import to Postman

1 `PORT = 5000`

2 `MONGO_URI = mongodb://localhost:27017/products`



http://localhost:5000/api/products

POST



http://localhost:5000/api/products

Params Authorization Headers (9) **Body** Scripts Settings

☐ none ☐ form-data ☐ x-www-form-urlencoded ☒ raw ☐ binary ☐ GraphQL JSON

```
1 {
2   "name": "Laptop",
3   "price": 50000,
4   "category": "Electronics",
5   "stock": 10
6 }
7
```

Body Cookies Headers (7) Test Results

Pretty

Raw

Preview

JSON



```
1 {
2   "name": "Laptop",
3   "price": 50000,
4   "category": "Electronics",
5   "stock": 10,
6   "_id": "69b7e568fd683fe7295124a7",
7   "createdAt": "2026-03-16T11:11:36.903Z",
8   "updatedAt": "2026-03-16T11:11:36.903Z",
9   "_v": 0
10 }
```



http://localhost:5000/api/products

GET



http://localhost:5000/api/products

Params Authorization Headers (7) Body Scripts Settings

☒ none ☐ form-data ☐ x-www-form-urlencoded ☐ raw ☐ binary ☐ GraphQL

This request does not have a body

Body Cookies Headers (7) Test Results

Pretty

Raw

Preview

JSON ▾



```
1  [
2    {
3      "_id": "69b7e568fd683fe7295124a7",
4      "name": "Laptop",
5      "price": 50000,
6      "category": "Electronics",
7      "stock": 10,
8      "createdAt": "2026-03-16T11:11:36.903Z",
9      "updatedAt": "2026-03-16T11:11:36.903Z",
10     "__v": 0
11   },
12   {
13     "_id": "69b7e934fd683fe7295124ab",
14     "name": "Laptop",
15     "price": 50000,
16     "category": "Electronics",
17     "stock": 10,
18     "createdAt": "2026-03-16T11:27:48.729Z",
19     "updatedAt": "2026-03-16T11:27:48.729Z",
20     "__v": 0
21   },
22 ]
```


Compass

- My Queries
- Data Modeling

CONNECTIONS (2)

Search connections

products

admin

config

local

products

products

users

users

USERSproductsUSERSUSERS+

products > products > products

> Open MongoDB shell

Documents 1AggregationsSchemaIndexes 1Validation

Type a query: { field: 'value' } or [Generate query](#)

ExplainResetFindOptions

ADD DATA

UPDATE

DELETE

EXPORT DATA

EXPORT CODE

251 - 1 of 1

```
_id: ObjectId('69b7e568fd683fe7295124a7')
name: "Laptop"
price: 59999
category: "Electronics"
stock: 18
createdAt: 2026-03-16T11:11:36.963+08:00
updatedAt: 2026-03-16T11:11:36.963+08:00
__v: 0
```