

## Week 5 | DML and Join SQL Queries

Name: Dharani S

SRN: PES2UG24CS157

Section: C

### Task 1

#### Creating tables

##### Hostel

```
(PES2UG24CS157@root) [(none)]>CREATE DATABASE hostel;
Query OK, 1 row affected (0.01 sec)

(PES2UG24CS157@root) [(none)]>USE hostel;
Database changed
(PES2UG24CS157@root) [hostel]>CREATE TABLE Hostel (
    → Hostel_ID INT PRIMARY KEY,
    → Hostel_Name VARCHAR(100) NOT NULL,
    → Location VARCHAR(100) NOT NULL,
    → Capacity INT NOT NULL DEFAULT 0,
    → CONSTRAINT chk_hostel_capacity CHECK (Capacity ≥ 0)
    → );
Query OK, 0 rows affected (0.04 sec)

(PES2UG24CS157@root) [hostel]>DESC Hostel;
+-----+-----+-----+-----+-----+-----+
| Field          | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| Hostel_ID      | int           | NO   | PRI | NULL    |       |
| Hostel_Name    | varchar(100)  | NO   |     | NULL    |       |
| Location       | varchar(100)  | NO   |     | NULL    |       |
| Capacity       | int           | NO   |     | 0        |       |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.02 sec)
```

## Staff

```
(PES2UG24CS157@root) [hostel]>CREATE TABLE Staff (  
→   Staff_ID      INT PRIMARY KEY,  
→   Staff_Name    VARCHAR(100) NOT NULL,  
→   Salary        DECIMAL(10,2) NOT NULL,  
→   Designation   VARCHAR(50) NOT NULL DEFAULT 'Support Staff',  
→   Hostel_ID     INT NOT NULL,  
→   Supervisor_ID INT NULL,  
→   CONSTRAINT chk_staff_salary CHECK (Salary > 0),  
→   CONSTRAINT fk_staff_hostel FOREIGN KEY (Hostel_ID)  
→       REFERENCES Hostel(Hostel_ID),  
→   CONSTRAINT fk_staff_supervisor FOREIGN KEY (Supervisor_ID)  
→       REFERENCES Staff(Staff_ID) ON DELETE SET NULL  
→ );
```

Query OK, 0 rows affected (0.08 sec)

```
(PES2UG24CS157@root) [hostel]>DESC Staff;
```

| Field         | Type          | Null | Key | Default       | Extra |
|---------------|---------------|------|-----|---------------|-------|
| Staff_ID      | int           | NO   | PRI | NULL          |       |
| Staff_Name    | varchar(100)  | NO   |     | NULL          |       |
| Salary        | decimal(10,2) | NO   |     | NULL          |       |
| Designation   | varchar(50)   | NO   |     | Support Staff |       |
| Hostel_ID     | int           | NO   | MUL | NULL          |       |
| Supervisor_ID | int           | YES  | MUL | NULL          |       |

6 rows in set (0.01 sec)

## Room

```
(PES2UG24CS157@root) [hostel]>CREATE TABLE Room (  
→ Hostel_ID INT NOT NULL,  
→ Room_Number INT NOT NULL,  
→ Floor INT NOT NULL DEFAULT 0,  
→ PRIMARY KEY (Hostel_ID, Room_Number),  
→ CONSTRAINT fk_room_hostel FOREIGN KEY (Hostel_ID)  
→ REFERENCES Hostel(Hostel_ID) ON DELETE CASCADE  
→ );
```

Query OK, 0 rows affected (0.03 sec)

```
(PES2UG24CS157@root) [hostel]>DESC Room;
```

| Field       | Type | Null | Key | Default | Extra |
|-------------|------|------|-----|---------|-------|
| Hostel_ID   | int  | NO   | PRI | NULL    |       |
| Room_Number | int  | NO   | PRI | NULL    |       |
| Floor       | int  | NO   |     | 0       |       |

3 rows in set (0.01 sec)

```
(PES2UG24CS157@root) [hostel]>_
```

## Bed

```
(PES2UG24CS157@root) [hostel]>CREATE TABLE Bed (  
→ Hostel_ID INT NOT NULL,  
→ Room_Number INT NOT NULL,  
→ Bed_Number INT NOT NULL,  
→ Status VARCHAR(10) NOT NULL DEFAULT 'Vacant',  
→ PRIMARY KEY (Hostel_ID, Room_Number, Bed_Number),  
→ CONSTRAINT chk_bed_status CHECK (Status IN ('Occupied','Vacant')),  
→ CONSTRAINT fk_bed_room FOREIGN KEY (Hostel_ID, Room_Number)  
→ REFERENCES Room(Hostel_ID, Room_Number) ON DELETE CASCADE  
→ );
```

Query OK, 0 rows affected (0.04 sec)

```
(PES2UG24CS157@root) [hostel]>DESC Bed;
```

| Field       | Type        | Null | Key | Default | Extra |
|-------------|-------------|------|-----|---------|-------|
| Hostel_ID   | int         | NO   | PRI | NULL    |       |
| Room_Number | int         | NO   | PRI | NULL    |       |
| Bed_Number  | int         | NO   | PRI | NULL    |       |
| Status      | varchar(10) | NO   |     | Vacant  |       |

4 rows in set (0.00 sec)

```
(PES2UG24CS157@root) [hostel]>_
```

## Student

```
(PES2UG24CS157@root) [hostel]>DESC Student;
+-----+-----+-----+-----+-----+-----+
| Field      | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| Student_ID | int           | NO   | PRI | NULL    |       |
| First_Name  | varchar(50)   | NO   |     | NULL    |       |
| Middle_Name | varchar(50)   | YES  |     | NULL    |       |
| Last_Name   | varchar(50)   | NO   |     | NULL    |       |
| Gender      | varchar(10)   | NO   |     | NULL    |       |
| DOB         | date          | NO   |     | NULL    |       |
| Email       | varchar(100)  | NO   | UNI | NULL    |       |
+-----+-----+-----+-----+-----+-----+
7 rows in set (0.01 sec)

(PES2UG24CS157@root) [hostel]>_
```

## Student\_phone

```
(PES2UG24CS157@root) [hostel]>CREATE TABLE Student_Phone (
→      Student_ID      INT NOT NULL,
→      Phone_Number    VARCHAR(15) NOT NULL,
→      PRIMARY KEY (Student_ID, Phone_Number),
→      CONSTRAINT fk_phone_student FOREIGN KEY (Student_ID)
→      REFERENCES Student(Student_ID) ON DELETE CASCADE
→ );
Query OK, 0 rows affected (0.04 sec)

(PES2UG24CS157@root) [hostel]>DESC Student_Phone;
+-----+-----+-----+-----+-----+-----+
| Field      | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| Student_ID | int           | NO   | PRI | NULL    |       |
| Phone_Number | varchar(15)   | NO   | PRI | NULL    |       |
+-----+-----+-----+-----+-----+-----+
2 rows in set (0.00 sec)

(PES2UG24CS157@root) [hostel]>_
```

## Facility

```
(PES2UG24CS157@root) [hostel]>CREATE TABLE Facility (  
→ Facility_ID INT PRIMARY KEY,  
→ Facility_Name VARCHAR(100) NOT NULL,  
→ Operating_Hours VARCHAR(20) DEFAULT '24x7',  
→ Hostel_ID INT NOT NULL,  
→ CONSTRAINT fk_facility_hostel FOREIGN KEY (Hostel_ID)  
→ REFERENCES Hostel(Hostel_ID) ON DELETE CASCADE  
→ );
```

Query OK, 0 rows affected (0.08 sec)

```
(PES2UG24CS157@root) [hostel]>DESC Facility;
```

| Field           | Type         | Null | Key | Default | Extra |
|-----------------|--------------|------|-----|---------|-------|
| Facility_ID     | int          | NO   | PRI | NULL    |       |
| Facility_Name   | varchar(100) | NO   |     | NULL    |       |
| Operating_Hours | varchar(20)  | YES  |     | 24x7    |       |
| Hostel_ID       | int          | NO   | MUL | NULL    |       |

4 rows in set (0.00 sec)

```
(PES2UG24CS157@root) [hostel]>_
```

## Uses

```
(PES2UG24CS157@root) [hostel]>CREATE TABLE Uses (  
→ Student_ID INT NOT NULL,  
→ Facility_ID INT NOT NULL,  
→ Usage_Date DATE NOT NULL,  
→ PRIMARY KEY (Student_ID, Facility_ID, Usage_Date),  
→ CONSTRAINT fk_uses_student FOREIGN KEY (Student_ID)  
→ REFERENCES Student(Student_ID) ON DELETE CASCADE,  
→ CONSTRAINT fk_uses_facility FOREIGN KEY (Facility_ID)  
→ REFERENCES Facility(Facility_ID) ON DELETE CASCADE  
→ );
```

Query OK, 0 rows affected (0.07 sec)

```
(PES2UG24CS157@root) [hostel]>DESC Uses;
```

| Field       | Type | Null | Key | Default | Extra |
|-------------|------|------|-----|---------|-------|
| Student_ID  | int  | NO   | PRI | NULL    |       |
| Facility_ID | int  | NO   | PRI | NULL    |       |
| Usage_Date  | date | NO   | PRI | NULL    |       |

3 rows in set (0.00 sec)

## Allocation

```
(PES2UG24CS157@root) [hostel]>CREATE TABLE Allocation (  
→ Allocation_ID INT PRIMARY KEY,  
→ Student_ID INT NOT NULL,  
→ Hostel_ID INT NOT NULL,  
→ Room_Number INT NOT NULL,  
→ Allocation_Date DATE NOT NULL,  
→ Check_in_Date DATE NOT NULL,  
→ Check_out_Date DATE NULL,  
→ CONSTRAINT fk_alloc_student FOREIGN KEY (Student_ID)  
→ REFERENCES Student(Student_ID) ON DELETE CASCADE,  
→ CONSTRAINT fk_alloc_room FOREIGN KEY (Hostel_ID, Room_Number)  
→ REFERENCES Room(Hostel_ID, Room_Number) ON DELETE CASCADE  
→ );
```

Query OK, 0 rows affected (0.07 sec)

```
(PES2UG24CS157@root) [hostel]>DESC Allocation;
```

| Field           | Type | Null | Key | Default | Extra |
|-----------------|------|------|-----|---------|-------|
| Allocation_ID   | int  | NO   | PRI | NULL    |       |
| Student_ID      | int  | NO   | MUL | NULL    |       |
| Hostel_ID       | int  | NO   | MUL | NULL    |       |
| Room_Number     | int  | NO   |     | NULL    |       |
| Allocation_Date | date | NO   |     | NULL    |       |
| Check_in_Date   | date | NO   |     | NULL    |       |
| Check_out_Date  | date | YES  |     | NULL    |       |

7 rows in set (0.01 sec)

## Payment

```
(PES2UG24CS157@root) [hostel]>CREATE TABLE Payment (  
→ Payment_ID INT PRIMARY KEY,  
→ Student_ID INT NOT NULL,  
→ Payment_Date DATE NOT NULL,  
→ Amount DECIMAL(10,2) NOT NULL,  
→ Payment_Type VARCHAR(20) NOT NULL,  
→ CONSTRAINT chk_payment_amount CHECK (Amount > 0),  
→ CONSTRAINT fk_payment_student FOREIGN KEY (Student_ID)  
→ REFERENCES Student(Student_ID)  
→ );
```

Query OK, 0 rows affected (0.06 sec)

```
(PES2UG24CS157@root) [hostel]>DESC Payment;
```

| Field        | Type          | Null | Key | Default | Extra |
|--------------|---------------|------|-----|---------|-------|
| Payment_ID   | int           | NO   | PRI | NULL    |       |
| Student_ID   | int           | NO   | MUL | NULL    |       |
| Payment_Date | date          | NO   |     | NULL    |       |
| Amount       | decimal(10,2) | NO   |     | NULL    |       |
| Payment_Type | varchar(20)   | NO   |     | NULL    |       |

5 rows in set (0.00 sec)

## Receipt

```
(PES2UG24CS157@root) [hostel]>CREATE TABLE Receipt (  
→ Receipt_ID INT PRIMARY KEY,  
→ Payment_ID INT NOT NULL UNIQUE,  
→ Receipt_Date DATE NOT NULL,  
→ CONSTRAINT fk_receipt_payment FOREIGN KEY (Payment_ID)  
→ REFERENCES Payment(Payment_ID)  
→ );
```

Query OK, 0 rows affected (0.08 sec)

```
(PES2UG24CS157@root) [hostel]>DESC Receipt;
```

| Field        | Type | Null | Key | Default | Extra |
|--------------|------|------|-----|---------|-------|
| Receipt_ID   | int  | NO   | PRI | NULL    |       |
| Payment_ID   | int  | NO   | UNI | NULL    |       |
| Receipt_Date | date | NO   |     | NULL    |       |

3 rows in set (0.00 sec)

## All 11 tables

```
(PES2UG24CS157@root) [hostel]>SHOW TABLES;
+-----+
| Tables_in_hostel |
+-----+
| allocation        |
| bed               |
| facility          |
| hostel            |
| payment           |
| receipt           |
| room              |
| staff             |
| student           |
| student_phone     |
| uses              |
+-----+
11 rows in set (0.01 sec)

(PES2UG24CS157@root) [hostel]>_
```



## Inserting sample data

### Hostel

```
(PES2UG24CS157@root) [hostel]>INSERT INTO Hostel VALUES
→ (1, 'Sunrise Hostel', 'North Campus', 120),
→ (2, 'Blue Ridge Hostel', 'South Campus', 90),
→ (3, 'Lake View Hostel', 'East Campus', 60);
Query OK, 3 rows affected (0.02 sec)
Records: 3  Duplicates: 0  Warnings: 0

(PES2UG24CS157@root) [hostel]>SELECT * FROM Hostel;
+-----+-----+-----+-----+
| Hostel_ID | Hostel_Name      | Location      | Capacity |
+-----+-----+-----+-----+
|          1 | Sunrise Hostel   | North Campus  |      120 |
|          2 | Blue Ridge Hostel | South Campus  |       90 |
|          3 | Lake View Hostel | East Campus   |       60 |
+-----+-----+-----+-----+
3 rows in set (0.00 sec)

(PES2UG24CS157@root) [hostel]>_
```

### Staff

```
(PES2UG24CS157@root) [hostel]>
(PES2UG24CS157@root) [hostel]>INSERT INTO Staff (Staff_ID, Staff_Name, Designation, Salary, Hostel_ID, Supervisor_ID) VALUES
→ (2, 'Sunil Kumar', 'Security', 22000, 1, 1),
→ (3, 'Geeta Rao', 'Cleaner', 18000, 1, 1),
→ (5, 'Mohan Das', 'Security', 21000, 2, 4),
→ (6, 'Priya Menon', 'Maintenance', 25000, 2, 4),
→ (8, 'Farhan Sheikh', 'Cleaner', 17500, 3, 7);
Query OK, 5 rows affected (0.00 sec)
Records: 5  Duplicates: 0  Warnings: 0

(PES2UG24CS157@root) [hostel]>SELECT * FROM Staff;
+-----+-----+-----+-----+-----+-----+
| Staff_ID | Staff_Name      | Salary      | Designation | Hostel_ID | Supervisor_ID |
+-----+-----+-----+-----+-----+-----+
|          1 | Ramesh Iyer     | 45000.00    | Warden      |          1 | NULL          |
|          2 | Sunil Kumar     | 22000.00    | Security    |          1 |              1 |
|          3 | Geeta Rao       | 18000.00    | Cleaner     |          1 |              1 |
|          4 | Anita Sharma    | 46000.00    | Warden      |          2 | NULL          |
|          5 | Mohan Das       | 21000.00    | Security    |          2 |              4 |
|          6 | Priya Menon     | 25000.00    | Maintenance |          2 |              4 |
|          7 | Kiran Bose      | 44000.00    | Warden      |          3 | NULL          |
|          8 | Farhan Sheikh   | 17500.00    | Cleaner     |          3 |              7 |
+-----+-----+-----+-----+-----+-----+
8 rows in set (0.00 sec)
```

## Room

```
(PES2UG24CS157@root) [hostel]>INSERT INTO Room VALUES  
→ (1, 101, 1), (1, 102, 1), (1, 201, 2),  
→ (2, 101, 1), (2, 102, 1),  
→ (3, 101, 1);  
Query OK, 6 rows affected (0.01 sec)  
Records: 6 Duplicates: 0 Warnings: 0
```

```
(PES2UG24CS157@root) [hostel]>SELECT * FROM Room;
```

| Hostel_ID | Room_Number | Floor |
|-----------|-------------|-------|
| 1         | 101         | 1     |
| 1         | 102         | 1     |
| 1         | 201         | 2     |
| 2         | 101         | 1     |
| 2         | 102         | 1     |
| 3         | 101         | 1     |

```
6 rows in set (0.00 sec)
```

## Bed

```
(PES2UG24CS157@root) [hostel]>INSERT INTO Bed VALUES
→ (1, 101, 1, 'Occupied'), (1, 101, 2, 'Occupied'),
→ (1, 102, 1, 'Occupied'), (1, 102, 2, 'Vacant'),
→ (1, 201, 1, 'Occupied'), (1, 201, 2, 'Vacant'),
→ (2, 101, 1, 'Occupied'), (2, 101, 2, 'Vacant'),
→ (2, 102, 1, 'Occupied'), (2, 102, 2, 'Occupied'),
→ (3, 101, 1, 'Occupied'), (3, 101, 2, 'Vacant');
```

Query OK, 12 rows affected (0.01 sec)

Records: 12 Duplicates: 0 Warnings: 0

```
(PES2UG24CS157@root) [hostel]>SELECT * FROM Bed;
```

| Hostel_ID | Room_Number | Bed_Number | Status   |
|-----------|-------------|------------|----------|
| 1         | 101         | 1          | Occupied |
| 1         | 101         | 2          | Occupied |
| 1         | 102         | 1          | Occupied |
| 1         | 102         | 2          | Vacant   |
| 1         | 201         | 1          | Occupied |
| 1         | 201         | 2          | Vacant   |
| 2         | 101         | 1          | Occupied |
| 2         | 101         | 2          | Vacant   |
| 2         | 102         | 1          | Occupied |
| 2         | 102         | 2          | Occupied |
| 3         | 101         | 1          | Occupied |
| 3         | 101         | 2          | Vacant   |

12 rows in set (0.00 sec)

# Student

```
(PES2UG24CS157@root) [hostel]>INSERT INTO Student VALUES
→ (1, 'Aditya', NULL, 'Verma', 'M', '2005-03-14', 'aditya.verma@pes.edu'),
→ (2, 'Neha', 'R', 'Kulkarni', 'F', '2005-07-22', 'neha.kulkarni@pes.edu'),
→ (3, 'Rohan', NULL, 'Shetty', 'M', '2004-11-05', 'rohan.shetty@pes.edu'),
→ (4, 'Sanya', 'K', 'Malhotra', 'F', '2005-01-30', 'sanya.malhotra@pes.edu'),
→ (5, 'Vikram', NULL, 'Nair', 'M', '2004-09-18', 'vikram.nair@pes.edu'),
→ (6, 'Ishita', 'P', 'Bansal', 'F', '2005-05-09', 'ishita.bansal@pes.edu'),
→ (7, 'Arjun', NULL, 'Reddy', 'M', '2005-02-27', 'arjun.reddy@pes.edu'),
→ (8, 'Meera', 'S', 'Pillai', 'F', '2004-12-12', 'meera.pillai@pes.edu');
Query OK, 8 rows affected (0.02 sec)
Records: 8 Duplicates: 0 Warnings: 0

(PES2UG24CS157@root) [hostel]>SELECT * FROM Student;
+-----+-----+-----+-----+-----+-----+-----+
| Student_ID | First_Name | Middle_Name | Last_Name | Gender | DOB | Email |
+-----+-----+-----+-----+-----+-----+-----+
| 1 | Aditya | NULL | Verma | M | 2005-03-14 | aditya.verma@pes.edu |
| 2 | Neha | R | Kulkarni | F | 2005-07-22 | neha.kulkarni@pes.edu |
| 3 | Rohan | NULL | Shetty | M | 2004-11-05 | rohan.shetty@pes.edu |
| 4 | Sanya | K | Malhotra | F | 2005-01-30 | sanya.malhotra@pes.edu |
| 5 | Vikram | NULL | Nair | M | 2004-09-18 | vikram.nair@pes.edu |
| 6 | Ishita | P | Bansal | F | 2005-05-09 | ishita.bansal@pes.edu |
| 7 | Arjun | NULL | Reddy | M | 2005-02-27 | arjun.reddy@pes.edu |
| 8 | Meera | S | Pillai | F | 2004-12-12 | meera.pillai@pes.edu |
+-----+-----+-----+-----+-----+-----+-----+
8 rows in set (0.00 sec)

(PES2UG24CS157@root) [hostel]>_
```

## Student\_phone

```
(PES2UG24CS157@root) [hostel]>INSERT INTO Student_Phone VALUES
→ (1, '9876500001'), (1, '9876500011'),
→ (2, '9876500002'),
→ (3, '9876500003'),
→ (4, '9876500004'), (4, '9876500014'),
→ (5, '9876500005'),
→ (6, '9876500006'),
→ (7, '9876500007'),
→ (8, '9876500008');
```

```
Query OK, 10 rows affected (0.01 sec)
Records: 10  Duplicates: 0  Warnings: 0
```

```
(PES2UG24CS157@root) [hostel]>SELECT * FROM Student_Phone;
```

| Student_ID | Phone_Number |
|------------|--------------|
| 1          | 9876500001   |
| 1          | 9876500011   |
| 2          | 9876500002   |
| 3          | 9876500003   |
| 4          | 9876500004   |
| 4          | 9876500014   |
| 5          | 9876500005   |
| 6          | 9876500006   |
| 7          | 9876500007   |
| 8          | 9876500008   |

```
10 rows in set (0.00 sec)
```

```
(PES2UG24CS157@root) [hostel]>_
```

## Facility

```
(PES2UG24CS157@root) [hostel]>INSERT INTO Facility VALUES
→ (1, 'WiFi Lounge', '24 Hours', 1),
→ (2, 'Laundry Room', '06:00-20:00', 1),
→ (3, 'Gym', '05:00-22:00', 2),
→ (4, 'Study Room', '24 Hours', 2),
→ (5, 'Common Room', '08:00-23:00', 3);
Query OK, 5 rows affected (0.02 sec)
Records: 5  Duplicates: 0  Warnings: 0
```

```
(PES2UG24CS157@root) [hostel]>SELECT * FROM Facility;
+-----+-----+-----+-----+
| Facility_ID | Facility_Name | Operating_Hours | Hostel_ID |
+-----+-----+-----+-----+
|          1 | WiFi Lounge   | 24 Hours        |          1 |
|          2 | Laundry Room  | 06:00-20:00     |          1 |
|          3 | Gym           | 05:00-22:00     |          2 |
|          4 | Study Room    | 24 Hours        |          2 |
|          5 | Common Room   | 08:00-23:00     |          3 |
+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```

```
(PES2UG24CS157@root) [hostel]>_
```

## Uses

```
(PES2UG24CS157@root) [hostel]>INSERT INTO Uses VALUES
→ (1, 1, '2026-01-20'), (2, 1, '2026-01-20'), (3, 1, '2026-01-22'),
→ (1, 2, '2026-01-21'),
→ (4, 3, '2026-01-20'), (5, 3, '2026-01-21'),
→ (4, 4, '2026-01-25'), (6, 4, '2026-01-22'),
→ (7, 5, '2026-01-23');
Query OK, 9 rows affected (0.01 sec)
Records: 9  Duplicates: 0  Warnings: 0
```

```
(PES2UG24CS157@root) [hostel]>SELECT * FROM Uses;
+-----+-----+-----+
| Student_ID | Facility_ID | Usage_Date |
+-----+-----+-----+
|          1 |          1 | 2026-01-20 |
|          2 |          1 | 2026-01-20 |
|          3 |          1 | 2026-01-22 |
|          1 |          2 | 2026-01-21 |
|          4 |          3 | 2026-01-20 |
|          5 |          3 | 2026-01-21 |
|          4 |          4 | 2026-01-25 |
|          6 |          4 | 2026-01-22 |
|          7 |          5 | 2026-01-23 |
+-----+-----+-----+
9 rows in set (0.00 sec)
```

## Allocation

```
(PES2UG24CS157@root) [hostel]>INSERT INTO Allocation VALUES
→ (1, 1, 1, 101, '2026-01-05', '2026-01-06', NULL),
→ (2, 2, 1, 101, '2026-01-05', '2026-01-06', NULL),
→ (3, 3, 1, 102, '2026-01-06', '2026-01-07', NULL),
→ (4, 4, 2, 101, '2026-01-05', '2026-01-06', NULL),
→ (5, 5, 2, 102, '2026-01-06', '2026-01-07', NULL),
→ (6, 6, 2, 102, '2026-01-06', '2026-01-07', NULL),
→ (7, 7, 3, 101, '2026-01-07', '2026-01-08', NULL),
→ (8, 3, 1, 201, '2025-06-01', '2025-06-02', '2025-12-20');
Query OK, 8 rows affected (0.02 sec)
Records: 8  Duplicates: 0  Warnings: 0
```

```
(PES2UG24CS157@root) [hostel]>SELECT * FROM Allocation;
```

| Allocation_ID | Student_ID | Hostel_ID | Room_Number | Allocation_Date | Check_in_Date | Check_out_Date |
|---------------|------------|-----------|-------------|-----------------|---------------|----------------|
| 1             | 1          | 1         | 101         | 2026-01-05      | 2026-01-06    | NULL           |
| 2             | 2          | 1         | 101         | 2026-01-05      | 2026-01-06    | NULL           |
| 3             | 3          | 1         | 102         | 2026-01-06      | 2026-01-07    | NULL           |
| 4             | 4          | 2         | 101         | 2026-01-05      | 2026-01-06    | NULL           |
| 5             | 5          | 2         | 102         | 2026-01-06      | 2026-01-07    | NULL           |
| 6             | 6          | 2         | 102         | 2026-01-06      | 2026-01-07    | NULL           |
| 7             | 7          | 3         | 101         | 2026-01-07      | 2026-01-08    | NULL           |
| 8             | 3          | 1         | 201         | 2025-06-01      | 2025-06-02    | 2025-12-20     |

8 rows in set (0.00 sec)

## Payment

```
(PES2UG24CS157@root) [hostel]>INSERT INTO Payment VALUES
→ (1, 1, '2026-01-10', 45000, 'Online'),
→ (2, 2, '2026-01-11', 45000, 'Cash'),
→ (3, 3, '2026-01-12', 42000, 'Card'),
→ (4, 4, '2026-01-10', 48000, 'Online'),
→ (5, 5, '2026-01-13', 48000, 'Cheque'),
→ (6, 6, '2026-01-14', 48000, 'Online'),
→ (7, 7, '2026-01-15', 40000, 'Cash'),
→ (8, 1, '2026-06-01', 45000, 'Online');
```

```
Query OK, 8 rows affected (0.02 sec)
Records: 8  Duplicates: 0  Warnings: 0
```

```
(PES2UG24CS157@root) [hostel]>SELECT * FROM Payment;
```

| Payment_ID | Student_ID | Payment_Date | Amount   | Payment_Type |
|------------|------------|--------------|----------|--------------|
| 1          | 1          | 2026-01-10   | 45000.00 | Online       |
| 2          | 2          | 2026-01-11   | 45000.00 | Cash         |
| 3          | 3          | 2026-01-12   | 42000.00 | Card         |
| 4          | 4          | 2026-01-10   | 48000.00 | Online       |
| 5          | 5          | 2026-01-13   | 48000.00 | Cheque       |
| 6          | 6          | 2026-01-14   | 48000.00 | Online       |
| 7          | 7          | 2026-01-15   | 40000.00 | Cash         |
| 8          | 1          | 2026-06-01   | 45000.00 | Online       |

8 rows in set (0.00 sec)

## Receipt

```
(PES2UG24CS157@root) [hostel]>INSERT INTO Receipt VALUES  
→ (1, 1, '2026-01-10'),  
→ (2, 2, '2026-01-11'),  
→ (3, 3, '2026-01-12'),  
→ (4, 4, '2026-01-10'),  
→ (5, 5, '2026-01-13'),  
→ (6, 6, '2026-01-14'),  
→ (7, 7, '2026-01-15');
```

Query OK, 7 rows affected (0.01 sec)

Records: 7 Duplicates: 0 Warnings: 0

```
(PES2UG24CS157@root) [hostel]>SELECT * FROM Receipt;
```

| Receipt_ID | Payment_ID | Receipt_Date |
|------------|------------|--------------|
| 1          | 1          | 2026-01-10   |
| 2          | 2          | 2026-01-11   |
| 3          | 3          | 2026-01-12   |
| 4          | 4          | 2026-01-10   |
| 5          | 5          | 2026-01-13   |
| 6          | 6          | 2026-01-14   |
| 7          | 7          | 2026-01-15   |

7 rows in set (0.00 sec)



## Task 2

### PART A

**Q1. Insert a new student, Kabir S. Oberoi (Male, DOB 2005-08-19, email kabir.oberoi@pes.edu), into Student.**

```
(PES2UG24CS157@root) [hostel]>INSERT INTO Student (Student_ID, First_Name, Middle_Name, Last_Name, Gender, DOB, Email)
→ VALUES (9, 'Kabir', 'S', 'Oberoi', 'M', '2005-08-19', 'kabir.oberoi@pes.edu');
Query OK, 1 row affected (0.01 sec)

(PES2UG24CS157@root) [hostel]>SELECT * FROM Student WHERE Student_ID = 9;
+-----+-----+-----+-----+-----+-----+-----+
| Student_ID | First_Name | Middle_Name | Last_Name | Gender | DOB       | Email                |
+-----+-----+-----+-----+-----+-----+-----+
|          9 | Kabir      | S           | Oberoi    | M      | 2005-08-19 | kabir.oberoi@pes.edu |
+-----+-----+-----+-----+-----+-----+-----+
1 row in set (0.00 sec)

(PES2UG24CS157@root) [hostel]>_
```

**Q2. In a single INSERT statement, add both of Kabir's phone numbers – 9876500009 and 9876500019 – to Student\_Phone.**

```
(PES2UG24CS157@root) [hostel]>INSERT INTO Student_Phone (Student_ID, Phone_Number)
→ VALUES (9, '9876500009'), (9, '9876500019');
Query OK, 2 rows affected (0.01 sec)
Records: 2  Duplicates: 0  Warnings: 0

(PES2UG24CS157@root) [hostel]>SELECT * FROM Student_Phone WHERE Student_ID = 9;
+-----+-----+
| Student_ID | Phone_Number |
+-----+-----+
|          9 | 9876500009   |
|          9 | 9876500019   |
+-----+-----+
2 rows in set (0.00 sec)
```

**Q3. In a single INSERT statement, record three new facility usage events: Kabir uses the WiFi Lounge (Facility\_ID 1) on 2026-08-22, Kabir uses the Common Room (Facility\_ID 5) on 2026-08-23, and Vikram Nair (Student\_ID 5) uses the Gym (Facility\_ID 3) on 2026-08-22.**

```
(PES2UG24CS157@root) [hostel]>SELECT * FROM Uses WHERE Student_ID IN (9, 5) AND Usage_Date ≥ '2026-08-22';
+-----+-----+-----+
| Student_ID | Facility_ID | Usage_Date |
+-----+-----+-----+
|          5 |          3 | 2026-08-22 |
|          9 |          1 | 2026-08-22 |
|          9 |          5 | 2026-08-23 |
+-----+-----+-----+
3 rows in set (0.01 sec)

(PES2UG24CS157@root) [hostel]>_
```

**Q4. The university approves a 10% salary hike for every Warden across all hostels. Update Staff accordingly.**

```
(PES2UG24CS157@root) [hostel]>UPDATE Staff
  → SET Salary = Salary * 1.10
  → WHERE Designation = 'Warden';
Query OK, 3 rows affected (0.01 sec)
Rows matched: 3  Changed: 3  Warnings: 0

(PES2UG24CS157@root) [hostel]>SELECT * FROM Staff WHERE Designation = 'Warden';
+-----+-----+-----+-----+-----+-----+
| Staff_ID | Staff_Name | Salary | Designation | Hostel_ID | Supervisor_ID |
+-----+-----+-----+-----+-----+-----+
| 1 | Ramesh Iyer | 49500.00 | Warden | 1 | NULL |
| 4 | Anita Sharma | 50600.00 | Warden | 2 | NULL |
| 7 | Kiran Bose | 48400.00 | Warden | 3 | NULL |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)

(PES2UG24CS157@root) [hostel]>_
```

**Q5. Rohan Shetty (Student\_ID 3) checks out of Room 102, Hostel 1 on 2026-08-20. Close his current allocation record and free up his bed (Bed\_Number 1 in that room).**

```
(PES2UG24CS157@root) [hostel]>SELECT * FROM Allocation WHERE Student_ID = 3;
+-----+-----+-----+-----+-----+-----+-----+
| Allocation_ID | Student_ID | Hostel_ID | Room_Number | Allocation_Date | Check_in_Date | Check_out_Date |
+-----+-----+-----+-----+-----+-----+-----+
| 3 | 3 | 1 | 102 | 2026-01-06 | 2026-01-07 | 2026-08-20 |
| 8 | 3 | 1 | 201 | 2025-06-01 | 2025-06-02 | 2025-12-20 |
+-----+-----+-----+-----+-----+-----+-----+
2 rows in set (0.00 sec)

(PES2UG24CS157@root) [hostel]>SELECT * FROM Bed WHERE Hostel_ID = 1 AND Room_Number = 102;
+-----+-----+-----+-----+
| Hostel_ID | Room_Number | Bed_Number | Status |
+-----+-----+-----+-----+
| 1 | 102 | 1 | Vacant |
| 1 | 102 | 2 | Vacant |
+-----+-----+-----+-----+
2 rows in set (0.00 sec)

(PES2UG24CS157@root) [hostel]>_
```

**Q6. Record a new payment of 45000 (Online) made by Kabir on 2026-08-22, and the receipt generated for it on the same date.**

```
(PES2UG24CS157@root) [hostel]>SELECT * FROM Payment WHERE Payment_ID = 9;
+-----+-----+-----+-----+-----+
| Payment_ID | Student_ID | Payment_Date | Amount   | Payment_Type |
+-----+-----+-----+-----+-----+
|          9 |          9 | 2026-08-22   | 45000.00 | Online       |
+-----+-----+-----+-----+-----+
1 row in set (0.00 sec)

(PES2UG24CS157@root) [hostel]>SELECT * FROM Receipt WHERE Payment_ID = 9;
+-----+-----+-----+
| Receipt_ID | Payment_ID | Receipt_Date |
+-----+-----+-----+
|          8 |          9 | 2026-08-22   |
+-----+-----+-----+
1 row in set (0.00 sec)

(PES2UG24CS157@root) [hostel]>_
```

**Q7. Delete every payment that does not yet have a matching receipt. Do this with a subquery – do not hard-code any Payment\_ID.**

```
(PES2UG24CS157@root) [hostel]>SELECT * FROM Payment
→ WHERE Payment_ID NOT IN (SELECT Payment_ID FROM Receipt);
+-----+-----+-----+-----+-----+
| Payment_ID | Student_ID | Payment_Date | Amount   | Payment_Type |
+-----+-----+-----+-----+-----+
|          8 |          1 | 2026-06-01   | 45000.00 | Online       |
+-----+-----+-----+-----+-----+
1 row in set (0.00 sec)

(PES2UG24CS157@root) [hostel]>
(PES2UG24CS157@root) [hostel]>DELETE FROM Payment
→ WHERE Payment_ID NOT IN (SELECT Payment_ID FROM Receipt);
Query OK, 1 row affected (0.01 sec)
```

**Q8. List the names of all staff members working in Hostel 1 along with the first and last names of all students currently allocated to Hostel 1. Combine both**

result sets using UNION ALL. Display the name(s) and role (Staff or Student) for each record.

```
(PES2UG24CS157@root) [hostel]>SELECT Staff_Name AS Name, 'Staff' AS Role
→ FROM Staff
→ WHERE Hostel_ID = 1
→ UNION ALL
→ SELECT CONCAT(s.First_Name, ' ', s.Last_Name) AS Name, 'Student' AS Role
→ FROM Student s
→ JOIN Allocation a ON s.Student_ID = a.Student_ID
→ WHERE a.Hostel_ID = 1 AND a.Check_out_Date IS NULL;
+-----+-----+
| Name          | Role   |
+-----+-----+
| Ramesh Iyer   | Staff  |
| Sunil Kumar   | Staff  |
| Geeta Rao     | Staff  |
| Aditya Verma  | Student|
| Neha Kulkarni | Student|
+-----+-----+
5 rows in set (0.01 sec)

(PES2UG24CS157@root) [hostel]>_
```

**Q9. Using INTERSECT, find the Student\_IDs of students who have both made at least one payment and used at least one facility.**

```
(PES2UG24CS157@root) [hostel]>SELECT Student_ID FROM Payment
→ INTERSECT
→ SELECT Student_ID FROM Uses;
+-----+
| Student_ID |
+-----+
|           1 |
|           2 |
|           3 |
|           4 |
|           5 |
|           6 |
|           7 |
|           9 |
+-----+
8 rows in set (0.00 sec)

(PES2UG24CS157@root) [hostel]>_
```

**Q10. Using EXCEPT, find every student who has never made a payment.**

```
(PES2UG24CS157@root) [hostel]>SELECT Student_ID FROM Student
    → EXCEPT
    → SELECT Student_ID FROM Payment;
+-----+
| Student_ID |
+-----+
|           8 |
+-----+
1 row in set (0.00 sec)

(PES2UG24CS157@root) [hostel]>_
```

## Part B

**Q1. List the Student\_ID, first, middle and last name, hostel name and room number of every student who currently has an active allocation (Check\_out\_Date IS NULL).**

```
(PES2UG24CS157@root) [hostel]>SELECT s.Student_ID, s.First_Name, s.Middle_Name, s.Last_Name,
→ h.Hostel_Name, a.Room_Number
→ FROM Student s
→ JOIN Allocation a ON s.Student_ID = a.Student_ID
→ JOIN Hostel h ON a.Hostel_ID = h.Hostel_ID
→ WHERE a.Check_out_Date IS NULL;
```

| Student_ID | First_Name | Middle_Name | Last_Name | Hostel_Name       | Room_Number |
|------------|------------|-------------|-----------|-------------------|-------------|
| 1          | Aditya     | NULL        | Verma     | Sunrise Hostel    | 101         |
| 2          | Neha       | R           | Kulkarni  | Sunrise Hostel    | 101         |
| 4          | Sanya      | K           | Malhotra  | Blue Ridge Hostel | 101         |
| 5          | Vikram     | NULL        | Nair      | Blue Ridge Hostel | 102         |
| 6          | Ishita     | P           | Bansal    | Blue Ridge Hostel | 102         |
| 7          | Arjun      | NULL        | Reddy     | Lake View Hostel  | 101         |

6 rows in set (0.00 sec)

**Q2. List every staff member along with the name of their supervisor**

```
(PES2UG24CS157@root) [hostel]>SELECT st.Staff_ID, st.Staff_Name, sup.Staff_Name AS Supervisor_Name
→ FROM Staff st
→ LEFT JOIN Staff sup ON st.Supervisor_ID = sup.Staff_ID;
```

| Staff_ID | Staff_Name    | Supervisor_Name |
|----------|---------------|-----------------|
| 1        | Ramesh Iyer   | NULL            |
| 2        | Sunil Kumar   | Ramesh Iyer     |
| 3        | Geeta Rao     | Ramesh Iyer     |
| 4        | Anita Sharma  | NULL            |
| 5        | Mohan Das     | Anita Sharma    |
| 6        | Priya Menon   | Anita Sharma    |
| 7        | Kiran Bose    | NULL            |
| 8        | Farhan Sheikh | Kiran Bose      |

8 rows in set (0.00 sec)

**Q3. List every payment together with the paying student's name and the corresponding receipt number, if one has been generated.**

```
(PES2UG24CS157@root) [hostel]>SELECT p.Payment_ID, CONCAT(s.First_Name, ' ', s.Last_Name) AS Student_Name,
→ p.Amount, r.Receipt_ID
→ FROM Payment p
→ JOIN Student s ON p.Student_ID = s.Student_ID
→ LEFT JOIN Receipt r ON p.Payment_ID = r.Payment_ID;
+-----+-----+-----+-----+
| Payment_ID | Student_Name | Amount | Receipt_ID |
+-----+-----+-----+-----+
| 1 | Aditya Verma | 45000.00 | 1 |
| 2 | Neha Kulkarni | 45000.00 | 2 |
| 3 | Rohan Shetty | 42000.00 | 3 |
| 4 | Sanya Malhotra | 48000.00 | 4 |
| 5 | Vikram Nair | 48000.00 | 5 |
| 6 | Ishita Bansal | 48000.00 | 6 |
| 7 | Arjun Reddy | 40000.00 | 7 |
| 9 | Kabir Oberoi | 45000.00 | 8 |
+-----+-----+-----+-----+
8 rows in set (0.00 sec)

(PES2UG24CS157@root) [hostel]>_
```

**Q4. Find every student who has never used any hostel facility.**

```
(PES2UG24CS157@root) [hostel]>SELECT s.Student_ID, s.First_Name, s.Last_Name
→ FROM Student s
→ LEFT JOIN Uses u ON s.Student_ID = u.Student_ID
→ WHERE u.Student_ID IS NULL;
+-----+-----+-----+
| Student_ID | First_Name | Last_Name |
+-----+-----+-----+
| 8 | Meera | Pillai |
+-----+-----+-----+
1 row in set (0.00 sec)

(PES2UG24CS157@root) [hostel]>_
```

**Q5. For each hostel, count how many students currently reside in it (include hostels with zero current residents).**

```
(PES2UG24CS157@root) [hostel]>SELECT h.Hostel_ID, h.Hostel_Name,
→ COUNT(a.Student_ID) AS Current_Residents
→ FROM Hostel h
→ LEFT JOIN Allocation a
→ ON h.Hostel_ID = a.Hostel_ID AND a.Check_out_Date IS NULL
→ GROUP BY h.Hostel_ID, h.Hostel_Name;
+-----+-----+-----+
| Hostel_ID | Hostel_Name | Current_Residents |
+-----+-----+-----+
| 1 | Sunrise Hostel | 2 |
| 2 | Blue Ridge Hostel | 3 |
| 3 | Lake View Hostel | 1 |
+-----+-----+-----+
3 rows in set (0.01 sec)

(PES2UG24CS157@root) [hostel]>_
```

**Q6. List every facility usage record as: facility name, student name, usage date – ordered by facility, then date.**

```
(PES2UG24CS157@root) [hostel]>SELECT f.Facility_Name, CONCAT(s.First_Name, ' ', s.Last_Name) AS Student_Name,
→ u.Usage_Date
→ FROM Uses u
→ JOIN Facility f ON u.Facility_ID = f.Facility_ID
→ JOIN Student s ON u.Student_ID = s.Student_ID
→ ORDER BY f.Facility_Name, u.Usage_Date;
```

| Facility_Name | Student_Name   | Usage_Date |
|---------------|----------------|------------|
| Common Room   | Arjun Reddy    | 2026-01-23 |
| Common Room   | Kabir Oberoi   | 2026-08-23 |
| Gym           | Sanya Malhotra | 2026-01-20 |
| Gym           | Vikram Nair    | 2026-01-21 |
| Gym           | Vikram Nair    | 2026-08-22 |
| Laundry Room  | Aditya Verma   | 2026-01-21 |
| Study Room    | Ishita Bansal  | 2026-01-22 |
| Study Room    | Sanya Malhotra | 2026-01-25 |
| WiFi Lounge   | Aditya Verma   | 2026-01-20 |
| WiFi Lounge   | Neha Kulkarni  | 2026-01-20 |
| WiFi Lounge   | Rohan Shetty   | 2026-01-22 |
| WiFi Lounge   | Kabir Oberoi   | 2026-08-22 |

12 rows in set (0.00 sec)

**Q7. For every room, report how many beds in it are currently vacant.**

```
(PES2UG24CS157@root) [hostel]>SELECT r.Hostel_ID, r.Room_Number,
→ COUNT(b.Bed_Number) AS Vacant_Beds
→ FROM Room r
→ LEFT JOIN Bed b
→ ON r.Hostel_ID = b.Hostel_ID AND r.Room_Number = b.Room_Number
→ AND b.Status = 'Vacant'
→ GROUP BY r.Hostel_ID, r.Room_Number;
```

| Hostel_ID | Room_Number | Vacant_Beds |
|-----------|-------------|-------------|
| 1         | 101         | 0           |
| 1         | 102         | 2           |
| 1         | 201         | 1           |
| 2         | 101         | 1           |
| 2         | 102         | 0           |
| 3         | 101         | 1           |

6 rows in set (0.00 sec)

(PES2UG24CS157@root) [hostel]>\_



**Q8. List every staff member with the name and location of the hostel they work at.**

```
(PES2UG24CS157@root) [hostel]>SELECT st.Staff_ID, st.Staff_Name, h.Hostel_Name, h.Location
→ FROM Staff st
→ JOIN Hostel h ON st.Hostel_ID = h.Hostel_ID;
+-----+-----+-----+-----+
| Staff_ID | Staff_Name | Hostel_Name | Location |
+-----+-----+-----+-----+
| 1 | Ramesh Iyer | Sunrise Hostel | North Campus |
| 2 | Sunil Kumar | Sunrise Hostel | North Campus |
| 3 | Geeta Rao | Sunrise Hostel | North Campus |
| 4 | Anita Sharma | Blue Ridge Hostel | South Campus |
| 5 | Mohan Das | Blue Ridge Hostel | South Campus |
| 6 | Priya Menon | Blue Ridge Hostel | South Campus |
| 7 | Kiran Bose | Lake View Hostel | East Campus |
| 8 | Farhan Sheikh | Lake View Hostel | East Campus |
+-----+-----+-----+-----+
8 rows in set (0.00 sec)

(PES2UG24CS157@root) [hostel]>
```

**Q9. For each hostel, compute the total fee revenue collected from its currently-residing students.**

```
(PES2UG24CS157@root) [hostel]>SELECT h.Hostel_ID, h.Hostel_Name,
→ SUM(p.Amount) AS Total_Revenue
→ FROM Hostel h
→ JOIN Allocation a ON h.Hostel_ID = a.Hostel_ID AND a.Check_out_Date IS NULL
→ JOIN Payment p ON a.Student_ID = p.Student_ID
→ GROUP BY h.Hostel_ID, h.Hostel_Name;
+-----+-----+-----+
| Hostel_ID | Hostel_Name | Total_Revenue |
+-----+-----+-----+
| 1 | Sunrise Hostel | 90000.00 |
| 2 | Blue Ridge Hostel | 144000.00 |
| 3 | Lake View Hostel | 40000.00 |
+-----+-----+-----+
3 rows in set (0.00 sec)
```

**Q10. List every facility together with how many times it has been used, including facilities that have never been used.**

```
(PES2UG24CS157@root) [hostel]>SELECT f.Facility_ID, f.Facility_Name,
→      COUNT(u.Student_ID) AS Usage_Count
→ FROM Facility f
→ LEFT JOIN Uses u ON f.Facility_ID = u.Facility_ID
→ GROUP BY f.Facility_ID, f.Facility_Name;
+-----+-----+-----+
| Facility_ID | Facility_Name | Usage_Count |
+-----+-----+-----+
|          1 | WiFi Lounge  |           4 |
|          2 | Laundry Room  |           1 |
|          3 | Gym           |           3 |
|          4 | Study Room    |           2 |
|          5 | Common Room   |           2 |
+-----+-----+-----+
5 rows in set (0.00 sec)

(PES2UG24CS157@root) [hostel]>_
```

**Q11. Write a query using a RIGHT JOIN between HOSTEL and FACILITY to list all facilities along with the name of the hostel providing each facility.**

```
(PES2UG24CS157@root) [hostel]>SELECT f.Facility_Name, h.Hostel_Name
→ FROM Hostel h
→ RIGHT JOIN Facility f ON h.Hostel_ID = f.Hostel_ID;
+-----+-----+
| Facility_Name | Hostel_Name |
+-----+-----+
| WiFi Lounge  | Sunrise Hostel |
| Laundry Room  | Sunrise Hostel |
| Gym           | Blue Ridge Hostel |
| Study Room    | Blue Ridge Hostel |
| Common Room   | Lake View Hostel |
+-----+-----+
5 rows in set (0.00 sec)
```

**Q12. Write a query using a LEFT JOIN to list all students (First\_Name, Last\_Name, Email\_Address) along with their assigned Room\_Number. Ensure**

that students who do not have an allocated room, such as Rohan, are also included in the result.

```
(PES2UG24CS157@root) [hostel]>-- Q12
(PES2UG24CS157@root) [hostel]>SELECT s.First_Name, s.Last_Name, s.Email AS Email_Address, a.Room_Number
→ FROM Student s
→ LEFT JOIN Allocation a
→ ON s.Student_ID = a.Student_ID AND a.Check_out_Date IS NULL;
+-----+-----+-----+-----+
| First_Name | Last_Name | Email_Address | Room_Number |
+-----+-----+-----+-----+
| Aditya     | Verma     | aditya.verma@pes.edu | 101 |
| Neha       | Kulkarni  | neha.kulkarni@pes.edu | 101 |
| Rohan      | Shetty    | rohan.shetty@pes.edu | NULL |
| Sanya      | Malhotra  | sanya.malhotra@pes.edu | 101 |
| Vikram     | Nair      | vikram.nair@pes.edu | 102 |
| Ishita     | Bansal    | ishita.bansal@pes.edu | 102 |
| Arjun      | Reddy     | arjun.reddy@pes.edu | 101 |
| Meera      | Pillai    | meera.pillai@pes.edu | NULL |
| Kabir      | Oberoi    | kabir.oberoi@pes.edu | NULL |
+-----+-----+-----+-----+
9 rows in set (0.00 sec)

(PES2UG24CS157@root) [hostel]>_
```