

PROGRAM1

Code:

```
create table emp(si int,name1 varchar(20),destination varchar(20),branch varchar(20));

insert into emp values
(1,'Suresh','Manager','Chennai'),(2,'Ramesh','Supervisor','Madurai'),(3,'Hari','Assistant','Trichy');

select * from emp;

alter table emp
add salary int;

alter table emp modify name1 varchar(20);

select * from emp;

describe emp;

rename table emp to employee;

delete from employee where si = 2;

select * from employee;
```

Output:

si	name1	destination	branch
1	Suresh	Manager	Chennai
2	Ramesh	Supervisor	Madurai
3	Hari	Assistant	Trichy

si	name1	destination	branch	salary
1	Suresh	Manager	Chennai	NULL
2	Ramesh	Supervisor	Madurai	NULL
3	Hari	Assistant	Trichy	NULL

Field	Type	Null	Key	Default	Extra
si	int	YES		NULL	
name1	varchar(20)	YES		NULL	
destination	varchar(20)	YES		NULL	
branch	varchar(20)	YES		NULL	
salary	int	YES		NULL	

si	name1	destination	branch	salary
1	Suresh	Manager	Chennai	NULL
2	Ramesh	Supervisor	Madurai	NULL
3	Hari	Assistant	Trichy	NULL