

Step-by-Step Guide for Setting Up a Cron Job to Execute Reset expired request.

This guide will help you create a cron job that executes the following cURL command to reset expired requests:

Description

In the Manual Adjudication app, when operators open records, their status changes from "NEW" to "PROCESSING". Records in the "PROCESSING" state are not available for other operators until their status is reset to either "NEW" or "PROCESSED". However, sometimes operators open a record but do not submit a decision, leaving the record stuck in the "PROCESSING" state. Such records remain inaccessible to other operators.

To address this issue, a cron job is configured to call the "resetExpiredRecords" API. This API resets all "PROCESSING" state records back to the "NEW" state, making them available for the adjudication process once again.

```
curl --location --request PUT 'http://localhost:7070/api/resetExpiredRequests'
```

Step 1: Open the Crontab File

To edit the cron jobs for the current user, use the following command:

```
crontab -e
```

If prompted, select your preferred text editor (e.g., nano, vim).

Step 2: Schedule the Cron Job

Add the following lines to schedule the cURL command to run daily at 23:00 and 00:00:

```
0 23 * * * curl --location --request PUT
'http://localhost:7070/api/resetExpiredRequests'

0 0 * * * curl --location --request PUT
'http://localhost:7070/api/resetExpiredRequests'
```

Explanation of the Cron Syntax:

Field	Description
'0' (Minute)	Run the command at the 0th minute.
'23' (Hour)	Run the command at 23:00 (11:00 PM).
'0' (Hour)	Run the command at 00:00 (Midnight).
'*' (Day)	Run the command every day.
'*' (Month)	Run the command every month.

'*' (Weekday) Run the command on any day of the week.

Step 3: Save and Exit

- If using **nano**, press 'CTRL + O' to save and 'CTRL + X' to exit.
 - If using **vim**, press 'ESC', type ':wq', and press 'ENTER'.
-

Step 4: Verify the Cron Job

To confirm that the cron job is added, list the current cron jobs:

```
crontab -l
```

You should see the lines you just added.

Step 5: Check Logs (Optional)

To ensure the cron job is running correctly, check the system logs:

For Debian/Ubuntu:

```
grep CRON /var/log/syslog
```

For CentOS/RedHat:

```
tail -f /var/log/cron
```

Your cron job is now set up to execute the cURL command daily at 23:00 and 00:00. If you encounter issues, verify that the 'cron' service is running and ensure the cURL command works independently in the terminal.