

# CS23336-Introduction to Python Programming

**Started on** Wednesday, 28 August 2024, 2:37 PM

**State** Finished

**Completed on** Wednesday, 28 August 2024, 2:58 PM

**Time taken** 20 mins 51 secs

**Marks** 5.00/5.00

**Grade** 100.00 out of 100.00

## Question 1

Correct

Mark 1.00 out of 1.00

Flag question

### Question text

complete function to implement coin change making problem i.e. finding the minimum number of coins of certain denominations that add up to given amount of money.

The only available coins are of values 1, 2, 3, 4

Input Format:

Integer input from stdin.

Output Format:

return the minimum number of coins required to meet the given target.

Example Input:

16

Output:

4

Explanation:

We need only 4 coins of value 4 each

Example Input:

25

Output:

7

Explanation:

We need 6 coins of 4 value, and 1 coin of 1 value

Answer:(penalty regime: 0 %)

Reset answer

```
1 def coinChange(n):
2     coins=[4,3,2,1]
3     nc=0
4     for coin in coins:
5         while n>=coin:
6             n-=coin
7             nc+=1
8     return nc
9
10
11
```

## Feedback

Test	Expected	Got
print(coinChange(16))	4	4

Passed all tests!

Correct

Marks for this submission: 1.00/1.00.

## Question 2

Correct

Mark 1.00 out of 1.00

Flag question

### Question text

A strobogrammatic number is a number that looks the same when rotated 180 degrees (looked at upside down).

Write a program to determine if a number is strobogrammatic. The number is represented as a string.

**Example 1:****Input:**

69

**Output:**

true

**Example 2:****Input:**

88

**Output:**

true

**Example 3:****Input:**

962

**Output:**

false

**Example 4:****Input:**

1

**Output:**

true

For example:

Test	Result
------	--------

<code>print(Strobogrammatic(69))</code>	<code>true</code>
---	-------------------

<code>print(Strobogrammatic(962))</code>	<code>false</code>
--	--------------------

Answer:(penalty regime: 0 %)

Reset answer

```
1 def Strobogrammatic(n):  
2     n=str(n)  
3     r={'0':'0','1':'1','6':'9','8':'8','9':'6'}  
4     for i in range(len(n)//2+1):
```

```

5         if n[i] not in r or r[n[i]]!=n[-i-1]:
6             return "false"
7     return "true"

```

## Feedback

Test	Expected	Got
print(Strobogrammatic(69))	true	true
print(Strobogrammatic(88))	true	true
print(Strobogrammatic(962))	false	false

Passed all tests!

Correct

Marks for this submission: 1.00/1.00.

## Question 3

Correct

Mark 1.00 out of 1.00

Flag question

### Question text

A number is considered to be ugly if its only prime factors are 2, 3 or 5.

[1, 2, 3, 4, 5, 6, 8, 9, 10, 12, 15, ...] is the sequence of ugly numbers.

Task:

complete the function which takes a number n as input and checks if it's an ugly number.

return ugly if it is ugly, else return not ugly

Hint:

An ugly number U can be expressed as:  $U = 2^a * 3^b * 5^c$ , where a, b and c are nonnegative integers.

For example:

Test	Result
<code>print(checkUgly(6))</code>	ugly
<code>print(checkUgly(21))</code>	not ugly

Answer:(penalty regime: 0 %)

Reset answer

```
1 def checkUgly(n):
2     if n<=0:
3         return "not ugly"
4     while n%2==0:
5         n//=2
6     while n%3==0:
7         n//=3
8     while n%5==0:
9         n//=5
10    if n==1:
11        return "ugly"
12    else:
13        return "not ugly"
14
```

## Feedback

Test	Expected	Got
<code>print(checkUgly(6))</code>	ugly	ugly
<code>print(checkUgly(21))</code>	not ugly	not ugly

Passed all tests!

Correct

Marks for this submission: 1.00/1.00.

## Question 4

Correct

Mark 1.00 out of 1.00

Flag question

## Question text

Write a function that returns the value of  $a+aa+aaa+aaaa$  with a given digit as the value of  $a$ .

Suppose the following input is supplied to the program:

9

Then, the output should be:

$9+99+999+9999=11106$

Sample Input Format:

9

Sample Output format:

11106

For example:

Test	Result
------	--------

<code>print(Summation(8))</code>	9872
----------------------------------	------

Answer:(penalty regime: 0 %)

Reset answer

```
1 def Summation(a):
2     n1=int("%s" %a)
3     n2=int("%s%s" %(a,a))
4     n3=int("%s%s%s" %(a,a,a))
5     n4=int("%s%s%s%s" %(a,a,a,a))
6     return n1+n2+n3+n4
```

## Feedback

Test	Expected	Got
<code>print(Summation(8))</code>	9872	9872
<code>print(Summation(10))</code>	10203040	10203040

Passed all tests!

Correct

Marks for this submission: 1.00/1.00.

## Question 5

Correct

Mark 1.00 out of 1.00

Flag question

### Question text

An e-commerce company plans to give their customers a special discount for Christmas.

They are planning to offer a flat discount. The discount value is calculated as the sum of all the prime digits in the total bill amount.

Write an algorithm to find the discount value for the given total bill amount.

Constraints

$1 \leq \text{orderValue} < 10^7$

Input

The input consists of an integer `orderValue`, representing the total bill amount.

Output

Print an integer representing the discount value for the given total bill amount.

Example Input

578

Output

12

For example:

Test	Result
<code>print(christmasDiscount(578))</code>	12

Answer:(penalty regime: 0 %)

Reset answer

```
1 def christmasDiscount(n):
```

```
2 discount=0
3 for digit in str(n):
4     digit=int(digit)
5     if digit in[2,3,5,7]:
6         discount+=digit
7 return discount
8
```

## Feedback

Test	Expected	Got
print(christmasDiscount(578))	12	12

Passed all tests!

Correct

Marks for this submission: 1.00/1.00.

[Finish review](#)