Started on	Tuesday, 20 August 2024, 2:45 PM
State	Finished
Completed on	Tuesday, 27 August 2024, 2:52 PM
Time taken	7 days
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Given an array of N integer, we have to maximize the sum of arr[i] * i, where i is the index of the element (i = 0, 1, 2, ..., N).Write an algorithm based on Greedy technique with a Complexity O(nlogn).

Input Format:

First line specifies the number of elements-n

The next n lines contain the array elements.

Output Format:

Maximum Array Sum to be printed.

Sample Input:

5

2 5 3 4 0

Sample output:

40

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
#include<math.h>
int main(){
    int a;
    scanf("%d",&a);
    int aaa[a];
    int aa;
    for(int i=0;i<a;i++){
        scanf("%d",&aaa[i]);
    }
    for(int i=0;i<a;i++){
        for(int j=i+1;j<a;j++){
            if(aaa[i]>aaa[j]){
                aa=aaa[i];
                aaa[i]=aaa[j];
                aaa[j]=aa;
            }
        }
```

	Input	Expected	Got	
✔	5 2 5 3 4 0	40	40	✔
✔	10 2 2 2 4 4 3 3 5 5 5	191	191	✔

	Input	Expected	Got	
✔	2 45 3	45	45	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

◄ 3-G-Burger Problem

Jump to...

5-G-Product of Array elements-Minimum ►