

Cisco Packet Tracer

File Edit Options View Tools Extensions Help

Logical Physical x: 384, y: 62

```
graph TD
    Switch0[2960-24TT Switch0] --- PC0[PC-PT PC0  
172.16.0.1  
255.255.0.0]
    Switch0 --- PC1[PC-PT PC1  
172.16.0.2  
255.255.0.0]
    Switch0 --- PC2[PC-PT PC2  
172.16.0.4  
255.255.0.0]
    Switch0 --- Printer0[Printer-PT Printer0  
172.16.0.3  
255.255.0.0]
```

PC0

Physical Config **Desktop** Programming Attributes

Command Prompt

```
Pinging 172.16.0.3 with 32 bytes of data:

Reply from 172.16.0.3: bytes=32 time=1ms TTL=128
Reply from 172.16.0.3: bytes=32 time=5ms TTL=128
Reply from 172.16.0.3: bytes=32 time=10ms TTL=128
Reply from 172.16.0.3: bytes=32 time<1ms TTL=128

Ping statistics for 172.16.0.3:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 10ms, Average = 4ms

C:\>Ping 172.16.0.4

Pinging 172.16.0.4 with 32 bytes of data:

Reply from 172.16.0.4: bytes=32 time=1ms TTL=128
Reply from 172.16.0.4: bytes=32 time<1ms TTL=128
Reply from 172.16.0.4: bytes=32 time<1ms TTL=128
Reply from 172.16.0.4: bytes=32 time<1ms TTL=128

Ping statistics for 172.16.0.4:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 1ms, Average = 0ms

C:\>
```

Time: 00:29:59

Realtime Simulation

Copper Straight-Through

09:45 PM 07-10-2022