Rate File Generator

Usage: rfg input_file_name [path_for_output_file]
Convert formated text file into Bulteh rate file
Parameters:

input_file_name - name of input file (formated text file) with full path
path_for_output_file - folder,where output file will be placed
If ommited, output file will be placed in same folder,
where the input file is

The input file contains 2 parts: header data and rate data:

1. Header data Format is as follows:

>HEADER_FIELD_NAME = VALUE
Leading and tailing whitespaces will be removed from VALUE
No whitespaces allowed before '>' symbol. One Parameter per row!
Below is the list of HEADER_FIELDs that must have VALUE defined in the input file:
>START_TIME;
>END_TIME;
>CP_NAME;
>CP_ADDRESS;
>CP_CODE;
>FILE_NAME;
>RATE_FAT_BELOW_MIN;
>RATE_SNF_BELOW_MIN;
>RATE_FAT_SNF_BELOW_MIN;
>VENDOR_RANK;
>MILK_TYPE

START_TIME - END_TIME define period of validity of the output rate file
date and time must be defined in this format: "dd.MM.yyy hh:mm:ss"
allowed range for year is 2000-2099
example:
>START_TIME = 02.01.2000 00:00:00
>END_TIME = 12.01.2089 23:59:59

CP_NAME - name of collection point, can be long 35 characters max
CP_ADDRESS - collection point address, can be long 35 characters max
CP_CODE - collection point code, can be long 8 characters max
FILE_NAME - name of the output file, which will be created.
Can be long 8 characters max, WITHOUT extension
example:
>CP_NAME = Benny Impex Private Limited
>CP_CODE = BIPL0001

RATE_FAT_BELOW_MIN - rate value to be applied if FAT is below the MIN_FAT value
RATE_SNF_BELOW_MIN - rate value to be applied if SNF is below the MIN_SNF value
RATE_FAT_SNF_BELOW_MIN - rate value to be applied if both FAT and SNF are below the MIN_FAT and MIN_SNF values.

example:
>RATE_FAT_BELOW_MIN = 0.1
VENDOR_RANK- Can only be 0 or 1
MILK_TYPE- Can be one of these: COW,BUFFALO,MIXED
example:
>MILK_TYPE = COW

2. Rate Data is provided as a 2D table, below the Header:

The following is an example of 2D table for the Fat range from 3.0 to 4.0 and SNF range from 8.0 to 9.0:

```
*FAT,8.0,8.1,8.2,8.3,8.4,8.5,8.6,8.7,8.8,8.9,9.0
3.0,0.5,0.5,0.5,0.6,0.6,0.6,0.7,0.7,0.7,0.8,0.8
3.1,0.6,0.6,0.6,0.7,0.7,0.7,0.8,0.8,0.8,0.9,0.9
3.2,0.7,0.7,0.7,0.8,0.8,0.8,0.9,0.9,0.9,1.0,1.0
3.3,0.8,0.8,0.8,0.9,0.9,0.9,1.0,1.0,1.0,1.1,1.1
3.4,0.9,0.9,0.9,1.0,1.0,1.0,1.1,1.1,1.1,1.2,1.2
3.5,1.0,1.0,1.0,1.1,1.1,1.1,1.2,1.2,1.2,1.3,1.3
3.6,1.1,1.1,1.1,1.2,1.2,1.2,1.3,1.3,1.3,1.4,1.4
3.7,1.2,1.2,1.2,1.3,1.3,1.3,1.4,1.4,1.4,1.5,1.5
3.8,1.3,1.3,1.3,1.4,1.4,1.4,1.5,1.5,1.5,1.6,1.6
3.9,1.4,1.4,1.4,1.5,1.5,1.5,1.6,1.6,1.6,1.7,1.7
4.0,1.5,1.5,1.5,1.6,1.6,1.6,1.7,1.7,1.7,1.8,1.8
```

All Rate data must be provided in one continuous block and no other data should be available inside this Rate data block.

Header data can be provided before, after or before and after the Rate data block.