

Vendor File Generator

Description: `vendor\_cmd` is a utility for generating Bulteh (.VEN) vendor files from given text file template.

Input file (VFDS in the older versions):

The input file which contains data for generating new vendor files is *provisionally* called VFDS (Vendor File Data Source file).

VFDS file is a simple text file with the similar format as exported vendor files from **Milk Vendor GUI utilities**, only difference is that this file contains additional keywords describing vendor file header parameters. Those are missing in standard CSV file Import/Export approach.

VFDS file is separated in two parts:

1. Header data sector part
2. Data sector part

Note: Keywords can be in any order or position

* Required/allowed keywords:

VMin

VMax

TMin

TMax

CP_CODE

CP_NAME

CP_ADDRESS

FILE_NAME

START_TIME

END_TIME

VFDS file contains 10 keywords. If provided keywords count is more or less than 10, error code 0xAB is returned.

Parameters format

- Every keyword should start with > symbol!
- Every keyword is separated with = from his value!
- Whitespaces before > symbol are not allowed. It has to be the first character in the line!
- Only one keyword per row is allowed!
- If duplicating keyword is found only one of the duplicating lines will be considered
- Trailing and Leading spaces are ignored.

Example:

```
>VMin = 997
>VMax = 1387
>TMin = 5277
>TMax = 9181
>CP_CODE = CPOINT1
```

>CP_NAME = COLPOINT TEST NAME
>CP_ADDRESS = NEW DELHI INDIA
>FILE_NAME = OUTFILE
>START_TIME = 02.08.2012 4:21:11
>END_TIME = 09.08.2018 6:55:12

Comments:

Every row beginning with * as its first symbol is considered for comment. It will not be interpreted.

Usage:

`vendor_cmd.exe -i MyTemplate.txt -o MyVendorFile.ven`

Error codes:

`**vendor\_cmd**` will be terminated in case of errors or exceptions and it will return one of the following error codes, otherwise success exit code is **0**

*Input file cannot be opened or read = **0x96***

*Invalid command line parameters or arguments = **0xA1***

*Error when parsing input (template) file = **0xAB***

*Invalid vendor/transporter code in the input file = **0x8C***

*Invalid keyword value = **0x8D***