



R&D Project Proposal

Robot motion planning in dynamic environment: A comparative study

Dharmin Bakaraniya

Supervised by

Prof. Dr. Ervin Prassler Dr. Cesar Lopez Martinez

1. Introduction

The topic for this R&D is motion planning for dynamic environment. By solving this problem, we can ensure

- Safe environment for humans and for robots
- Cost effective transportation of goods

Motion planning in dynamic environment needs to perform the following task

- Reach the desired target position
- Avoid static and moving obstacle
- Consider actuator constraints
- Consider geometry of robot

It needs to perform these tasks in *fast* and *efficient* manner. The *fast* nature of planner dictates that the planning of motion should be at least performed in real time for the robot to react to its environment. An approach is *efficient* if the planner

- does not collide
- takes minimal time to reach goal position
- does not require a large amount of sensor data
- does not require a lot of computational resources

1.1. Problem Statement

- Current approaches are not generalised for all types of robot. They work best for circular holonomic robots. Velocity based approaches, which perform very well, are mostly tested on point sized robots.
- Some approaches are defined and tested for non-holonomic vehicles, but they either lack in terms of computation speed or they do not guarantee a solution.
- Most of the approaches do not even address how the objects needs to be perceived. They do not address how errors from perception and control would influence the planner's efficiency.
- This work will provide a comparative study on existing approaches for motion planning in time varying environment.

2. Related Work

- All the existing approaches have tested their efficiency on different robots and in different test environment.
- As the measuring criterion for each of them is different, it becomes an impossible task to determine a clear winner.
- There are several existing survey article:
 - Mohanan et al.[1] covers 101 research papers that were published between 1985 and 2016 in the field of motion planning in dynamic environment. They have addressed all the approaches but a comparative analysis of all the approaches with their contributions and deficiencies is left to be desired.
 - Hoy et al.[2] provides a survey for algorithms which provide collision free navigation for robots. This survey is not only detailed but also quite broad as it covers obstacle avoidance algorithm as well. Even though it provides a comparison between main approaches based on numerous criterion, it still does not evaluate these approaches on a standard uniform test.
 - Keshmiri et al.[3] provides a survey specifically for motion planning in dynamic environment. It covers all the approaches presented in research papers published between 1986 and 2008 totalling up to 150 papers. They have provided a comparison on how much contribution has been made in motion planning field based on different approach but regarding the actual approaches itself, only a summary of at most 23 sentences for each approach is provided.
 - Approaches [4] and [5] are quite dated and does not cover any state of the art approaches in motion planning for dynamic environment.
- Existing approaches generally provide critique and deficiencies on their previous works. These are generally helpful but they mostly compare their approach with the existing solutions and only point out the deficiencies that they have addressed. Therefore, though these comparisons are helpful, they might not be completely reliable.

2.1. Approaches in motion planning for dynamic environment

2.1.1. Velocity based

- Dynamic window approach: Fox et al.[6] proposed the original idea for simply optimizing a function which balances robot's distance from goal, distance from nearest obstacle and current velocity. This approach, despite being robust, simple and fast did not work for dynamic environment. Later, Brock et al.[7] extended this approach for global path planning and for dynamic environments by combining it with NF1 algorithm. This eradicated the problem of local minima. It has been since extended in [8] and [9]
- Velocity obstacle (VO): Originally developed by Fiorini et al.[10], this approach proposes to avoid obstacles by choosing velocity outside collision cone. This approach unifies the representation for avoiding static and dynamic obstacles. This idea has since been transformed to incorporate many scenarios[11][12][13][14]. For multi robot systems, Van den berg et al.[15][16][17] have extended VO approach.
- ICS based approach: Inevitable collision states (ICS)[18][19][20] have proposed a solution to avoid states that has no outcome other than collision. They propose that this states if avoided will ensure that the robot will never collide. They have approached this problem in a mathematical way. They provide a very fast and almost infinite look ahead option[1].

2.1.2. Roadmap based

- Randomized kinodynamic planning: Hsu et al.[21] provides an extension of probabilistic roadmap approach by considering kinodynamics of the robot before choosing a motion control.
- Van den berg et al.[22] provides an extension on roadmap based motion planning for static and dynamic obstacles.

2.1.3. Other

• Nearness diagram: [23] proposes a divide and conquer strategy for motion planning in dynamic environment using a geometry based approach for their implementation.

3. Project Plan

3.1. Work Packages and milestones

The bare minimum will include the following packages:

Work packages	Tasks
Literature review	Gather literature on motion planning for dynamic environment
	Define use cases based on general situations of motion planning
	Create a solid review criteria based on use case
	Compare different approaches based on review criteria
	Exclude approaches based on review criteria
	Create annotated bibliography for top 30 approaches
	Create summary of annotated bibliography and add it to report
Identify parameters	Define performance metrics to test approaches
for Experiments	Identify parameters and assumptions of dynamic environment
	which will be used for experiments
	Refine use cases (if needed)
	Choose top 3 motion planning approaches based on use case
	Add description of dynamic environment, use cases and
	performance metrics to report
Experiments	Implement top 3 motion planning approaches
	Test 3 approaches on use cases and gather results
	Analyse results and provide explanation for it
	Provide conclusion of experiment
	Document experiment results, proof and conclusion
Documentation	Document conclusion and review
	Refine report for better readability

Table 3.1: Work packages and milestones

3.2. Project Schedule

Please see Figure 3.1




Figure 3.1: Gannt chart for workpackages

3.3. Deliverables

3.3.1. Minimum

- Annotated bibliography on top 30 approaches for motion planning in dynamic environment
- Description of review criteria, use cases, performance metrics
- Comparison of 3 approaches of motion planning in dynamic environment in simulation
- Proof of these 3 approaches being best based on experiment results and analysis
- R & D report

3.3.2. Expected

- All items in minimum deliverable
- Comparison of 3 approaches of motion planning in dynamic environment on actual robot

3.3.3. Desired

- All items in expected deliverable
- Experiment results of 3 approaches on more use cases and complex scenarios
- Comparison of an additional algorithm

References

- [1] M. Mohanan and A. Salgoankar, "A survey of robotic motion planning in dynamic environments," *Robotics and Autonomous Systems*, vol. 100, pp. 171 185, 2018.
- [2] M. Hoy, A. S. Matveev, and A. V. Savkin, "Algorithms for collision-free navigation of mobile robots in complex cluttered environments: a survey," *Robotica*, vol. 33, no. 3, p. 463–497, 2015.
- [3] S. Keshmiri and S. Payandeh, "An overview of mobile robotic agents motion planning in dynamic environments," in *Proceedings of the 14th IASTED International Conference, Robotics and Applications (RA20), MA, Boston*, pp. 152–159, 2009.
- [4] K. Fujimura, *Motion planning in dynamic environments*. Springer Science & Business Media, 1991.
- [5] T. Tsubouchi, "Motion planning for mobile robots in a time-varying environment: A survey," *Journal of Robotics and Mechatronics*, vol. 8, no. 1, pp. 15–24, 1996.
- [6] D. Fox, W. Burgard, and S. Thrun, "The dynamic window approach to collision avoidance," *IEEE Robotics & Automation Magazine*, vol. 4, no. 1, pp. 23–33, 1997.
- [7] O. Brock and O. Khatib, "High-speed navigation using the global dynamic window approach," in *Robotics and Automation*, 1999. Proceedings. 1999 IEEE International Conference on, vol. 1, pp. 341–346, IEEE, 1999.
- [8] M. Seder and I. Petrovic, "Dynamic window based approach to mobile robot motion control in the presence of moving obstacles," in *Robotics and Automation*, 2007 IEEE International Conference on, pp. 1986–1991, IEEE, 2007.
- [9] P. Ogren and N. E. Leonard, "A convergent dynamic window approach to obstacle avoidance," *IEEE Transactions on Robotics*, vol. 21, no. 2, pp. 188– 195, 2005.
- [10] P. Fiorini and Z. Shiller, "Motion planning in dynamic environments using velocity obstacles," *The International Journal of Robotics Research*, vol. 17, no. 7, pp. 760–772, 1998.

- [11] Z. Shiller, O. Gal, T. Fraichard, et al., "The nonlinear velocity obstacle revisited: The optimal time horizon," in Workshop on guaranteeing safe navigation in dynamic environments. In IEEE international conference on robotics and automation, 2010.
- [12] E. Owen and L. Montano, "A robocentric motion planner for dynamic environments using the velocity space," in 2006 IEEE/RSJ International Conference on Intelligent Robots and Systems, pp. 4368–4374, Oct 2006.
- [13] E. Owen and L. Montano, "Motion planning in dynamic environments using the velocity space," in 2005 IEEE/RSJ International Conference on Intelligent Robots and Systems, pp. 2833–2838, Aug 2005.
- [14] S. J. Guy, J. Chhugani, C. Kim, N. Satish, M. Lin, D. Manocha, and P. Dubey, "Clearpath: highly parallel collision avoidance for multi-agent simulation," in *Proceedings of the 2009 ACM SIGGRAPH/Eurographics Symposium on Computer Animation*, pp. 177–187, ACM, 2009.
- [15] J. Van Den Berg, M. Lin, and D. Manocha, "Reciprocal velocity obstacles for real-time multi-agent navigation," in *Robotics and Automation*, 2008. ICRA 2008. IEEE International Conference on, pp. 1928–1935, IEEE, 2008.
- [16] J. Van Den Berg, S. J. Guy, M. Lin, and D. Manocha, "Reciprocal n-body collision avoidance," in *Robotics research*, pp. 3–19, Springer, 2011.
- [17] J. Van Den Berg, D. Ferguson, and J. Kuffner, "Anytime path planning and replanning in dynamic environments," in *Robotics and Automation*, 2006. ICRA 2006. Proceedings 2006 IEEE International Conference on, pp. 2366– 2371, IEEE, 2006.
- [18] T. Fraichard and H. Asama, "Inevitable collision states—a step towards safer robots?," *Advanced Robotics*, vol. 18, no. 10, pp. 1001–1024, 2004.
- [19] S. Petti and T. Fraichard, "Safe motion planning in dynamic environments," in *Intelligent Robots and Systems*, 2005.(IROS 2005). 2005 IEEE/RSJ International Conference on, pp. 2210–2215, IEEE, 2005.
- [20] L. Martinez-Gomez and T. Fraichard, "Collision avoidance in dynamic environments: an ics-based solution and its comparative evaluation," in *Robotics and Automation*, 2009. ICRA'09. IEEE International Conference on, pp. 100–105, IEEE, 2009.
- [21] D. Hsu, R. Kindel, J.-C. Latombe, and S. Rock, "Randomized kinodynamic motion planning with moving obstacles," *The International Journal of Robotics Research*, vol. 21, no. 3, pp. 233–255, 2002.

- [22] J. P. Van Den Berg and M. H. Overmars, "Roadmap-based motion planning in dynamic environments," *IEEE Transactions on Robotics*, vol. 21, no. 5, pp. 885–897, 2005.
- [23] J. Minguez and L. Montano, "Nearness diagram (nd) navigation: collision avoidance in troublesome scenarios," *IEEE Transactions on Robotics and Automation*, vol. 20, no. 1, pp. 45–59, 2004.