Name :- Aditya B. Mirajgave
Reg No :- 2024BIT021

Page No. ( ) Date :

Assignment no. 1

Solution of ISE - 1 paper

(1)(a) — ?

→ 65 69

Justification :-

ASCII value of 'A' is 65 and since 'A' is stored in variable 'a' which of type 'int', 'A' will be stored as 65 and a+4 = 69

(b) — ?

→ Output :-

-6

-a-++a+--a = -5 - 6 + 5 = -6

Since a = 5, ++a will be 6 and then --a will be again 5

(c) — ?

→ Output :-

" A\t bc\5d "

Justification :-

Since " " is replaced by "".

Printers Nanded

Scanned with OKEN Scanner

Page No. ( ) Date :

d) — ?

→ Output :-

16

Justification :-

8 + 16/2

= 8 + 8

= 16

Q2) — ?

b) — ? Output :-

→ -24246

Justification :-

The range of short is from -32768 to 32767. Total numbers are 65536.

65536 x 76 = 4980736

6022026 - 4980736 = 41290

Since, 41290 > 32767

∴ 41290 - 65536

= -24246

Printer's Nanded

Scanned with OKEN Scanner

Page No. ( ) Date :

c) — ?

→ isBlank() gives output 'true' if there are blank spaces in string and isEmpty() will give output 'true' if the string is Empty.

if a string contains a space, isBlank() will give output 'true' whereas isEmpty() will give output 'false'.

Hence isBlank() cannot be used as as a replacement for isEmpty().

Printers Nanded

Scanned with OKEN Scanner