EXPERIMENT 5

IMPLEMENTATION OF MESH TOPOLOGY USING PACKET TRACER

Aim

To implement a mesh topology using Packet Tracer and to transmit data between the devices connected in the mesh topology.

Software Used

Cisco Packet Tracer (end devices, switches, connecting cables)

Procedure

Step 1: Start Cisco Packet Tracer.

Step 2: Click **End Devices**, select the Generic PC and click in the workspace to place it. Place four PCs in the same way.

Step 3: Click **Switches**, select the 2960 switch and place four switches in the workspace.

Step 4: Click **Connections**, connect each PC to one switch, and then connect every switch to all the other switches, so that each switch has a direct link to every other switch.

Step 5: Wait until the amber link lights on the switch ports turn green. This happens after the Spanning Tree Protocol (STP) process finishes, and the ports can then forward frames.

Step 6: Click PC0, open the **Config** tab, select FastEthernet0 and type the IP address. The subnet mask is generated automatically. Do the same for every PC with a different IP address.

Step 7: To confirm data transfer, click a PC, open **Desktop** and then **Command Prompt**, and ping the IP address of another PC. The ping statistics are displayed.

Execution Screenshot




Fig: Mesh topology with ICMP ping from PC0 to PC2

Result

Thus the mesh topology is implemented with the Packet Tracer simulation tool.