

# Rajalakshmi Engineering College

Name: Dharshini A  
Email: 241001049@rajalakshmi.edu.in  
Roll no: 241001049  
Phone: 8056618801  
Branch: REC  
Department: IT - Section 2  
Batch: 2028  
Degree: B.E - IT

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 6\_Q1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Elsa subscribes to a premium service with a base monthly cost, a service tax and an extra feature cost. Assist her in writing an inheritance program that takes input for these values and calculates the total monthly cost.

Refer to the below class diagram:

##### ***Input Format***

The first line of input consists of a double value, representing the base monthly cost.

The second line consists of a double value, representing the service tax.

The third line consists of a double value, representing the extra feature cost.

### **Output Format**

The output prints "Rs. X" where X is a double value, rounded off to two decimal places.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 10.0

2.5

5.0

Output: Rs. 17.50

### **Answer**

```
import java.util.Scanner;
```

```
class Subscription {  
    protected double baseMonthlyCost;  
  
    public Subscription(double baseMonthlyCost) {  
        this.baseMonthlyCost = baseMonthlyCost;  
    }  
}
```

```
class PremiumSubscription extends Subscription {  
    private double serviceTax;  
    private double extraFeatureCost;  
  
    public PremiumSubscription(double baseMonthlyCost, double serviceTax,  
double extraFeatureCost) {  
        super(baseMonthlyCost);  
        this.serviceTax = serviceTax;  
        this.extraFeatureCost = extraFeatureCost;  
    }  
  
    public double calculateMonthlyCost() {  
        return baseMonthlyCost + serviceTax + extraFeatureCost;  
    }  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        Scanner scanner = new Scanner(System.in);  
  
        double baseMonthlyCost = scanner.nextDouble();  
        double serviceTax = scanner.nextDouble();  
        double extraFeatureCost = scanner.nextDouble();  
  
        PremiumSubscription premiumSubscription = new  
PremiumSubscription(baseMonthlyCost, serviceTax, extraFeatureCost);  
  
        double totalMonthlyCost = premiumSubscription.calculateMonthlyCost();  
  
        System.out.printf("Rs. %.2f%n", totalMonthlyCost);  
  
        scanner.close();  
    }  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Dharshini A  
Email: 241001049@rajalakshmi.edu.in  
Roll no: 241001049  
Phone: 8056618801  
Branch: REC  
Department: IT - Section 2  
Batch: 2028  
Degree: B.E - IT

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 6\_Q2

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Alice is managing an online store and wants to implement a program using inheritance to calculate the selling price of products after applying discounts.

Guide her by following the instructions:

Create a base class called Product with a public double attribute price. Create a subclass called DiscountedProduct, which extends Product and includes a private double attribute discount rate. This subclass has a method called calculateSellingPrice() to determine the final selling price after applying the discount.

Formula: Discounted selling price = price \* (1 - discount rate)

***Input Format***

The first line of input consists of a double value p, the initial price of the product.

The second line consists of a double value d, the discount rate.

### **Output Format**

The output prints "Rs. X", where X is a double value, representing the calculated discounted selling price, rounded off to two decimal places.

If the discount rate is greater than 1, print "Not applicable".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 50.00

0.20

Output: Rs. 40.00

### **Answer**

```
import java.util.Scanner;
```

```
class Product {  
    public double price;  
  
    public Product(double price) {  
        this.price = price;  
    }  
}
```

```
class DiscountedProduct extends Product {  
    private double discountRate;  
  
    public DiscountedProduct(double price, double discountRate) {  
        super(price);  
        this.discountRate = discountRate;  
    }  
  
    public double calculateSellingPrice() {  
        if (discountRate > 1.0) {  
            return -1;  
        }  
    }  
}
```

```
    }  
    return price * (1 - discountRate);  
  }  
}  
  
class ProductPricing {  
    public static void main(String[] args) {  
        Scanner scanner = new Scanner(System.in);  
  
        double initialPrice = scanner.nextDouble();  
        double discountRate = scanner.nextDouble();  
        DiscountedProduct discountedProduct = new  
DiscountedProduct(initialPrice, discountRate);  
        double sellingPrice = discountedProduct.calculateSellingPrice();  
  
        if (sellingPrice >= 0) {  
            System.out.printf("Rs. %.2f%n", sellingPrice);  
        } else {  
            System.out.println("Not applicable");  
        }  
        scanner.close();  
    }  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Dharshini A  
Email: 241001049@rajalakshmi.edu.in  
Roll no: 241001049  
Phone: 8056618801  
Branch: REC  
Department: IT - Section 2  
Batch: 2028  
Degree: B.E - IT

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 6\_Q3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Preethi is working on a project to automate sales tax calculations for items in a store. She wants to create a program that takes the price of an item and the sales tax rate as input and calculates the final price of the item after applying the sales tax.

Write a program using the class SalesTaxCalculator, which contains an overloaded method named calculateFinalPrice to handle both integer and double inputs. The program should also include a Main class that takes user input, calls the appropriate method from SalesTaxCalculator, and prints the final price of the item.

Formula Used: Final price = price + ((price \* sales tax rate) / 100)

**Input Format**

The first line of input consists of an integer price (the price of the item for integer inputs).

The second line of input consists of an integer taxRate (the sales tax rate for integer inputs).

The third line of input consists of a double price (the price of the item for double inputs).

The fourth line of input consists of a double taxRate (the sales tax rate for double inputs).

### ***Output Format***

The first line of output prints an integer, representing the final price of the item after applying the sales tax for integer inputs (a and b).

The second line prints a double value, representing the final price of the item after applying the sales tax for double-value inputs (m and n), rounded to two decimal places.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 100

10

100.0

5.0

Output: 110

105.00

### ***Answer***

```
import java.util.Scanner;
```

```
class SalesTaxCalculator {
```

```
    public static int calculateFinalPrice(int price, int taxRate) {  
        return price + (price * taxRate) / 100;
```

```
    }
```

```
    public static double calculateFinalPrice(double price, double taxRate) {  
        return price + (price * taxRate) / 100;
```



```
}  
}  
class Main {  
    public static void main(String[] args) {  
        Scanner scanner = new Scanner(System.in);  
        int intPrice = scanner.nextInt();  
        int intTaxRate = scanner.nextInt();  
        double doublePrice = scanner.nextDouble();  
        double doubleTaxRate = scanner.nextDouble();  
  
        int finalPriceInt = SalesTaxCalculator.calculateFinalPrice(intPrice,  
intTaxRate);  
        double finalPriceDouble =  
SalesTaxCalculator.calculateFinalPrice(doublePrice, doubleTaxRate);  
  
        System.out.println(finalPriceInt);  
        System.out.format("%.2f", finalPriceDouble);  
    }  
}
```

**Status :** Correct

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: Dharshini A  
Email: 241001049@rajalakshmi.edu.in  
Roll no: 241001049  
Phone: 8056618801  
Branch: REC  
Department: IT - Section 2  
Batch: 2028  
Degree: B.E - IT

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 6\_Q4

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Mr.Kapoor wants to create a program to calculate the volume of a Cuboid and a Cube using method overriding.

Implements a base class Cuboid with attributes for length, width, and height. Include a method calculateVolume() that computes the volume of the cuboid.

Extends the base class with a subclass Cube representing a cube, where all sides are equal. Override the calculateVolume() method in the Cube class to compute the volume of the cube.

The program should take user input for the dimensions of the cuboid and the side length of the cube and display the calculated volumes with two decimal places.

### ***Input Format***

The first line of input consists of 3 space-separated double values, representing the cuboid length, width, and height, respectively.

The second line consists of a double value, representing the side length of the cube.

### ***Output Format***

The first line of output prints the volume of the cuboid, rounded off to two decimal places.

The second line prints the volume of the cube, rounded off to two decimal places.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 60.0 60.0 60.0  
50.0

Output: Volume of Cuboid: 216000.00  
Volume of Cube: 125000.00

### ***Answer***

```
import java.util.Scanner;

class Cuboid {
    double length;
    double width;
    double height;

    public Cuboid(double length, double width, double height) {
        this.length = length;
        this.width = width;
        this.height = height;
    }

    public double calculateVolume() {
        return length * width * height;
    }
}
```

```
}  
}  
class Cube extends Cuboid {  
    double side;
```

```
    public Cube(double side) {  
        super(side, side, side);  
        this.side = side;  
    }  
    @Override  
    public double calculateVolume() {  
        return side * side * side;  
    }  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        Scanner scanner = new Scanner(System.in);  
  
        double cuboidLength = scanner.nextDouble();  
        double cuboidWidth = scanner.nextDouble();  
        double cuboidHeight = scanner.nextDouble();  
  
        // Regular object instantiation for Cuboid  
        Cuboid cuboid = new Cuboid(cuboidLength, cuboidWidth, cuboidHeight);  
        System.out.printf("Volume of Cuboid: %.2f\n", cuboid.calculateVolume());  
  
        double cubeSide = scanner.nextDouble();  
  
        // Upcasting - Using superclass reference for subclass object (DMD)  
        Cuboid cube = new Cube(cubeSide); // Upcasting  
        System.out.printf("Volume of Cube: %.2f", cube.calculateVolume()); // Calls  
        Cube's method dynamically  
  
        scanner.close();  
    }  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Dharshini A  
Email: 241001049@rajalakshmi.edu.in  
Roll no: 241001049  
Phone: 8056618801  
Branch: REC  
Department: IT - Section 2  
Batch: 2028  
Degree: B.E - IT

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 6\_Q5

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem statement:

Tim was tasked with developing a grocery shopping app. You have a class hierarchy that includes Item, Produce, and OrganicProduce. Your goal is to calculate the total cost of a shopping list, which may contain a mix of regular produce and organic produce items. Additionally, you need to apply discounts to organic items. Apply a 10% discount on organic produce items

Class Hierarchy:

Item: Base class for all items.

Produce: Subclass of Item for regular produce items.

OrganicProduce: Subclass of Produce for organic produce items.

### ***Input Format***

The first line of input consists of an integer, 'n'.

For each 'n' item, the user will provide:

- A string 'type' representing the item type ('Regular' or 'Organic').
- A string 'name' represents the item name.
- A double 'price' represents the item price.

### ***Output Format***

The output will display the total cost of the shopping list, including discounts on organic items.

Refer to the sample output for format specifications.

### ***Sample Test Case***

Input: 1

Regular Banana 1.99

Output: 1.99

### ***Answer***

```
import java.util.Scanner;

class Item {
    String name;
    double price;
    public Item(String name, double price) {
        this.name = name;
        this.price = price;
    }
    public double calculateCost() {
        return price;
    }
}

class Produce extends Item {
    public Produce(String name, double price) {
        super(name, price);
    }
}
```

```

    @Override
    public double calculateCost() {
        return super.calculateCost();
    }
}
class OrganicProduce extends Produce {
    public OrganicProduce(String name, double price) {
        super(name, price);
    }
    @Override
    public double calculateCost() {
        return price * 0.90;
    }
}

```

```

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int n = sc.nextInt();
        sc.nextLine(); // Consume newline

        double totalCost = 0.0;

        for (int i = 0; i < n; i++) {
            String type = sc.next();
            String name = sc.next();
            double price = sc.nextDouble();

            if (type.equals("Regular")) {
                Item item = new Produce(name, price);
                totalCost += item.calculateCost();
            } else if (type.equals("Organic")) {
                Item item = new OrganicProduce(name, price);
                totalCost += item.calculateCost();
            }
        }

        System.out.printf("%.2f%n", totalCost);
    }
}

```

Status : Correct

Marks : 10/10



# Rajalakshmi Engineering College

Name: Dharshini A  
Email: 241001049@rajalakshmi.edu.in  
Roll no: 241001049  
Phone: 8056618801  
Branch: REC  
Department: IT - Section 2  
Batch: 2028  
Degree: B.E - IT

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 6\_PAH

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

John is planning a long road trip and wants to calculate the distance his car can travel based on its speed and fuel capacity. As John knows that different cars have different fuel efficiencies, he wants a program that can help him estimate the travel distance for any given car.

To do this, you are tasked with creating a program that calculates the travel distance of a car based on its speed and fuel capacity. The calculation is simple and follows the formula:

Travel Distance = Speed \* Fuel Capacity

You need to model this system using a Vehicle class and a Car class. The Vehicle class will have attributes for the speed and fuel capacity, while the Car class will inherit from the Vehicle class and include a method to

calculate the travel distance.

### ***Input Format***

The first line of input consists of a double value representing the speed of the car in km/h.

The second line of input consists of a double value representing the fuel capacity of the car in liters.

### ***Output Format***

The first line should print "Speed: X km/h", where X is the speed of the car, rounded to two decimal places.

The second line should print "Fuel Capacity: Y liters", where Y is the fuel capacity of the car, rounded to two decimal places.

The third line should print "Travel Distance: Z km", where Z is the total travel distance the car can cover, rounded to two decimal places.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 10.0

1.0

Output: Speed: 10.00 km/h

Fuel Capacity: 1.00 liters

Travel Distance: 10.00 km

### ***Answer***

```
import java.util.Scanner;
```

```
class Vehicle {  
    double speed;  
    double fuelCapacity;
```

```
    public Vehicle(double speed, double fuelCapacity) {  
        this.speed = speed;  
        this.fuelCapacity = fuelCapacity;
```

```

    }
}

class Car extends Vehicle {
    public Car(double speed, double fuelCapacity) {
        super(speed, fuelCapacity);
    }

    public double calculateTravelDistance() {
        return speed * fuelCapacity;
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        double speed = scanner.nextDouble();
        double fuelCapacity = scanner.nextDouble();

        Car car = new Car(speed, fuelCapacity);

        System.out.println("Speed: " + String.format("%.2f", car.speed) + " km/h");
        System.out.println("Fuel Capacity: " + String.format("%.2f", car.fuelCapacity)
+ " liters");
        System.out.println("Travel Distance: " + String.format("%.2f",
car.calculateTravelDistance()) + " km");

        scanner.close();
    }
}

```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

In a company, each manager has a unique employee ID and a monthly salary. You are required to design a program that will calculate and display the annual(12 months) salary of a manager based on the input details provided by the user.

Implement the solution using a single inheritance approach.

Employee: The base class with attributes name and employeeID.

Manager: The derived class inheriting from Employee, with an additional attribute salary.

### ***Input Format***

The first line of input consists of a string name, representing the manager's name.

The second line of input consists of an integer employeeID, representing the manager's employee ID.

The third line of input consists of a double salary, representing the manager's monthly salary.

### ***Output Format***

The first line of output prints: Name: <name>

The second line of output prints: Annual Salary: Rs. <annual\_salary> (rounded to two decimal places).

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: Davis

234

28750.75

Output: Name: Davis

Annual Salary: Rs. 345009.00

### ***Answer***

```
import java.util.Scanner;
import java.text.DecimalFormat;

class Employee {
    String name;
```

```
int employeeID;

public Employee(String name, int employeeID) {
    this.name = name;
    this.employeeID = employeeID;
}

}

class Manager extends Employee {
    double salary;

    public Manager(String name, int employeeID, double salary) {
        super(name, employeeID);
        this.salary = salary;
    }

    public double calculateAnnualSalary() {
        return salary * 12;
    }
}

class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        DecimalFormat df = new DecimalFormat("0.00");

        String name = scanner.nextLine();
        int employeeID = scanner.nextInt();
        double salary = scanner.nextDouble();

        Manager manager = new Manager(name, employeeID, salary);

        System.out.println("Name: " + manager.name);
        System.out.println("Annual Salary: Rs. " +
df.format(manager.calculateAnnualSalary()));

        scanner.close();
    }
}
```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Ram is designing a program to calculate the Body Mass Index (BMI). Your task is to assist him by following the given specifications.

Create a base class BMIcalculator with a method calculateBMI() to compute BMI using the formula  $\text{weight} / (\text{height} * \text{height})$ .

Extend the class with a subclass CustomBMIcalculator that overrides the method calculateBMI() to calculate BMI based on custom criteria, assigning categories such as "Underweight," "Normal Weight," "Overweight," or "Obese."

BMI < 18.5, category = "Underweight" BMI >= 18.5 & < 24.9, category = "Normal Weight" BMI >= 25 & < 29.9, category = "Overweight" else category = "Obese"

Implement user input for weight and height and display both the standard and custom BMI calculations.

#### ***Input Format***

The first line of input consists of a double value, representing the weight in kgs.

The second line consists of a double value, representing the height in meters.

#### ***Output Format***

The first line of output prints: "Standard BMI Calculation:"

The second line of output prints: "BMI: " followed by the calculated BMI value (to two decimal places).

The third line of output prints: "Custom BMI Calculation:"

The fourth line of output prints: "Category: " followed by the BMI category.

Refer to the sample output for formatting specifications.

#### ***Sample Test Case***

Input: 69.7

2.6

Output: Standard BMI Calculation:

BMI: 10.31

Custom BMI Calculation:

Category: Underweight

### **Answer**

```
import java.util.Scanner;
```

```
class BMIcalculator {  
    double weight;  
    double height;
```

```
    public BMIcalculator(double weight, double height) {  
        this.weight = weight;  
        this.height = height;  
    }
```

```
    public double calculateBMI() {  
        return weight / (height * height);  
    }
```

```
    public void displayBMI() {  
        System.out.printf("BMI: %.2f\n", calculateBMI());  
    }  
}
```

```
class CustomBMIcalculator extends BMIcalculator {
```

```
    public CustomBMIcalculator(double weight, double height) {  
        super(weight, height);  
    }  
    @Override  
    public double calculateBMI() {  
        return super.calculateBMI();  
    }
```

```
    public void displayCustomBMI() {  
        double bmi = calculateBMI();  
        String category;
```

```

        if (bmi < 18.5) {
            category = "Underweight";
        } else if (bmi >= 18.5 && bmi < 24.9) {
            category = "Normal Weight";
        } else if (bmi >= 25 && bmi < 29.9) {
            category = "Overweight";
        } else {
            category = "Obese";
        }

        System.out.println("Category: " + category);
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        double weight = scanner.nextDouble();
        double height = scanner.nextDouble();

        BMICalculator bmiCalculator = new BMICalculator(weight, height);
        System.out.println("Standard BMI Calculation:");
        bmiCalculator.displayBMI();

        CustomBMICalculator customBMICalculator = new
        CustomBMICalculator(weight, height);
        System.out.println("Custom BMI Calculation:");
        customBMICalculator.displayCustomBMI();

        scanner.close();
    }
}

```

**Status :** Correct

**Marks : 10/10**

#### 4. Problem Statement

Sharon, a software developer, is working on a project to automate velocity calculations for various objects. She wants to create a class named VelocityCalculator with overloaded methods calculateVelocity to calculate



the velocity. One method will accept distance in meters and time in seconds as integers, while another will accept distance and time as doubles.

Help her in completing the project.

Formula: Velocity = distance / time

### ***Input Format***

The first line of input consists of an integer, representing the distance in meters (for the integer method).

The second line consists of an integer, representing the time in seconds (for the integer method).

The third line consists of a double value, representing the distance in meters (for the double method).

The fourth line consists of a double value, representing the time in seconds (for the double method).

### ***Output Format***

The first line prints the velocity calculated using the integer inputs in the format:

Velocity with integer inputs: <velocity> m/s

The second line prints the velocity calculated using the double inputs in the format:

Velocity with double inputs: <velocity> m/s

Note:

The velocity for the double inputs should be printed with two decimal places.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 100

10

100.5

10.2

Output: Velocity with integer inputs: 10 m/s

Velocity with double inputs: 9.85 m/s

### **Answer**

```
import java.util.Scanner;

class VelocityCalculator {
    public static int calculateVelocity(int distance, int time) {
        return distance/time;
    }
    public static double calculateVelocity(double distance, double time){
        return distance/time;
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        int distanceInt = scanner.nextInt();
        int timeInt = scanner.nextInt();

        double distanceDouble = scanner.nextDouble();
        double timeDouble = scanner.nextDouble();

        int velocityInt = VelocityCalculator.calculateVelocity(distanceInt, timeInt);
        double velocityDouble =
VelocityCalculator.calculateVelocity(distanceDouble, timeDouble);

        System.out.println("Velocity with integer inputs: " + velocityInt + " m/s");
        System.out.printf("Velocity with double inputs: %.2f m/s", velocityDouble);

        scanner.close();
    }
}
```

Status : Correct

Marks : 10/10

# Rajalakshmi Engineering College

Name: Dharshini A  
Email: 241001049@rajalakshmi.edu.in  
Roll no: 241001049  
Phone: 8056618801  
Branch: REC  
Department: IT - Section 2  
Batch: 2028  
Degree: B.E - IT

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 6\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

Adams has a reputation company with a great number of employees. He must calculate the salary weekly according to the hourly rate and working hours. Create a program to define a class Employee with attributes name and hourly rate. Create a subclass HourlyEmployee that calculates the weekly salary based on the number of hours worked.

(The first 40 hours are based on the regular hour rate. If the work hours are greater than 40 then the work wage is 1.5 times the hourly rate)

Note: Use Math(Math.max, Math.min) functions .

Example

Input:

Chris

10

45

Output:

Weekly Salary: Rs.475.00

Explanation:

Calculation:

The first 40 hours are paid normally:  $40 \times 10 = 400.00$  The extra 5 hours are paid at 1.5 times the hourly rate:  $5 \times (10 \times 1.5) = 5 \times 15 = 75.00$  Total salary:  $400.00 + 75.00 = 475.00$

### ***Input Format***

The first line of input consists of a string that represents the name of the employee.

The second line consists of a double value that represents the rate for an hour.

The last line consists of an integer that represents the total hours worked.

### ***Output Format***

The output displays the total salary of the employee, where salary is rounded to two decimal places in the format: "Weekly Salary: Rs.<double value>".

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: Dave

10.0

40

Output: Weekly Salary: Rs.400.00

### ***Answer***

```
import java.util.Scanner;
```

```
import java.text.DecimalFormat;
```

```
class Employee {  
    String name;  
    double hourlyRate;  
  
    public Employee(String name, double hourlyRate) {  
        this.name = name;  
        this.hourlyRate = hourlyRate;  
    }  
}
```

```
class HourlyEmployee extends Employee {  
    int hoursWorked;  
  
    public HourlyEmployee(String name, double hourlyRate, int hoursWorked) {  
        super(name, hourlyRate);  
        this.hoursWorked = hoursWorked;  
    }  
}
```

```
    public double calculateWeeklySalary() {  
        double regularHours = Math.min(this.hoursWorked, 40);  
        double overtimeHours = Math.max(0, this.hoursWorked - 40);  
        double regularPay = regularHours * this.hourlyRate;  
        double overtimePay = overtimeHours * this.hourlyRate * 1.5;  
        return regularPay + overtimePay;  
    }  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        Scanner scanner = new Scanner(System.in);
```

```
        String name = scanner.nextLine();  
        double hourlyRate = scanner.nextDouble();  
        int hoursWorked = scanner.nextInt();
```

```
        HourlyEmployee employee = new HourlyEmployee(name, hourlyRate,  
hoursWorked);
```

```
double weeklySalary = employee.calculateWeeklySalary();
DecimalFormat df = new DecimalFormat("#.00");
String formattedSalary = df.format(weeklySalary);
System.out.println("Weekly Salary: Rs." + formattedSalary);
scanner.close();
}
}
```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Arun wants to calculate the age gap between the grandfather and the son and determine the father's age after 5 years.

Your task is to assist him in developing a program using three classes: GrandFather, Father, and Son, where the GrandFather stores the grandfather's age, the Father extends GrandFather to include the father's age and calculates his age after 5 years, and Son extends Father to include the son's age and calculate the age difference between the grandfather and the son.

### **Input Format**

The input consists of three integers representing the ages of the grandfather, father, and son, one per line.

### **Output Format**

The first line of output prints "Grandfather and son's age gap:" followed by an integer representing the age gap between the grandfather and the son, ending with "years".

The second line prints "Father's Age:" followed by an integer representing the father's age after 5 years, ending with "years".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 50

30

3

Output: Grandfather and son's age gap: 47 years

Father's Age: 35 years

**Answer**

```
import java.util.Scanner;
```

```
import java.util.Scanner;
```

```
class GrandFather {  
    protected int grandfatherAge;
```

```
    public void setGrandfatherAge(int grandfatherAge) {  
        this.grandfatherAge = grandfatherAge;  
    }  
}
```

```
class Father extends GrandFather {  
    protected int fatherAge;
```

```
    public void setFatherAge(int fatherAge) {  
        this.fatherAge = fatherAge;  
    }  
}
```

```
    public int calculateFatherAgeAfter5Years() {  
        return fatherAge + 5;  
    }  
}
```

```
class Son extends Father {  
    private int sonAge;
```

```
    public void setSonAge(int sonAge) {  
        this.sonAge = sonAge;  
    }  
}
```

```
    public int calculateGrandfatherSonAgeDifference() {  
        return grandfatherAge - sonAge;  
    }  
}
```



```

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        Son son = new Son();

        int grandfatherAge = scanner.nextInt();
        son.setGrandfatherAge(grandfatherAge);

        int fatherAge = scanner.nextInt();
        son.setFatherAge(fatherAge);

        int sonAge = scanner.nextInt();
        son.setSonAge(sonAge);

        System.out.println("Grandfather and son's age gap: "+
            son.calculateGrandfatherSonAgeDifference() + " years");

        int fatherAgeAfter5Years = son.calculateFatherAgeAfter5Years();
        System.out.println("Father's Age: " + fatherAgeAfter5Years + " years");
    }
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

A painter needs to determine the cost to paint different shapes based on their surface area. The program should be designed to handle the area of a sphere and calculate the total painting cost using the following formulas:

Area of sphere:  $\text{Area} = 4 * \pi * r^2$  where  $\pi = 3.14$   
 Total painting cost:  $\text{Cost} = \text{cost per square meter} * \text{area of sphere}$

The program will consist of three classes:

Shape class: This class should set the shape type and radius.

Area class: This class should extend Shape to calculate the area.

Cost class: This class should extend Area to calculate the total painting cost.

#### **Input Format**

The input consists of a string representing the shape type, a double value

representing the radius, and another double value representing the cost per square meter on each line.

### **Output Format**

For a valid shape type of "Sphere":

- The first line prints: "Area of Sphere is: <calculated\_area>" rounded to two decimal places.
- The second line prints: "Cost to paint the shape is: <total\_painting\_cost>" rounded to two decimal places.

For any other shape types, print: "Invalid type".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: Sphere

3.4

5.8

Output: Area of Sphere is: 145.19

Cost to paint the shape is: 842.12

### **Answer**

```
import java.util.Scanner;
```

```
import java.util.Scanner;
```

```
class Shape {
```

```
    protected String shapeType;
```

```
    protected double radius;
```

```
    public void setShape(String shapeType, Scanner scanner) {
```

```
        this.shapeType = shapeType;
```

```
        if ("Sphere".equals(shapeType)) {
```

```
            this.radius = scanner.nextDouble();
```

```
        }
```

```
    }
```

```
}
```

```

class Area extends Shape {
    protected double area;

    public void calculateArea() {
        if ("Sphere".equals(shapeType)) {
            double pi = 3.14;
            area = 4 * pi * radius * radius;
        }
    }
}

```

```

class Cost extends Area {
    private double costPerSqMeter;
    private double totalCost;

    public void setCost(double costPerSqMeter) {
        this.costPerSqMeter = costPerSqMeter;
    }

    public void calculateCost() {
        if ("Sphere".equals(shapeType)) {
            totalCost = costPerSqMeter * area;
            System.out.printf("Area of Sphere is: %.2f\n", area);
            System.out.printf("Cost to paint the shape is: %.2f\n", totalCost);
        } else {
            System.out.println("Invalid type");
        }
    }
}

```

```

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        String s = scanner.next();
        Cost shape = new Cost();
        shape.setShape(s, scanner);
        double costToPaint = scanner.nextDouble();
        shape.calculateArea();
        shape.setCost(costToPaint);
        shape.calculateCost();
    }
}

```

Status : Correct

Marks : 10/10

#### 4. Problem Statement

Mary is managing a business and wants to analyze its profitability. She operates both a regular business model and a seasonal business model. To assess profitability, she uses a program that calculates and compares the profit margins for both models based on revenue and cost.

The program defines:

BusinessUtility class with a method calculateMargin(double revenue, double cost). SeasonalBusinessUtility (inherits from BusinessUtility) and overrides calculateMargin(double revenue, double cost), adding a seasonal adjustment of 10% to the base margin. ProfitabilityChecker class with a method checkProfitability(double regularMargin), which prints "Business is profitable." if the regular margin is 10% or more, otherwise prints "Business is not profitable."

Mary inputs revenue and cost, and the program compute and display the regular and seasonal margins using:

$$\text{Margin} = ((\text{Revenue} - \text{Cost}) / \text{Revenue}) \times 100$$

$$\text{Seasonal Margin} = \text{Margin} + 10$$

#### **Input Format**

The first line of input consists of a double value  $r$ , representing the revenue.

The second line consists of a double value  $c$ , representing the cost.

#### **Output Format**

The first line prints a double value, representing the regular profit margin, rounded to two decimal places, in the format: "Regular Margin: X. XX%", where X.XX denotes the calculated regular margin.

The second line prints a double value, representing the seasonal profit margin, rounded to two decimal places, in the format: "Seasonal Margin: X. XX%", where X.XX denotes the calculated seasonal margin.

The third line prints a string, indicating whether the business is profitable or not profitable, based on the regular margin.

If the regular margin is less than 10, print "Business is not profitable.". If it is 10 or greater, print "Business is profitable."

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 1000.0

800.0

Output: Regular Margin: 20.00%

Seasonal Margin: 30.00%

Business is profitable.

### **Answer**

```
import java.util.Scanner;
```

```
class BusinessUtility {  
    public double calculateMargin(double revenue, double cost) {  
        return ((revenue - cost) / revenue) * 100;  
    }  
}
```

```
class SeasonalBusinessUtility extends BusinessUtility {  
    @Override  
    public double calculateMargin(double revenue, double cost) {  
        double baseMargin = super.calculateMargin(revenue, cost);  
        return baseMargin + 10;  
    }  
}
```

```
class ProfitabilityChecker {  
    public void checkProfitability(double regularMargin) {  
        if (regularMargin >= 10) {  
            System.out.println("Business is profitable.");  
        } else {  
            System.out.println("Business is not profitable.");  
        }  
    }  
}
```

```

    }
}

class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        double revenue = scanner.nextDouble();
        double cost = scanner.nextDouble();
        BusinessUtility business = new BusinessUtility();
        SeasonalBusinessUtility seasonalBusiness = new
SeasonalBusinessUtility();
        double regularMargin = business.calculateMargin(revenue, cost);
        double seasonalMargin = seasonalBusiness.calculateMargin(revenue,
cost);

        System.out.printf("Regular Margin: %.2f%%\n", regularMargin);
        System.out.printf("Seasonal Margin: %.2f%%\n", seasonalMargin);

        ProfitabilityChecker checker = new ProfitabilityChecker();
        checker.checkProfitability(regularMargin);
        scanner.close();
    }
}

```

**Status :** Correct

**Marks :** 10/10