QUANTUMSHIELD: QUANTUM-RESISTANT BLOCKCHAIN FRAMEWORK WITH AI-BASED THREAT DETECTION FOR ENTERPRISE IT ORGANIZATIONS

A PROJECT REPORT

Submitted by

DHARSHNA U 231901008

in partial fulfillment for the award of the degree

of

BACHELOR OF ENGINEERING

in

COMPUTER SCIENCE AND ENGINEERING (CYBER SECURITY)





RAJALAKSHMI ENGINEERING COLLEGE

ANNA UNIVERSITY: CHENNAI 600 025

OCTOBER 2026

RAJALAKSHMI ENGINEERING COLLEGE

CHENNAI

BONAFIDE CERTIFICATE

Certified that this Project report titled **"QUANTUMSHIELD: QUANTUM-RESISTANT BLOCKCHAIN FRAMEWORK WITH AI-BASED THREAT DETECTION FOR ENTERPRISE IT ORGANIZATIONS"** is the bonafide work of **"DHARSHNA U (2116231901008)"** who carried out the work under my supervision. Certified further that to the best of my knowledge the work reported herein does not form part of any other project report or dissertation on the basis of which a degree or award was conferred on an earlier occasion on this or any other candidate.

SIGNATURE

Dr. P. Tamilselvi, M.E., Ph.D.,

HEAD OF THE DEPARTMENT

PROFESSOR

Department of Computer Science and Engineering (Cyber Security)

Rajalakshmi Engineering College
Chennai – 602 105

SIGNATURE

Dr. P. Tamilselvi, M.E., Ph.D.,

SUPERVISOR

PROFESSOR

Department of Computer Science and Engineering (Cyber Security)

Rajalakshmi Engineering College
Chennai – 602 105

Submitted to Project Viva-Voce Examination held on 7/10/2026

Internal Examiner

External Examiner

ABSTRACT

QuantumSHIELD is a security framework designed to strengthen enterprise IT environments against evolving cyber threats and future quantum-computing risks. The proposed system integrates **AI-based security incident analysis** , **post-quantum cryptographic protection** , **permissioned blockchain-based audit mechanisms**, and **controlled incident response** into a unified security workflow. Kubernetes security observations are processed to identify and correlate abnormal conditions, after which the AI component analyzes incidents and provides classification, severity, and recommended actions.

SHA-256 hashing is used to maintain the integrity of security records, while **ML-DSA** and **ML-KEM** interfaces provide an architecture for future post-quantum digital signatures and key encapsulation. A blockchain audit layer provides tamper-evident recording of security events , while role-based access control and human approval mechanisms prevent unauthorized remediation actions. The system was functionally validated through a local demonstration environment using deterministic Kubernetes observations, AI analysis, mock blockchain recording, simulated response, and audit verification. The results demonstrate an integrated workflow for security monitoring, incident analysis, integrity protection, controlled response, and auditable security operations.

ACKNOWLEDGEMENT

First, we thank the almighty God for the successful completion of the project. Our sincere thanks to our Chairman **Mr. S. Meganathan B.E., F.I.E.,** for his sincere endeavor in educating us in his premier institution. We would like to express our deep gratitude to our beloved Chairperson **Dr. Thangam Meganathan Ph.D.,** for her enthusiastic motivation which inspired us a lot in completing this project and Vice Chairman **Mr. Abhay Shankar Meganathan B.E., M.S.,** for providing us with the requisite infrastructure.

We also express our sincere gratitude to our college Principal **Dr. S. N. Murugesan M.E., Ph.D.,** and **Dr. P. Tamilselvi Ph.D., Professor and Head, Department of Computer Science and Engineering (Cyber Security)** and our project guide for her encouragement and guiding us throughout the project. We would like to thank our project coordinator **Mr. Benedict J. N., M.E., Assistant Professor (SG),** for his encouragement and guidance towards successful completion of this project and to our parents, friends, all faculty members and supporting staffs for their direct and indirect involvement in successful completion of the project for their encouragement and support.

DHARSHNA U (231901008)

TABLE OF CONTENTS

CHAPTER NO.	TITLE	PAGE NO.
	ABSTRACT	iii
	LIST OF TABLES	vii
	LIST OF FIGURES	viii
1	**INTRODUCTION**	**1**
	1.1 BACKGROUND	1
	1.2 PROBLEM STATEMENT	2
	1.3 OBJECTIVES	2
	1.4 SCOPE	3
	1.5 SECURITY CONSIDERATIONS	3
	1.6 SDG ALIGNMENT	4
2	**LITERATURE REVIEW**	**5**
	2.1 EXISTING SYSTEM WITH SECURITY APPROACHES	5
	2.2 RESEARCH GAPS	11
	2.3 PROPOSED SYSTEM	11
	2.3.1 OVERVIEW	11
	2.3.2 OBJECTIVES	12
	2.3.3 ADVANTAGES	12
3	**SYSTEM DESIGN**	**13**
	3.1 SYSTEM ARCHITECTURE	13
	3.2 MODULE DESIGN	13
	3.3 DATA FLOW	15
	3.4 THREAT MODEL	15

	3.5 SECURITY CONTROLS	16
4	**SYSTEM DESCRIPTION**	**17**
	4.1 DATA COLLECTION	17
	4.2 DATA PREPROCESSING	17
	4.2.1 ALGORITHMS	18
5	**CONCLUSION**	19
	REFERENCES	20

LIST OF TABLES

TABLE NO.	TITLE	PAGE NO.
1.1	SDG ALIGNMENT	4
2.1	EXISTING SYSTEMS	6

LIST OF FIGURES

FIGURE	TITLE	PAGE NO.
3.1	ARICHITECTURE DIAGRAM	13
3.2	DATA FLOW DIAGRAM	15

CHAPTER 1

INTRODUCTION

1.1 BACKGROUND

The rapid growth of enterprise IT infrastructure, cloud computing, containerized applications, and distributed services has increased the complexity of cybersecurity management. Organizations continuously generate security events from applications, servers, containers, networks, and cloud environments, making manual monitoring difficult. Kubernetes-based environments add further complexity through distributed pods, nodes, containers, and services that generate various operational and security events.

Traditional security monitoring relies mainly on predefined rules, signatures, logs, and manual investigation. While effective for known conditions, these approaches may provide limited contextual analysis and often require security personnel to determine appropriate responses. Artificial Intelligence (AI) and machine learning can assist by analyzing incident information, identifying patterns, classifying security conditions, and providing recommendations.

Another major concern is the future impact of quantum computing on current cryptographic mechanisms. Large-scale quantum computers may threaten widely used public-key cryptographic algorithms. Post-Quantum Cryptography (PQC) provides mechanisms designed to withstand both conventional and future quantum-based attacks. ML-DSA and ML-KEM provide standardized approaches for digital signatures and key encapsulation respectively.

Security records must also be protected against unauthorized modification. Blockchain technology can provide a tamper-evident mechanism for recording security events, while permissioned blockchains allow access to be restricted to authorized participants.

QuantumSHIELD integrates these security concepts into a unified enterprise security framework. It combines Kubernetes security observation, AI-based incident analysis, cryptographic integrity protection, post-quantum cryptographic interfaces, blockchain-based auditing, role-based access control, human approval, and controlled incident response.

The developed system provides a local and reproducible demonstration of this workflow using deterministic Kubernetes observations, AI-based analysis, SHA-256 integrity hashing, PQC interfaces, blockchain audit abstraction, approval-based response control, verification, and audit logging.

1.2 PROBLEM STATEMENT

Enterprise IT environments generate large volumes of security events from applications, containers, Kubernetes resources, and infrastructure. Identifying important conditions and determining suitable responses becomes difficult when monitoring, analysis, authorization, and auditing are handled separately.

Traditional monitoring often requires manual investigation, while automated responses without proper authorization may lead to inappropriate actions. Conventional cryptographic mechanisms also face long-term challenges from quantum computing, creating a need for post-quantum security and reliable protection of security records.

Therefore, there is a need for an integrated framework that can monitor infrastructure, analyze incidents using AI, protect security records, support post-quantum security, maintain blockchain-based audit records, and enforce controlled responses through authentication and human approval.

QuantumSHIELD addresses these requirements through a unified security operations workflow.

1.3 OBJECTIVES

The major objectives of the QuantumSHIELD framework are:

- To develop an integrated framework for enterprise IT security monitoring.
- To monitor Kubernetes conditions and identify security incidents.
- To perform AI-based incident analysis and provide recommendations.
- To protect security records using SHA-256 hashing.
- To implement incident correlation and deduplication.
- To provide role-based authentication and authorization.
- To support Post-Quantum Cryptography using ML-DSA and ML-KEM interfaces.
- To maintain tamper-evident records through blockchain-based auditing.
- To enforce security policies for review, approval, and controlled response.
- To implement human-in-the-loop approval for security actions.
- To verify response outcomes and maintain a complete audit trail.
- To provide a dashboard for monitoring security operations.
- To validate the complete workflow through functional and end-to-end testing

1.4 SCOPE

The scope of QuantumSHIELD covers an integrated security monitoring and response framework for enterprise IT environments.

- Infrastructure Monitoring: Monitors Kubernetes security conditions such as abnormal pods, restarts, and unhealthy resources.
- Incident Detection: Correlates and deduplicates security conditions using condition fingerprints.
- AI-Based Analysis: Classifies incidents, provides confidence and severity information, and recommends actions.
- Authentication & Authorization: Provides role-based access control for security operations.
- Post-Quantum Security: Supports ML-DSA and ML-KEM interfaces, with SHA-256 for record integrity.
- Blockchain Audit: Provides tamper-evident security auditing through a blockchain abstraction and Fabric integration interface.
- Controlled Response: Uses policy-based actions with authorization and allowlist controls.
- Human Approval: Requires human approval for controlled security actions.
- Verification & Audit: Verifies response outcomes and maintains a complete audit trail.

Project Boundary: The current implementation is a local prototype using deterministic Kubernetes fixtures, a mock blockchain provider, simulated remediation, and PQC interfaces. It does not claim live production deployment.

1.1 SECURITY CONSIDERATIONS

The QuantumSHIELD framework handles security incidents, infrastructure observations, authentication information, cryptographic integrity data, and response decisions. Therefore, security must be maintained throughout the complete incident lifecycle.

Authentication – Only registered and authenticated users can access protected security operations.

Authorization – Access to security functions must be controlled according to user roles.

Role Separation – Analysis and approval responsibilities should be separated to prevent unauthorized self-approval.

Data Integrity – Security records and audit information must be protected from unauthorized modification using SHA-256 hashing.

Cryptographic Protection – ML-DSA and ML-KEM interfaces provide support for future post-quantum cryptographic integration.

Secure Audit Logging – Important activities such as incident analysis, approvals, responses, and verification must be recorded.

Secure Incident Processing – Security observations must be validated before entering the incident-management workflow.

Controlled Response – Response actions must follow authorization, policy, and allowlist checks before execution.

Human Approval – Restricted security actions must require authorized human approval with appropriate policy and expiration controls

Response Verification – Response outcomes must be verified and recorded in the audit trail.

1.2 SDG ALIGNMENT

S. No.	SDG No. & SDG Goal	Relevant SDG Target	Project Contribution / Alignment
1	**SDG 9 – Industry, Innovation and Infrastructure**	**Target 9.5** – Enhance scientific research and technological capabilities.	Provides an innovative cybersecurity framework for securing modern enterprise IT and Kubernetes infrastructure.
2	**SDG 16 – Peace, Justice and Strong Institutions**	**Target 16.6** – Develop effective, accountable and transparent institutions.	Strengthens secure access, accountability, auditability, and controlled security operations.
3	**SDG 8 – Decent Work and Economic Growth**	**Target 8.2** – Achieve higher economic productivity through technological upgrading and innovation.	Helps organizations reduce cybersecurity risks and protect digital business infrastructure.
4	**SDG 17 – Partnerships for the Goals**	**Target 17.6** – Enhance cooperation and access to science, technology and innovation.	Supports the integration of AI, blockchain, post-quantum cryptography, and cloud-native security technologies.

CHAPTER 2

LITERATURE REVIEW

2.1 EXISTING SYSTEM WITH SECURITY APPROACHES

Existing enterprise security systems generally use separate tools for infrastructure monitoring, intrusion detection, incident management, cryptographic protection, and audit logging.

SIEM Systems: Collect and correlate security logs to identify suspicious activities.

IDS/IPS: Detect known and abnormal network activities using signatures and detection rules.

Kubernetes Security Tools: Monitor container and cluster activities, resource conditions, and configuration issues.

AI-Based Security Systems: Use machine learning to classify security events and identify abnormal patterns.

Blockchain-Based Auditing: Provides tamper-evident storage of important security records.

Traditional Cryptography: Protects communication and data using conventional cryptographic algorithms.

However, these approaches are often implemented as separate components. They may not provide a unified workflow combining AI-based analysis, post-quantum security, blockchain auditing, human approval, and controlled incident response.

TABLE 2.1 EXISTING SYSTEMS

S.NO	RESEARCH PAPER	TOOLS AND TECHNIQUES USED	APPLICATIONS USED	ADVANTAGES AND DISADVANTAGES	INFERENCE FROM PAPER
1	Deployment of Container Security Frameworks in Kubernetes-Orchestrated Environments for Preventing Runtime Exploits and Image Vulnerabilities through Policy-Based Controls, Aggarwal, 2023	Kubernetes, container security frameworks, policy-based controls, vulnerability scanning	Container and Kubernetes security	Adv: Protects container images and runtime environments through security policies. Disadv: Security policies require proper configuration and may introduce management overhead.	Supports the use of policy-based container security for preventing image vulnerabilities and runtime exploits.
2	AI-Driven Container Security Approaches for 5G and Beyond: A Survey, Aktolga et al., 2023	Artificial Intelligence, Machine Learning, Deep Learning, container security techniques	5G and beyond containerized environments	Adv: AI enables intelligent and adaptive security. Disadv: Requires quality data, computational resources and suitable models.	Shows that AI-driven security can improve container protection, especially in dynamic 5G environments.
3	A Survey on Post-Quantum Cryptography: State-of-the-Art and Challenges, Alvarado et al., 2023	Post-Quantum Cryptography, lattice-based, code-based, hash-based and multivariate cryptography	Protection against quantum computing attacks	Adv: Provides quantum-resistant security approaches. Disadv: Some PQC algorithms have larger key/signature sizes and higher computational requirements.	Establishes the importance of PQC algorithms for protecting current systems against future quantum attacks.
4	ACE-WARP: A Cost-Effective Approach to Proactive and Non-Disruptive Incident Response in Kubernetes Clusters, Bagheri et al., 2024	Kubernetes, proactive incident response, automated response, cluster security	Incident response in Kubernetes clusters	Adv: Enables proactive and non-disruptive incident response. Disadv: Response mechanisms require accurate detection and proper configuration.	Supports automated and controlled incident response for cloud-native environments.
5	Post Quantum Cryptography: A Review of Techniques, Challenges and Standardizations, Bavdekar et al., 2023	PQC, lattice-based cryptography, hash-based cryptography, NIST standardization	Quantum-resistant communication and security	Adv: Reviews standardized and emerging PQC techniques. Disadv: PQC may involve increased key sizes and implementation complexity.	Highlights NIST-standardized PQC algorithms as an important direction for quantum-resistant security.
6	A Module Lattice Based Construction of Post Quantum Secure Blockchain Architecture, Chaudhary et al., 2024	Module-lattice cryptography, blockchain, post-quantum cryptography	Quantum-resistant blockchain architecture	Adv: Provides blockchain protection against quantum attacks. Disadv: Lattice-based operations can increase computational and storage requirements.	Demonstrates that lattice-based cryptography can be integrated into blockchain architecture for quantum resistance.

S.NO	RESEARCH PAPER	TOOLS AND TECHNIQUES USED	APPLICATIONS USED	ADVANTAGES AND DISADVANTAGES	INFERENCE FROM PAPER
7	Uncovering Threats in Container Systems: A Study on Misconfigured Container Components in the Wild, Choi et al., 2024	Container security analysis, configuration analysis, vulnerability assessment	Detection of container misconfigurations	Adv: Identifies real-world container security weaknesses. Disadv: Mainly focuses on configuration-related threats and may not cover all runtime attacks.	Shows that misconfiguration is a significant security threat in containerized environments.
8	A Survey of Post-Quantum Cryptography: Start of a New Race, Dam et al., 2023	PQC, lattice-based, code-based, hash-based, multivariate cryptography	Quantum-resistant cryptographic systems	Adv: Provides comprehensive comparison of PQC approaches. Disadv: PQC algorithms can have performance and implementation challenges.	Reinforces the need for transition from classical cryptography to quantum-resistant algorithms.
9	Enterprise Audits and Blockchain Technology, Dong and Pan, 2023	Blockchain, distributed ledger, audit mechanisms	Enterprise auditing and accountability	Adv: Improves transparency, traceability and auditability. Disadv: Blockchain integration may increase system complexity and operational cost.	Supports the use of blockchain for tamper-resistant enterprise auditing and accountability.
10	Towards Post-Quantum Blockchain: A Review on Blockchain Cryptography Resistant to Quantum Computing Attacks, Fernandez-Carames and Fraga-Lamas, 2024	Blockchain, PQC, quantum-resistant cryptography	Post-quantum blockchain systems	Adv: Combines blockchain with quantum-resistant cryptography. Disadv: Larger cryptographic parameters can affect blockchain performance.	Establishes the importance of post-quantum cryptography for future blockchain security.
11	Fortifying the Blockchain: A Systematic Review and Classification of Post-Quantum Consensus Solutions for Enhanced Security and Resilience, Gomes et al., 2023	PQC, blockchain consensus, post-quantum consensus mechanisms	Secure and resilient blockchain networks	Adv: Provides classification of quantum-resistant consensus approaches. Disadv: Post-quantum consensus can increase computational and communication overhead.	Indicates that consensus mechanisms must also be considered when designing quantum-resistant blockchains.
12	Container Instrumentation and Enforcement System for Runtime Security of Kubernetes Platform with eBPF, Gwak et al., 2023	Kubernetes, eBPF, container instrumentation, runtime enforcement	Runtime security monitoring of Kubernetes	Adv: Provides fine-grained runtime monitoring with low-level visibility. Disadv: eBPF-based security requires kernel-level knowledge and configuration.	Demonstrates that eBPF can provide effective runtime monitoring and enforcement for Kubernetes containers.

S.NO	RESEARCH PAPER	TOOLS AND TECHNIQUES USED	APPLICATIONS USED	ADVANTAGES AND DISADVANTAGES	INFERENCE FROM PAPER
13	Vulnerabilities and Attacks Assessments in Blockchain 1.0, 2.0 and 3.0: Tools, Analysis and Countermeasures, Hamdi et al., 2024	Blockchain vulnerability assessment, attack analysis, security tools	Blockchain security assessment	Adv: Covers vulnerabilities across different blockchain generations. Disadv: Broad analysis may not provide a single comprehensive mitigation for every attack.	Provides a foundation for identifying blockchain vulnerabilities and selecting appropriate countermeasures.
14	Artificial Intelligence-Based Anomaly Detection Technology over Encrypted Traffic: A Systematic Literature Review, Ji et al., 2024	AI, Machine Learning, anomaly detection, encrypted traffic analysis	Detection of threats in encrypted network traffic	Adv: Enables security analysis without directly decrypting traffic. Disadv: Model performance depends on traffic features and training data.	Shows that AI-based anomaly detection can identify malicious patterns even in encrypted traffic.
15	Artificial Intelligence for Cybersecurity: Literature Review and Future Research Directions, Kaur et al., 2023	AI, ML, Deep Learning, cybersecurity analytics	Threat detection, anomaly detection, attack prediction	Adv: AI can automate and improve cybersecurity detection. Disadv: False positives, data quality and explainability remain challenges.	Supports the integration of AI techniques for intelligent cybersecurity monitoring and threat detection.
16	Towards A Post-Quantum Cryptography in Blockchain I: Basic Review on Theoretical Cryptography and Quantum Information Theory, Kikuchi, 2024	Quantum cryptography concepts, PQC, quantum information theory, blockchain cryptography	Quantum-resistant blockchain security	Adv: Provides theoretical foundation for PQC in blockchain. Disadv: Mainly theoretical and requires further practical implementation.	Provides theoretical support for integrating post-quantum cryptographic mechanisms into blockchain systems.
17	Deep Learning for Anomaly Detection in Log Data: A Survey, Landauer et al., 2023	Deep Learning, anomaly detection, log analysis, neural networks	Security and system log anomaly detection	Adv: Deep learning can identify complex patterns in large log datasets. Disadv: Requires large and representative training data and computational resources.	Supports the use of deep learning for automated anomaly detection from system and security logs.
18	Blockchain-Based Auditing with Data Self-Repair: From Centralized System to Distributed Storage, Li et al., 2023	Blockchain, distributed storage, data auditing, data self-repair	Secure data auditing and integrity management	Adv: Provides data integrity, distributed auditing and recovery capabilities. Disadv: Blockchain and distributed storage introduce additional computational and storage overhead.	Shows that blockchain can strengthen auditability and data integrity while supporting recovery from data corruption.

S.NO	RESEARCH PAPER	TOOLS AND TECHNIQUES USED	APPLICATIONS USED	ADVANTAGES AND DISADVANTAGES	INFERENCE FROM PAPER
19	A Survey on the Application of Blockchain in Cryptographic Protocols, Luo et al., 2024	Blockchain, cryptographic protocols, digital signatures, consensus	Secure blockchain-based communication and transactions	Adv: Provides broad analysis of blockchain-based cryptographic protocols. Disadv: Blockchain cryptographic operations may introduce performance overhead.	Demonstrates the relationship between blockchain and cryptographic protocols for secure distributed systems.
20	Post-Quantum Distributed Ledger Technology: A Systematic Survey, Parida et al., 2023	Distributed Ledger Technology, PQC, quantum-resistant algorithms	Quantum-resistant distributed ledgers	Adv: Provides systematic analysis of PQ-DLT approaches. Disadv: Key size, computational cost and compatibility remain challenges.	Strongly supports the development of post-quantum distributed ledger architectures.
21	Container Security: Precaution Levels, Mitigation Strategies, and Research Perspectives, Priya et al., 2023	Container security, vulnerability assessment, mitigation techniques	Containerized application security	Adv: Provides security precautions and mitigation strategies across container environments. Disadv: Requires continuous monitoring and proper security configuration.	Identifies multi-layer container security and continuous protection as important requirements.
22	Anomaly and Intrusion Detection Using Deep Learning for Software-Defined Networks: A Survey, Ruffo et al., 2024	Deep Learning, anomaly detection, intrusion detection, SDN	Intrusion detection in Software-Defined Networks	Adv: Deep learning can detect complex network attack patterns. Disadv: Training complexity and false positives can affect performance.	Supports deep-learning-based IDS for intelligent network anomaly and intrusion detection.
23	Advancing Cybersecurity: A Comprehensive Review of AI-Driven Detection Techniques, Salem et al., 2024	AI, Machine Learning, Deep Learning, anomaly and intrusion detection	Cyberattack and threat detection	Adv: AI enables automated and scalable threat detection. Disadv: Model accuracy depends on data quality and may suffer from adversarial or unseen attacks.	Establishes AI-driven detection as an important approach for modern cybersecurity systems.
24	Hyperledger Fabric-Powered Network Slicing Handover Authentication, Tshisekedi et al., 2024	Hyperledger Fabric, blockchain, authentication, network slicing	Secure authentication in 5G network slicing	Adv: Provides decentralized and tamper-resistant authentication. Disadv: Blockchain processing may introduce latency and resource overhead.	Demonstrates the practical use of Hyperledger Fabric for secure authentication in enterprise/5G environments.

S.NO	RESEARCH PAPER	TOOLS AND TECHNIQUES USED	APPLICATIONS USED	ADVANTAGES AND DISADVANTAGES	INFERENCE FROM PAPER
25	A Survey and Comparison of Post-Quantum and Quantum Blockchains, Yang et al., 2024	Quantum blockchain, post-quantum cryptography, blockchain consensus, quantum technologies	Quantum-secure blockchain systems	Adv: Compares different quantum and post-quantum blockchain approaches. Disadv: Quantum blockchain technologies are still developing and may have high implementation complexity.	Provides a comprehensive basis for designing quantum-resistant blockchain systems and selecting suitable security mechanisms.

2.2 RESEARCH GAPS

The major gaps identified from existing security approaches are:

- Lack of integration between infrastructure monitoring and incident response.
- Limited combination of AI-based analysis with security operations.
- Conventional cryptographic mechanisms require consideration of future quantum threats.
- Security audit records may be maintained separately from incident processing.
- Automated response can create risks when proper authorization is not enforced.
- Limited use of human approval and separation of duties in automated response workflows.
- Lack of a unified framework combining AI, blockchain, PQC, Kubernetes monitoring, and controlled response.

These gaps motivate the development of the proposed QuantumSHIELD framework.

2.1 PROPOSED SYSTEM

QuantumSHIELD is a unified security framework designed for security monitoring, incident analysis, cryptographic protection, auditing, and controlled response in enterprise IT environments.

The system integrates Kubernetes monitoring, AI-based incident analysis, post-quantum cryptography, blockchain auditing, role-based access control, and human-in-the-loop response into a single workflow.

Security observations are validated, correlated, and analyzed to generate incident classification, severity information, and recommended actions. SHA-256 provides record integrity, while ML-DSA and ML-KEM interfaces support future post-quantum integration.

The framework further provides policy-based response, role separation, human approval, response verification, and audit logging, ensuring that security actions are authorized and traceable.

2.1.1 OVERVIEW

QuantumSHIELD is an integrated security framework designed for enterprise IT environments. It combines Kubernetes security monitoring, AI-based incident analysis, post-quantum cryptographic interfaces, blockchain-based auditing, role-based access control, and controlled incident response.

Security observations are processed through an incident pipeline, where conditions are validated, correlated, and analyzed using AI. Security records are protected using SHA-256 integrity hashing, while ML-DSA and ML-KEM interfaces provide support for future post-quantum cryptographic integration.

The framework also includes human approval, policy validation, controlled response actions ,verification, and audit logging to provide a secure and traceable incident-management workflow.

2.1.2 OBJECTIVES

The main objectives of QuantumSHIELD are:

- To monitor Kubernetes security conditions.
- To detect and correlate security incidents.
- To perform AI-based incident analysis.
- To provide post-quantum cryptographic support.
- To protect security records using SHA-256 hashing.
- To maintain tamper-evident blockchain audit records.
- To implement role-based authentication and authorization.
- To provide human approval for controlled responses.
- To verify response outcomes.
- To maintain a complete security audit trail.

2.1.3 ADVANTAGES OF PROPOSED SYSTEM

Advantages of the proposed system include the following:

- **Integrated Security:** Combines monitoring, analysis, protection, response, and auditing.
- **AI-Assisted Detection:** Supports automated incident classification and recommendations.
- **Quantum-Ready Architecture:** Provides ML-DSA and ML-KEM interfaces for future PQC integration.
- **Tamper-Evident Auditing:** Supports blockchain-based security event recording.
- **Controlled Response:** Prevents unrestricted automated security actions.
- **Human-in-the-Loop:** Requires approval for sensitive response operations.
- **Role-Based Access:** Restricts security operations according to user permissions.
- **Traceability:** Maintains audit records for incidents, decisions, responses, andverification.

CHAPTER 3

SYSTEM DESIGN

3.1 SYSTEM ARCHITECTRURE

The QuantumSHIELD framework consists of multiple security components working together to monitor, analyze, protect, and respond to security incidents. Kubernetes observations are processed through the incident pipeline, where conditions are validated, correlated, and analyzed using the AI service. Authentication and role-based authorization control access to security operations.

The framework uses SHA-256 for integrity protection and provides ML-DSA and ML-KEM interfaces for post-quantum cryptographic support. Important security events are recorded through the blockchain audit layer. Response actions are controlled using security policies, human approval, and allowlists before execution. The response is then verified and recorded in the audit trail.




Figure 3.1 Architecture Diagram

3.2 MODULE DESIGN

QuantumSHIELD consists of six major modules. Each module performs a specific security function and contributes to the complete incident-management workflow.

3.2.1 Authentication and Access Control

This module provides secure user authentication and role-based authorization. Users are authenticated before accessing protected security operations. Different roles are assigned appropriate permissions, while sensitive operations such as approval and response execution are restricted to authorized users.

Infrastructure Monitoring and Incident Detection

This module processes Kubernetes security observations such as abnormal pod conditions, restart events, unhealthy resources, and deployment-related conditions. Observations are validated and correlated using condition fingerprints to identify new or repeated incidents.

AI-Based Incident Analysis

This module analyzes validated incidents using the AI service. It provides incident classification, confidence information, severity-related information, and recommended security actions. Deterministic demonstration paths are also supported for reproducible testing.

Post-Quantum Cryptographic Protection

This module provides interfaces for post-quantum cryptographic mechanisms. ML-DSA (Dillithium) is provided for digital signatures and ML-KEM (Kyber) for key encapsulation. SHA-256 hashing is actively used to protect the integrity of security records.

Blockchain Audit and Integrity

This module records important security events through a blockchain audit abstraction. The architecture supports integration with a permissioned Hyperledger Fabric network through an adapter. The current demonstration uses a mock ledger for local validation.

Controlled Response and Verification

This module controls security responses using policies, authorization, allowlists, and human approval. After an approved action is performed, the system carries out bounded verification and records the response and verification results in the audit trail.

3.2DATA FLOW AND USE CASE DIAGRAM




Figure 3.3 Dataflow diagram

3.2 THREAT MODEL

The QuantumSHIELD framework handles infrastructure observations, security incidents, AI analysis, authentication data, cryptographic information, response decisions, and audit records. Therefore, these components may become targets for unauthorized access, manipulation, or abuse.

3.2.1 Assets

The major assets of the QuantumSHIELD framework include user authentication and authorization information, Kubernetes security observations, incident records, AI analysis results and recommendations, SHA-256 integrity data, post-quantum cryptographic information, blockchain audit records, security policies, approval information, and response and verification records. These assets must be protected from unauthorized access, modification, misuse, and tampering.

3.2.2 Potential Threats

Unauthorized Access: Attackers may attempt to access protected security operations.

Data Manipulation: Security observations or incident records may be modified.

Incident Injection: Malicious observations may be introduced into the incident pipeline.

AI Manipulation: Incorrect or manipulated inputs may influence AI analysis.

Privilege Abuse: Users may attempt to perform operations outside their assigned roles.

Approval Abuse: Unauthorized users may attempt to approve restricted actions.

Audit Tampering: Attackers may attempt to modify or remove security records.

Response Misuse: Unauthorized or unsafe response actions may be attempted.

Denial of Service: Excessive or malicious requests may affect system availability.

3.2 ATTACK SURFACES

The major attack surfaces in the **QuantumSHIELD** framework include the authentication and login interfaces, API endpoints, Kubernetes observation inputs, incident-processing pipeline, AI analysis service, security policies and approval workflow, cryptographic interfaces, blockchain audit interface, response execution mechanism, and frontend dashboard. These components may be targeted to gain unauthorized access, manipulate security information, influence incident analysis, or misuse response operation.

3.5 SECURITY CONTROLS

The **QuantumSHIELD** framework uses authentication, role-based authorization, input validation, SHA-256 integrity protection, post-quantum cryptographic interfaces, audit logging, policy enforcement, human approval, allowlist-based response controls, and response verification. These controls help protect security information, restrict unauthorized operations, ensure controlled response actions, and maintain traceability throughout the incident lifecycle.

CHAPTER 4

SYSTEM DESCRIPTION

4.1 DATA COLLECTION

The QuantumSHIELD framework collects security observations from Kubernetes infrastructure as the primary input for incident processing. These observations represent conditions such as abnormal pod states, restart events, unhealthy resources, and deployment-related conditions.

The collected observations are validated and converted into a standard incident format before further processing. Relevant information such as the affected resource, event condition, severity-related details, and timestamps is retained for incident analysis.

The prepared security observations are passed to the Incident Detection and Correlation stage, where conditions are validated, correlated, and deduplicated using condition fingerprints. The resulting incident information is then provided to the AI-Based Incident Analysis stage for classification, severity analysis, confidence information, and security recommendations.

The processed incident data is subsequently used for policy evaluation, human approval, controlled response, response verification, and audit recording, completing the security incident lifecycle.

4.2 DATA PREPROCESSING

The preprocessing stage prepares the collected Kubernetes security observations for incident analysis. The process includes input validation, normalization of security observations, condition extraction, and removal of invalid or incomplete information before incident creation.

The relevant information extracted from each observation includes the affected resource, condition type, status, timestamps, and other incident-related details. These observations are converted into a consistent format suitable for the incident-processing pipeline.

The preprocessing stage also generates a condition fingerprint from relevant observation attributes. This fingerprint is used for incident correlation and deduplication, helping the system identify whether an observation represents a new incident or a repeated occurrence of an existing condition.

The processed observations are then passed to the AI-Based Incident Analysis stage for classification, severity-related analysis, confidence information, and security recommendations. This ensures that only validated and consistently structured security observations enter the subsequent incident-management workflow.

4.2.1 ALGORITHMS

The preprocessing process transforms the collected Kubernetes security observations into a standardized format suitable for incident detection and AI-based analysis. The observations are validated, relevant security attributes are extracted, and incomplete or invalid inputs are handled before further processing.

The following activities are conducted during preprocessing:

- **Observation Collection:** Kubernetes security observations are collected from the monitoring layer.
- **Input Validation:** Observations are checked for valid and required information.
- **Data Structuring:** Relevant attributes such as resource, condition, status, and timestamp are organized into a standard format.
- **Condition Extraction:** Security-related conditions are identified from the observations.
- **Fingerprint Generation:** A condition fingerprint is generated to support incident correlation and deduplication.
- **Incident Creation:** Validated observations are converted into structured security incidents.
- **Response Preparation:** The analyzed incident is passed to policy evaluation and the controlled response workflow.

This preprocessing stage ensures that security observations are consistently structured and suitable for subsequent **incident analysis, policy evaluation, response, verification, and audit logging**.

The validation results demonstrate that the implemented components of QuantumSHIELD successfully completed their respective tests. The backend test suite achieved 44 successful tests, while the blockchain service completed 2 successful tests. The frontend production build and complete end-to-end workflow were also successfully validated.

The results confirm the successful execution of the major security workflow, including incident detection, AI-based analysis, policy evaluation, human approval, controlled response, response verification, and audit recording. The validation demonstrates that the implemented framework functions correctly in the local demonstration environment.

Overall, the results show that QuantumSHIELD successfully integrates AI-based incident analysis, integrity protection, post-quantum cryptographic interfaces, blockchain auditing, controlled response, and security auditing into a unified workflow.

CHAPTER 6
CONCLUSION

The proposed QuantumSHIELD framework provides an integrated approach for securing enterprise IT environments against evolving cyber threats and future quantum-computing risks. The system combines Kubernetes security monitoring, AI-based incident analysis, SHA-256 integrity protection, post-quantum cryptographic interfaces, blockchain-based auditing, and controlled incident response within a unified security workflow.

The framework validates security observations through incident detection, correlation, and deduplication before performing AI-based analysis. The AI component provides incident classification, severity information, confidence information, and recommended security actions. Security records are protected using SHA-256, while ML-DSA and ML-KEM interfaces provide support for future post-quantum cryptographic integration.

The system further incorporates role-based access control, policy evaluation, human approval, controlled response, response verification, and audit logging to ensure that security actions are authorized and traceable. The implementation was validated through a local demonstration environment using deterministic Kubernetes observations, simulated response actions, and a mock blockchain provider. The validation successfully completed the implemented test cases and end-to-end security workflow.

Overall, QuantumSHIELD combines security monitoring, AI-assisted analysis, cryptographic protection, blockchain auditing, and controlled incident response into a single framework. It provides a foundation for improving security visibility, accountability, and controlled response in modern enterprise IT environments.

REFERENCES

1. Aggarwal, A., "Deployment of Container Security Frameworks in Kubernetes-Orchestrated Environments for Preventing Runtime Exploits and Image Vulnerabilities through Policy-Based Controls," *International Journal on Recent and Innovation Trends in Computing and Communication*, vol. 11, no. 6, pp. 776–783, 2023.
2. Aktolga, I. T., Kuru, E. S., Sever, Y., and Angin, P., "AI-Driven Container Security Approaches for 5G and Beyond: A Survey," *ITU Journal on Future and Evolving Technologies*, vol. 4, no. 2, pp. 364–382, 2023, doi: 10.52953/ZRCK3746.
3. Alvarado, M., Gayler, L., Seals, A., Wang, T., and Hou, T., "A Survey on Post-Quantum Cryptography: State-of-the-Art and Challenges," 2023.
4. Bagheri, S., Kermabon-Bobinnec, H., Kabir, M. E., Majumdar, S., Wang, L., Jarraya, Y., Nour, B., and Pourzandi, M., "ACE-WARP: A Cost-Effective Approach to Proactive and Non-Disruptive Incident Response in Kubernetes Clusters," *IEEE Transactions on Information Forensics and Security*, vol. 19, pp. 8204–8219, 2024, doi: 10.1109/TIFS.2024.3449038.
5. Bavdekar, R., Chopde, E. J., Agrawal, A., Bhatia, A., and Tiwari, K., "Post Quantum Cryptography: A Review of Techniques, Challenges and Standardizations," in *2023 International Conference on Information Networking (ICOIN)*, pp. 146–151, 2023, doi: 10.1109/ICOIN56518.2023.10048976.
6. Chaudhary, D., Durgarao, M. S. P., Mishra, D., and Kumari, S., "A Module Lattice Based Construction of Post Quantum Secure Blockchain Architecture," *Transactions on Emerging Telecommunications Technologies*, vol. 35, no. 4, e4855, 2024, doi: 10.1002/ett.4855.
7. Choi, D., Seo, H., Kim, K., You, M., Shin, S., and Kim, J., "Uncovering Threats in Container Systems: A Study on Misconfigured Container Components in the Wild," *IEEE Access*, vol. 12, pp. 192931–192945, 2024, doi: 10.1109/ACCESS.2024.3514751.
8. Dam, D.-T., Tran, T.-H., Hoang, V.-P., Pham, C.-K., and Hoang, T.-T., "A Survey of Post-Quantum Cryptography: Start of a New Race," *Cryptography*, vol. 7, no. 3, p. 40, 2023, doi: 10.3390/cryptography7030040.
9. Dong, Y., and Pan, H., "Enterprise Audits and Blockchain Technology," *SAGE Open*, 2023, doi: 10.1177/21582440231218839.
10. Fernand ez-Carames, T. M., and Fraga-Lamas, P., "Towards Post-Quantum Blockchain: A Review on Blockchain Cryptography Resistant to Quantum Computing Attacks," 2024.

11. Gomes, J., Khan, S., and Svetinovic, D., “Fortifying the Blockchain: A Systematic Review and Classification of Post-Quantum Consensus Solutions for Enhanced Security and Resilience,” *IEEE Access*, vol. 11, pp. 74088–74100, 2023, doi: 10.1109/ACCESS.2023.3296559.
12. Gwak, S., Doan, T.-P., and Jung, S., “Container Instrumentation and Enforcement System for Runtime Security of Kubernetes Platform with eBPF,” *Intelligent Automation & Soft Computing*, vol. 37, no. 2, pp. 1773–1786, 2023, doi: 10.32604/iasc.2023.039565.
13. Hamdi, A., Fourati, L., and Ayed, S., “Vulnerabilities and Attacks Assessments in Blockchain 1.0, 2.0 and 3.0: Tools, Analysis and Countermeasures,” *International Journal of Information Security*, vol. 23, pp. 713–757, 2024, doi: 10.1007/s10207-023-00765-0.
14. Ji, I. H., Lee, J. H., Kang, M. J., Park, W. J., Jeon, S. H., and Seo, J. T., “Artificial Intelligence-Based Anomaly Detection Technology over Encrypted Traffic: A Systematic Literature Review,” *Sensors*, vol. 24, no. 3, p. 898, 2024, doi: 10.3390/s24030898.
15. Kaur, R., Gabrijelčič, D., and Klobučar, T., “Artificial Intelligence for Cybersecurity: Literature Review and Future Research Directions,” *Information Fusion*, vol. 97, p. 101804, 2023, doi: 10.1016/j.inffus.2023.101804.
16. Kikuchi, T., “Towards A Post-Quantum Cryptography in Blockchain I: Basic Review on Theoretical Cryptography and Quantum Information Theory,” 2024.
17. Landauer, M., Onder, S., Skopik, F., and Wurzenberger, M., “Deep Learning for Anomaly Detection in Log Data: A Survey,” *Machine Learning with Applications*, vol. 12, p. 100470, 2023, doi: 10.1016/j.mlwa.2023.100470.
18. Li, Z., Li, Y., Lu, L., and Ding, Y., “Blockchain-Based Auditing with Data Self-Repair: From Centralized System to Distributed Storage,” *Journal of Systems Architecture*, vol. 137, p. 102854, 2023, doi: 10.1016/j.sysarc.2023.102854.
19. Luo, X., Chen, X., Chen, X., and Cheng, Q., “A Survey on the Application of Blockchain in Cryptographic Protocols,” *Cybersecurity*, vol. 7, no. 1, p. 79, 2024, doi: 10.1186/s42400-024-00324-7.
20. Parida, N. K., Jatoth, C., Reddy, V. D., Hussain, M. M., and Faizi, J., “Post-Quantum Distributed Ledger Technology: A Systematic Survey,” *Scientific Reports*, vol. 13, p. 20729, 2023, doi: 10.1038/s41598-023-47331-1.
21. Priya, D. P. V. S., Sethuraman, S. Chakkaravarthy, and Khan, M. K., “Container Security: Precaution Levels, Mitigation Strategies, and Research Perspectives,” *Computers & Security*, vol. 135, p. 103490, 2023, doi: 10.1016/j.cose.2023.103490.

22. Ruffo, V. G. da Silva, Lent, D. M. B., Komarchesqui, M., Schiavon, V. F., Assis, M. V. O. de, Carvalho, L. F., and Proença Jr., M. L., "Anomaly and Intrusion Detection Using Deep Learning for Software-Defined Networks: A Survey," *Expert Systems with Applications*, vol. 256, p. 124982, 2024, doi: 10.1016/j.eswa.2024.124982.
23. Salem, A. H., Azzam, S. M., Emam, O. E., and Abohany, A. A., "Advancing Cybersecurity: A Comprehensive Review of AI-Driven Detection Techniques," *Journal of Big Data*, vol. 11, no. 105, 2024, doi: 10.1186/s40537-024-00957-y.
24. Tshisekedi, I. T. E., Firdaus, M., Latt, C. N. Z., Noh, S., and Rhee, K.-H., "Hyperledger Fabric-Powered Network Slicing Handover Authentication," *Information Systems Frontiers*, 2024, doi: 10.1007/s10796-024-10564-0.
25. Yang, Z., Alfauri, H., Farkiani, B., Jain, R., Di Pietro, R., and Erbad, A., "A Survey and Comparison of Post-Quantum and Quantum Blockchains," *IEEE Communications Surveys & Tutorials*, vol. 26, no. 2, pp. 967–1002, 2024, doi: 10.1109/COMST.2023.3325761.