



Chemical Composition: - It is hydrated aluminium magnesium silicate.

Formula :- $(\text{Mg Al})_5 \text{Si}_8 \text{O}_{22} (\text{OH})_4$

Grade: - **Salt Gel Attapulgit Powder**

Grade Description: -

Attapulgit is sometimes referred to as salt gel and/or fuller's earth. Attapulgit is a hydrous magnesium aluminosilicate with formula $(\text{Mg,Al})_2\text{Si}_4\text{O}_{10}(\text{OH})_4(\text{H}_2\text{O})$ that occurs in a type of clay soil produced in fine powder as gel and absorbent grades. It has a needle-like structure.

Attapulgit, a naturally occurring clay mineral with a rodlike structure, was identified as a game-changing viscosity modifier in drilling mud in high salt, high pressure, and high heat environments.

Processing of the clays consists of drying and grinding the crude clay to specific particle size distributions with specific ranges of gel viscosity measured by a variety of means depending on the end use.

Salt Gel Physical Parameters: -

PARAMETERS	REQUIREMENT
Suspension properties Viscosity dial reading at 600 rpm	35 cps minimum
Residue greater than 75 micrometers	4% maximum
Moisture	8% maximum

Application Attapulgit Salt Gel Grade : -

- (1) Use in Oil drilling and water drilling
- (2) Petro chemical
- (3) High viscosity maintains
- (4) Construction chemical
- (5) Bonding agent for granulation of powder
- (6) Laundry washing powder, etc.

Packing: - HDPE with linear 25kgs packing.