

Chemical Composition: - It is hydrated aluminium magnesium silicate.

Formula :- (Mg Al)5 Si8 O22 (OH)4

Grade: - Attapulгите Powder API-13A Section 12 Grade

Grade Description: -

Certified API Spec 13A Section 12 compliant attapulгите clay mineral specifically engineered for saltwater, offshore, and high-salinity oil & gas exploration drilling fluids.

Delivers rapid suspension and reliable rheological stability under saturated electrolyte brine without flocculation.

API-13A Section 12 Certified Physical Parameters: -

PARAMETERS	REQUIREMENT
Suspension Viscosity dial reading at 600 rpm	30 cps minimum (API Spec 13A)
Wet Screen Residue > 75 micrometers (200 mesh)	8.0% maximum
Moisture Content (as shipped)	10.0% maximum
Dispersibility in Saturated NaCl Brine	Immediate thixotropic gel build
Packaging	25 kg multi-wall HDPE moisture-proof bags

Application Attapulгите API-13A Section 12 Grade : -

- (1) High-salinity saltwater drilling muds (API 13A Sec 12)
- (2) Offshore and geothermal deep well drilling fluids
- (3) Saturated brine and seawater rheology control
- (4) Horizontal directional drilling (HDD) in saline strata
- (5) Civil diaphragm walling and saline slurry trenching

Packing: - HDPE with linear 25kgs packing.