

**Chemical Composition:** - It is hydrated aluminium magnesium silicate.

**Formula :-** ( Mg Al)5 Si8 O22 (OH)4

**Grade:** - Premium 325 Attapulgite Powder

**Grade Description:** -

Attapulgite powder is a premium quality, fine powder attapulgite product which offers excellent thickening and suspending properties for numerous below applications.

**Premium 325 Physical Parameters:** -

| PARAMETERS                             | REQUIREMENT   |
|----------------------------------------|---------------|
| MOISTURE                               | 6-8%          |
| FORM                                   | POWDER        |
| COLOUR                                 | OFF WHITE     |
| Ph (2% in water)                       | 7-9           |
| Surface Area (BET)m2/gm                | 210 +10%      |
| Specific Gravity                       | 2.3-2.4       |
| 325#MESH (wet)                         | 98.5 % max    |
| Bulk Density                           | 0.3-0.4 gm/ml |
| Al2O3                                  | 5-10%         |
| Fe2O3                                  | 4-5%          |
| SiO2                                   | 36-42%        |
| CaO                                    | 4-5%          |
| MgO                                    | 8-12%         |
| Loi                                    | 20-25%        |
| Brookfield viscosity (7% water&50 rpm) | 1200-1600 Cp  |
| Oil Abs (ml/100 g)                     | 100           |

**Application Attapulgite Premium 325 :** -

PAINT, COATING, FERTILIZERS, CERAMICS, CONSTRUCTION CHEMICALS, ADMIXTURE, SEALANTS, FOUNDRYFLUX CHEMICAL, ADHESIVES, LIQUID SUSPENSIONS, DETERGENT etc.

**Packing:** - HDPE with linear 25kgs packing.