Bento Clay Tech

Manufacturers of Attapulgite Minerals

Product Data Sheet

Attapulgite Premium 325

Chemical Composition: - It is hydrated aluminium magnesium silicate.

Formula :- (Mg Al)5 Si8 O22 (OH)4

Grade: - Premium 325 Attapulgite Powder

Grade Description: -

Attapulgite powder is a premium quality, fine powder attapulgite product which offers excellent thickening and suspending properties for numerous below applications.

Premium 325 Physical Parameters: -

PARAMETERS	REQUIREMENT
MOISTURE	**6-8%**
FORM	**POWDER**
COLOUR	**OFF WHITE**
Ph (2% in water)	**7.-9**
Surface Area (BET)m2/gm	**210 +10%**
Specific Gravity	**2.3-2.4**
325#MESH (wet)	**98.5 % max**
Bulk Density	**0.3-0.4 gm/ml**
Al2O3	**5-10%**
Fe2O3	**4-5%**
SiO2	**36-42%**
CaO	**4-5%**
MgO	**8-12%**
Loi	**20-25%**
Brookfield viscosity (7% water&50 rpm)	**1200-1600 Cp**
Oil Abs (ml/100 g)	**100**

Application Attapulgite Premium 325 : -

PAINT, COATING, FERTILIZERS, CERAMICS, CONSTRUCTION CHEMICALS, ADMIXTURE, SEALANTS, FOUNDRYFLUX CHEMICAL, ADHESIVES, LIQUID SUSPENSIONS, DETERGENT etc.

Packing: - HDPE with liner, 25 kg packing.

Manufacturing Works: L.S. 341/P-2, Behind Manpasand Dhaba, Vallabhipur Highway, Kardej, Bhavnagar – 364060, Gujarat, India

Email: dipak@bentoclay.com | bentoclayclaytech@gmail.com **Contact: +91 74358 18628 | Website: https://bentoclayclaytech.com/**