

Inter VLAN Routing using Switch Virtual Interface

Friday, June 12, 2026

8:34 AM

Commands for VLAN Configuration:-

Switch:

-- to configure VLAN 10

```
Enable
configure terminal
vlan 10
name HR
exit
```

-- to configure VLAN 20

```
vlan 20
name Sales
exit
```

-- to assign access ports to the respective VLAN's

```
interface range fastEthernet 0/1 -2
switchport access vlan 10
exit
```

```
interface range fastEthernet 0/3 -4
switchport access vlan 20
exit
exit
```

-- to view VLANs

```
show vlan brief
```

Multilayer Switch:

-- to configure VLAN 10

```
enable
configure terminal
vlan 10
name HR
```

exit

-- to configure VLAN 20

```
vlan 20
name Sales
exit
exit
```

-- to view VLANs

show vlan brief

Commands for Trunking Configuration:-

Switch:

-- to configure fa 0/5 as trunk port

```
enable
configure terminal
interface fastEthernet 0/5
switchport mode trunk
exit
exit
```

-- to view trunk ports

show interface trunk

Multilayer Switch:

-- to configure fa 0/1 as trunk port

```
enable
configure terminal
interface fastEthernet 0/1
switchport trunk encapsulation dot1q
switchport mode trunk
exit
```

Commands for Switch Virtual Interface Configuration:-

Multilayer Switch:

-- to configure interface vlan 10

```
enable
configure terminal
interface vlan 10
ip address 10.0.0.1 255.0.0.0
no shutdown
exit
```

-- to configure interface vlan 20

```
interface vlan 20
ip address 20.0.0.1 255.0.0.0
no shutdown
exit
exit
```

-- to view the virtual interface

```
show ip interface brief
```

Commands for Inter VLAN Routing Configuration:-

Multilayer Switch:

-- to configure IVR

```
enable
configure terminal
ip routing
```