

SWITCHING PROJECT TOPOLOGY

Wednesday, June 17, 2026 8:20 AM

Networks used in the Topology:-

1. Data Centre - 192.168.1.0/24
2. Core Switch to C Block - 192.168.2.0/24
3. A Block (Business Operations):

HR	10.0.0.0/8	VLAN 10
Sales	20.0.0.0/8	VLAN 20
Marketing	30.0.0.0/8	VLAN 30

4. B Block (Technical Operations):

IT Support	40.0.0.0/8	VLAN 40
R&D	50.0.0.0/8	VLAN 50
Operations	60.0.0.0/8	VLAN 60

5. C Block (Management & Administration):

Finance	70.0.0.0/8	VLAN 70
Legal	80.0.0.0/8	VLAN 80
Management	90.0.0.0/8	VLAN 90

IP addresses in Data Centre:-

DNS Server	192.168.1.10
DHCP Server	192.168.1.20
Google Server	192.168.1.30
Azure Server	192.168.1.40

Connections in the Topology:-

1. DC Switch (interface fastEthernet 0/1 -4) to Core Switch (interface fastEthernet 0/1 -4)

2. A Block Switch (interface fastEthernet 0/1 -4) to Core Switch (interface fastEthernet 0/5 -8)
3. B Block Switch (interface fastEthernet 0/1 -4) to Core Switch (interface fastEthernet 0/9 -12)
4. C Block Switch(interface fastEthernet 0/1) to Router (interface fastEthernet 0/1)
5. Router (interface fastEthernet 0/0) to Core Switch (interface fastEthernet 0/13)

6. In A Block Switch,

Ports 5 and 6	VLAN 10
Ports 7 and 8	VLAN 20
Ports 9,10 and 11	VLAN 30

7. In B Block Switch,

Ports 5 and 6	VLAN 40
Ports 7 and 8	VLAN 50
Ports 9 and 10	VLAN 60

8. In C Block Switch,

Ports 2 and 3	VLAN 70
Ports 4	VLAN 80
Ports 5 and 6	VLAN 90