RAJALAKSHMI ENGINEERING COLLEGE

Dheeraj Kanna P 250701166-2025-CSE

D2

Started on	Monday, 31 August 2026, 10:00 AM
State	Finished
Completed on	Monday, 31 August 2026, 10:00 AM
Time taken	21 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main(){
    int n;
    scanf("%d",&n);
    int A[n],B[n];
    for(int i=0;i<n;i++){
        scanf("%d",&A[i]);
    }
    for(int i=0;i<n;i++){
        for(int j=0;j<n-i-1;j++){
            if(A[j]>A[j+1]){
                int temp=A[j];
                A[j]=A[j+1];
                A[j+1]=temp;
            }
        }
    }
    for(int i=0;i<n;i++){
        scanf("%d",&B[i]);
    }
    for(int i=0;i<n;i++){
        for(int j=0;j<n-i-1;j++){
            if(B[j]<B[j+1]){
                int temp=B[j];
                B[j]=B[j+1];
                B[j+1]=temp;
            }
        }
    }
    int sum=0;
    for(int i=0;i<n;i++){
        sum+=(A[i]*B[i]);
    }
    printf("%d",sum);

}
```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course