RAJALAKSHMI ENGINEERING COLLEGE

Dheeraj Kanna P 250701166-2025-CSE

D2

Started on	Monday, 31 August 2026, 10:02 AM
State	Finished
Completed on	Monday, 31 August 2026, 10:02 AM
Time taken	25 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than `⌊n / 2⌋` times. You may assume that the majority element always exists in the array.

Example 1:

```
Input: nums = [3,2,3]
Output: 3
```

Example 2:

```
Input: nums = [2,2,1,1,1,2,2]
Output: 2
```

Constraints:

- `n == nums.length`
- `1 <= n <= 5 * 10^4`
- `-2^31 <= nums[i] <= 2^31 - 1`

For example:

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

Answer: (penalty regime: 0 %)

```c
#include<stdio.h>
int main(){
    int n;
    scanf("%d",&n);
    int arr[n];
    for(int i=0;i<n;i++){
        scanf("%d",&arr[i]);
    }
    int can=arr[0];
    int cnt=1;
    for(int i=1;i<n;i++){
        if(arr[i]==can){
            cnt++;
        }
        else{
            cnt--;
        }
        if(cnt==0){
            can=arr[i];
            cnt=1;
        }
    }
    cnt=0;
    for(int i=0;i<n;i++){
        if(arr[i]==can){
            cnt++;
```

```
27          }
28      }
29      if(cnt>n/2){
30          printf("%d",can);
31      }
32      else{
33          printf("No major element exist");
34      }
35  }
```

	Input	Expected	Got	
✔	3 3 2 3	3	3	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course