
Edge-preserving Smoothing using Patch-Based Filtering

Table of Contents

Variables and Parameters	1
Gaussian Mask	1
Subsampling Image with gaussian blur of std 0.66	2
Noisy Image	2
Smoothing image	2
Tweaked Parameters	5

Objectives:

- Apply the patch based filtering
- Calculate and minimize the RMSD

Variables and Parameters


```
isotropize = 1.0;
factor = 2;
patch_size = 9;
window_size = 25;
addpath('.../common/');
load '.../data/barbara.mat';
input_image = imageOrig;
sigmaOptimal = 1.0;
```

Gaussian Mask

```
gaussian_mask = fspecial('gaussian',...
    [patch_size, patch_size], isotropize);
[rows, cols] = size(gaussian_mask);
gaussian_mask_stretched = myLinearContrastStretching(gaussian_mask);
images = zeros(rows, cols, 1);
images(:, :, 1) = gaussian_mask_stretched;
```

Mask used to make images Isotropic

```
myShowImages(images, 'Mask for isotropism');
```



Subsampling Image with gaussian blur of std 0.66

```
input_image = input_image(1:factor:size(input_image, 1),...  
    1:factor:size(input_image, 2));  
gaussian_filter = fspecial('gaussian', [3, 3], 0.66);  
input_image = imfilter(input_image, gaussian_filter);  
[rows, cols] = size(input_image);
```

Noisy Image

```
noisy_image = myGaussianNoiser(input_image);  
rmsd_with_noisy_image = myRMSDofImage(input_image, noisy_image);  
disp(['RMSD with noisy image = ', num2str(rmsd_with_noisy_image)]);
```

RMSD with noisy image = 4.6815

Smoothing image

```
tic;  
output_image = myPatchBasedFiltering(noisy_image, patch_size,...  
    window_size, sigmaOptimal, gaussian_mask);  
elapsed_time = toc;  
if elapsed_time > 300  
    save(' ../images/barbara_patch_optimal.mat', 'output_image')  
end  
  
images = zeros(rows, cols, 3);  
images(:, :, 1) = input_image;  
images(:, :, 2) = noisy_image;
```

```
images(:, :, 3) = output_image;
myShowImages(images, ...
    'Side by Side comparison of original, noisay and smooth barbara');

images = zeros(rows, cols, 1);
images(:, :, 1) = input_image;
myShowImages(images, 'Original barbara');


images = zeros(rows, cols, 1);
images(:, :, 1) = noisy_image;
myShowImages(images, 'Noisy barbara');

images = zeros(rows, cols, 1);
images(:, :, 1) = output_image;
myShowImages(images, 'Smooth barbara');

optimal_RMSD = myRMSDofImage(input_image, output_image);
disp(['RMSD with optimal output = ', num2str(optimal_RMSD)]);
disp(['Optimal sigma = ', num2str(sigmaOptimal)]);

RMSD with optimal output = 2.762
Optimal sigma = 1
```

Side by Side comparison of original, noisay and smooth barbara




Edge-preserving Smoothing using Patch-Based Filtering

Original barbara



Noisy barbara





Tweaked Parameters

RMSD with 0.9 sigmaOptimal

```
tic;
output_image_1 = myPatchBasedFiltering(noisy_image, patch_size,...
    window_size, 0.9*sigmaOptimal, gaussian_mask);
elapsed_time = toc;
if elapsed_time > 300
    save('../images/barabara_01.mat', 'output_image_1')
end
new_RMSD = myRMSDofImage(input_image, output_image_1);
disp(['RMSD with 0.9*sigmaOptimal output = ', num2str(new_RMSD)]);

RMSD with 0.9*sigmaOptimal output = 2.7189
```

RMSD with 1.1 sigmaOptimal

```
tic;
output_image_2 = myPatchBasedFiltering(noisy_image, patch_size,...
    window_size, 1.1*sigmaOptimal, gaussian_mask);
elapsed_time = toc;
if elapsed_time > 300
    save('../images/barabara_02.mat', 'output_image_2')
end
new_RMSD = myRMSDofImage(input_image, output_image_2);
disp(['RMSD with 1.1*sigmaOptimal output = ', num2str(new_RMSD)]);

RMSD with 1.1*sigmaOptimal output = 2.8881
```

Published with MATLAB® R2014b