Command Prompt

Packet Tracer PC Command Line 1.0

PC > ipconfig

Fast Ethernet 0 Connection (default port)

Link-Local IPv6 Address . . . . : FE80::260:70FF

IP Address 20.0.0.2

Subnet Mask 255.0.0.0

Default Gateway 20.0.0.1

PC > ping 10.0.0.2

Pinging 10.0.0.2 with 32 bytes of data

Request timed out.

Reply from 10.0.0.2: bytes=32 times=3ms

Ping statistics for 10.0.0.2

Packets: Sent = 4, Received = 3, Lost = 1

Approximate round trip times in milli-seconds

Minimum = 3ms, Maximum = 3ms, Average = 3ms

Ex No: 11-b RIP using Cisco Packet Tracer

AIM: To simulate and configure RIP (Routing Information Protocol) using Cisco Packet Tracer and verify communication b/w different networks.

STEPS / PROCEDURE:

1. Create the network
   - Place 3 routers (Router0, Router1, Router2) and 2 PCs (PC0, PC1)
   - Connect the routers using serial links & PCs through Fast Ethernet
   - Assign the given IP addresses to all PCs & router interfaces.
2. Configure Router Interfaces.
   - Open Router → CLI and enter:

```
enable
configure terminal
interface <interface-name>
ip address <IP-address> <subnet-mask>
no shutdown
```

   - For serial interfaces, configure clock rate 64000 & bandwidth 64 where required
3. Configure RIP
   - Enable RIP on each router:

```
router rip
```

   - Advertise all directly connected networks using:

```
network <network-address>
```

   Example:

```
router rip
network 10.0.0.0
network 192.168.1.248
network 192.168.1.252.
```

   - Repeat the RIP configuration on Router1 & Router2 with their respective connected networks.
4. Verify connectivity
   - Open PC → desktop → command Prompt
   - Test communication using [ping <destination-IP>]
   - Verify that PC0 can successfully communicate with PC1 through routers
5. Verify Dynamic Routing
   - Use tracert to check the route taken by packets
   - Disconnect one routing link & test again
   - RIP automatically selects alternative available route

RESULT: Thus RIP dynamic routing successfully configured using Cisco Packet tracer. Communication b/w different networks