



Codly v1.3.0 manual

Your code blocks on steroids

O RLY?

Dherse

Contents

| | |
|---|----|
| 1. Codly | 3 |
| 1.1. Initialization | 3 |
| 1.2. Enabling and disabling codly | 3 |
| 1.3. Short guide to this manual | 3 |
| 2. A primer on Codly's show-rule like system | 4 |
| 2.1. Enabled (enabled) | 5 |
| 2.2. Header (header) | 5 |
| 2.3. Header Repeat (header-repeat) | 6 |
| 2.4. Header Cell Args (header-cell-args) | 6 |
| 2.5. Header Transform (header-transform) | 7 |
| 2.6. Footer (footer) | 7 |
| 2.7. Footer Repeat (footer-repeat) | 7 |
| 2.8. Footer Cell Args (footer-cell-args) | 8 |
| 2.9. Footer Transform (footer-transform) | 8 |
| 2.10. Offset (offset) | 9 |
| 2.11. Offset from other code block (offset-from) | 10 |
| 2.12. Range (range) | 11 |
| 2.13. Ranges (ranges) | 11 |
| 2.14. Smart skip (smart-skip) | 12 |
| 2.15. Languages (languages) | 13 |
| 2.16. Default language color (default-color) | 14 |
| 2.17. Radius (radius) | 15 |
| 2.18. Inset (inset) | 16 |
| 2.19. Fill (fill) | 17 |
| 2.20. Zebra fill (zebra-fill) | 18 |
| 2.21. Stroke (stroke) | 19 |
| 2.22. Language box inset (lang-inset) | 19 |
| 2.23. Language box outset (lang-outset) | 20 |
| 2.24. Language box radius (lang-radius) | 20 |
| 2.25. Language box stroke (lang-stroke) | 21 |
| 2.26. Language box fill (lang-fill) | 21 |
| 2.27. Language box formatter (lang-format) | 22 |
| 2.28. Display language name (display-name) | 23 |
| 2.29. Display language icon (display-icon) | 23 |
| 2.30. Line number format (number-format) | 24 |
| 2.31. Line number alignment (number-align) | 24 |
| 2.32. Line number placement (number-placement) | 25 |
| 2.33. Smart indentation (smart-indent) | 26 |
| 2.34. Skip last line if empty (skip-last-empty) | 27 |
| 2.35. Breakable (breakable) | 27 |
| 2.36. Skips (skips) | 28 |
| 2.37. Skip line (skip-line) | 28 |
| 2.38. Skip number (skip-number) | 29 |
| 2.39. Annotations (annotations) | 30 |
| 2.40. Annotation formatter (annotation-format) | 31 |
| 2.41. Highlight lines (highlighted-lines) | 32 |
| 2.42. Highlight lines default color (highlighted-default-color) | 33 |
| 2.43. Highlights (highlights) | 34 |
| 2.44. Highlight radius (highlight-radius) | 34 |
| 2.45. Highlight fill (highlight-fill) | 35 |
| 2.46. Highlight stroke (highlight-stroke) | 35 |
| 2.47. Highlight inset (highlight-inset) | 35 |
| 2.48. Highlight outset (highlight-outset) | 36 |
| 2.49. Highlight clip (highlight-clip) | 36 |
| 2.50. Reference by (reference-by) | 36 |
| 2.51. Reference separator (reference-sep) | 36 |
| 2.52. Reference number format (reference-number-format) | 36 |
| 2.53. Language name aliases (aliases) | 37 |

| | |
|---|----|
| 3. Referencing code blocks, highlights, and annotations | 38 |
| 3.1. Shorthand line references | 38 |
| 3.2. Highlight references | 38 |
| 4. Getting nice icons | 39 |
| 4.1. Typst language icon (<code>typst-icon</code>) | 39 |
| 5. Other functions | 40 |
| 5.1. Skip (<code>codly-skip</code>) | 40 |
| 5.2. Range (<code>codly-range</code>) | 40 |
| 5.3. Offset (<code>codly-offset</code>) | 40 |
| 5.4. Local (<code>local</code>) | 41 |
| 5.5. No Codly (<code>no-codly</code>) | 44 |
| 5.6. Yes Codly (<code>yes-codly</code>) | 44 |
| 5.7. Enable (<code>codly-enable</code>) | 44 |
| 5.8. Disable (<code>codly-disable</code>) | 44 |
| 5.9. Reset (<code>codly-reset</code>) | 46 |
| 6. Codly performance | 47 |

1. Codly

Codly is a library that enhances the way you write code blocks in Typst. It provides a set of tools to help you manage your code blocks, highlights them, skip parts of them, and more. This manual will guide you through the different features of Codly, how to use them, and how to integrate them into your Typst projects.

Notification

If you find any issues with Codly, please report them on the GitHub repository: <https://github.com/Dherse/codly>.

1.1. Initialization

To start using Codly, you must first import it into your Typst project.

| Example code | Rendered output |
|--|-----------------|
| <pre>1 #import "@preview/codly:1.3.0": * 2 3 #show: codly-init</pre> | |

As you can see, this does nothing but initialize codly. You can also import it with a specific version, as shown in the example above. For the latest version, always refer to the [Typst Universe page](#).

From this point on, any code block that is included in your Typst project will be enhanced by Codly.

| Example code | Typst | Rendered output |
|--|-------|----------------------------|
| <pre>1 ``` 2 Hello, world! 3 ```</pre> | | <pre>1 Hello, world!</pre> |






1.2. Enabling and disabling codly

By default Codly will be enabled after initialization. However, disabling codly can be done using the [codly-disable](#) function, the [enabled](#) argument of the [codly](#) function, or the [no-codly](#) and [yes-codly](#) functions. To enable Codly again, use the [codly-enable](#) function or by setting the [enabled](#) parameter again.

1.3. Short guide to this manual

Codly can take a lot of different argument to configure your code blocks. Some of these arguments can have pretty complex behaviour, so this manual is here to help you understand how to use them. Each argument is accompanied by a card that gives you important information about its usage. The card contains the following information:

- the type(s) of values accepted ;
- the default value that is pre-set ;
- whether the argument can take a contextual function: if it can, you can pass it a function that will be called within a typst [context](#) block to customize the value of the argument yourself¹ ;
- whether the argument is automatically reset after the code block is rendered ;
- whether the argument is already released in the current version of Codly or will be released in the next version.

| | |
|--|--|
|  Type | bool or auto |
|  Default value | true |
|  Contextual function | ✓ yes |
|  Automatically reset | ✓ yes |
|  Already released in 1.2.0 | ✗ no |

Additionally to the card, most arguments are accompanied by an example that shows how to use the argument in a code block. The example is followed by a rendered output of the code block, which shows how the argument affects the code block.

¹ This is mostly intended for libraries that wish to extend Codly, or for users that wish to have dynamic control over argument values using their own logic.

2. A primer on Codly's show-rule like system

Codly uses a function called `codly` to create a kind of show-rule which you can use to configure how your code blocks are displayed. The `codly` function takes a set of arguments that define how the code block should be displayed. Here is the equivalent definition of the `codly` function:

```
1  let codly(
2    enabled: true,
3    offset: 0,
4    offset-from: none,
5    range: none,
6    ranges: (),
7    languages: (:),
8    display-name: true,
9    display-icon: true,
10   default-color: rgb("#283593"),
11   radius: 0.32em,
12   inset: 0.32em,
13   fill: none,
14   zebra-fill: luma(240),
15   stroke: 1pt + luma(240),
16   lang-inset: 0.32em,
17   lang-outset: (x: 0.32em, y: 0pt),
18   lang-radius: 0.32em,
19   lang-stroke: (lang) => lang.color + 0.5pt,
20   lang-fill: (lang) => lang.color.lighten(80%),
21   lang-format: codly.default-language-block,
22   number-format: (number) => [ #number ],
23   number-align: left + horizon,
24   number-placement: "outside",
25   smart-indent: false,
26   annotations: none,
27   annotation-format: numbering.with("(1)"),
28   highlights: none,
29   highlight-radius: 0.32em,
30   highlight-fill: (color) => color.lighten(80%),
31   highlight-stroke: (color) => 0.5pt + color,
32   highlight-inset: 0.32em,
33   highlight-outset: 0pt,
34   highlight-clip: true,
35   reference-by: line,
36   reference-sep: "-",
37   reference-number-format: numbering.with("1"),
38   header: none,
39   header-repeat: false,
40   header-transform: (x) => x,
41   header-cell-args: (),
42   footer: none,
43   footer-repeat: false,
44   footer-transform: (x) => x,
45   footer-cell-args: (),
46   breakable: false,
47 ) = {}
```

The `codly` functions acts like a set-rule, this means that calling it will set the configuration for all code blocks that follow it, with the exception of a few arguments that are explicitly set for each code block. To perform changes locally, you can use the `local` function, or set the arguments before the code block and reset them after to their previous values.

Warning

Unlike regular set-rules in native Typst, there are two considerations:

- The `codly` function uses states to store the configuration, this means that it is dependent on layout order for the order in which settings are applied.
- The `codly` function is not local, it sets the configuration for all code blocks that follow it in layout order, unless overridden by another `codly` call. This means that you cannot use it to set the configuration for a specific code block. To perform this, use the `local` function to set the configuration for a specific “section”.

2.1. Enabled (`enabled`)

| | |
|--------------------------------|-------------------|
| <code></></code> Type | <code>bool</code> |
| <code>(*)</code> Default value | <code>true</code> |
| ⚙ Contextual function | ✓ yes |
| 🕒 Automatically reset | ✗ no |
| 🧪 Already released in 1.2.0 | ✓ yes |

Whether `codly` is enabled or not. If it is disabled, the code block will be displayed as a normal code block, without any additional `codly`-specific formatting. This is useful if you want to disable `codly` for a specific block. You can also disable `codly` locally using the `no-codly` function, or disable it and enable it again using the `codly-disable` and `codly-enable` functions.

2.1.1. Example

| Example code | Rendered output |
|--|--|
| <pre>1 *Enabled = true*: 2 #codly(enabled: true) 3 ```typ 4 Hello, world! 5 ``` 6 7 *Enabled = false*: 8 #codly(enabled: false) 9 ```typ 10 Hello, world! 11 ```</pre> | <p>Enabled = true:</p> <pre>1 Hello, world!</pre> <p>Enabled = false:</p> <pre>Hello, world!</pre> |

2.2. Header (`header`)






| | |
|--------------------------------|---|
| <code></></code> Type | <code>content</code> or <code>none</code> |
| <code>(*)</code> Default value | <code>none</code> |
| ⚙ Contextual function | ✓ yes |
| 🕒 Automatically reset | ✓ yes |
| 🧪 Already released in 1.2.0 | ✓ yes |

An optional header to display above the code block. It can be optionally repeated on all subsequent pages with the `header-repeat` argument. And additional customizations are available with the `header-cell-args` and `header-transform` arguments.

2.2.1. Example






| Example code | Rendered output |
|---|--|
| <pre>1 #codly(header: [*Hello, world!*]) 2 ```typ 3 Hello, world! 4 ```</pre> | <p>Hello, world!</p> <pre>1 Hello, world!</pre> |

2.3. Header Repeat (header-repeat)

| | |
|--|--------------------|
|  Type | <code>bool</code> |
|  Default value | <code>false</code> |
|  Contextual function | ✓ yes |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

Whether to repeat the header on each page. This is only applicable if a header is provided, if the code block is `breakable`, and if it actually breaks on more than one page. For more information see [grid.header:repeat](#).


2.4. Header Cell Args (header-cell-args)

| | |
|--|--|
|  Type | <code>array</code> , <code>dictionary</code> , or <code>arguments</code> |
|  Default value | <code>()</code> |
|  Contextual function | ✓ yes |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |









Additional arguments to be provided to the `grid.cell` containing the header. Lets you customize the header cell further. Internally, codly wraps the content of the `header` argument in a `grid.cell` with these arguments. The only argument that is always common is the `body` argument which is the value of the `header` argument, and the `colspan` which is always set to `2`.

For a full description of the argument, look at the documentation of the [grid.cell](#) function.

2.4.1. Example

| Example code | Rendered output |
|--|---|
|  <pre>1 //Centering the header: 2 #codly(3 header: [*Hello, world!*], 4 header-cell-args: (align: center,) 5) 6 7 ```typ 8 Hello, world! 9 ```</pre> | <div>1 Hello, world!</div> <div>typ</div> |

2.5. Header Transform (`header-transform`)









| | |
|--|---|
|  Type | <code>function</code> |
|  Default value | <code>(x) => x</code> |
|  Contextual function |  no |
|  Automatically reset |  no |
|  Already released in 1.2.0 |  yes |

Function that transforms the header into arbitrary content to be stored in the `grid.cell`. Can be seen as a show-rule for the header. This allows to perform global transformation/show-rule like operations on the header.

2.5.1. Example


| Example code | Rendered output |
|---|--|
|  <code>Typst</code> <pre>1 //Making the header bold and blue: 2 #codly(3 header: [Hello, world!], 4 header-transform: (x) => { 5 set text(fill: blue) 6 strong(x) 7 } 8) 9 10 ```typ 11 Hello, world! 12 ```</pre> | <code>typ</code> <pre>1 Hello, world!</pre> |

2.6. Footer (`footer`)









| | |
|--|---|
|  Type | <code>content</code> or <code>none</code> |
|  Default value | <code>none</code> |
|  Contextual function |  yes |
|  Automatically reset |  yes |
|  Already released in 1.2.0 |  yes |

An optional footer to display below the code block. See [header](#) for more information.

2.6.1. Example






| Example code | Rendered output |
|---|--|
|  <code>Typst</code> <pre>1 #codly(footer: [*Hello, world!*]) 2 ```typ 3 Hello, world! 4 ```</pre> | <code>typ</code> <pre>1 Hello, world! Hello, world!</pre> |

2.7. Footer Repeat (`footer-repeat`)

| | |
|--|---|
|  Type | <code>bool</code> |
|  Default value | <code>false</code> |
|  Contextual function |  yes |
|  Automatically reset |  no |
|  Already released in 1.2.0 |  yes |



Whether to repeat the footer on each page. See [header-repeat](#) for more information.

2.8. Footer Cell Args (footer-cell-args)






| | |
|--|--|
|  Type | <code>array</code> , <code>dictionary</code> , or <code>arguments</code> |
|  Default value | <code>()</code> |
|  Contextual function | ✓ yes |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

Additional arguments to be provided to the `grid.cell` containing the footer. See [header-cell-args](#) for more information.

2.8.1. Example



| Example code | Rendered output |
|--|--|
|  <pre>1 //Centering the footer: 2 #codly(3 footer: [*Hello, world!*], 4 footer-cell-args: (align: center,) 5) 6 7 ```typ 8 Hello, world! 9 ```</pre> | <pre>1 Hello, world! Hello, world!</pre>  |

2.9. Footer Transform (footer-transform)





| | |
|--|--------------------------|
|  Type | <code>function</code> |
|  Default value | <code>(x) => x</code> |
|  Contextual function | ✗ no |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

Function that transforms the footer into arbitrary content to be stored in the `grid.cell`. Can be seen as a show-rule for the footer. See [header-transform](#) for more information.

2.9.1. Example

| Example code | Rendered output |
|---|--|
|  <pre>1 //Making the footer bold and blue: 2 #codly(3 footer: [Hello, world!], 4 footer-transform: (x) => { 5 set text(fill: blue) 6 strong(x) 7 } 8) 9 10 ```typ 11 Hello, world! 12 ```</pre> | <pre>1 Hello, world! Hello, world!</pre>  |

2.10. Offset (offset)

| | |
|--|-------|
|  Type | int |
| (*) Default value | 0 |
|  Contextual function | ✓ yes |
|  Automatically reset | ✓ yes |
|  Already released in 1.2.0 | ✓ yes |





The offset to apply to line numbers.

This is purely cosmetic, only impacting the shown line numbers in the final output.

2.10.1. Example

| Example code | Typst | Rendered output |
|-------------------------|-------|----------------------------------|
| 1 *No offset:* | | No offset: |
| 2 ```typ | | 1 Hello, world! typ |
| 3 Hello, world! | | |
| 4 ``` | | |
| 5 | | |
| 6 *Offset by 5:* | | Offset by 5: |
| 7 #codly(offset: 5) | | 6 Hello, world! typ |
| 8 ```typ | | |
| 9 Hello, world! | | |
| 10 ``` | | |

2.11. Offset from other code block (offset - from)

| | |
|--|---|
|  Type | <code>none</code> or <code>label</code> |
| (*) Default value | <code>none</code> |
|  Contextual function | ✓ yes |
|  Automatically reset | ✓ yes |
|  Already released in 1.2.0 | ✓ yes |

The offset to apply to line numbers, relative to another code block. This is useful when you want to match line numbers between two code blocks. This code block will continue the line numbers from the other code block, with the specified offset.

This is done by giving a `label` to the parent raw block, and then setting it as the `offset-from` on the second code block.

Info

Note that the offset obtained from the other code block is added to the offset specified in the `offset` argument.

Warning

Important: this feature works with any `offset` set on the other code block, including `offset-from` but may give unexpected results if both code blocks have `offset-from` set to each other or if the preceeding code block has `range` or `skips` set.






Experiment

This feature should be considered experimental. Please report any issues you encounter on GitHub: <https://github.com/Dherse/codly>.

2.11.1. Example

| Example code | Rendered output |
|--|---|
| <pre>1 ```py 2 def fib(n): 3 if n <= 1: 4 return n 5 return fib(n - 1) + fib(n - 2) 6 ``` <fib-fn> 7 8 *Will continue at line 5* 9 #codly(offset-from: <fib-fn>) 10 ```py 11 fib(25) 12 ```</pre> | <pre>1 def fib(n): 2 if n <= 1: 3 return n 4 return fib(n - 1) + fib(n - 2) Will continue at line 5 5 fib(25)</pre> |

2.12. Range (range)

| | |
|--|---|
|  Type | <code>none</code> or <code>array</code> |
|  Default value | <code>none</code> |
|  Contextual function | ✓ yes |
|  Automatically reset | ✓ yes |
|  Already released in 1.2.0 | ✓ yes |

The range of line numbers to display, one-indexed. If set to `none`, all lines are displayed. Can also be achieved using the convenience function `codly-range`. If set to `none`, all lines are displayed.






Info

Line numbers are one-indexed, meaning that to reference the fourth line, you use the number `4`.

2.12.1. Example

| Example code | Typst | Rendered output |
|--|-------|--|
| <pre>1 #codly(range: (2, 4)) 2 ``py 3 def fib(n): 4 if n <= 1: 5 return n 6 return fib(n - 1) + fib(n - 2) 7 fib(25) 8 ``</pre> | | <pre>2 if n <= 1: 3 return n 4 return fib(n - 1) + fib(n - 2)</pre> |

2.13. Ranges (ranges)

| | |
|--|---|
|  Type | <code>none</code> or <code>array</code> |
|  Default value | <code>none</code> |
|  Contextual function | ✓ yes |
|  Automatically reset | ✓ yes |
|  Already released in 1.2.0 | ✓ yes |

The ranges of line numbers to display, one-indexed. If set to `none`, all lines are displayed. Can also be achieved using the convenience function `codly-range` if provided with more than one range. If set to `none`, all lines are displayed. Note that it override the `range` argument.






Info

Line numbers are one-indexed, meaning that to reference the fourth line, you use the number `4`.

2.13.1. Example

| Example code | Typst | Rendered output |
|---|-------|---|
| <pre>1 #codly(ranges: ((2, 2), (4, 4))) 2 ``py 3 def fib(n): 4 if n <= 1: 5 return n 6 return fib(n - 1) + fib(n - 2) 7 fib(25) 8 ``</pre> | | <pre>2 if n <= 1: 4 return fib(n - 1) + fib(n - 2)</pre> |

2.14. Smart skip (smart-skip)

| | |
|--|--|
|  Type | <code>bool</code> or <code>dictionary</code> |
|  Default value | <code>false</code> |
|  Contextual function | ✓ yes |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

Whether to automatically insert a `skips` entry between ranges of displayed values. They must be discontinuous for a skip to be added. The skip will be the size of the discontinuity. It can also be a dictionary with the keys:

- `first` : whether to include a skip if the start of the block is outside of the ranges
- `last` : whether to include a skip if the end of the code block is outside of the ranges
- `rest` : whether to include a skip for unspecified values and/or in the middle of the code block.


You can specify one or more of these keys, if the `rest` is not specified, it defaults to `none` .




Experiment

This feature should be considered experimental. Please report any issues you encounter on GitHub: <https://github.com/Dherse/codly>.






2.14.1. Example

| Example code | Rendered output |
|---|---|
|  <code>#codly(</code> <code> smart-skip: true,</code> <code> ranges: ((2, 2), (4, 4))</code> <code>)</code> <code>```py</code> <code>def fib(n):</code> <code> if n <= 1:</code> <code> return n</code> <code> return fib(n - 1) + fib(n - 2)</code> <code>fib(25)</code> <code>```</code> | <code>...</code> <code>2 if n <= 1:</code> <code>...</code> <code>4 return fib(n - 1) + fib(n - 2)</code> <code>...</code> |

2.14.2. Example: Using a dictionary

| Example code | Rendered output |
|--|---|
|  <code>#codly(</code> <code> smart-skip: (</code> <code> first: false,</code> <code> last: false,</code> <code> rest: true</code> <code>),</code> <code> ranges: ((2, 2), (4, 4))</code> <code>)</code> <code>```py</code> <code>def fib(n):</code> <code> if n <= 1:</code> <code> return n</code> <code> return fib(n - 1) + fib(n - 2)</code> <code>fib(25)</code> <code>```</code> | <code>2 if n <= 1:</code> <code>...</code> <code>4 return fib(n - 1) + fib(n - 2)</code> |

2.15. Languages (languages)



| | |
|--|------------|
|  Type | dictionary |
|  Default value | (:) |
|  Contextual function | ✓ yes |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

The language definitions to use for language block formatting. It is defined as a dictionary where the keys are the language names and each value is another dictionary containing the following keys:

- `name` : the “pretty” name of the language as a content/showable value
- `color` : the color of the language, if omitted uses the default color
- `icon` : the icon of the language, if omitted no icon is shown.

If an entry is missing, and language blocks are enabled, will show the “un-prettified” language name, with the default color.




2.15.1. Example

| Example code | Rendered output |
|--|--|
|  <pre>1 #codly(2 languages: (3 py: (4 name: [Python], color: green, icon: 5 "🐍" 6), 7) 8 ``py 9 def fib(n): 10 if n <= 1: 11 return n 12 return fib(n - 1) + fib(n - 2) 13 fib(25) 14 ``</pre> |  <pre>1 def fib(n): 2 if n <= 1: 3 return n 4 return fib(n - 1) + fib(n - 2) 5 fib(25)</pre> |







2.15.2. Pre-existing language definitions

Info

Check out the [codly-languages](#) package on Typst universe. It contains pre-definition for many language and is extremely easy to use. You can consider it officially endorsed by the codly author as of the 19th of November 2024.


| Example code | Rendered output |
|--|--|
|  <pre>1 #import "@preview/codly-languages:0.1.7": * 2 #codly(languages: codly-languages) 3 ``rust 4 fn main() { 5 println!("Hello, world!"); 6 } 7 `` 8 ``zig 9 const std = @import("std"); 10 11 pub fn main() void { 12 std.debug.print("Hello, world!", .{}); 13 } 14 ``</pre> |  <pre>1 fn main() { 2 println!("Hello, world!"); 3 } <pre>1 const std = @import("std"); 2 3 pub fn main() void { 4 std.debug.print("Hello, world!", .{}); 5 }</pre></pre> |

2.16. Default language color (default-color)





| | |
|--|---|
|  Type | <code>color</code> , <code>gradient</code> , or <code>pattern</code> |
|  Default value | <code>rgb("#283593")</code>  |
|  Contextual function | ✓ yes |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

The default color to use for language blocks. Used when a language is not defined in the `languages` argument. Also note that it is only used when the `lang-format` is its `auto` or you are using it in a custom formatter. If you are using a custom formatter, it is passed to the formatter as a named argument `color` .

2.16.1. Example

| Example code | Rendered output |
|--|---|
|  <pre>1 *Default color:* 2 ```py 3 print('Hello, world!') 4 print('Hello, world!') 5 ``` 6 *Overriden default color:* 7 #codly(default-color: orange) 8 ```py 9 print('Hello, world!') 10 print('Hello, world!') 11 ```</pre> | <p>Default color:</p> <pre>1 print('Hello, world!') 2 print('Hello, world!')</pre> <p>Overriden default color:</p> <pre>1 print('Hello, world!') 2 print('Hello, world!')</pre> |

2.17. Radius (radius)






| | |
|--|---------------------|
|  Type | <code>length</code> |
| (*) Default value | <code>0.32em</code> |
|  Contextual function | ✓ yes |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

The radius of the border of the code block, see `block.radius` for more information.

2.17.1. Example

| Example code | Rendered output |
|--|---|
| <div></div> <pre>1 *Default radius:* 2 ```py 3 print('Hello, world!') 4 print('Hello, world!') 5 ``` 6 *Overriden radius:* 7 #codly(radius: 2em) 8 ```py 9 print('Hello, world!') 10 print('Hello, world!') 11 ``` 12 *Zero radius:* 13 #codly(radius: 0pt) 14 ```py 15 print('Hello, world!') 16 print('Hello, world!') 17 ```</pre> | <div>Default radius:</div> <div><pre>1 print('Hello, world!') 2 print('Hello, world!')</pre><div>py</div></div> <div>Overriden radius:</div> <div><pre>1 print('Hello, world!') 2 print('Hello, world!')</pre><div>py</div></div> <div>Zero radius:</div> <div><pre>1 print('Hello, world!') 2 print('Hello, world!')</pre><div>py</div></div> |

2.18. Inset (inset)

| | |
|--|--|
|  Type | <code>length</code> or <code>dictionary</code> |
|  Default value | <code>0.32em</code> |
|  Contextual function | ✓ yes |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

Inset of the code lines, that is the distance between the border and the code lines. It can also be a dictionary with the keys same keys as in the Typst built-in `block.inset` .






2.18.1. Example

| Example code | Rendered output |
|---|--|
|  Typst <pre>1 *Default inset:* 2 ```py 3 print('Hello, world!') 4 ``` 5 *Overriden inset:* 6 #codly(inset: 1em) 7 ```py 8 print('Hello, world!') 9 ```</pre> | Default inset: <pre>1 print('Hello, world!')</pre> Overriden inset: <pre>1 print('Hello, world!')</pre> |

2.18.2. Example: Dictionary inset


| Example code | Rendered output |
|---|--|
|  Typst <pre>1 *Default inset:* 2 ```py 3 print('Hello, world!') 4 ``` 5 *Overriden inset:* 6 #codly(inset: (x: 0.32em, y: 0.1em)) 7 ```py 8 print('Hello, world!') 9 ```</pre> | Default inset: <pre>1 print('Hello, world!')</pre> Overriden inset: <pre>1 print('Hello, world!')</pre> |

2.19. Fill (fill)






| | |
|--|--|
|  Type | <code>none</code> , <code>color</code> , <code>gradient</code> , or <code>pattern</code> |
|  Default value | <code>none</code> |
|  Contextual function | ✓ yes |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

The fill of the code block when not zebra-striped.

2.19.1. Example

| Example code | Rendered output |
|--|---|
|  <pre>1 *Default fill:* 2 ```py 3 print('Hello, world!') 4 print('Hello, world!') 5 ``` 6 *Overriden fill:* 7 #codly(fill: gradient.linear(..color.map.flare)) 8 ```py 9 print('Hello, world!') 10 print('Hello, world!') 11 ``` 12 *No fill:* 13 #codly(fill: none) 14 ```py 15 print('Hello, world!') 16 print('Hello, world!') 17 ```</pre> | <p>Default fill:</p> <pre>1 print('Hello, world!') 2 print('Hello, world!')</pre> <p>Overriden fill:</p> <pre>1 print('Hello, world!') 2 print('Hello, world!')</pre> <p>No fill:</p> <pre>1 print('Hello, world!') 2 print('Hello, world!')</pre> |

2.20. Zebra fill (zebra-fill)






| | |
|--|--|
|  Type | <code>none</code> , <code>color</code> , <code>gradient</code> , or <code>pattern</code> |
|  Default value | <code>luma(240)</code> |
|  Contextual function | ✓ yes |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

Background color of the code lines when zebra-stripped. If set to `none` , no zebra-stripping is applied.

2.20.1. Example

| Example code | Rendered output |
|--|---|
|  <pre>1 *Default zebra:* 2 ```py 3 print('Hello, world!') 4 print('Hello, world!') 5 ``` 6 *No zebra:* 7 #codly(zebra-fill: none) 8 ```py 9 print('Hello, world!') 10 print('Hello, world!') 11 ``` 12 *Overriden zebra:* 13 #codly(zebra-fill: 14 gradient.linear(..color.map.flare)) 15 ```py 16 print('Hello, world!') 17 ```</pre> | Default zebra: <pre>1 print('Hello, world!') 2 print('Hello, world!')</pre> No zebra: <pre>1 print('Hello, world!') 2 print('Hello, world!')</pre> Overriden zebra: <pre>1 print('Hello, world!')</pre> |

2.21. Stroke (stroke)






| | |
|--|---|
|  Type | <code>none</code> or <code>stroke</code> |
|  Default value | <code>1pt + luma(240)</code> <input type="text"/> |
|  Contextual function | ✓ yes |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

The stroke to surround the whole code block with?

2.21.1. Example

| Example code | Rendered output |
|---|---|
|  | |
| 1 *Default stroke: | Default stroke: |
| 2 <code>```py</code> | 1 <code>print('Hello, world!')</code>  |
| 3 <code>print('Hello, world!')</code> | |
| 4 <code>```</code> | |
| 5 *No stroke: | No stroke: |
| 6 <code>#codly(stroke: none)</code> | 1 <code>print('Hello, world!')</code>  |
| 7 <code>```py</code> | |
| 8 <code>print('Hello, world!')</code> | |
| 9 <code>```</code> | |
| 10 *Overriden stroke: | Overriden stroke: |
| 11 <code>#codly(stroke: 1pt + blue)</code> | 1 <code>print('Hello, world!')</code>  |
| 12 <code>```py</code> | |
| 13 <code>print('Hello, world!')</code> | |
| 14 <code>```</code> | |

2.22. Language box inset (lang-inset)






| | |
|--|--|
|  Type | <code>length</code> or <code>dictionary</code> |
|  Default value | <code>0.32em</code> |
|  Contextual function | ✓ yes |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

The inset of the language block. This only applies if you're using the default language block formatter. It can also be a dictionary with the keys same keys as in the Tyspt built-in `block.inset`

2.22.1. Example



| Example code | Rendered output |
|---|---|
|  | |
| 1 <code>#codly(lang-inset: 5pt)</code> | 1 <code>print('Hello, world!')</code>  |
| 2 <code>```py</code> | 2 <code>print('Goodbye, world!')</code> |
| 3 <code>print('Hello, world!')</code> | |
| 4 <code>print('Goodbye, world!')</code> | |
| 5 <code>```</code> | |

2.23. Language box outset (lang-outset)






| | |
|--|---------------------|
|  Type | dictionary |
|  Default value | (x: 0.32em, y: 0em) |
|  Contextual function | ✓ yes |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

The X and Y outset of the language block, applied as a `dx` and `dy` during the `place` operation. This applies in every case, whether or not you're using the default language block formatter. The default value is chosen to get rid of the `inset` applied to each line.

2.23.1. Example



| Example code | Rendered output |
|--|--|
|  <pre>1 #codly(lang-outset: (x: -10pt, y: 5pt)) 2 ```py 3 print('Hello, world!') 4 print('Goodbye, world!') 5 ```</pre> | <pre>1 print('Hello, world!') 2 print('Goodbye, world!')</pre>  |

2.24. Language box radius (lang-radius)





| | |
|--|--------|
|  Type | length |
|  Default value | 0.32em |
|  Contextual function | ✓ yes |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

The radius of the border of the language block.

2.24.1. Example

| Example code | Rendered output |
|--|--|
|  <pre>1 #codly(lang-radius: 10pt) 2 ```py 3 print('Hello, world!') 4 print('Goodbye, world!') 5 ```</pre> | <pre>1 print('Hello, world!') 2 print('Goodbye, world!')</pre>  |

2.25. Language box stroke (lang-stroke)





| | |
|--|--|
|  Type | <code>none</code> , <code>stroke</code> , or <code>function</code> |
| (*) Default value | <code>(lang) => lang.color + 0.5pt</code> |
|  Contextual function | ✗ no |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

The stroke of the language block. Can be a function that takes in the language `dictionary` or `none` (see argument `languages`) and returns a stroke.

2.25.1. Example

| Example code | Typst | Rendered output |
|---|-------|--|
| <pre>1 *Fixed stroke:* 2 #codly(lang-stroke: 1pt + red) 3 ```py 4 print('Hello, world!') 5 print('Goodbye, world!') 6 ``` 7 *Function mapping:* 8 #codly(lang-stroke: (lang) => 2pt + lang.color) 9 ```py 10 print('Hello, world!') 11 print('Goodbye, world!') 12 ```</pre> | | <p>Fixed stroke:</p> <pre>1 print('Hello, world!') 2 print('Goodbye, world!')</pre> <p>Function mapping:<pre>1 print('Hello, world!') 2 print('Goodbye, world!')</pre></p> |

2.26. Language box fill (lang-fill)






| | |
|--|--|
|  Type | <code>none</code> , <code>color</code> , <code>gradient</code> , <code>pattern</code> , or <code>function</code> |
| (*) Default value | <code>(lang) => lang.color.lighten(80%)</code> |
|  Contextual function | ✗ no |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

The background color of the language block. Can be a function that takes in the language `dictionary` or `none` (see argument `languages`) and returns a stroke.

2.26.1. Example

| Example code | Typst | Rendered output |
|--|-------|--|
| <pre>1 *Fixed fill:* 2 #codly(lang-fill: red) 3 ```py 4 print('Hello, world!') 5 print('Goodbye, world!') 6 ``` 7 *Function mapping:* 8 #codly(lang-fill: (lang) => lang.color.lighten(40%)) 9 ```py 10 print('Hello, world!') 11 print('Goodbye, world!') 12 ```</pre> | | <p>Fixed fill:</p> <pre>1 print('Hello, world!') 2 print('Goodbye, world!')</pre> <p>Function mapping:<pre>1 print('Hello, world!') 2 print('Goodbye, world!')</pre></p> |

2.27. Language box formatter (lang-format)

| | |
|--|--|
|  Type | <code>type(auto)</code> , <code>none</code> , or <code>function</code> |
|  Default value | <code>auto</code> |
|  Contextual function | ✗ no |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

The formatter for the language block. A value of `none` will not display the language block. To use the default formatter, set to `auto`. The function takes three arguments:

- `lang` : the language key (e.g. `py`)
- `icon` : the language icon, can be none or empty content
- `color` : the language color

The function should return a content/showable value.





Info

The language formatter should avoid using `state` as this can lead to quadratic execution time, see [typst/typst #5220](#) for more information. Internally, when set to `auto`, codly uses an inlined function to avoid using states.

2.27.1. Example



| Example code | Rendered output |
|--|--|
|  <pre>1 *Default formatter:* 2 ```py 3 print('Hello, world!') 4 ``` 5 *Function mapping:* 6 #codly(lang-format: (_, _, _) => [No!]) 7 ```py 8 print('Hello, world!') 9 ```</pre> | <p>Default formatter:</p> <pre>1 print('Hello, world!')</pre> <p>Function mapping:)</p> <pre>1 print('Hello, world!')</pre> |

2.28. Display language name (display-name)





| | |
|--|-------|
|  Type | bool |
| (*) Default value | true |
|  Contextual function | ✓ yes |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

Whether to display the name of the language in the language block. This only applies if you're using the default language block formatter.

2.28.1. Example


| Example code | Rendered output |
|--|--|
|  <pre>1 #codly(2 display-name: false, 3 languages: (4 py: (5 name: [Python], color: green, 6 icon: "🐍" 7), 8), 9) 10 ```py 11 print('Hello, world!') 12 print('Goodbye, world!') 13 ```</pre> | <pre>1 print('Hello, world!') 2 print('Goodbye, world!')</pre>  |

2.29. Display language icon (display-icon)






| | |
|--|-------|
|  Type | bool |
| (*) Default value | true |
|  Contextual function | ✓ yes |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

Whether to display the icon of the language in the language block. This only applies if you're using the default language block formatter.

2.29.1. Example

| Example code | Rendered output |
|--|--|
|  <pre>1 #codly(2 display-icon: false, 3 languages: (4 py: (5 name: [Python], color: green, 6 icon: "🐍" 7), 8), 9) 10 ```py 11 print('Hello, world!') 12 print('Goodbye, world!') 13 ```</pre> | <pre>1 print('Hello, world!') 2 print('Goodbye, world!')</pre> <div>Python</div> |

2.30. Line number format (number-format)






| | |
|--|--|
|  Type | <code>function</code> or <code>none</code> |
|  Default value | <code>numbering.with("I")</code> |
|  Contextual function | ✗ no |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

The format of the line numbers, a function that takes in number and returns a content. If set to none, disables line numbers.

2.30.1. Example

| Example code | Typst | Rendered output |
|--|-------|---|
| <pre>1 #codly(number-format: numbering.with("I.")) 2 ```py 3 print('Hello, world!') 4 print('Goodbye, world!') 5 ```</pre> | | <pre>I. print('Hello, world!') II. print('Goodbye, world!')</pre> |

2.31. Line number alignment (number-align)





| | |
|--|-----------------------------|
|  Type | <code>alignment</code> |
|  Default value | <code>left + horizon</code> |
|  Contextual function | ✓ yes |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

The alignment of the numbers.

2.31.1. Example


| Example code | Typst | Rendered output |
|---|-------|--|
| <pre>1 #codly(number-align: right + top) 2 ```py 3 # Iterative Fibonacci 4 # As opposed to the recursive 5 # version 6 def fib(n): 7 if n <= 1: 8 return n 9 last, current = 0, 1 10 for _ in range(2, n + 1): 11 last, current = current, last + current 12 return current 13 fib(25) 14 ```</pre> | | <pre>1 # Iterative Fibonacci 2 # As opposed to the recursive 3 # version 4 def fib(n): 5 if n <= 1: 6 return n 7 last, current = 0, 1 8 for _ in range(2, n + 1): 9 last, current = current, last + current 10 return current 11 fib(25)</pre> |

2.32. Line number placement (number-placement)






| | |
|--|----------|
|  Type | str |
| (*) Default value | "inside" |
|  Contextual function | ✗ no |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✗ no |

Sets the placement of the numbers, either `"inside"` (the default) or `"outside"` of the code block.

2.32.1. Example


| Example code | Rendered output |
|--|--|
|  <pre>1 *Line number outside of the block:* 2 #codly(number-placement: "outside") 3 ```py 4 print('Hello, world!') 5 print('Goodbye, world!') 6 ``` 7 *Line number inside of the block:* 8 #codly(number-placement: "inside") 9 ```py 10 print('Hello, world!') 11 print('Goodbye, world!') 12 ```</pre> | <p>Line number outside of the block:</p> <pre>1 print('Hello, world!') 2 print('Goodbye, world!')</pre> <p>Line number inside of the block:</p> <pre>1 print('Hello, world!') 2 print('Goodbye, world!')</pre> |

2.33. Smart indentation (smart-indent)






| | |
|--|-------|
|  Type | bool |
|  Default value | true |
|  Contextual function | ✗ no |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

Whether to use smart indentation, which will check for indentation on a line and use a bigger left side inset instead of spaces. This allows for linebreaks to continue at the same level of indentation. This is on by default, but disabling it can improve performance.

2.33.1. Example

| Example code | Rendered output |
|--|--|
|  | |
| <pre>1 *Enabled (default):* 2 ```py 3 def quicksort(L): 4 qsort = lambda L: [] if L==[] else qsort([x for x in L[1:] if x< L[0]]) + L[0:1] + qsort([x for x in L[1:] if 6 x>=L[0]]) 7 qsort(L) 8 ``` 9 *Disabled:* 10 #codly(smart-indent: false) 11 ```py 12 def quicksort(L): 13 qsort = lambda L: [] if L==[] else qsort([x for x in L[1:] if x< L[0]]) + L[0:1] + qsort([x for x in L[1:] if 15 x>=L[0]]) 16 qsort(L) 17 ```</pre> | <p>Enabled (default):</p> <pre>1 def quicksort(L): qsort = lambda L: [] if L==[] else 2 qsort([x for x in L[1:] if x< L[0]]) + L[0:1] + qsort([x for x in L[1:] if 3 x>=L[0]]) qsort(L)</pre> <p>Disabled:</p> <pre>1 def quicksort(L): qsort = lambda L: [] if L==[] else 2 qsort([x for x in L[1:] if x< L[0]]) + L[0:1] + qsort([x for x in L[1:] if 3 x>=L[0]]) qsort(L)</pre> |

2.34. Skip last line if empty (skip-last-empty)






| | |
|--|-------|
|  Type | bool |
|  Default value | true |
|  Contextual function | ✓ yes |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

Whether to automatically skip the last line of the code block if it is empty. This avoids having an unnecessary empty line at the end of the code block.

2.34.1. Example






| Example code | Typst | Rendered output |
|--|-------|--|
| <pre>1 *Enabled (default):* 2 ```py 3 def fib(n): 4 if n <= 1: 5 return n 6 return fib(n - 1) + fib(n - 2) 7 8 ``` 9 *Disabled:* 10 #codly(skip-last-empty: false) 11 ```py 12 def fib(n): 13 if n <= 1: 14 return n 15 return fib(n - 1) + fib(n - 2) 16 17 ```</pre> | | <p>Enabled (default):</p> <pre>1 def fib(n): 2 if n <= 1: 3 return n 4 return fib(n - 1) + fib(n - 2)</pre> <p>Disabled:</p> <pre>1 def fib(n): 2 if n <= 1: 3 return n 4 return fib(n - 1) + fib(n - 2) 5</pre> |

2.35. Breakable (breakable)

| | |
|--|-------|
|  Type | bool |
|  Default value | true |
|  Contextual function | ✗ no |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |



Whether the codeblocks are breakable across page and column breaks.

2.36. Skips (skips)






| | |
|--|---|
|  Type | <code>array</code> or <code>none</code> |
|  Default value | <code>none</code> |
|  Contextual function | ✓ yes |
|  Automatically reset | ✓ yes |
|  Already released in 1.2.0 | ✓ yes |

Insert a skip at the specified line numbers, setting its offset to the length of the skip. The skip is formatted using the `skip-number` argument. Each skip is an array with two values: the line where the skip is inserted (zero indexed) and the number of lines of the skip. The same behavior can be achieved using the `codly-skip` function.

2.36.1. Example



| Example code | Rendered output |
|---|--|
|  <pre>1 #codly(skips: ((4, 32),)) 2 ```py 3 def fib(n): 4 if n <= 1: 5 return n 6 return fib(n - 1) + fib(n - 2) 7 fib(25) 8 ```</pre> |  <pre>1 def fib(n): 2 if n <= 1: 3 return n ... 36 return fib(n - 1) + fib(n - 2) 37 fib(25)</pre> |

2.37. Skip line (skip-line)






| | |
|--|---|
|  Type | <code>content</code> or <code>none</code> |
|  Default value | <code>align(center)[...]</code> |
|  Contextual function | ✓ yes |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

Sets the content with which the line code is filled when a skip is encountered.

2.37.1. Example



| Example code | Rendered output |
|---|--|
|  <pre>1 #codly(2 skips: ((4, 32),), 3 skip-line: align(center, 4 emoji.face.shock) 5) 6 ```py 7 def fib(n): 8 if n <= 1: 9 return n 10 return fib(n - 1) + fib(n - 2) 11 fib(25) 12 ```</pre> |  <pre>1 def fib(n): 2 if n <= 1: 3 return n ... 36 return fib(n - 1) + fib(n - 2) 37 fib(25)</pre> |

2.38. Skip number (skip-number)





| | |
|--|---|
|  Type | <code>content</code> or <code>none</code> |
|  Default value | <code>[...]</code> |
|  Contextual function | ✓ yes |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

Sets the content with which the line number columns is filled when a skip is encountered. If line numbers are disabled, this has no effect.

2.38.1. Example

| Example code | Rendered output |
|--|--|
|  <pre>1 #codly(2 skips: ((4, 32),), 3 skip-number: align(center, 4 emoji.face.shock) 5) 6 ```py 7 def fib(n): 8 if n <= 1: 9 return n 10 return fib(n - 1) + fib(n - 2) 11 fib(25) 12 ```</pre> |  <pre>1 def fib(n): 2 if n <= 1: 3 return n 4 5 ... 36 return fib(n - 1) + fib(n - 2) 37 fib(25)</pre> |

2.39. Annotations (annotations)

| | |
|--|---|
|  Type | <code>array</code> or <code>none</code> |
| (*) Default value | <code>none</code> |
|  Contextual function | ✓ yes |
|  Automatically reset | ✓ yes |
|  Already released in 1.2.0 | ✓ yes |

The annotations to display on the code block. A list of annotations that are automatically numbered and displayed on the right side of the code block.

Each entry is a dictionary with the following keys:

- `start` : the line number to start the annotation
- `end` : the line number to end the annotation, if missing or `none` the annotation will only contain the start line
 - ▶ `content` : the content of the annotation as a showable value, if missing or `none` the annotation will only contain the number
 - ▶ `label` : **if and only if** the code block is in a `figure`, sets the label by which the annotation can be referenced.

Generally you probably want the `content` to be contained within a `rotate(90deg)` .

Note: Annotations cannot overlap. **Known issues:**

- Annotations that spread over a page break will not work correctly
- Annotations on the first line of a code block will not work correctly.
- Annotations that span lines that overflow (one line of code two lines of text) will not work correctly.


Info

Line numbers are one-indexed, meaning that to reference the fourth line, you use the number `4` .






Experiment

This feature should be considered experimental. Please report any issues you encounter on GitHub: <https://github.com/Dherse/codly>.

2.39.1. Example






| Example code | Rendered output |
|--|---|
| <pre>1 #codly(2 annotations: (3 (4 start: 2, end: 5, 5 content: block(6 width: 2em, 7 rotate(-90deg, reflow: true, 8 align(center)[Function body]) 9) 10), 11), 12) 13 ```py 14 def fib(n): 15 if n <= 1: 16 return n 17 else: 18 return fib(n - 1) + fib(n - 2) 19 fib(25) 20 ```</pre> | <pre>1 def fib(n): 2 if n <= 1: 3 return n 4 else: 5 return fib(n - 1) + fib(n - 2) 6 fib(25)</pre> <div> } (1) Function body</div> |

2.40. Annotation formatter (`annotation-format`)

| | |
|--|--|
|  Type | <code>none</code> or <code>function</code> |
|  Default value | <code>numbering.with("(1)")</code> |
|  Contextual function | ✗ no |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

The format of the annotation number. Can be `none` or a function that formats the annotation number.

2.41. Highlight lines (highlighted-lines)

| | |
|--|---|
|  Type | <code>array</code> or <code>none</code> |
|  Default value | <code>()</code> |
|  Contextual function | ✓ yes |
|  Automatically reset | ✓ yes |
|  Already released in 1.2.0 | ✗ no |

Changes the background fill of certain lines to give them the appearance of being highlighted. This is done by specifying an array of a combination of:


- **line numbers:** the line number (one-indexed) as it is shown in the document (including offsets, skips, etc.)
- **array of line number & fill:** an array of strictly two elements containing the line number (same as before) and a color, gradient, or pattern fill.

The default highlighting color is controlled by the `highlighted-default-color` argument.







Info

Line numbers are one-indexed, meaning that to reference the fourth line, you use the number `4`.

2.41.1. Example


| Example code | Rendered output |
|---|--|
|  | |
| <pre>1 *Using default highlight color:* 2 #codly(3 highlighted-lines: (1, 3) 4) 5 ```py 6 def fib(n): 7 if n <= 1: 8 return n 9 else: 10 return fib(n - 1) + fib(n - 2) 11 fib(25) 12 ``` 13 *Per-line color selection:* 14 #codly(15 highlighted-lines: ((1, 16 red.lighten(60%)), 2, 3) 17)```py 18 def fib(n): 19 if n <= 1: 20 return n 21 else: 22 return fib(n - 1) + fib(n - 2) 23 fib(25) 24 ```</pre> | <p>Using default highlight color:</p> <pre>1 def fib(n): 2 if n <= 1: 3 return n 4 else: 5 return fib(n - 1) + fib(n - 2) 6 fib(25)</pre> <p>Per-line color selection:</p> <pre>1 def fib(n): 2 if n <= 1: 3 return n 4 else: 5 return fib(n - 1) + fib(n - 2) 6 fib(25)</pre> |

2.42. Highlight lines default color (highlighted-default-color)






| | |
|--|---|
|  Type | color , pattern , or gradient |
|  Default value | orange.lighten(60%)  |
|  Contextual function | ✓ yes |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✗ no |

Changes the default color of highlighted lines.

2.42.1. Example

| Example code  | Rendered output |
|---|--|
| <pre>1 *Using default highlight color:* 2 #codly(3 highlighted-default-color: 4 green.lighten(60%), 5 highlighted-lines: (1, 3) 6) 7 ```py 8 def fib(n): 9 if n <= 1: 10 return n 11 else: 12 return fib(n - 1) + fib(n - 2) 13 fib(25) 14 *Per-line color selection still works:* 15 #codly(16 highlighted-lines: ((1, 17 red.lighten(60%)), 2, 3) 18)```py 19 def fib(n): 20 if n <= 1: 21 return n 22 else: 23 return fib(n - 1) + fib(n - 2) 24 fib(25)</pre> | <p>Using default highlight color:</p> <pre>1 def fib(n): 2 if n <= 1: 3 return n 4 else: 5 return fib(n - 1) + fib(n - 2) 6 fib(25)</pre> <p>Per-line color selection still works:</p> <pre>1 def fib(n): 2 if n <= 1: 3 return n 4 else: 5 return fib(n - 1) + fib(n - 2) 6 fib(25)</pre> |

2.43. Highlights (highlights)

| | |
|--|---------------|
|  Type | array or none |
|  Default value | none |
|  Contextual function | ✓ yes |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✓ yes |

You can apply highlights to the code block using the `highlights` argument. It consists of a list of dictionaries, each with the following keys:

- `line` : the line number to start highlighting
- `start` : the character position to start highlighting, zero if omitted or `none`
- `end` : the character position to end highlighting, the end of the line if omitted or `none`
- `fill` : the fill of the highlight, defaults to the default color
- `tag` : an optional tag to be displayed alongside the highlight.
- `label` : **if and only if** the code block is in a `figure`, sets the label by which the highlight can be referenced.

As with other code block settings, annotations are reset after each code block.



Info

Line numbers are one-indexed, meaning that to reference the fourth line, you use the number `4`.






Info

Character positions are zero-indexed, meaning that to reference the fourth character, you use the number `3`.

2.43.1. Example

| Example code | Rendered output |
|---|---|
|  <pre>1 #codly(highlights: (2 (line: 4, start: 2, end: none, fill: 3 red), 4 (line: 5, start: 13, end: 19, fill: 5 green, tag: "(a)"), 6 (line: 5, start: 26, fill: blue, tag: 7 "(b)"), 8)) 9 ```py 10 def fib(n): 11 if n <= 1: 12 return n 13 else: 14 return fib(n - 1) + fib(n - 2) 15 print(fib(25)) 16 ```</pre> |  <pre>1 def fib(n): 2 if n <= 1: 3 return n 4 else: 5 return fib(n - 1) (a) + fib(n - 2) (b) 6 print(fib(25))</pre> |

2.44. Highlight radius (highlight-radius)

| | |
|--|--------|
|  Type | length |
|  Default value | 0.32em |
|  Contextual function | ✓ yes |
|  Automatically reset | ✓ yes |
|  Already released in 1.2.0 | ✓ yes |

The radius of the highlights.

2.45. Highlight fill (highlight-fill)

| | |
|-----------------------------|-------------------------------|
| </> Type | function |
| (*) Default value | (color) => color.lighten(80%) |
| ⚙ Contextual function | ✗ no |
| 🔄 Automatically reset | ✗ no |
| 🧪 Already released in 1.2.0 | ✓ yes |

The fill transformer of the highlights, is a function that takes in the highlight color and returns a fill.

2.46. Highlight stroke (highlight-stroke)

| | |
|-----------------------------|--------------------------|
| </> Type | stroke or function |
| (*) Default value | (color) => 0.5pt + color |
| ⚙ Contextual function | ✗ no |
| 🔄 Automatically reset | ✗ no |
| 🧪 Already released in 1.2.0 | ✓ yes |

The stroke transformer of the highlights, is a function that takes in the highlight color and returns a stroke.

2.47. Highlight inset (highlight-inset)

| | |
|-----------------------------|----------------------|
| </> Type | length or dictionary |
| (*) Default value | 0.32em |
| ⚙ Contextual function | ✓ yes |
| 🔄 Automatically reset | ✗ no |
| 🧪 Already released in 1.2.0 | ✓ yes |

The inset of the highlight blocks. It can also be a dictionary with the keys same keys as in the Typst built-in `block.inset`.

2.47.1. Example: Alignment of lines

If alignment between highlighted and non-highlighted lines is critical for your use case, as could be the case in presentation, you can set the horizontal inset to be zero, or close to zero, to maintain alignment between the lines.

| Example code | Rendered output |
|--|--|
| <pre>1 #codly(2 highlight-inset: (x: 0pt, y: 0.32em), 3 highlights: ((line: 2, start: 0),) 4) 5 ```kotlin 6 private val n = 0 7 private val n = 0 8 ```</pre> | <pre>1 private val n = 0 2 private val n = 0</pre> <div>kotlin</div> |

2.48. Highlight outset (`highlight-outset`)

| | |
|-----------------------------|--|
| </> Type | <code>length</code> or <code>dictionary</code> |
| (*) Default value | <code>0em</code> |
| ⚙ Contextual function | ✓ yes |
| 🔄 Automatically reset | ✗ no |
| 🧪 Already released in 1.2.0 | ✓ yes |

The outset of the highlight blocks. It can also be a dictionary with the keys same keys as in the Tyspt built-in `block.outset`.

2.49. Highlight clip (`highlight-clip`)

| | |
|-----------------------------|-------------------|
| </> Type | <code>bool</code> |
| (*) Default value | <code>true</code> |
| ⚙ Contextual function | ✓ yes |
| 🔄 Automatically reset | ✗ no |
| 🧪 Already released in 1.2.0 | ✓ yes |

Whether highlight box clips code. See the documentation of the Tyspt built-in `block.clip`.

2.50. Reference by (`reference-by`)

| | |
|-----------------------------|---------------------|
| </> Type | <code>str</code> |
| (*) Default value | <code>"line"</code> |
| ⚙ Contextual function | ✓ yes |
| 🔄 Automatically reset | ✗ no |
| 🧪 Already released in 1.2.0 | ✓ yes |

The mode by which references are displayed. Two modes are available:

- `line` : references are displayed as line numbers
- `item` : references are displayed as items, i.e by the `tag` for highlights and `content` for annotations.

2.51. Reference separator (`reference-sep`)

| | |
|-----------------------------|--|
| </> Type | <code>str</code> or <code>content</code> |
| (*) Default value | <code>"_ "</code> |
| ⚙ Contextual function | ✓ yes |
| 🔄 Automatically reset | ✗ no |
| 🧪 Already released in 1.2.0 | ✓ yes |






The separator to use when referencing highlights and annotations.

2.52. Reference number format (`reference-number-format`)

| | |
|-----------------------------|----------------------------------|
| </> Type | <code>function</code> |
| (*) Default value | <code>numbering.with("1")</code> |
| ⚙ Contextual function | ✗ no |
| 🔄 Automatically reset | ✗ no |
| 🧪 Already released in 1.2.0 | ✓ yes |



The format of the reference number line number, only used if `reference-by` is set to `"line"`.

2.53. Language name aliases (aliases)

| | |
|--|------------|
|  Type | dictionary |
|  Default value | (:) |
|  Contextual function | ✗ no |
|  Automatically reset | ✗ no |
|  Already released in 1.2.0 | ✗ no |

Creates aliases between languages, allowing them to have separate `languages` but the same syntax highlighting. An example of that could be `cuda` and `c++` having the same highlighting but different icons.

2.53.1. Example

| Example code  | Rendered output |
|--|--|
| <pre>1 #import "@preview/codly-languages:0.1.7": * 2 3 #codly(4 languages: codly-languages, 5 aliases: ("cuda": "c++") 6) 7 ```cuda 8 int main() { 9 std::cout << "Hello, World!" << 10 std::endl; 11 return 0; 12 }</pre> | <pre>1 int main() { 2 std::cout << "Hello, World!" << std::endl; 3 return 0; 4 }</pre>  |

3. Referencing code blocks, highlights, and annotations

This section of the documentation will detail how you can use codly to reference: lines, highlights, and annotations in your code blocks. To do this, here are the requirements that must be met **for each code block**:

- Numbering of figures must be turned on: `set figure(numbering: ...)`.
- The code block must be contained within a raw figure: `figure(kind: raw)`.
- The figure must have a label of its own: `figure(...)[...] <my-label>`.

3.1. Shorthand line references

You can reference lines directly, if you have set a label correctly, using the shorthand syntax `@my-label:2` to reference the second line (one-indexed) of the code block with the label `<my-label>`. It will always use the `reference-number-format` argument of the `codly` function to format the line number.


Info

Line numbers are one-indexed, meaning that to reference the fourth line, you use the number `4`.

Experiment

Due to upcoming changes to v0.13 of Typst, this entire feature has been re-done to be more robust, but that means that the styling might have changed slightly and it might have introduced new issues. If you find any issues, report them on <https://github.com/Dherse/codly>.

Example code

 Typst

```
1 #figure(  
2   caption: "A code block with a label"  
3 ) [  
...  
8 ] <my-label>  
9 I can reference my code block: @my-label. Or  
  a specific line: @my-label:2.
```

Rendered output

 typ

1 = Example

2 *Hello, world!*

Listing 1: A code block with a label


I can reference my code block: Listing 1. Or a specific line: Listing 1-2.

3.2. Highlight references

You can also highlight by reference, to do this, you need to set a label for your highlight in the `highlights` argument of the `codly` function. You can then reference the highlight using the shorthand syntax `@my-highlight` to reference the highlight with the label `<my-highlight>`. There are two supported `reference-by` modes:

- `"line"`: references the line of the highlight
- `"item"`: references the tag of the highlight, this requires that the `tag` be set **for each tagged highlight**.

Example code

 Typst

```
1 #codly(  
2   highlights: ((line: 2, start: 2, end: 7,  
3     label: <hl-1>),  
...  
13 Reference a highlight by its label: @hl-1.
```

Rendered output

 typ

1 = Example


2 *Hello, world!*

Listing 2: A code block with a label

Reference a highlight by its label: Listing 2-2.

And using `"item"` mode:

Example code

 Typst

```
1 #codly(  
2   highlights: ((line: 2, start: 2, end: 7,  
3     label: <hl-2>, tag: [ Highlight ]), ),  
4   reference-by: "item",  
...  
14 Reference a highlight by its label: @hl-2.
```

Rendered output

 typ

1 = Example

2 *Hello, world! Highlight*

Listing 3: A code block with a label

Reference a highlight by its label: Listing 3-Highlight.

4. Getting nice icons

This is a short, non-exhaustive guide on how to get nicer icons for the languages of your code blocks. In the documentation, codly makes use of `tabler-icons` to display the language icons. But a more general approach is the following:

1. Chose a font that contains icons, such as:
 - [Tabler Icons](#)
 - [Font Awesome](#)
 - [Material Icons](#)
 - Look on [Google Fonts](#) for more options
2. Download the font and put it in your project (if using the CLI, you need to set the `--font` argument)
3. Using your font selector, select the icon you wish to use
 - For example, the language icon in Tabler Icons is `ebbe` (the unicode value of the icon, which you can find in the documentation of the font)
 - Use the `text` function to display the icon in your document by setting the font, size, and the unicode value of the icon:

```
1 text(font: "tabler-icons" Font name, size: 1em, "\u{ebbe} UTF-8 icon code}") Typst code
```

4. You can store it the `languages` argument of the `codly` function to use it for all code blocks in your document:

| Example code | Rendered output |
|---|--|
| <pre>1 #let icon = text(font: "tabler-icons", 2 size: 1em, "\u{ebbe}") 3 #codly(languages: (text: (icon: icon, name: 4 "Text"))) 5 ``text 6 Hello, world! 7 ```</pre> | <pre>1 Hello, world!</pre> Text |

5. Congrats, you now have fancy icons!
6. ...
7. But you can notice that the baseline of the icon is wrong, I find that this is generally the case with tabler, you can set the baseline to `0.1em` in the icon to fix it:

| Example code | Rendered output |
|--|--|
| <pre>1 #let icon = text(font: "tabler-icons", 2 size: 1em, "\u{ebbe}", baseline: 0.1em) 3 #codly(languages: (text: (icon: icon, name: 4 "Text"))) 5 ``text 6 Hello, world! 7 ```</pre> | <pre>1 Hello, world!</pre> Text |

4.1. Typst language icon (`typst-icon`)

Additionally, codly ships with language definitions for the Typst language. You can use the `typst-icon` function to get the Typst icon for your code blocks. This function takes no arguments and returns the proper settings for codly to use the Typst icon.

i Info

You can use the `..` spread operator to spread it into your own `languages` dictionary.

| Example code | Rendered output |
|---|--|
| <pre>1 #codly(languages: typst-icon) 2 ``typ 3 = Here's a title 4 Hello, world! 5 ```</pre> | <pre>1 = Here's a title 2 Hello, world!</pre> Typst |

5. Other functions

5.1. Skip (`codly-skip`)

Convenience function for setting the skips, see the `skips` argument of the `codly` function.

5.2. Range (`codly-range`)

Convenience function for setting the range, see the `range` argument of the `codly` function. If you provide more than one range, as a list of arguments, it will set the `ranges` argument instead.

With a single range:

| Example code | Rendered output |
|--|--------------------------------|
| <pre>1 #codly-range(2, end: 2) 2 ```py 3 def fib(n): 4 if n <= 1: 5 return n 6 return fib(n - 1) + fib(n - 2) 7 fib(25) 8 ```</pre> | <pre>2 if n <= 1:</pre> |

With more than one range:

| Example code | Rendered output |
|--|---|
| <pre>1 #codly-range(2, end: 2, (4, 5)) 2 ```py 3 def fib(n): 4 if n <= 1: 5 return n 6 return fib(n - 1) + fib(n - 2) 7 fib(25) 8 ```</pre> | <pre>2 if n <= 1: 4 return fib(n - 1) + fib(n - 2) 5 fib(25)</pre> |

5.3. Offset (`codly-offset`)

Convenience function for setting the offset, see the `offset` argument of the `codly` function.

5.4. Local (local)

Codly provides a convenience function called `local` that allows you to locally override the global settings for a specific code block. This is useful when you want to apply a specific style to a code block without affecting the rest of the code blocks in your document. It works by overriding the default codly show rule locally with an override of the arguments by those you provide. It does not rely on states (much) and should no longer add layout passes to the rendering which could cause documents to not converge.

Warning

When using `nested: false` on your local states, the outermost local state will be overridden by the inner local state(s). This means that the inner local state will be the only one that is applied to the code block. And that any previous local states (in the same hierarchy) will be ignored for subsequent code blocks.

Info

Once custom elements become available in Typst, and codly moves to using those and set rules, this limitation will be lifted and you will be able to use nested local states without performance impact.

| Example code | Rendered output |
|---|--|
| <pre>1 *Global state with red color* 2 #codly(fill: red) 3 ```typ 4 = Example 5 *Hello, World!* 6 ``` 7 *Locally set it to gray* 8 #local(9 fill: luma(240), 10 ```typ 11 = Example 12 *Hello, World!* 13 ``` 14) 15 * It's back to being red* 16 ```typ 17 = Example 18 *Hello, World!* 19 ```</pre> | <p>Global state with red color</p> <pre>1 = Example 2 *Hello, World!*</pre> <p>Locally set it to gray</p> <pre>1 = Example 2 *Hello, World!*</pre> <p>It's back to being red</p> <pre>1 = Example 2 *Hello, World!*</pre> |

5.4.1. Local state for per-language configuration

Additionally, local settings can be used to set per-language configuration using a show rule on your `raw` blocks. This can be done in one of two ways: by using a show rule on `raw.where(block: true, lang: "<lang>")` and calling the `local` function, or by using the `codly` function. The main differentiators are that the `local` function is faster and does not rely on states, while the `codly` function is more flexible, but slower and **will also style all following blocks**, you must therefore manually reset the changes.

Experiment

This should work in most cases, but this feature should be considered experimental. Please report any issues you encounter on GitHub: <https://github.com/Dherse/codly>.


Info

Note that you only want to do show rules on `raw` blocks where `block: true`, otherwise this will make your document slow.

Warning

If you use the `local` function in a show rule, nested `local` states **will not work** with the settings you have set! Use the `codly` method instead. If using the `codly` method, and you **must** manually reset the changed settings in the show rule!

Example code

 Typst

```
1 #show raw.where(block: true, lang: "rust"):
2   local.with(
3     number-format: numbering.with("I")
4   )
5
6 #show raw.where(block: true, lang: "py"):
7   it => {
8     codly(number-format: numbering.with("①"))
9     it
10    codly(number-format: numbering.with("1"))
11  }
12
13 *Numbered with Roman numerals*
14 ```rust
15 fn main() {
16   println!("Rust code has Roman numbers");
17 }
18
19 *Numbered with circled numbers*
20 ```py
21 print("Python code has circled numbers")
22
23 *Override with local state*
24 #local(
25   fill: blue.lighten(80%),
26   ```py
27   print("Python code is green")
28   ```
29 )
```

Rendered output

Numbered with Roman numerals

```
I   fn main() {
II  println!("Rust code has Roman numbers");
III }
```

Numbered with circled numbers

```
① print("Python code has circled numbers")
```

Override with local state

```
1 print("Python code is green")
```

5.4.2. Nested local state

Codly does support nested local state, the innermost local state will override the outermost local state. This allows you to have different styles for different parts of your code block. This function takes the same arguments as the `codly` function, but only the arguments that are different from the global settings need to be provided.

⚠ Warning

Nested local states can slow down documents significantly if over-used (explicitly set `nested: true`). Use them sparingly and only when necessary. Another solution is to use the normal `codly` function before and after your code block. You can also use the the argument `nested: false` on `local` to prevent nested local states, which significantly reduces the performance impact.

| Example code | Rendered output |
|---|---|
| <pre>1 *Global state with red color* 2 #codly(fill: red) 3 ```typ 4 = Example 5 *Hello, World!* 6 ``` 7 *Locally set it to blue* 8 #local(9 nested: true, 10 fill: blue, 11){ 12 ```typ 13 = Example 14 *Hello, World!* 15 ``` 16 *Now it's green:* 17 #local(nested: true, fill: green)[18 ```typ 19 = Example 20 *Hello, World!* 21 ``` 22] 23 *Now its zebras are also blue:* 24 #local(nested: true, zebra-fill: blue)[25 ```typ 26 = Example 27 *Hello, World!* 28 ``` 29] 30 31 *Back to blue:* 32 ```typ 33 = Example 34 *Hello, World!* 35 ``` 36] 37 *Back to red:* 38 ```typ 39 = Example 40 *Hello, World!* 41 ```</pre> | <p>Global state with red color</p> <pre>1 = Example 2 *Hello, World!*</pre> <p>Locally set it to blue</p> <pre>1 = Example 2 *Hello, World!*</pre> <p>Now it's green:</p> <pre>1 = Example 2 *Hello, World!*</pre> <p>Now its zebras are also blue:</p> <pre>1 = Example 2 *Hello, World!*</pre> <p>Back to blue:</p> <pre>1 = Example 2 *Hello, World!*</pre> <p>Back to red:</p> <pre>1 = Example 2 *Hello, World!*</pre> |

5.5. No Codly (no-codly)

This is a convenience function equivalent to `local(enabled: false, body)` .

| Example code | Rendered output |
|---|--|
| <pre>1 *Enabled codly* 2 ```typ 3 = Example 4 *Hello, World!* 5 ``` 6 7 *Disabled codly* 8 #no-codly[9 ```typ 10 = Example 11 *Hello, World!* 12 ``` 13]</pre> | <div>Enabled codly</div> <div>1 = Example typ</div> <div>2 *Hello, World!*</div> <div>Disabled codly</div> <div>= Example</div> <div>*Hello, World!*</div> |

5.6. Yes Codly (yes-codly)

This is a convenience function equivalent to `local(enabled: false, body)` .

| Example code | Rendered output |
|---|--|
| <pre>1 *Disabled codly* 2 #codly(enabled: false) 3 ```typ 4 = Example 5 *Hello, World!* 6 ``` 7 8 *Enabled codly* 9 #yes-codly[10 ```typ 11 = Example 12 *Hello, World!* 13 ``` 14]</pre> | <div>Disabled codly</div> <div>= Example</div> <div>*Hello, World!*</div> <div>Enabled codly</div> <div>1 = Example typ</div> <div>2 *Hello, World!*</div> |

5.7. Enable (codly-enable)

Enables codly globally, equivalent to `codly(enabled: true)` .

| Example code | Rendered output |
|---|--|
| <pre>1 *Disabled codly* 2 #codly-disable() 3 ```typ 4 = Example 5 *Hello, World!* 6 ``` 7 #codly-enable() 8 *Enabled codly* 9 ```typ 10 = Example 11 *Hello, World!* 12 ```</pre> | <div>Disabled codly</div> <div>= Example</div> <div>*Hello, World!*</div> <div>Enabled codly</div> <div>1 = Example typ</div> <div>2 *Hello, World!*</div> |

5.8. Disable (codly-disable)

Disables codly globally, equivalent to `codly(enabled: false)` .

| Example code | Rendered output |
|---|--|
| <pre> 1 *Enabled codly* 2 ```typ 3 = Example 4 *Hello, World!* 5 ``` 6 7 *Disabled codly* 8 #codly-disable() 9 ```typ 10 = Example 11 *Hello, World!* 12 ``` </pre> | <div> Enabled codly <pre> 1 = <u>Example</u> 2 *Hello, World!* </pre> </div> <div> Disabled codly <pre> = <u>Example</u> *Hello, World!* </pre> </div> |

5.9. Reset (codly-reset)

Resets all codly settings to their default values. This is useful when you want to reset the settings of a code block to the default values after applying local settings.

| Example code | Rendered output |
|---|--|
| <pre>1 *Global state with red color* 2 #codly(fill: red) 3 ```typ 4 = Example 5 *Hello, World!* 6 ``` 7 *Reset it* 8 #codly-reset() 9 ```typ 10 = Example 11 *Hello, World!* 12 ```</pre> | <p>Global state with red color</p> <pre>1 = Example 2 *Hello, World!*</pre> <p>Reset it</p> <pre>1 = Example 2 *Hello, World!*</pre> |

6. Codly performance