HTML List :

HTML <ul> Tag.

The <ul> tag defines an unordered (bulleted) list. use the <ul> tag together with the <li> tag to create unordered list.

Example:

```
<ul>
    <li> Hi </li>
    <li> Hello </li>
    <li> Bye </li>
</ul>
```

We can use the Style attribute to change the bullet size.

like -   Circle
            disc
            square.

ex: <ul Style="list-style-type: circle">

HTML <ol> Tag.

The <ol> tag defines an ordered list. An Ordered list can be numerical or alphabetical.

The <li> tag is used to define each list item.

attribute:	value	Desc.
reversed	reversed	specifies that the list order should be reversed (9, 8, 7, 6, 5, 4, 3 ...)
start	number	specifies the start value of an ordered list.
type	1 A a I i	Specifies the kind of marker to use in the list.

ex:-

```
<ol type = 1>

    <li> Hi </li>
    <li> Bye </li>
    <li> goodbye </li>

</ol>
```

HTML <li> Tag.

The <li> tag defines a list item.

The <li> tag is used inside ordered lists(<ol>, unordered list <ul> and in menu lists (menu)

Attribute	Value	Desc.
value	number	only for Lists. Specifies the start value of a list item. The following list item will increment from that number.

ex:-   `<li value = "100"> Coffee </li>`

HTML <dl> Tag.

The <dl> tag defines a description list.

The <dl> tag is used in conjunction with <dt> (defines terms/name) and <dd> (describe each term/name).

ex:

```
<dl>
    <dt> Coffee </dt>
    <dd> Black hot drink</dd>
    <dt> Milk </dt>
    <dd> white cold drink </dd>
</dl>
```

HTML <dt> Tag.

The <dt> tag defines a term/name in a description list.

The <dt> tag is used in conjunction with <dl> (defines a description list).

ex :-
```
<dl>
      <dt> Coffee </dt>
      <dd> Black hot drinks </dd>
</dl>
```

HTML <dd> Tag.

The <dd> Tag is used to describe a term/name in description list.

The <dd> tag is used in conjunction with <dl> (defines a description list) and <dt> (defines terms/names).

Inside a <dd> tag you can put paragraph, line break, images, links, lists etc.