

NAME : Dhinesh Kumar R

BATCH : 12-2 Frontend

EID : EID-26-007265

DATE : 29/08/26

HTML Test

29/08/26

①

HTML

HTML Stands for Hypertext Markup Language. HTML is used to structure the unstructured informations like in webpage using → Heading, title, Paragraph, Images, etc.

The word Hyper means it connects one to another. The word text means the content and Markup means using tag to structure the content. Language is a rules and syntax used to communicate with humans and systems.

②

HTML is not a Programming Language. It is called Markup Language. Because it uses tags to structure the content in a web page.

③

TAG

Predefined

HTML tag is a keyword enclosed with a angular bracket. It has two types One is closing tag and other is self-closing tag or void element

ELEMENTS

HTML elements contain a opening tag, closing tag and a content between the opening and closing tag.

④

<!DOCTYPE html>

It is not a html Tag.

It is used for declaration of document type.

<!DOCTYPE html> It tells the browser that it was a HTML5 document.

Otherwise the browser runs it in

Old browser and HTML5 features

may not work.

⑤

Basic structure of html document.

```
<!DOCTYPE html>
<html lang="en">
  <html>
  <head>
    <meta charset="UTF-8">
    <meta viewport="System width">
    <meta property="og:title"; content="Structure">
    <title> Structure </title>
  </head>
  <body>
    <Section>
      <Section>
        <h1> Basic Structure </h1>
        <p> This is Structure </p>
      </Section>
    </Section>
  </body>
</html>
```

Purpose :-

<html> → It is the root element of html document, every document should start with <html> and end with </html>

<head> → This contains the element for the webpage or browser understanding.

<body> → This contains the content displayed in webpage.

⑥

HTML attributes

HTML attributes are used to add additional information to a webpage. Every attribute should have a value.

Example : `<img src = "value">`

Here `<img>` is a tag and `src` is a ^{attribute}~~value~~ and `"value"` is the value.

⑦

Difference between Src and href.

Src and href both are attribute but they have different behaviour.

Src = It is called source it shows the value given in the display of the webpage. Path is usually.

href = It is hypertext reference, it shows the value given in another webpage it is usually links.

Src used for image tag, href used for `<a>`.

8) Purpose of alt in .

Usually,

```
<img src = "value" alt = "image">
```

In this example if the value is not shown then will be a broken image and the text is shown as image what the alt attribute contain.

Alt attribute is used to add additional information of a attribute.

It helps users and developers to understand. And developers rectify the ~~Solati~~ problem.

9)

Block - Level

Inline element.

Block level Elements usually start with the new line and it take total available width.

Inline Element usually not start with new line, ~~but~~ and it takes only the content width

* Don't put a block level element in a block level element

* It helps developers to understand the structure

Eg: `<h1>`, `<br>`,
`<div>`

* It usually like a helping tag or formatting tag.

* Can use a ^{tag} inline in inline tag and also use inline tag in block-level tag.

Eg: `<p>`, `<span>`,
`<strong>`.

(10)

Semantic HTML :

Semantic means having a meaning. It usually has a behaviour. It helps developers to understand structure

Example `<header>`, `<main>`, `<footer>`

But non non Semantic doesn't have a behaviour we use to wrap the content or element

Example. `<span>`, `<div>`

⑪ <div>

<div> is block-level non-semantic tag. It usually wraps the element we can use multiple <div> in a <div> to structure. It has closing tag </div>

 is inline non-semantic tag. It is used in between tags and the content between the can be used to formatting etc. It has closing tag

⑫ HTML Lists:-

HTML Lists are used to list the content, types of list are Ordered list , Unordered list , and Description List <dl>.

 is a unordered list. It is used list with the bullet point.

`<ol>`

`<ol>` is Ordered list it is used to list the content orderly from 1 to etc...

`<dl>`

`<dl>` is used to describe the list. It has child elements like `<dt>` and `<dd>`.

(13)

* `<table>`

It is the table tag every table should start with this tag. This a Parent element.

`<tr>`

It is tablerow used to open a new row.

`<th>`

used to enter the value in row and it was header and bold by default.

`<td>`

used to enter the value in each column.

`<thead>`

`<thead>` is used to describe the header of the table.

`<tbody>`

`<tbody>` is used to describe the body of the table. The content shown in the table.

`<tfoot>`

`<tfoot>` is used to end the table where `<tr>` was used below of the table all tags helps developers to identify.

⑭.

`charset = "UTF-8"`

It is used in metadata.

Charset is an attribute and

UTF-8 is an value. UTF stands for Uniformed Transformation Format.

It allows the browser to form many characters like symbols and emojis, it supports.

Viewport .

Viewport meta tag is used to describe the screen size of the web browser according to device.

(15) OPEN GRAPH <OG> :

Open graph meta tag is used to show additional information while sharing through various social media platform.

Example : <Og : title> describe title of website while sharing the website.

<Og : title> → It is used to show the title of a website while sharing.

<Og : type> → It is used to describe the type of the website like, video, Article, Product Page, etc.

<Og : Image> → It is used to display the ^{as logo} Image of a website while sharing in other word we say ^{thumb} - nail

<Og:url> It is used to shows the url of the webpage . And it should be with https .

<Og:description> It is used to describe the webpage in lines while sharing . It comes under the title .