

# Packet Tracer Lab Evaluation Report

Generated: 2026-08-07 03:54 UTC

|               |                                      |
|---------------|--------------------------------------|
| Student Name  | dhinesh                              |
| Student ID    | 93ffe9f9-dd31-46ba-a6a5-d02e8301716a |
| Overall Score | 0.0 / 100.0                          |
| Result        | <b>FAIL X</b>                        |

## Lab Question

### OSPF Area 0 with Static Default Route Redistribution

Scenario:

A company network consists of three routers connected in a linear topology:

R1 – R2 – R3

Each router has its own Local Area Network (LAN) for local users.

To ensure proper routing and external connectivity:

OSPF Area 0 is configured between all routers for dynamic route exchange.

R1 acts as the edge router and is configured with a static default route toward an external network.

The default route must be redistributed into OSPF, allowing all internal routers to reach unknown destinations.

Proper CIDR-based subnetting is used for LAN and WAN addressing.

The objective is to achieve full LAN-to-LAN connectivity and correct default route propagation across the network.

The network is to be implemented and tested using Cisco Packet Tracer.

IP Addressing Details:

LAN Networks:

R1 LAN: 10.30.0.0 /27

R2 LAN: 10.30.0.32 /27

R3 LAN: 10.30.0.64 /27

WAN Links (/30 Subnets):

R1 – R2: 10.0.0.0 /30

R2 – R3: 10.0.0.4 /30

Tasks:

Create the given linear topology (R1–R2–R3) in Cisco Packet Tracer.

Assign IP addresses to all router interfaces and LAN hosts using the given CIDR addressing scheme.

Configure OSPF Process ID 1 on R1, R2, and R3.

Place all router interfaces in OSPF Area 0.

Configure a static default route on R1 pointing toward the external network.

Redistribute (advertise) the default route into OSPF.

Verify OSPF neighbour relationships and routing tables.

Ensure all LAN networks are reachable across the topology.

Confirm that internal routers learn the default route via OSPF.

Test end-to-end connectivity and confirm successful communication using ping.

## Evaluation Details

| # | Check                                     | Status        | Score | Details                      |
|---|-------------------------------------------|---------------|-------|------------------------------|
| 1 | Verify OSPF process 1 is configured on R1 | <b>X FAIL</b> | 0%    | OSPF is not configured on R1 |

| #  | Check                                                   | Status        | Score | Details                                                     |
|----|---------------------------------------------------------|---------------|-------|-------------------------------------------------------------|
| 2  | Verify OSPF process 1 is configured on R2               | <b>X FAIL</b> | 0%    | Device 'R2' not found. Available devices: Switch0, Switch1, |
| 3  | Verify OSPF process 1 is configured on R3               | <b>X FAIL</b> | 0%    | Device 'R3' not found. Available devices: Switch0, Switch1, |
| 4  | Verify R1 LAN network 10.30.0.0/27 is advertised        | <b>X FAIL</b> | 0%    | OSPF network statement for 10.30.0.0 not found on R1        |
| 5  | Verify R1-R2 WAN link network 10.0.0.0/30 is advertised | <b>X FAIL</b> | 0%    | OSPF network statement for 10.0.0.0 not found on R1         |
| 6  | Verify R2 LAN network 10.30.0.32/27 is advertised       | <b>X FAIL</b> | 0%    | Device 'R2' not found. Available devices: Switch0, Switch1, |
| 7  | Verify R2-R1 WAN link network 10.0.0.0/30 is advertised | <b>X FAIL</b> | 0%    | Device 'R2' not found. Available devices: Switch0, Switch1, |
| 8  | Verify R2-R3 WAN link network 10.0.0.4/30 is advertised | <b>X FAIL</b> | 0%    | Device 'R2' not found. Available devices: Switch0, Switch1, |
| 9  | Verify R3 LAN network 10.30.0.64/27 is advertised       | <b>X FAIL</b> | 0%    | Device 'R3' not found. Available devices: Switch0, Switch1, |
| 10 | Verify R3-R2 WAN link network 10.0.0.4/30 is advertised | <b>X FAIL</b> | 0%    | Device 'R3' not found. Available devices: Switch0, Switch1, |
| 11 | Verify default-information originate is configured      | <b>X FAIL</b> | 0%    | 'default-information originate' not found in OSPF on R1     |

**Summary:** FAILED — Score: 0.0/100.0 (0%) — 0/11 checks passed. Reason: required checks failed, score 0% below threshold 70%.