Started on	Saturday, 5 October 2024, 11:12 PM
State	Finished
Completed on	Saturday, 5 October 2024, 11:19 PM
Time taken	7 mins 27 secs
Marks	11.00/11.00
Grade	**100.00** out of 100.00
Name	DHIRU BHAI 730423104017

Question 1

Correct

Mark 1.00 out of 1.00

What is the output of the below Java program with constructors?

```
public class Constructor2
{
  int count=10;
  Constructor2(int count)
  {
    System.out.println("Count=" + count);
  }

  public static void main(String[] args)
  {
    Constructor2 con = new Constructor2();
  }
}
```

a. Count=0

b. Count=10

c. Compiler error ✔

d. None of the above

Question 2

Correct

Mark 1.00 out of 1.00

What is the output of the below Java program with many constructors?

```
public class Constructor7
{
  Constructor7(int a)
  {
    System.out.println("Book=" + a);
  }
  Constructor7(float a)
  {
    System.out.println("Pen="+ a );
  }
  public static void main(String[] args)
  {
    Constructor7 con = new Constructor7(50.5f);
  }
}
```

Answer: Pen=50.5 ✔

Question 3

Correct

Mark 1.00 out of 1.00

In Java, a constructor with no parameters or no arguments is called ___ constructor.

Answer: Default ✔

Question 4

Correct

Mark 1.00 out of 1.00

Predict the output of following Java program

```
class T {
  int t = 20;
  T() {
    t = 40;
  }
}
class Main {
  public static void main(String args[]) {
    T t1 = new T();
    System.out.println(t1.t);
  }
}
```

Answer: 40

Question 5

Correct

Mark 1.00 out of 1.00

Find the Output

```
public class Main{
private Main(int w)//line 1
{
System.out.print(w);
}
public static Main()//line 5
{
System.out.print("hello");
}
public static void main(String args[])
{
Main t=new Main(10);
}
}
```

a. Won't compile because of line(1) , constructor can't be private

b. Won't compile because of line(5) , constructor can't be static ✔

c. 10

d. 10 50

Question 6

Correct

Mark 1.00 out of 1.00

Predict the output?

```
package main;
class T {
  private int t = 20;
}
class Main {
   public static void main(String args[]) {
      T t1 = new T();
      System.out.println(t1.t);
   }
}
```

a. 20

b. 0

c. compiler error ✔

d. No output is printed

Question 7

Correct

Mark 1.00 out of 1.00

The name of a constructor and the name of a class are ___.

Answer: Same ✔

Question 8

Correct

Mark 1.00 out of 1.00

What is the output of the below Java program with overloaded constructors?

```
public class Constructor3
{
  int birds=10;
  Constructor3()
  {
    this(20);
  }
  Constructor3(int birds)
  {
    System.out.println("Birds=" + birds);
  }

  public static void main(String[] args)
  {
    Constructor3 con = new Constructor3();
  }
}
```

a. Birds=0

b. Birds=10

c. Birds=20 ✔

d. Compiler error

Question 9

Correct

Mark 1.00 out of 1.00

Is there any compiler error in the below Java program?

```
class Point {
   int m_x, m_y;
   public Point(int x, int y) {    m_x = x;    m_y = y;  }
   public static void main(String args[])
   {
     Point p = new Point();
   }
}
```

a. Yes ✔

b. No

Question 10

Correct

Mark 1.00 out of 1.00

Constructor gets automatically called when an object gets instantiated. True or False?

Answer: True ✔

Question 11

Correct

Mark 1.00 out of 1.00

The default return type of a constructor is

- a. float
- b. No return type ✔
- c. boolean
- d. int
- e. char