Q: What is the full form of JRE in Java?
A. Java Real-time Environment
B. Java Runtime Environment
C. Java Rendering Engine
D. Java Resource Editor

Who is the original creator (author) of the Java programming language?
A. Bjarne Stroustrup
B. James Gosling
C. Dennis Ritchie
D. Guido van Rossum

Which of the following is NOT a feature of Java?
A. Object-Oriented
B. Platform Independent
C. Pointer Support
D. Robust

What is the main use of JDK (Java Development Kit)?
A. To run Java programs only
B. To compile and run Java programs
C. To design web pages
D. To execute JavaScript code

Which of the following is a common feature in both C++ and Java?
A. Automatic garbage collection
B. Multiple inheritance through classes
C. Object-Oriented Programming
D. Use of pointers

Why is setting the JRE path important in Java?
A. To create a database connection
B. To compile C++ programs
C. To run Java programs using JVM
D. To edit HTML pages

Which of the following is NOT a primitive data type in Java?
A. int
B. float
C. boolean
D. String

What is the purpose of Wrapper classes in Java?
A. To wrap HTML tags inside Java code
B. To convert primitive data types into objects
C. To handle database connections
D. To perform file operations

What is the use of type casting in Java?
A. To convert a variable from one method to another
B. To convert one data type into another
C. To copy classes
D. To encrypt data

Which of the following is NOT a type of type casting in Java?
A. Widening Casting
B. Narrowing Casting
C. Explicit Casting
D. Boolean Casting

Which of the following is a correct Wrapper class for the primitive type char in Java?
A. Char
B. character
C. Character
D. CHAR

What is the main purpose of garbage collection in Java?
A. To compile the Java code
B. To close unused files
C. To free memory by destroying unused objects
D. To manage database connections

What is the role of the finalize() method in Java garbage collection?
A. It prevents an object from being garbage collected
B. It is used to manually collect garbage
C. It is called by the garbage collector before reclaiming the object's memory
D. It deletes objects from memory immediately

Which of the following statements about the String class in Java is correct?
A. String is a primitive data type
B. String objects are mutable
C. String is a class in java.util package
D. String objects are immutable

What does the charAt(int index) method of the String class return?
A. The Unicode value of the string
B. The character at the specified index
C. A substring starting from the index
D. ASCII value of the string

What does the constructor StringBuffer(String str) do in Java?
A. Creates a String and converts it to lowercase
B. Creates an immutable StringBuffer
C. Creates a new StringBuffer with the content of the given String
D. Appends the string to an empty String

What is the purpose of the this keyword in Java?
A. To refer to the superclass object
B. To create a new object
C. To refer to the current class object
D. To destroy the current object

What is the default value of an uninitialized boolean variable in Java class?
A. true
B. 0
C. false
D. null

What does System.out.println() do?
A. Reads input
B. Terminates the program
C. Prints output
D. Declares a variable

What will be the result of 10 + 20 + "Java" in Java?

A. 1020Java
B. 30Java
C. Java1020
D. Compile-time error

Which method is called when an object is created?
A. main()
B. finalize()
C. Constructor
D. start()

Which exception is thrown when dividing by zero in Java?
A. NullPointerException
B. ArithmeticException
C. NumberFormatException
D. DivideByZeroException

What will be the output of the following code?

```
public class Test {
   public static void main(String[] args) {
      int a = 10;
      int b = 20;
      System.out.println(a + b);
   }
}
```

A. 1020
B. a + b
C. 30
D. Compilation error

What does the following line do?

```
String name = "Java";
```

A. Declares a variable
B. Declares and initializes a String
C. Creates an object of type String
D. All of the above

Which of the following will compile successfully?

A. int a = 5.5;
B. String s = "5";
C. boolean b = "true";
D. char c = "A";

What will be the output of this code?

```
public class Test {
   public static void main(String[] args) {
      int a = 10, b = 20;
      a = b;
      b = a;
      System.out.println(a + " " + b);
   }
}
```

A. 10 20
B. 20 10
C. 20 20
D. 10 10

What is the output of this code?

```
public class Test {
   public static void main(String[] args) {
      String s1 = "hello";
      String s2 = "hello";
      System.out.println(s1 == s2);
   }
}
```

A. true
B. false
C. Compilation error
D. Runtime error

What is the output?

```
public class Test {
   public static void main(String[] args) {
      String str = "Java";
      System.out.println(str.charAt(2));
   }
}
```

A. a
B. v
C. J
D. Error

What will happen?

```
public class Test {
   public static void main(String[] args) {
      int a = 5 / 0;
      System.out.println(a);
   }
}
```

A. 0
B. Infinity
C. Error
D. Exception at runtime

What is the output?

```
public class Test {
   public static void main(String[] args) {
      int a = 2, b = 3;
      System.out.println((a > b) ? a : b);
   }
```

```
}
```

A. 2
B. 3
C. true
D. false

What is the result of this code?

```
public class Test {
   public static void main(String[] args) {
      int a = 5 * 2 / 2 + 2;
      System.out.println(a);
   }
}
```

A. 6
B. 7
C. 10
D. 8

inprotected.com