Memory-Pressure Forecasting and Growth-Based Warnings: An Empirical Study★

Abstract. Forecasting rising memory pressure can support monitoring, but accurate forecasts do not by themselves identify memory leaks. We compare persistence, linear trend, restricted ARIMA and a small LSTM on one Antarex fault-injection recording and three Westermo industrial recordings, using chronological splits and 60- or 300-second horizons. Forecast error and growth-warning performance are evaluated separately. In the original Antarex run, LSTM reduces RMSE from ARIMA's 1.516 to 1.216 percentage points of RAM. Its warning rule, however, recognizes 34 of 35 injected events against trend-only's 35, with timestamp recall 0.466 versus 0.859. A matched study of five random seeds and two LSTM input configurations adds 40 runs. Extra features improve mean RMSE on only two of four recordings. Multivariate Antarex warning F1 is 0.571 ± 0.031, below trend-only's 0.830, and false alarm starts range from 43 to 137 against 86. A saved-score analysis explains the original missed event through an unmet forecast-growth threshold. Westermo has no confirmed leak labels and supports forecasting conclusions only. Local replay/inference timings describe prototype functionality; live performance and advance warning before memory exhaustion remain unvalidated.

Keywords: Memory pressure · Time-series forecasting · LSTM · Warning evaluation · Operating-system telemetry

1 Introduction

An operating system can report growing memory use without identifying its cause. A larger workload, a cache, or an application retaining allocations can produce similar aggregate measurements. A forecast of memory availability is therefore a resource estimate, not proof of a memory leak. This distinction matters when a forecasting model is used to trigger operational warnings.

We study whether a more accurate short-horizon forecast gives more useful warnings on recorded telemetry. The target is the memory-pressure proxy

$$y_t = 1 - \frac{\text{available memory}_t}{\text{total physical memory}_t}. \tag{1}$$

It measures the fraction of RAM unavailable for immediate use. Models predict y_{t+h} using observations through time t. Warning rules then assess recent growth, optionally requiring the forecast to indicate continued growth. These two tasks are evaluated separately.

★ AI assistance was used in preparing this manuscript and its supporting code. The disclosure at the end describes its scope.

The study uses controlled Antarex fault injections and three unlabeled Westermo industrial test-system recordings. Its contribution is empirical: (1) a reproducible comparison of forecast error and warning coverage under the same temporal evaluation protocol; (2) a matched five-seed comparison of memory-only and multivariate LSTMs; and (3) an explanation of a missed injected event using the saved decision scores. We also measure the local replay and inference prototype. We do not propose a new neural architecture, diagnose allocation-level causes, or demonstrate advance warning before memory exhaustion.

2 Related Work and Research Gap

Software-aging research links resource behavior, workload and failure. Measurement-based models estimate resource exhaustion [32]; web-server experiments examine aging under workload [8]. Surveys organize aging, rejuvenation and online failure-prediction methods [6,26]. These works establish the research direction; they do not imply that every rising RAM trace is a leak. Zhao et al. use injected leaks to study accelerated failures [36], illustrating the additional outcome evidence needed to discuss exhaustion.

Different observation levels support different conclusions. Valgrind provides dynamic instrumentation [21]; adaptive profiling and methods using garbage-collector information inspect heap behavior [10,15]. Beneder et al. examine runtime measurements on embedded Linux [3]. Differential aging analysis compares software versions [20]. RESIN combines detection, diagnosis and mitigation in production infrastructure [18]. Our aggregate telemetry has neither heap-allocation traces nor paired software versions, so those diagnostic claims are outside its scope.

Jindal et al. detect leak patterns from memory-utilization histories using LBR and Precog variants [14]. Assi et al. compare Box–Jenkins and LSTM forecasts for Windows performance [1]. Statistical forecasting and simple benchmarks remain essential comparisons [4,12]. LSTM provides a learned sequence model [11], but architecture studies and strong linear baselines caution against assuming that complexity ensures better forecasts [7,34]. Hybrid ARIMA–neural forecasting [35], software-fault ARIMA–LSTM forecasting [27], and hLSTM-Aging [2] use different model combinations. We evaluate separate predictors and do not reproduce their architectures or compare scores from different tasks.

Table 1 summarizes the closest methodological contrasts. Its final column describes the boundary relevant to this study, rather than asserting that an earlier method is generally inadequate.

Assumptions and benchmark quality affect anomaly-detection results [5,33,28]. Forecast errors and warning scores assess different outcomes [13,25,31]. Chronological holdouts and training-only scaling make the information available at each prediction explicit [30,16].

Research gap. On these recordings, it remains unclear whether lower forecast error improves growth-warning coverage, false-alarm frequency and recognition delay under one temporal protocol. We address this question using matched origins, injected-event labels, repeated seeds and a memory-only ablation. Unlabeled workload data support forecasting comparisons, not leak-detection claims.

Table 1. Selected earlier studies and the evidence they provide. Table prepared with OpenAI Codex assistance (GPT-6-based, October 2026).

Study	Observation and purpose	Boundary for the present comparison
Jindal et al. [14]	Utilization histories; LBR/Precog leak-pattern methods	Their labels and algorithms differ from our injected-event and forecast-warning protocol.
Assi et al. [1]	Windows counters; ARIMA/LSTM forecast errors	Forecast-error ranking alone does not answer our timestamp/event warning question.
Zhao et al. [36]	Injected leaks; accelerated failure study	Failure outcomes are available there; our audited block has no exhaustion outcome.
Lou et al. [18]	Production service with detection, diagnosis and mitigation	Requires evidence beyond our aggregate replay and growth warnings.
Battisti et al. [2]	Hybrid neural model for software-aging forecasts	Different architecture and target setting; its scores cannot rank our warning rules.
Kim et al. [17]	Evaluation of time-series anomaly detection	Warns about point adjustment; we retain timestamp scores and separate event counts.

3 Data and Experimental Protocol

3.1 Dataset Choice and Forecast Horizons

Antarex was chosen because it combines real machine telemetry with recorded, controlled fault injections [22,24,23]. The experiment uses the complete recovered CPU-MEM_mono block, approximately 12 days long, containing 228 injected leak episodes. Only the metric streams needed by this pipeline were selected. The nested archive was verified using recorded size and CRC; the full outer archive was not acquired, and its published MD5 was not verified. This is a defined subset, not validation of the entire Antarex release.

Westermo supplies a complementary industrial workload: 19 test systems monitored twice per minute for one month [29]. All 19 CSVs were acquired and checked against repository metadata; systems 1–3 were selected in numerical order for this pilot. Each is modeled separately. They have no confirmed memory-leak labels, so their contribution is forecasting evaluation and descriptive alarm counts only. Both sources are available under CC BY 4.0, with their attribution retained.

Antarex is aligned to a five-second grid; Westermo retains its native 30-second cadence. The preset horizons are 12 Antarex steps (60 s) and 10 Westermo steps (300 s). These choices keep both forecasts roughly ten observations ahead while respecting each source's cadence. They are practical pilot settings, not validated optimal warning lead times. The same 60-observation history spans 295 s and 1770 s respectively. Consequently, error magnitudes across sources should not be interpreted as a controlled comparison at an equal physical horizon.

Table 2. Recording scope and eligible samples. A: Antarex; W1–W3: Westermo systems. Train is the eligible count before LSTM training stride. Table formatted with OpenAI Codex assistance (GPT-6-based, October 2026).

Recording	Grid rows	Train	Validation	Test	Inputs
A	207361	145081	31032	31032	7
W1	86401	59691	12891	12891	8
W2	86401	60412	12891	12745	7
W3	86401	60412	12891	12891	8

3.2 Causal Preparation and Feature Availability

Antarex uses the most recent source observation at or before each grid time, with maximum age 2.1 s. Counter differences produce page-fault, swap and disk rates using actual elapsed time. Counter resets, nonpositive intervals and intervals above 7.2 s invalidate a rate. CPU features use non-overlapping tick categories. Westermo's published CPU and disk rates are retained without differentiating them again. Missing values and gaps are not interpolated.

The retained Antarex inputs are memory pressure, anonymous and committed memory, busy and I/O-wait CPU fractions, and total and major page-fault rates. Swap and monitored disk streams are constant in its training partition and are removed. Westermo uses memory pressure, user/system/I/O-wait CPU rates, disk read/write rates, one-minute load and swap use; system 2 drops constant swap. Westermo has no page-fault fields. A training standard deviation at most 10^{-12} identifies constant inputs. Removing them avoids undefined standardization and extra uninformative inputs; it does not show that disk or swap is useless under other workloads. The feature ablation below evaluates the retained feature set as a group, not each feature's causal effect.

Each recording is split by time extent into 70% training, 15% validation and 15% test. Boundaries are set before constructing windows. Training means and population standard deviations scale later data. A window is retained only when its history and target lie in one valid contiguous segment and one partition. The first Antarex row in each partition is excluded to avoid rates depending on a preceding partition. Westermo systems 1 and 2 contain 652 and 8 missing grid rows respectively. The memory-only ablation uses exactly the same coverage mask as the multivariate model, so sample availability cannot account for their difference.

Antarex injection starts and ends define half-open labeled intervals $[s, e)$. They are checked against supplied fault labels. IDs, timestamps, commands and fault labels are never predictor inputs. Labels confirm the controlled injection task; there are no process-allocation measurements establishing naturally occurring leaks. A non-leak label can also coincide with another injected fault and does not certify a healthy system.

3.3 Predictors and Repeated Runs

Persistence repeats the latest memory pressure. Linear trend extends a least-squares line fitted to 12, 30 or 60 recent values; validation RMSE selects the window. Restricted

ARIMA uses orders $(1, 1, 0)$, $(3, 1, 0)$ and $(5, 1, 0)$ without drift. Parameters are estimated by Yule–Walker on the longest contiguous training segment, and validation RMSE selects the order. This limited comparison does not implement a full Box–Jenkins search. Forecasts are clipped to $[0, 1]$ for scoring.

Both LSTM variants use one unidirectional layer with 32 hidden units and a linear output from its final hidden state. The recurrent state resets for each window. Training uses standardized-target mean squared error, Adam at 0.001, batch size 64 and gradient clipping at 1.0. Training retains every twelfth eligible Antarex origin and every fourth Westermo origin; validation/test use all eligible origins. The best validation-RMSE checkpoint is selected from at most 20 epochs, with patience four. There is no dropout, bidirectional layer or hybrid ARIMA stage.

The original September Colab experiment used seed 42. The revision trains both feature variants from scratch with seeds 7, 21, 42, 84 and 123 on the same local CPU runtime: 40 runs in total. All checkpoints are frozen before the new test scores are computed. Every seed is reported, with mean and sample standard deviation (SD). This is variation from training randomness on fixed data, not uncertainty across new machines. Memory-only LSTM matches the baselines' input variable; model fitting and training sample use still differ. Fixed hidden width yields 4513 parameters for memory-only, versus 5281 or 5409 for seven or eight inputs. No new labeled recording is added.

4 Warning Procedure and Evaluation

4.1 Growth Rules and Threshold Calibration

Let g_t be the least-squares slope over the latest 12 memory-pressure observations, expressed in percentage points (pp) of RAM per minute. For forecast $f_m(t)$ with horizon h in seconds, define

$$q_m(t) = \frac{100[f_m(t) - y_t]}{h/60}, \qquad s_m(t) = \min\{g_t, q_m(t)\}. \tag{2}$$

Trend-only uses $s(t) = g_t$. Forecast-assisted warnings require both observed and forecast growth. A warning becomes active on the third consecutive eligible score at or above its threshold; one failure clears it. Gaps and split boundaries reset the count. Three readings suppress isolated excursions but add 10 s of confirmation at Antarex cadence and 60 s at Westermo cadence. This was a fixed engineering choice, not an optimized duration or a statistical-significance test. Mann–Kendall testing and autocorrelation corrections are alternative future comparisons [19,9].

Each rule selects independently from $\{0.01, 0.025, 0.05, 0.1, 0.2, 0.4, 0.8, 1.6, 3.2\}$ pp/min and a disabled option. Antarex validation point F1 is maximized, with ties resolved by fewer false-positive timestamps and then the higher threshold; disabled ranks highest in the last tie-break. The original thresholds were 0.8 for trend-only and 0.4 for LSTM-assisted. Every ARIMA candidate produced zero validation warning timestamps after confirmation, so the disabled option won the tie. This describes the selected no-drift ARIMA and rule, not a general inability of ARIMA to support warnings. Each new LSTM run recalibrates on validation only; original results are preserved separately.

Algorithm 1 Telemetry forecasting and causal warning generation

Require: Archived telemetry or live OS sampler; history 60; trend history 12
if archived experiment **then**
    Align past observations; derive rates; retain gaps and label provenance
    Split chronologically; fit scalers on training rows; form valid windows
    Fit predictors on training data; select checkpoints on validation RMSE
    Select warning thresholds using validation labels; freeze choices
else
    Initialize five-second sampler and exploratory trend threshold
end if
for each new observation at time t **do**
    Read available telemetry; compute y_t using Eq. 1
    Reset history/count after a gap; wait until history is sufficient
    Compute observed slope g_t from the last 12 readings
    if compatible archived-model inputs **then**
        Scale history with saved training statistics; predict $f_m(t)$
        Set $s_t = g_t$ for trend-only or Eq. 2 for assisted rules
    else
        Set $s_t = g_t$; do not substitute invented model inputs
    end if
    Update consecutive qualifying count; warn when count ≥ 3
    Save forecast, score, warning and transition into alarm state
end for
Score stored forecasts/decisions only where suitable outcomes exist

Algorithm 1 separates archived-model evaluation from the live monitor. The live branch records OS telemetry every five seconds using `psutil`, computes the same memory proxy and an exploratory observed-growth rule, and exports measurements. It does not apply the archived LSTM to incompatible Windows features.

4.2 What Each Measure Means

MAE is the average absolute difference between predicted and observed future pressure. RMSE squares the errors before averaging and taking the square root, giving large mistakes greater weight [13]. Both are reported in pp of total RAM. An RMSE of 1.5 pp describes forecast deviation on this scale; it is neither 98.5% detection accuracy nor a bound on every error.

At each eligible origin, TP means a warning during a recorded leak, FP a warning outside one, and FN an active leak without a warning. Precision = $\mathrm{TP}/(\mathrm{TP}+\mathrm{FP})$ asks how many warned timestamps are leak-active. Recall = $\mathrm{TP}/(\mathrm{TP}+\mathrm{FN})$ asks how much labeled leak time is covered. F1 = $2\mathrm{TP}/(2\mathrm{TP}+\mathrm{FP}+\mathrm{FN})$ balances these two aspects. Zero-denominator ratios remain undefined. Imbalance makes these measures more informative than overall accuracy alone [25].

An alarm start is an inactive-to-active transition, including activation after a gap. False alarm starts per non-leak hour (FA/h) divide starts outside injected-leak intervals

by observed non-leak exposure: eligible non-leak origins times cadence. Persistent false warnings are also reported as false-positive minutes. These are distinct costs.

Event recognition requires a new alarm start inside a fully covered injected interval, with a covered sample immediately before it. A prior alarm does not count again. Event recall is recognized events divided by eligible events; detection delay is first alarm time minus injection start. Medians and 90th percentiles describe detected events only, so missed-event counts accompany them. Detecting one timestamp does not make every timestamp in that interval correct [31,17]. These delays measure recognition after injection begins, not warning lead time before exhaustion.

5 Results and Interpretation

5.1 Forecast Accuracy and the Baseline Comparison

Table 3 preserves the original run. On Antarex, LSTM RMSE was 1.216 pp against ARIMA's 1.516 pp, a 19.8% reduction, while MAE changed only from 0.363 to 0.358 pp. The larger RMSE improvement indicates a stronger effect on large errors than on average absolute error. Across Westermo, the original LSTM reduced RMSE but ARIMA had lower MAE: no method wins under every loss.

The selected Antarex ARIMA$(3, 1, 0)$ coefficients are approximately -0.011, -0.010 and -0.011. With no drift, forecast increments quickly become small, making its predictions close to persistence; their RMSEs differ by only 0.000196 pp. Linear extrapolation performs worse in all four recordings, consistent with transient slopes not continuing through the forecast horizon. Figure 1 shows the fixed original example interval; full-test scores, rather than that interval, support the comparisons.

Table 3. Original test forecast errors: MAE / RMSE, in percentage points (pp) of total RAM. A uses 60 s; W1–W3 use 300 s. LSTM is the single Colab seed-42 run. Prepared with OpenAI Codex assistance (GPT-6-based, October 2026).

Model	A	W1	W2	W3
Persistence	0.361 / 1.517	0.094 / 0.363	0.109 / 0.317	0.240 / 0.715
Linear trend	0.377 / 1.744	0.145 / 0.376	0.144 / 0.348	0.329 / 0.818
ARIMA	0.363 / 1.516	0.093 / 0.318	0.105 / 0.291	0.230 / 0.658
Original LSTM	0.358 / 1.216	0.099 / 0.296	0.117 / 0.258	0.251 / 0.608

5.2 Random Seeds and the Memory-Only Ablation

The new CPU runs use Python 3.12.14, PyTorch 2.8.0+cpu and two Torch threads. Table 4 keeps them separate from Colab. On Antarex, multivariate mean RMSE is 1.204 pp versus memory-only 1.221 pp. Paired multivariate RMSE is lower in four of five Antarex seeds and all five W1 seeds, but only one W2 seed and no W3 seed. On W2 and W3, extra inputs also increase MAE in every paired seed. Additional telemetry therefore




Fig. 1. Original Antarex 60-second-ahead rolling forecasts, aligned by target time. Predictions shown at a time were issued 60 s earlier. Persistence and ARIMA nearly overlap. This is the first fixed 30-minute test interval, not a best-case selection. Plot prepared with OpenAI Codex assistance (GPT-6-based, October 2026).

does not consistently improve this fixed model and training budget. The experiment does not isolate which feature helps or harms.

Both LSTM variants have lower mean RMSE than restricted ARIMA on each recording, but all their mean MAEs exceed ARIMA's. Training minimizes squared error, which weights large deviations strongly; lower RMSE with worse MAE is therefore possible. Seed SD describes optimization variability on these recordings, not a confidence interval for other systems. No additional labeled dataset or independent holdout was introduced.

Table 4. Five-seed LSTM test errors: mean ± sample SD, in pp. Mem: memory-only; Multi: retained multivariate inputs. All five seeds are included. Prepared with OpenAI Codex assistance (GPT-6-based, October 2026).

Recording	MAE (Mem)	MAE (Multi)	RMSE (Mem)	RMSE (Multi)
A	0.378 ± 0.018	0.365 ± 0.024	1.221 ± 0.015	1.204 ± 0.020
W1	0.099 ± 0.008	0.103 ± 0.008	0.300 ± 0.001	0.297 ± 0.002
W2	0.110 ± 0.005	0.121 ± 0.004	0.260 ± 0.003	0.263 ± 0.003
W3	0.242 ± 0.011	0.278 ± 0.026	0.606 ± 0.005	0.618 ± 0.009

5.3 Warnings, Missed Events and Recognition Delay

There are 1933 leak-active origins among 31,032 Antarex test origins and 35 fully covered injected events. Table 5 shows that the original LSTM warning improves preci-

sion and reduces false alarm starts from 86 to 42, but covers less leak-active time and misses one event. False alarm rates are 2.128/h for trend-only and 1.039/h for LSTM; false-positive exposure is 34.17 and 13.50 min respectively. Their detected-event 90th-percentile delays are 56.0 and 45.7 s. The disabled ARIMA rule is equivalent to always-off and misses all events.

The difference follows from the warning objective. Regression rewards accurate future levels over all origins, whereas the assisted rule demands both observed and forecast growth above a threshold for three readings. A model can predict the level closely while predicting insufficient continued growth. The additional condition suppresses some false alarms and some true warnings; minimizing forecast RMSE does not optimize event recall or warning F1.

Table 5. Original Antarex test warnings. P/R: timestamp precision/recall; FA: false alarm starts; missed: events missed out of 35; delay: median seconds after injection among detected events only. A dash means undefined. Prepared with OpenAI Codex assistance (GPT-6-based, October 2026).

Rule	P	R	F1	FA	Missed	Delay (s)
Trend only	0.802	0.859	0.830	86	0	30
LSTM + trend	0.848	0.466	0.601	42	1	31
ARIMA (off)	–	0.000	0.000	0	35	–

Event 1534, a low-intensity injection starting at 22:00:14 UTC on 19 May 2018, demonstrates this mechanism (Fig. 2). During its 236 s and 47 eligible origins, forecast growth peaks at 0.216 pp/min, below the 0.4 threshold. Thus no reading can satisfy the forecast gate, irrespective of the three-reading requirement. Observed growth reaches 0.938 pp/min; trend-only warns after 56 s. Memory pressure spans approximately 3.20–7.17%. The recorded scores explain the decision failure, not its allocation-level cause.

The seed study weakens a general claim of fewer false alarms (Table 6). Multivariate precision is 0.758 ± 0.112 and recall 0.461 ± 0.010; memory-only gives 0.648 ± 0.071 and 0.482 ± 0.021. Multivariate false starts range from 43 to 137, compared with the unchanged trend count of 86; memory-only ranges from 126 to 168. Each variant misses zero to two events depending on seed. Trend-only F1 remains 0.830, above every new LSTM-assisted run. The original precision/false-alarm advantage is therefore not stable across all repetitions. Validation selects thresholds separately for each run; forecast training variability and threshold decisions both influence these results.




Fig. 2. Original missed injected event 1534. Shading marks the recorded injection. Top: current pressure and the forecast issued at the same origin (its target is 60 s later). Bottom: observed and forecast growth; predicted growth remains below the LSTM gate throughout the injection. pp: percentage points of RAM. Plot prepared with OpenAI Codex assistance (GPT-6-based, October 2026).

Table 6. Repeated LSTM-assisted Antarex warnings. F1 and FA/h are mean ± SD; missed is the range out of 35 events. Delay summarizes the five detected-event medians, not pooled events. Prepared with OpenAI Codex assistance (GPT-6-based, October 2026).

Inputs	F1	FA/h	Missed	Delay (s)
Multivariate	0.571 ± 0.031	2.014 ± 1.052	0–2	26.6 ± 3.4
Memory-only	0.551 ± 0.028	3.405 ± 0.449	0–2	30.4 ± 2.7

5.4 Prototype Checks and Measurement Limits

All 40 implementation tests passed, including loopback HTTP endpoints. Startup verified 76 source files covering 69,559 test origins. In a separate in-process benchmark on Windows with 8 logical CPUs and 7.8 GiB RAM, each recording received 100 replay/JSON requests and 100 warm model requests. Median replay times ranged from 7.05 to 21.84 ms; median warm inference ranged from 0.45 to 0.56 ms (95th percentiles 0.69–0.96 ms). All 404 first/warm inferences matched archived predictions within 10^{-6} pressure fraction. The first request, including library/model loading, took 5.34 s. Process resident memory increased from 25.4 to 402.3 MiB; this includes replay data, libraries and four models, not isolated monitoring overhead.

These measurements exclude HTTP transport and browser rendering. The live collector returned a Windows performance-counter error before any samples were recorded. No live timing, CPU-overhead or labeled live-detection result is reported. Longer live trials, missing-counter resilience and controlled overhead measurements remain unvalidated. The optional live mode uses exploratory trend warnings, not the archived Linux LSTM.

6 Limitations, Reproducibility and Conclusion

The expanded study still uses one labeled Antarex recording, controlled injections, overlapping windows and reused holdouts. Earlier test forecasts were inspected during development before the original warning protocol was finalized. Five-seed repetition measures optimization variability; it does not remove that development dependence. The multivariate/memory-only comparison controls history, origins and training settings but changes input dimension and parameter count. It cannot attribute improvement to an individual feature. Selected horizons, thresholds and confirmation length also require independent validation.

Antarex never reaches the illustrative 80% pressure level in the audited block; its peak is approximately 42.24%. No exhaustion or crash outcome is observed. The study therefore makes no claim of warning before memory runs out. Such a claim needs labeled trials with resource limits, observed depletion times and warning lead times, including failures to warn. Westermo cannot establish real-leak detection because its leak labels are unknown. Additional labeled recordings, process-level allocation evidence, matched multivariate statistical baselines, independent temporal holdouts and longer compatible live trials remain future work.

Reproducibility. The project retains preprocessing, baseline, LSTM and warning code, four executable notebooks, model configurations, weights, origin indices, checksums and scoring scripts. The revision adds a fixed seed/feature protocol, per-run forecasts and warning outcomes, a missed-event analysis and a prototype benchmark. Reproduction uses the verified input package, runs the seed study, then independently checks saved predictions and warning scores. The repository is currently private; these materials are not claimed to be publicly accessible. An anonymized supplementary code package accompanies this revision for author review, while raw/derived data packages

require separate access. Public dataset sources are cited above; a public code release or reviewer-access route must be arranged before claiming open reproducibility.

Conclusion. Lower forecasting error and better warning performance are different outcomes. LSTM reduced RMSE relative to restricted ARIMA, but trend-only covered more labeled time and had higher warning F1. The original LSTM precision/false-alarm benefit was not consistent across seeds. Extra features improved mean RMSE on only two of four recordings, and the missed-event scores exposed a failed forecast-growth gate. These findings support evaluating forecast accuracy and operational warnings separately. They do not establish production leak diagnosis or pre-exhaustion warning; independent labeled trials, process measurements and longer live evaluation are the next tests.

Disclosure of AI Assistance OpenAI Codex, a GPT-6-based assistant accessed during September–October 2026, assisted with code development, experimental analysis, manuscript drafting, revision and formatting. Numerical results were obtained from executed code and saved artifacts. AI assistance also supported plotting and table preparation, as noted in captions. The authors are responsible for checking the interpretation, citations and final submitted text.

References

1. Assi, M.J., Fahad, A.A., Al-Sarray, B.: Time series forecast modeling for the Windows operating system performance using Box-Jenkins and LSTM models. International Journal of Nonlinear Analysis and Applications **13**(2), 2121–2131 (2022). https://doi.org/10.22075/ijnaa.2022.26974.3505
2. Battisti, F., Silva, A., Pereira, L., Carvalho, T., Araujo, J., Choi, E., et al.: hLSTM-Aging: A Hybrid LSTM Model for Software Aging Forecast. Applied Sciences **12**(13), 6412 (2022). https://doi.org/10.3390/app12136412
3. Beneder, R., Glatz, B., Horauer, M., Rauscher, T.: Memory leak detection runtime-service for embedded Linux devices. In: Proceedings of the 2014 IEEE Emerging Technology and Factory Automation (ETFA). pp. 1–6. IEEE (2014). https://doi.org/10.1109/ETFA.2014.7005223
4. Box, G.E.P., Jenkins, G.M., Reinsel, G.C.: Time Series Analysis: Forecasting and Control. Wiley, 4 edn. (2008). https://doi.org/10.1002/9781118619193
5. Chandola, V., Banerjee, A., Kumar, V.: Anomaly detection: A survey. ACM Computing Surveys **41**(3), 1–58 (2009). https://doi.org/10.1145/1541880.1541882
6. Cotroneo, D., Natella, R., Pietrantuono, R., Russo, S.: A survey of software aging and rejuvenation studies. ACM Journal on Emerging Technologies in Computing Systems **10**(1), 1–34 (2014). https://doi.org/10.1145/2539117
7. Greff, K., Srivastava, R.K., Koutnik, J., Steunebrink, B.R., Schmidhuber, J.: LSTM: A Search Space Odyssey. IEEE Transactions on Neural Networks and Learning Systems **28**(10), 2222–2232 (2017). https://doi.org/10.1109/TNNLS.2016.2582924
8. Grottke, M., Li, L., Vaidyanathan, K., Trivedi, K.: Analysis of Software Aging in a Web Server. IEEE Transactions on Reliability **55**(3), 411–420 (2006). https://doi.org/10.1109/TR.2006.879609

9. Hamed, K.H., Ramachandra Rao, A.: A modified Mann-Kendall trend test for autocorrelated data. Journal of Hydrology **204**(1-4), 182–196 (1998). https://doi.org/10.1016/S0022-1694(97)00125-X
10. Hauswirth, M., Chilimbi, T.M.: Low-overhead memory leak detection using adaptive statistical profiling. In: Proceedings of the 11th international conference on Architectural support for programming languages and operating systems. pp. 156–164. ACM (2004). https://doi.org/10.1145/1024393.1024412
11. Hochreiter, S., Schmidhuber, J.: Long Short-Term Memory. Neural Computation **9**(8), 1735–1780 (1997). https://doi.org/10.1162/neco.1997.9.8.1735
12. Hyndman, R.J., Athanasopoulos, G.: Forecasting: Principles and Practice. OTexts, 3 edn. (2021), https://otexts.com/fpp3/
13. Hyndman, R.J., Koehler, A.B.: Another look at measures of forecast accuracy. International Journal of Forecasting **22**(4), 679–688 (2006). https://doi.org/10.1016/j.ijforecast.2006.03.001
14. Jindal, A., Staab, P., Kulkarni, P., Cardoso, J., Gerndt, M., Podolskiy, V.: Memory Leak Detection Algorithms in the Cloud-based Infrastructure. arXiv preprint arXiv:2106.08938 (2021). https://doi.org/10.48550/arXiv.2106.08938
15. Jump, M., McKinley, K.S.: Cork: dynamic memory leak detection for garbage-collected languages. In: Proceedings of the 34th annual ACM SIGPLAN-SIGACT symposium on Principles of programming languages. pp. 31–38. ACM (2007). https://doi.org/10.1145/1190216.1190224
16. Kapoor, S., Narayanan, A.: Leakage and the reproducibility crisis in machine-learning-based science. Patterns **4**(9), 100804 (2023). https://doi.org/10.1016/j.patter.2023.100804
17. Kim, S., Choi, K., Choi, H.S., Lee, B., Yoon, S.: Towards a Rigorous Evaluation of Time-Series Anomaly Detection. Proceedings of the AAAI Conference on Artificial Intelligence **36**(7), 7194–7201 (2022). https://doi.org/10.1609/aaai.v36i7.20680
18. Lou, C., Chen, C., Huang, P., Dang, Y., Qin, S., Yang, X., et al.: RESIN: A Holistic Service for Dealing with Memory Leaks in Production Cloud Infrastructure. In: 16th USENIX Symposium on Operating Systems Design and Implementation (OSDI). pp. 109–125. USENIX Association (2022), https://www.usenix.org/conference/osdi22/presentation/lou-resin
19. Mann, H.B.: Nonparametric Tests Against Trend. Econometrica **13**(3), 245–259 (1945). https://doi.org/10.2307/1907187
20. Matias, R., Andrzejak, A., Machida, F., Elias, D., Trivedi, K.: A Systematic Differential Analysis for Fast and Robust Detection of Software Aging. In: 2014 IEEE 33rd International Symposium on Reliable Distributed Systems. pp. 311–320. IEEE (2014). https://doi.org/10.1109/SRDS.2014.38
21. Nethercote, N., Seward, J.: Valgrind: a framework for heavyweight dynamic binary instrumentation. In: Proceedings of the 28th ACM SIGPLAN Conference on Programming Language Design and Implementation. pp. 89–100. ACM (2007). https://doi.org/10.1145/1250734.1250746
22. Netti, A., Kiziltan, Z., Babaoglu, O., Sirbu, A., Bartolini, A., Borghesi, A.: Antarex HPC Fault Dataset. Zenodo, version 1.0 (2018). https://doi.org/10.5281/zenodo.2553224
23. Netti, A., Kiziltan, Z., Babaoglu, O., Sirbu, A., Bartolini, A., Borghesi, A.: Online Fault Classification in HPC Systems through Machine Learning. arXiv preprint arXiv:1810.11208 (2018). https://doi.org/10.48550/arXiv.1810.11208, revised 2019
24. Netti, A., Kiziltan, Z., Babaoglu, O., Sîrbu, A., Bartolini, A., Borghesi, A.: FINJ: A Fault Injection Tool for HPC Systems. In: Euro-Par 2018: Parallel Processing Workshops. Lecture Notes in Computer Science, vol. 11339, pp. 800–812. Springer International Publishing (2019). https://doi.org/10.1007/978-3-030-10549-5_62

25. Saito, T., Rehmsmeier, M.: The Precision-Recall Plot Is More Informative than the ROC Plot When Evaluating Binary Classifiers on Imbalanced Datasets. PLOS ONE **10**(3), e0118432 (2015). https://doi.org/10.1371/journal.pone.0118432
26. Salfner, F., Lenk, M., Malek, M.: A survey of online failure prediction methods. ACM Computing Surveys **42**(3), 1–42 (2010). https://doi.org/10.1145/1670679.1670680
27. Samal, U., Kumar, A.: Improving software reliability: a hybrid ARIMA-LSTM approach for fault prediction. International Journal of System Assurance Engineering and Management **16**(5), 1757–1769 (2025). https://doi.org/10.1007/s13198-025-02743-2
28. Schmidl, S., Wenig, P., Papenbrock, T.: Anomaly detection in time series: a comprehensive evaluation. Proceedings of the VLDB Endowment **15**(9), 1779–1797 (2022). https://doi.org/10.14778/3538598.3538602
29. Strandberg, P.E., Marklund, Y.: The Westermo test system performance data set. arXiv preprint arXiv:2311.14510 (2023). https://doi.org/10.48550/arXiv.2311.14510
30. Tashman, L.J.: Out-of-sample tests of forecasting accuracy: an analysis and review. International Journal of Forecasting **16**(4), 437–450 (2000). https://doi.org/10.1016/S0169-2070(00)00065-0
31. Tatbul, N., Lee, T.J., Zdonik, S., Alam, M., Gottschlich, J.: Precision and Recall for Time Series. In: Advances in Neural Information Processing Systems. vol. 31 (2018), https://proceedings.neurips.cc/paper/2018/hash/8f468c873a32bb0619eaeb2050ba45d1-Abstract.html
32. Vaidyanathan, K., Trivedi, K.S.: A measurement-based model for estimation of resource exhaustion in operational software systems. In: International Symposium on Software Reliability Engineering. pp. 84–93. IEEE (1999), https://scholars.duke.edu/publication/755326
33. Wu, R., Keogh, E.: Current Time Series Anomaly Detection Benchmarks are Flawed and are Creating the Illusion of Progress. IEEE Transactions on Knowledge and Data Engineering **35**(3), 2421–2429 (2023). https://doi.org/10.1109/TKDE.2021.3112126
34. Zeng, A., Chen, M., Zhang, L., Xu, Q.: Are Transformers Effective for Time Series Forecasting? Proceedings of the AAAI Conference on Artificial Intelligence **37**(9), 11121–11128 (2023). https://doi.org/10.1609/aaai.v37i9.26317
35. Zhang, G.: Time series forecasting using a hybrid ARIMA and neural network model. Neurocomputing **50**, 159–175 (2003). https://doi.org/10.1016/S0925-2312(01)00702-0
36. Zhao, J., Jin, Y., Trivedi, K.S., Matias Jr., R.: Injecting Memory Leaks to Accelerate Software Failures. In: 2011 IEEE 22nd International Symposium on Software Reliability Engineering. pp. 260–269. IEEE (2011). https://doi.org/10.1109/ISSRE.2011.24