TerriTool Mobile Subscriptions Guide

RevenueCat · iOS · Android · Webhooks · Trials · Multi-Account

Document version	1.0
Date	June 2026
App	TerriTool React Native
Backend	Laravel (`staging.territool.com` / `app.territool.com`)

Table of contents

1. Architecture overview
2. RevenueCat identity & mobile integration
3. Android vs iOS: which webhook event fires when?
4. Ten accounts, one device, one payment method
5. Giving a trial to all ten emails
6. Backend webhook implementation
7. Android Base → Pro upgrade (proration)
8. Security, idempotency & checklist
9. Quick reference tables

---

1. Architecture overview

TerriTool monetizes mobile users through **RevenueCat** (`react-native-purchases`), which unifies **Apple App Store** and **Google Play** into one subscriber model. Your **Laravel backend** owns package names, credits, and trial flags—the mobile app reads that via `getusercredit` and `getuserstatus` .

```
User → TerriTool App → App Store / Play Store → RevenueCat → Webhook → Laravel DB
                              ↑                                    ↓
                         Purchase UI                    getusercredit / getuserstatus
```

Principle: Webhook + subscriber sync is the **source of truth** for paid state. Client `revenuecate-success` is a optional fast-path nudge after purchase.

Key mobile files

File	Role
`App/utils/RevenueCatService.js`	Configure RC, `identifyUser`, `app_user_id` format
`App/components/register/subscribe.js`	Purchase flow, Android proration, offerings
`App/components/register/SubscriptionGate.js`	Post-login paywall if trial inactive
`App/components/register/index_register_split.js`	Register → RC → `revenuecate-success`
`App/components/dashboard/editstatus.js`	Settings plan change paywall
`App/utils/subscriptionGate.js`	`free_trial_status` from `getusercredit`

Backend fields the app expects

Field	App usage
`package_name`	`Free Package`, `Base Package`, `Pro Package`, etc.
`duration`	Monthly / yearly (`packageTier` in Settings)
`subscription_date`	Renewal / trial end display
`free_trial_status`	Gates `SubscriptionGate` on login
`is_subscription_expired`	Active vs expired badge
Credit balance	Lead/contact credits

RevenueCat offering IDs (mobile)

Offering	ID
Register / subscribe paywall	`ofrng845104ada0`
Settings upgrade paywall	`TerriTool Monthly Non Free`

---

2. RevenueCat identity & mobile integration

App user ID format

Each TerriTool user gets a **unique** RevenueCat customer:

```
app_user_id = {numericUserId}_{email}
```

Example: `12345_user@example.com`

Set on register/login via `RevenueCatService.identifyUser()` → `Purchases.logIn(appUserId)`.

Webhook rule: Parse numeric user id from prefix before first `_` when the prefix is digits.

Current client → backend flows

Flow	Store purchase	Backend call
Register + first purchase	Yes	`POST /api/revenuecate-success` (`app_user_id`)
Login (inactive trial)	—	`GET getusercredit` → SubscriptionGate
Settings Base ↔ Pro	Yes	`getuserstatus` + `getusercredit` only (no `revenuecate-success` today)
Logout	—	`Purchases.logOut()` → next login switches RC user

API keys (mobile)

Platform	Key prefix
iOS	`appl_…`
Android	`goog_…`

Use matching RevenueCat projects/environments for staging vs production.

---

3. Android vs iOS: which webhook event fires when?

RevenueCat sends the **same event types** for both stores. Payload includes:

```
 "store": "APP_STORE"   // iOS
"store": "PLAY_STORE"  // Android
```

Backend should not branch on store for package assignment—map by `product_id` and active entitlements. Store field is for logging/analytics only. **Timing** differs for some downgrades (especially Android deferred).

Event reference

Event	Meaning
`INITIAL_PURCHASE`	First subscription or trial started
`RENEWAL`	Auto-renewal billing cycle
`PRODUCT_CHANGE`	Upgrade, downgrade, or SKU change
`CANCELLATION`	Auto-renew turned off (access often until period end)
`UNCANCELLATION`	Auto-renew re-enabled before expiry
`EXPIRATION`	Subscription ended
`BILLING_ISSUE`	Payment failed
`TEST`	Sandbox / dashboard test ping

3.1 New user — start 7-day free trial (store trial)

Flow: Register → SubscriptionGate → “Start 7-day free trial”

	iOS	Android
Store	App Store trial	Play trial offer
RC `store`	`APP_STORE`	`PLAY_STORE`
Typical event	`INITIAL_PURCHASE`	`INITIAL_PURCHASE`
`period_type`	`TRIAL`	`TRIAL`
Backend	Free/trial package, `free_trial_status` active, trial end date	Same

Example iOS payload (simplified):

```
{
  "type": "INITIAL_PURCHASE",
  "store": "APP_STORE",
  "app_user_id": "1_user1@example.com",
  "product_id": "com.territool.base.monthly.trial",
  "period_type": "TRIAL"
}
```

Example Android payload:

```
{
  "type": "INITIAL_PURCHASE",
  "store": "PLAY_STORE",
  "app_user_id": "2_user2@example.com",
  "product_id": "territool_base_monthly_trial",
  "period_type": "TRIAL"
}
```

3.2 Trial ends → first paid charge (Base Monthly)

	iOS	Android
Typical event	`RENEWAL`	`RENEWAL`
`period_type`	`NORMAL`	`NORMAL`
Backend	`Base Package`, `free_trial_status` inactive	Same


```
{ "type": "RENEWAL", "store": "PLAY_STORE", "product_id": "territool_base_monthly"
}
```

3.3 Settings — Free trial → Pro Monthly (`free_to_paid`)

App uses **new purchase** (no Android subscription replacement).

	iOS	Android
App call	`Purchases.purchasePackage(proPkg)`	Same
Events	`INITIAL_PURCHASE` or `PRODUCT_CHANGE`	Same
When Pro active	Immediately after store confirm	Immediately
Backend	`Pro Package`, credits for Pro	Same

3.4 Settings — Base Monthly → Pro Monthly (paid upgrade)

	iOS	Android
App behavior	Plain `purchasePackage` — Apple upgrades in subscription group	Subscription **replacement** + `IMMEDIATE_AND_CHARGE_PRORATED_PRICE`
Typical event	**`PRODUCT_CHANGE`** (immediate)	**`PRODUCT_CHANGE`** (immediate)
Billing	Apple prorates	Play charges prorated **difference today**; renewal date unchanged
Backend	Set `Pro Package` **immediately** on event/sync	Same

Example iOS:

```
{
  "type": "PRODUCT_CHANGE",
  "store": "APP_STORE",
  "app_user_id": "5_user5@example.com",
  "product_id": "com.territool.pro.monthly"
}
```

Example Android:

```
{
  "type": "PRODUCT_CHANGE",
  "store": "PLAY_STORE",
  "app_user_id": "5_user5@example.com",
  "product_id": "territool_pro_monthly"
}
```

App success message: *"Upgraded to TerriTool Pro — Your Pro plan is active."*

3.5 Settings — Pro Monthly → Base Monthly (downgrade)

	iOS	Android
App behavior	Plain `purchasePackage`	Replacement with **`DEFERRED`**
User keeps Pro until	Current period end	Current period end
Events	1. `PRODUCT_CHANGE` when confirmed	1. `PRODUCT_CHANGE` when confirmed
	2. `RENEWAL` at next cycle with Base SKU	2. `RENEWAL` at next cycle with Base SKU
Backend at step 1	Keep `Pro Package` until expiry	Same
Backend at step 2	Set `Base Package`	Same

App message: *“Plan change scheduled — switch to Base on your next billing date.”*

3.6 User cancels subscription

	iOS	Android
Event	`CANCELLATION`	`CANCELLATION`
Access	Until `expiration_at`	Until `expiration_at`
Later	`EXPIRATION`	`EXPIRATION`

```
{ "type": "CANCELLATION", "store": "APP_STORE", "product_id":
"com.territool.pro.monthly" }
```

3.7 Subscription ends

	iOS	Android
Event	`EXPIRATION`	`EXPIRATION`
Backend	Free/expired, gate to SubscriptionGate	Same

3.8 Monthly auto-renew (no plan change)

	iOS	Android
Event	`RENEWAL` each cycle	`RENEWAL` each cycle
Backend	Extend `subscription_date`, refresh credits	Same

3.9 Side-by-side summary

User action	iOS event(s)	Android event(s)	Update backend when?
Start store free trial	`INITIAL_PURCHASE`	`INITIAL_PURCHASE`	Immediately
Trial → paid Base	`RENEWAL`	`RENEWAL`	On event
Free → Pro (new paid)	`INITIAL_PURCHASE` / `PRODUCT_CHANGE`	Same	Immediately
Base → Pro upgrade	**`PRODUCT_CHANGE`**	**`PRODUCT_CHANGE`**	**Immediately**
Pro → Base downgrade	`PRODUCT_CHANGE` then `RENEWAL`	Same	**At renewal** (Pro until then)
Cancel auto-renew	`CANCELLATION`	`CANCELLATION`	Flag cancel; keep package
Access ends	`EXPIRATION`	`EXPIRATION`	Free/expired
Monthly renew	`RENEWAL`	`RENEWAL`	Extend date + credits

Backend rule on every webhook

```
1. Verify Authorization header
2. Idempotency check on event.id
3. GET RevenueCat subscriber for app_user_id
4. Map active product_id → package_name + credits
5. Write DB — subscriber snapshot wins over event type alone
```

---

4. Ten accounts, one device, one payment method

Question: Register emails user1@ … user10@ on the **same device** with the **same payment method** — what happens?

Short answer

- **10 separate TerriTool accounts** and **10 RevenueCat customers** are created.
- **One Apple ID / Google account** (same device + card) controls **store** trials and **paid** subscriptions.
- Store **intro trials do not repeat** for accounts 2–10 on the same store account.
- A **paid subscription** belongs to the **store account**, linked in RevenueCat to **whoever was logged in** at purchase time—not automatically to all 10 emails.

Per-account isolation (app + RevenueCat)

Account	Backend user id	RevenueCat `app_user_id`
user1@...	1	`1_user1@…`
user2@...	2	`2_user2@…`
...	...	...
user10@...	10	`10_user10@…`

On each login: `Purchases.logIn("{id}_{email}")`. Logout: `Purchases.logOut()`.

Same **device_token** (FCM) is sent on every register/login—backend *may* use this for push or fraud detection (server-side).

What Apple / Google enforce

Layer	Same device + same card
Store account	Usually **one** Apple ID / Google account
Intro free trial	**Once** per subscription group / offer rules
Paid subscription	Typically **one active sub** per product group per store account
TerriTool emails	**Independent** in your DB

Scenario A — each account tries store “7-day free trial”

```
user1@… → RC logIn(1_…) → Store trial → often SUCCESS
user2@… → RC logIn(2_…) → Store trial → often DENIED (no intro)
…
user10@… → same
```

TerriTool may still create all accounts; **billing trial** is store-limited.

Scenario B — user1 pays Pro; user2 logs in

```
user1 paid → entitlement on RC customer 1_user1@…
Logout → logIn(2_user2@…) → NO entitlement
user2 must pay separately OR use Restore (see Scenario C)
```

Scenario C — user2 taps “Restore purchases”

Restore uses the **store account** (same as user1). The store subscription may attach to **current** RC user (`2_user2@…`)—potential **wrong-account entitlement** if backend does not validate original purchaser.

Practical outcome table

#	Email	Store intro trial	TerriTool (typical)
1	user1@...	Often works	Free trial / Free Package
2–10	user2@...–user10@...	Usually **blocked**	Account exists; paywall or full price
Any	One paid sub on store	One billing relationship	Only linked RC `app_user_id` unless Restore moves it

Risks

1. **Trial farming** — many emails, one device
2. **Restore hijacking** — subscription restored onto wrong TerriTool user
3. **Duplicate device_token** — 10 registrations from one device
4. **Webhook** — must map purchase to correct `app_user_id` only

---

5. Giving a trial to all ten emails

Question: What if you want to give a trial to **all 10** emails?

What you cannot do

Ten Apple/Google store intro trials on the **same device + same payment method** — **not possible**. Stores allow roughly **one intro offer per store account** per subscription group.

The app button **"Start 7-day free trial"** calls `Purchases.purchasePackage` — that uses the **store intro offer**.

What you can do

Trials for all 10 must be **TerriTool-controlled** (backend or RevenueCat promotional)—not ten store intro offers.

Option A — Backend-only trial (recommended simplest)

Grant trial in **your database on registration** without store purchase.

On `mobileregistration` success:

- `package_name = "Free Package"`
- `free_trial_status = active` (1 / true)
- `subscription_date` = today + 7 days
- Grant trial credits (e.g. 60)
- User enters app **without** completing IAP

When trial ends:

- Set `free_trial_status = inactive`
- App shows **SubscriptionGate**
- User must complete **real** App Store / Play purchase

Pros	Cons
Each email gets 7 days	Not a store subscription until conversion
Same device OK	Fraud risk (10 × credits)
No store trial limit	Need device/abuse rules

Option B — RevenueCat promotional entitlement

Backend calls **RevenueCat REST API** to grant time-limited entitlement per `app_user_id` without store intro:

```
Register user3@… → logIn(3_user3@…) → Backend grants RC promotional entitlement 7 days
→ Backend sets Free Package + credits
```

Pros	Cons
Clean per-user RC record	Requires RC API integration
Webhook-friendly	More engineering

Option C — Hybrid (production pattern)

Account	Trial source
First on device	Store trial via paywall (current flow)
Same device, emails 2–10	Backend-only or RC promotional trial

Backend checks `device_token` / device fingerprint:

- First registration → normal paywall
- Additional accounts on same device → backend grants 7-day `Free Package` **without** store intro

---

Changes required vs today

Area	Today	For 10 trials
Register paywall	Store purchase → "trial activated"	Allow dashboard when **backend** grants trial
`revenuecate-success`	After store purchase	Also from register API **or** not required for backend trials
`free_trial_status`	From `getusercredit`	Set **active** per new user (with rules)
SubscriptionGate	Blocks if inactive	OK when backend sets active
Abuse control	Minimal	**Required** — limits per device

Example: all 10 get backend trial

```
user1@…  → Free Package, 7 days, 60 credits, free_trial_status=1
user2@…  → Same (same device_token OK)
…
user10@… → Same
```

After 7 days each user independently → inactive → must pay (one store sub per store account still applies at conversion).

Abuse controls (recommended)

- Max N trials per `device_token`
- Email verification before trial
- Reduced credits for additional accounts on same device
- Log `device_token` + `user_id` on registration

---

6. Backend webhook implementation

Webhook URLs

Environment	Example URL
Staging	`https://staging.territool.com/index.php/api/revenuecat/webhook`
Production	`https://app.territool.com/index.php/api/revenuecat/webhook`

Configure **Authorization secret** in RevenueCat dashboard; verify on every request.

Events to enable

`INITIAL_PURCHASE`, `RENEWAL`, `PRODUCT_CHANGE`, `CANCELLATION`, `UNCANCELLATION`, `EXPIRATION`, `BILLING_ISSUE`, optional `TEST`.

Product → package mapping (example)

```
// config/revenuecat_products.php
'com.territool.base.monthly' => [
    'package_name' => 'Base Package',
    'duration' => 'monthly',
    'credits_monthly' => 100,
],
'territool_pro_monthly' => [
    'package_name' => 'Pro Package',
    'duration' => 'monthly',
    'credits_monthly' => 120,
],
// Add every iOS + Android product id from RevenueCat dashboard
```

Handler outline (Laravel)

```
public function revenueCatWebhook(Request $request) {
    // 1. Verify Authorization
    // 2. Parse event; idempotency on event.id
    // 3. Resolve user from app_user_id
    // 4. GET subscriber from RevenueCat REST API
    // 5. syncUserSubscriptionFromRevenueCat($userId, $subscriber)
    // 6. Return 200
}
```

Refactor existing endpoint

`POST /api/revenuecate-success` should call the **same** `syncUserSubscriptionFromRevenueCat()` as the webhook (client nudge after purchase).

Recommended mobile addition: Call `revenuecate-success` after Settings paywall success for faster UI refresh.

---

7. Android Base → Pro upgrade (proration)

For **Base → Pro** on Android, the app uses:

```
Purchases.PRORATION_MODE.IMMEDIATE_AND_CHARGE_PRORATED_PRICE
```

	Meaning
IMMEDIATE	Pro access starts right away
CHARGE PRORATED PRICE	User pays price **difference** for remaining days in cycle
Same billing date	Renewal day unchanged (e.g. still the 1st each month)

Example: Base ₹999/mo → Pro ₹1,999/mo, upgrade mid-cycle → ~₹484 charge today (illustrative) → full Pro ₹1,999 on next renewal.

Pro → Base uses `DEFERRED` — change at **next billing date**.

iOS uses plain `purchasePackage`; Apple handles proration in the subscription group.

---

8. Security, idempotency & checklist

Security

- Verify RevenueCat webhook Authorization header
- RevenueCat secret API key **server only**
- Never trust client-sent `package_name`
- Validate Restore / transfer against original `app_user_id`

Idempotency

- Store `event.id` in `revenuecat_webhook_events` (unique index)
- Re-fetch subscriber on every webhook
- Prefer subscriber snapshot over event type when out-of-order

QA checklist (iOS + Android)

- [ ] New user store trial
- [ ] Trial → paid Base
- [ ] Base → Pro immediate upgrade
- [ ] Pro → Base deferred downgrade
- [ ] Cancel → active until expiration
- [ ] Expiration → SubscriptionGate
- [ ] Monthly renewal + credits
- [ ] Ten accounts same device (store vs backend trial behavior)

---

9. Quick reference tables

Store vs TerriTool vs RevenueCat

	Store (Apple/Google)	RevenueCat	TerriTool backend
Owns billing	Yes	Syncs	Credits + package label
Per email account	No (per store account)	Per `app_user_id`	Per user id
Intro trial limit	1 per rules	Reflects store	Can override with backend trial

When to use which trial strategy

Goal	Strategy
Normal production signup	Store trial + webhook + `revenuecate-success`
Multiple emails, one phone	Backend trial (Option A) or hybrid (Option C)
QA / internal testing	RC sandbox + backend trial flags
All 10 get 7 days	**Backend or RC promotional** — not 10 store intros

---

Document end

TerriTool — RevenueCat Subscriptions Guide v1.0
For questions: align product IDs in RevenueCat dashboard with `config/revenuecat_products.php` on the server and offering IDs in `subscribe.js` on mobile.