

```
Claude Code v2.1.74
Sonnet 4.6 · Claude Enterprise
~/Documents/Active/Northeastern University Academic Docs/Spring 2026/Vibe coding/HW4/MockReady

* Voice mode is now available · /voice to enable

* Conversation compacted (ctrl+o for history)

} /compact
  | Compacted (ctrl+o to see full summary)
  | Read claude.md (334 lines)
  | Read README.md (9 lines)
  | Skills restored (init)

} |

>> accept edits on (shift+tab to cycle)
```

```
• Explore (Explore session-related codebase files)
  | Done (12 tool uses · 37.6k tokens · 1m 4s)
  (ctrl+o to expand)

• The codebase is a pure skeleton - there is no implementation yet. Here's the current state:

What Exists
- claude.md / CLAUDE.md - fully written development guide
- docs/PROJ.md - complete product requirements (3310)
- backend/, frontend/, tasks/, docs/ directories with only .gitkeep files

What Needs to Be Built (Everything)

No session-related files exist yet - no models, schemas, services, routes, agents, or frontend components have been created. The entire implementation is pending.

---
To build the session history dashboard, we need to first lay the foundational layers. Here's what must exist before the dashboard can work:

1. Backend models - Session, SessionQuestion, EvaluationScore, User
2. Backend schemas - Pydantic response schemas for session list/detail
3. Backend service - session_service.py with a list_sessions(user_id) function
4. Backend route - GET /api/sessions endpoint
5. Frontend types - TypeScript types for sessions
6. Frontend API client - lib/api/sessions.ts
7. Frontend page - The actual dashboard UI at app/(candidate)/dashboard/page.tsx

Would you like me to start building this end-to-end, following TDD (tests first)? If so, I'll write a plan to tasks/todo.md first for your review before touching any implementation code.
```

To see the dashboard with real data you have two options:

Option A — Seed fake data directly in Supabase

Go to your Supabase dashboard → Table Editor, insert rows into sessions, session_questions, and evaluation_scores manually for the dev user (00000000-0000-0000-0000-000000000001).

Option B — Build US-C05 (session creation)

That's the next user story — it covers the interview flow: question generation, answer submission, and AI evaluation. Once built, the dashboard will populate automatically.

For now, the smoke test for US-C04 is effectively done — the dashboard loads, auth works, and the empty state renders correctly. Want me to mark 8.4 complete and close out the task?

› so the whole scope of all the phases was to just build a skeleton?

☒ No — the full read path is built and working:

- Backend: real FastAPI endpoints (/history, /trends, /{session_id}), SQLAlchemy ORM, Alembic migrations applied to your live Supabase DB, JWT auth, service layer with business logic
- Frontend: dashboard page, session detail page, trend chart with dimension lines, score breakdowns, empty state, loading/error states
- Tests: 22 backend + 29 frontend, all passing with >80% coverage

The only thing missing is data entry — the interview

session flow (US-C05+) where a candidate actually goes through questions and gets scored. US-C04 specifically says:

"View Session History Dashboard" — it's purely the read/display side.

Once you build the session creation flow in the next sprint, real sessions will show up in the dashboard automatically. The plumbing is all there.

› lets create it then

🔍 Searched for 1 pattern, read 2 files (ctrl+o to expand)

🔍 This is US-C01 + US-C02 + US-C03 combined — the full interview flow. Let me write the plan first before we touch any code.

🔍 Plan(Write session flow implementation plan)

```
└ Bash(cat /Users/dhruvgorasiya/Documents/Active/Northeastern\ University\ Academic\ Docs\Spring\2026\Vibe\coding\HW4\MockReady\backend\pyproject.toml)
Bash(ls /Users/dhruvgorasiya/Documents/Active/North
```

eastern\ University\ Academic\ Docs\ Spring\

2026\ Vibe\

coding\ HW4\ MockReady\ backend\ app\ agents\)

Read(~/Documents/Active/Northeastern University

Academic Docs\ Spring 2026\ Vibe

coding\ HW4\ MockReady\ frontend\ package.json)

+40 more tool uses (ctrl+o to expand)

└ Interrupted · What should Claude do instead?

› continue

 Write(~/Documents/Active/Northeastern University

Academic Docs\ Spring 2026\ Vibe

coding\ HW4\ MockReady\ tasks\ todo-session-flow.md)

└ Wrote 244 lines to

../tasks/todo-session-flow.md

1 # Task: Interview Session Flow (US-C01, U
S-C02, US-C03)

2

3 **PRD Reference:** US-C01 — Select Interv
iew Type and Role, US-C02 — Conduct a Pra
ctice Interview Session, US-C03 — Receive
Multi-Dimensional Feedback

4 **Branch:** `feature/session-flow`

5 **Status:** Planning

6

7 ---

8


9 ## Acceptance Criteria (from PRD)

... +234 lines (ctrl+o to expand)

 Plan written to tasks/todo-session-flow.md. Here's the breakdown:

10 phases total:

Phase	What
1	AgentLog model + migration
2	New Pydantic schemas (CreateSession, SubmitAnswer, AnswerFeedback)
3	3 AI agents with TDD (Question Generation, Answer Evaluation, Feedback Synthesis)
4	Service layer additions (create_session, submit_answer) with TDD
	Route handlers (POST /sessions, POST



Same rules apply — work one phase at a time, TDD throughout, confirm before moving to the next. Ready to start Phase 1?

✳ Cooked for 59s

› we dont need to do all the phases we just need to do the part which makes the new session work

☒ The minimum to make /sessions/new work end-to-end:

1. 3 AI agents — question generation, evaluation, feedback

2. 2 new service functions — create_session, submit_answer

3. 2 new routes — POST /sessions, POST /sessions/:id/questions/:qid/answer

4. Frontend — /sessions/new setup form + /sessions/[id]/interview interview screen

Skipping: AgentLog model, separate AnswerFeedback component, extensive phase-by-phase testing. Just build it working.

Want me to start now?

› yes

 Read 7 files (ctrl+o to expand)

 Good picture of the codebase. Let me build everything now — agents, service additions, routes, then frontend.

 Read 2 files (ctrl+o to expand)

Now I'll build everything. Starting with config, agents, schemas, service, routes, then frontend — all in sequence.

Update(app/core/config.py)

└ Added 1 line

```
11 )  
12 supabase_jwt_secret: str = "changem  
   e"  
13 anthropic_api_key: str = ""  
14 + claude_model: str = "claude-sonnet-  
   +4-6"  
15 cors_origins: list[str] = ["http://  
   localhost:3000"]  
16 dev_bypass_auth: bool = False  
17 dev_bypass_user_id: str = "00000000  
   -0000-0000-0000-0000000000001"
```

Now the three agents:

Write(app/agents/question_generation.py)

└ Wrote 46 lines to

app/agents/question_generation.py

```
1 import json
```

```
2
```

```
3 from anthropic import AsyncAnthropic
```



```
4
5 from app.core.config import settings
6
7 _client: AsyncAnthropic | None = None
8
9
10 def _get_client() -> AsyncAnthropic:
... +36 lines (ctrl+o to expand)
```

 Write(app/agents/answer_evaluation.py)

└ Wrote 60 lines to

app/agents/answer_evaluation.py

```
1 import json
2
3 from anthropic import AsyncAnthropic
4
5 from app.core.config import settings
6
7 _client: AsyncAnthropic | None = None
8
9
10 def _get_client() -> AsyncAnthropic:
... +50 lines (ctrl+o to expand)
```

 Write(app/agents/feedback_synthesis.py)

└ Wrote 64 lines to

app/agents/feedback_synthesis.py

```
1 import json
2
3 from anthropic import AsyncAnthropic
4
5 from app.core.config import settings
6
7 _client: AsyncAnthropic | None = None
8
9
10 def _get_client() -> AsyncAnthropic:
... +54 lines (ctrl+o to expand)
```

 Now add the new schemas:

 Update(app/schemas/session.py)

└ Added 48 lines

```
55
56 class TrendResponse(BaseModel):
57     points: list[TrendPoint]
58 +
59 +
60 +# --- Session creation ---
61 +
62 +
63 +class CreateSessionRequest(BaseModel):
```

```
64 + interview_type: InterviewType
65 + role: InterviewRole
66 + question_count: int = Field(default
    +t=3, ge=1, le=5)
67 +
68 +
69 +class QuestionInSession(BaseModel):
70 + id: UUID
71 + question_text: str
72 + order_index: int
73 +
74 +
75 +class SessionCreatedResponse(BaseModel
    +):
76 + id: UUID
77 + interview_type: InterviewType
78 + role: InterviewRole
79 + status: SessionStatus
80 + questions: list[QuestionInSession]
81 +
82 +
83 +# --- Answer submission ---
84 +
85 +
86 +class SubmitAnswerRequest(BaseModel):
87 + answer: str = Field(..., min_lengt
```

```

    +h=1)
88 +
89 +
90 +class DimensionFeedback(BaseModel):
91 +    clarity: str
92 +    depth: str
93 +    structure: str
94 +    relevance: str
95 +    communication_quality: str
96 +
97 +
98 +class AnswerFeedbackResponse(BaseModel
    +):
99 +    session_question_id: UUID
100 +    ai_scores: DimensionScores
101 +    composite_score: float
102 +    feedback_summary: str
103 +    dimension_feedback: DimensionFeedb
    +ack
104 +    improvement_suggestion: str
105 +    is_session_complete: bool

```

 Now add `create_session` and `submit_answer` to the service:

 Update(`app/services/session_service.py`)

└ Added 9 lines, removed 1 line

```
1 +import asyncio
2 +from datetime import datetime, timezone
3 from uuid import UUID
4
5 from fastapi import HTTPException, statu
   s
...
7 from sqlalchemy.ext.asyncio import Asyn
   cSession
8 from sqlalchemy.orm import selectinload
9
10 +from app.agents import answer_evaluatio
   +n, feedback_synthesis, question_generat
   +ion
11 from app.models.evaluation_score import
   EvaluationScore, ScoreedBy
12 -from app.models.question import Session
   -Question
13 +from app.models.question import Questio
   +n, SessionQuestion
14 from app.models.session import Session,
   SessionStatus
15 + from app.schemas.session import (
16 +     AnswerFeedbackResponse,
```

17 + DimensionFeedback,
18 DimensionScores,
19 + QuestionInSession,
20 QuestionResult,
21 + SessionCreatedResponse,
22 SessionDetail,
23 SessionHistoryResponse,
24 SessionSummary,

 Now update the agents `__init__.py` so imports resolve:

 Write(`app/agents/__init__.py`)

| Error writing file

 Read 1 file (ctrl+o to expand)

 Write(`app/agents/__init__.py`)

| Wrote 3 lines to `app/agents/__init__.py`

```
1 from app.agents import answer_evaluation,  
   feedback_synthesis, question_generation
```

```
2
```

```
3 __all__ = ["question_generation", "answer  
   _evaluation", "feedback_synthesis"]
```

 Now append `create_session` and `submit_answer` to the
service file:

Update(app/services/session_service.py)

└ Added 163 lines

```
195     )
196
197     return TrendResponse(points=points
198
199
200 + async def create_session(
201 +     db: AsyncSession, candidate_id: UU
202 +     +ID, request: CreateSessionRequest
203 + ) -> SessionCreatedResponse:
204 +     """Generate questions via AI and c
205 +     +reate a new session in in_progress sta
206 +     +te."""
207 +     raw_questions = await question_gen
208 +     +eration.generate_questions(
209 +     interview_type=request.intervi
210 +     +ew_type.value,
211 +     role=request.role.value,
212 +     question_count=request.questio
213 +     +n_count,
214 +     )
215 +
216 +
217 + # Create Session
```

```

211 + session = Session(
212 +     candidate_id=candidate_id,
213 +     interview_type=request.intervi
        +ew_type,
214 +     role=request.role,
215 +     status=SessionStatus.in_progre
        +ss,
216 +     started_at=datetime.now(timezo
        +ne.utc),
217 + )
218 + db.add(session)
219 + await db.flush() # get session.id
        + without committing
220 +
221 + questions_out: list[QuestionInSess
        +ion] = []
222 + for idx, q in enumerate(raw_questi
        +ons):
223 +     text = q.get("text", "")
224 +     # Persist the question to sati
        +sfy the FK constraint
225 +     question_row = Question(
226 +         text=text,
227 +         interview_type=request.int
        +erview_type.value,
228 +         role=request.role.value,

```



```
229 + )
230 + db.add(question_row)
231 + await db.flush()
232 +
233 + sq = SessionQuestion(
234 +     session_id=session.id,
235 +     question_id=question_row.i
    +d,
236 +     question_text=text, # sna
    +pshot
237 +     order_index=idx,
238 + )
239 + db.add(sq)
240 + await db.flush()
241 +
242 + questions_out.append(
243 +     QuestionInSession(id=sq.id
    +, question_text=text, order_index=idx)
244 + )
245 +
246 + await db.commit()
247 +
248 + return SessionCreatedResponse(
249 +     id=session.id,
250 +     interview_type=session.intervi
    +ew_type,
```

```

251 +     role=session.role,
252 +     status=session.status,
253 +     questions=questions_out,
254 + )
255 +
256 +
257 + async def submit_answer(
258 +     db: AsyncSession,
259 +     session_id: UUID,
260 +     question_id: UUID,
261 +     candidate_id: UUID,
262 +     answer: str,
263 + ) -> AnswerFeedbackResponse:
264 +     """Save answer, run evaluation + f
        + feedback agents in parallel, persist sc
        + ore."""
265 +     # Load session with questions
266 +     stmt = (
267 +         select(Session)
268 +         .where(Session.id == session_id, Session.candidate_id == candidate_id)
269 +         .options(selectinload(Session.questions).selectinload(SessionQuestion.evaluation_scores))
270 +     )

```

```

271 + result = await db.execute(stmt)
272 + session = result.scalar_one_or_non
    +e()
273 + if session is None:
274 +     raise HTTPException(status_cod
    +e=status.HTTP_404_NOT_FOUND, detail="S
    +ession not found")
275 +
276 + sq = next((q for q in session.ques
    +tions if q.id == question_id), None)
277 + if sq is None:
278 +     raise HTTPException(status_cod
    +e=status.HTTP_404_NOT_FOUND, detail="Q
    +uestion not found")
279 +
280 + if sq.candidate_answer is not None
    +:
281 +     raise HTTPException(
282 +         status_code=status.HTTP_40
    +9_CONFLICT, detail="Answer already sub
    +mitted"
283 +     )
284 +
285 + # Save the answer
286 + sq.candidate_answer = answer
287 + sq.submitted_at = datetime.now(tim

```

```

+ezone.utc)
288 + await db.flush()
289 +
290 + # Run evaluation and feedback agen
+ts in parallel
291 + eval_result, feedback_result = awa
+it asyncio.gather(
292 +     answer_evaluation.evaluate_ans
+wer(
293 +     question=sq.question_text,
294 +     answer=answer,
295 +     interview_type=session.int
+erview_type.value,
296 +     role=session.role.value,
297 + ),
298 +     feedback_synthesis.synthesize_
+feedback(
299 +     question=sq.question_text,
300 +     answer=answer,
301 +     scores={}, # will be fill
+ed after eval; feedback agent re-promp
+ts with context
302 +     reasoning={},
303 +     interview_type=session.int
+erview_type.value,
304 +     role=session.role.value,

```

```
305 +     ),
306 + )
307 +
308 + scores = DimensionScores(
309 +     clarity=eval_result["clarity"]
310 +     +,
311 +     depth=eval_result["depth"],
312 +     structure=eval_result["structu
313 +     +re"],
314 +     relevance=eval_result["relevan
315 +     +ce"],
316 +     communication_quality=eval_res
317 +     +ult["communication_quality"],
318 + )
319 +
320 + composite = round(
321 +     (scores.clarity + scores.depth
322 +     + + scores.structure + scores.relevance
323 +     + + scores.communication_quality)
324 +     / 5,
325 +     1,
326 + )
327 +
328 + evaluation_score = EvaluationScore
329 + +(
330 +     session_question_id=sq.id,
331 +     scored_by=ScoredBy.ai,
```

```
324 +     clarity=scores.clarity,
325 +     depth=scores.depth,
326 +     structure=scores.structure,
327 +     relevance=scores.relevance,
328 +     communication_quality=scores.c
    +ommunication_quality,
329 +     composite_score=composite,
330 +     reasoning=eval_result.get("rea
    +soning"),
331 + )
332 + db.add(evaluation_score)
333 +
334 + # Check if all questions are answe
    +red → complete the session
335 + all_answered = all(
336 +     q.candidate_answer is not None
    + or q.id == sq.id
337 +     for q in session.questions
338 + )
339 + if all_answered:
340 +     session.status = SessionStatus
    +.completed
341 +     session.completed_at = datetim
    +e.now(timezone.utc)
342 +
343 + await db.commit()
```

```

344 +
345 +   dim_feedback_raw = feedback_result
      +.get("dimension_feedback", {})
346 +   return AnswerFeedbackResponse(
347 +       session_question_id=sq.id,
348 +       ai_scores=scores,
349 +       composite_score=composite,
350 +       feedback_summary=feedback_resu
      +lt.get("feedback_summary", ""),
351 +       dimension_feedback=DimensionFe
      +edback(
352 +           clarity=dim_feedback_raw.g
      +et("clarity", ""),
353 +           depth=dim_feedback_raw.get
      +("depth", ""),
354 +           structure=dim_feedback_raw
      +.get("structure", ""),
355 +           relevance=dim_feedback_raw
      +.get("relevance", ""),
356 +           communication_quality=dim_
      +feedback_raw.get("communication_qualit
      +y", ""),
357 +       ),
358 +       improvement_suggestion=feedbac
      +k_result.get("improvement_suggestion",
      + ""),

```

```
359 +     is_session_complete=all_answer
      +ed,
360 + )
```

 Now add the two new routes:

 Update(app/api/v1/sessions.py)

```
|_ Added 9 lines, removed 1 line

7 from app.core.db import get_db
8 from app.core.security import get_current_user
9 from app.models.user import User
10 -from app.schemas.session import Session
    -Detail, SessionHistoryResponse, TrendResponse
    -sponse
10 +from app.schemas.session import (
11 +     AnswerFeedbackResponse,
12 +     CreateSessionRequest,
13 +     SessionCreatedResponse,
14 +     SessionDetail,
15 +     SessionHistoryResponse,
16 +     SubmitAnswerRequest,
17 +     TrendResponse,
18 +)
19 from app.services import session_service
```


20

```
21 router = APIRouter(prefix="/sessions",  
    tags=["sessions"])
```

 Update(app/api/v1/sessions.py)

└ Added 29 lines

```
21 router = APIRouter(prefix="/sessions",  
    tags=["sessions"])  
  
22  
23  
24 +@router.post("", response_model=Session  
    +CreatedResponse, status_code=201)  
25 +async def create_session(  
26 +    body: CreateSessionRequest,  
27 +    current_user: Annotated[User, Depen  
    +ds(get_current_user)],  
28 +    db: Annotated[AsyncSession, Depends  
    +(get_db)],  
29 +) -> SessionCreatedResponse:  
30 +    return await session_service.create  
    +_session(db, candidate_id=current_user.  
    +id, request=body)  
31 +  
32 +  
33 +@router.post(  
34 +    "/{session_id}/questions/{question_
```

```

+id}/answer",
35 + response_model=AnswerFeedbackRespon
    +se,
36 +)
37 +async def submit_answer(
38 + session_id: UUID,
39 + question_id: UUID,
40 + body: SubmitAnswerRequest,
41 + current_user: Annotated[User, Depen
    +ds(get_current_user)],
42 + db: Annotated[AsyncSession, Depends
    +(get_db)],
43 +) -> AnswerFeedbackResponse:
44 + return await session_service.submit
    +_answer(
45 +     db,
46 +     session_id=session_id,
47 +     question_id=question_id,
48 +     candidate_id=current_user.id,
49 +     answer=body.answer,
50 + )
51 +
52 +
53 @router.get("/history", response_model=
    SessionHistoryResponse)
54 async def get_session_history(

```

```
55  current_user: Annotated[User, Depen  
    ds(get_current_user)],
```

Now verify the backend starts without errors:

Bash(`cd "/Users/dhruvgorasiya/Documents/Active/Northeastern University Academic Docs/Spring 2026/Vibe coding/HW4/MockReady/backend" && uv run python -c "from app.mai..."`)

└ OK

Backend is good. Now the frontend — types, API client, setup page, interview page:

Read 2 files (ctrl+o to expand)

Update(`~/Documents/Active/Northeastern University Academic Docs/Spring 2026/Vibe coding/HW4/MockReady/frontend/lib/types/session.ts`)

└ Added 46 lines

```
56 export interface TrendResponse {  
57   points: TrendPoint[];  
58 }  
59 +  
60 +// --- Session creation ---  
61 +
```

```
62 +export interface QuestionInSession {
63 + id: string;
64 + question_text: string;
65 + order_index: number;
66 +}
67 +
68 +export interface CreateSessionRequest
    +{
69 + interview_type: InterviewType;
70 + role: InterviewRole;
71 + question_count?: number;
72 +}
73 +
74 +export interface SessionCreatedResponse
    +e {
75 + id: string;
76 + interview_type: InterviewType;
77 + role: InterviewRole;
78 + status: SessionStatus;
79 + questions: QuestionInSession[];
80 +}
81 +
82 +// --- Answer submission ---
83 +
84 +export interface SubmitAnswerRequest {
85 + answer: string;
```

```

86 +}
87 +
88 +export interface DimensionFeedback {
89 +  clarity: string;
90 +  depth: string;
91 +  structure: string;
92 +  relevance: string;
93 +  communication_quality: string;
94 +}
95 +
96 +export interface AnswerFeedbackRespons
    +e {
97 +  session_question_id: string;
98 +  ai_scores: DimensionScores;
99 +  composite_score: number;
100 +  feedback_summary: string;
101 +  dimension_feedback: DimensionFeedbac
    +k;
102 +  improvement_suggestion: string;
103 +  is_session_complete: boolean;
104 +}

```

 Update(~/Documents/Active/Northeastern University
 Academic Docs/Spring 2026/Vibe coding/HW4/MockRe
 ady/frontend/lib/api/sessions.ts)

└ Added 4 lines

```

1 import { apiFetch } from "@lib/api/client";
2 import type {
3   + AnswerFeedbackResponse,
4   + CreateSessionRequest,
5   + SessionCreatedResponse,
6   + SessionDetail,
7   + SessionHistoryResponse,
8   + SubmitAnswerRequest,
9   + TrendResponse,
10 } from "@lib/types/session";
11

```

 Update(~/Documents/Active/Northeastern University Academic Docs/Spring 2026/Vibe coding/HW4/MockReady/frontend/lib/api/sessions.ts)

└ Added 24 lines

```

27 export async function getScoreTrends(token: string): Promise<TrendResponse> {
28   return apiFetch<TrendResponse>(` ${BASE_URL}/trends`, {}, token);
29 }
30 +
31 +export async function createSession(
32 + request: CreateSessionRequest,
33 + token: string,

```

```

34 +): Promise<SessionCreatedResponse> {
35 + return apiFetch<SessionCreatedRespons
    +e>(
36 +   BASE,
37 +   { method: "POST", body: JSON.string
    +ify(request) },
38 +   token,
39 + );
40 +}
41 +
42 +export async function submitAnswer(
43 + sessionId: string,
44 + questionId: string,
45 + body: SubmitAnswerRequest,
46 + token: string,
47 +): Promise<AnswerFeedbackResponse> {
48 + return apiFetch<AnswerFeedbackRespons
    +e>(
49 +   `${BASE}/${sessionId}/questions/${q
    +uestionId}/answer`,
50 +   { method: "POST", body: JSON.string
    +ify(body) },
51 +   token,
52 + );
53 +}

```

• Now create the session setup page:

• Bash(mkdir -p "/Users/dhruvgorasiya/Documents/Active/Northeastern University Academic Docs/Spring 2026/Vibe coding/HW4/MockReady/frontend/app/(candidate)/sessions/ne...")

└ Done

• Write(~/Documents/Active/Northeastern University Academic Docs/Spring 2026/Vibe coding/HW4/MockReady/frontend/components/session/SessionSetupClient.tsx)

└ Wrote 108 lines to ../frontend/components/session/SessionSetupClient.tsx

```
1 "use client";  
2  
3 import { useState } from "react";  
4 import { useRouter } from "next/navigation";  
5 import { createSession } from "@lib/api/sessions";  
6 import type { InterviewType, InterviewRole } from "@lib/types/session";  
7  
8 const INTERVIEW_TYPES: { value: InterviewType; label: string }[] = [
```



```
9 { value: "behavioral", label: "Behavioral" },  
10 { value: "technical", label: "Technical" },  
... +98 lines (ctrl+o to expand)
```

Write(~/Documents/Active/Northeastern University
Academic Docs/Spring 2026/Vibe
coding/HW4/MockReady/frontend/app/(candidate)/sessions/new/page.tsx)

└ Wrote 5 lines to ../frontend/app/(candidate)/sessions/new/page.tsx

```
1 import SessionSetupClient from "@components/session/SessionSetupClient";  
2  
3 export default function NewSessionPage()  
4 {  
5   return <SessionSetupClient />;  
6 }
```

Now the interview session screen:

Write(~/Documents/Active/Northeastern University
Academic Docs/Spring 2026/Vibe
coding/HW4/MockReady/frontend/components/session/
InterviewSessionClient.tsx)

└ Wrote 267 lines to ../frontend/components/session/InterviewSessionClient.tsx

```
1 "use client";  
2  
3 import { useEffect, useRef, useState } from "react";  
4 import { useRouter } from "next/navigation";  
5 import { getSessionDetail, submitAnswer } from "@lib/api/sessions";  
6 import type {  
7   AnswerFeedbackResponse,  
8   QuestionInSession,  
9   SessionCreatedResponse,  
10 } from "@lib/types/session";  
... +257 lines (ctrl+o to expand)
```

 Write(~/Documents/Active/Northeastern University Academic Docs/Spring 2026/Vibe coding/HW4/MockReady/frontend/app/(candidate)/sessions/[id]/interview/page.tsx)

└ Wrote 13 lines to ../frontend/app/(candidate)/sessions/[id]/interview/page.tsx

```
1 import InterviewSessionClient from "@components/session/InterviewSessionClient";  
;
```

```
2
3 export default function InterviewSession
  Page({
4   params,
5 }): {
6   params: { id: string };
7 }} {
8   return (
9     <main className="mx-auto max-w-2xl p
      x-4 py-10">
10     <InterviewSessionClient sessionId=
      {params.id} />
... +3 lines (ctrl+o to expand)
```

 Now check TypeScript:

 Bash(`cd "/Users/dhruvgorasiya/Documents/Active/Northeastern University Academic Docs/Spring 2026/Vibe coding/HW4/MockReady/frontend" && npx tsc --noEmit`
`2>&1)`
└ (No output)

 Clean. Also update the EmptySessionState to link to the new /sessions/new route:

 Read 1 file (ctrl+o to expand)

🔵 EmptySessionState already links to /sessions/new.

Everything is wired up. Let me do a final import check on the backend:

🔵 Bash(cd "/Users/dhruvgorasiya/Documents/Active/Northeastern University Academic Docs/Spring 2026/Vibe coding/HW4/MockReady/backend" && uv run python -c "

from app.ag...)

└ All imports OK

🔵 Everything is built. Here's what was created:

Backend:

- agents/question_generation.py — calls Claude to generate 3 questions for the given role/type
- agents/answer_evaluation.py — scores answer on 5 dimensions with reasoning
- agents/feedback_synthesis.py — generates behavioral feedback + improvement tip
- session_service.create_session — generates questions, creates Session + Question + SessionQuestion rows
- session_service.submit_answer — saves answer, runs eval + feedback in parallel, persists score, marks

session complete on last question

- POST /api/v1/sessions and POST

/api/v1/sessions/{id}/questions/{qid}/answer

Frontend:

- /sessions/new — select interview type + role →

"Generating questions..." → redirects to interview screen

- /sessions/[id]/interview — shows question with 2-min timer, text input, submit → shows scores + feedback inline → next question → session complete screen → back to dashboard

Restart the backend and try

<http://localhost:3000/sessions/new>.

✱ Sautéed for 5m 15s

```
> ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^  
...<3 lines>...  
)  
^
```

File

"/Users/dhruvgorasiya/Documents/Active/Northeastern
University Academic Docs/Spring 2026/Vibe
coding/HW4/MockReady/backend/.venv/lib/python3.13/site-


```
{'type': 'error', 'error': {'type':  
'authentication_error', 'message': 'invalid  
x-api-key'}, 'request_id':  
'req_011CZKRqeWjUZtr5BpVjMVe9'}
```

🔵 The ANTHROPIC_API_KEY in .env is wrong — it has the JWT secret value instead of the actual API key. Check your .env:

🔵 Read 1 file (ctrl+o to expand)

🔵 The ANTHROPIC_API_KEY looks like it got corrupted — it contains what appears to be part of the JWT secret. You need to replace it with your real Anthropic API key.

Get it from console.anthropic.com → API Keys, then update .env:

```
ANTHROPIC_API_KEY=sk-ant-api03-<your-real-key>
```

Then restart the backend.

> ^

File

🔍 Read 1 file (ctrl+o to expand)

🔍 The key is there but Anthropic is rejecting it as invalid. Two things to check:

1. Did you restart the backend after saving .env? The server caches the config on startup — it won't pick up the new key until restarted.
2. Verify the key is valid — go to console.anthropic.com → API Keys and confirm that key is active and not revoked.

Kill the running backend (Ctrl+C) and restart:

```
uv run uvicorn app.main:app --reload --port 8000
```

>

▶ ▶ accept edits on (shift+tab to cycle)

Update available! Run: `brew upgrade claude-code`