

1. Declare a structure named Playlist to store details of a song: title (string), artist (string), and duration in seconds (integer). Initialize one Playlist variable with your favorite song's details and print each field.

```
#include <stdio.h>

struct Playlist
{
    char title[50];
    char artist[50];
    int duration;
};

int main()
{
    struct Playlist song = {"Tum Hi Ho", "Arijit Singh", 262};

    printf("Song Title: %s\n", song.title);
    printf("Artist: %s\n", song.artist);
    printf("Duration: %d seconds\n", song.duration);

    return 0;
}
```

Easy logic:

struct Playlist stores **title, artist, and duration** together.

2. Create a structure called FoodItem to store Zomato-style menu data: itemName (string), price (float), and rating (float). Initialize an array of 3 FoodItem variables with real menu items and display their details using a loop.

```
#include <stdio.h>

struct FoodItem
{
    char itemName[50];
    float price;
    float rating;
};

int main()
{
    struct FoodItem food[3] =
    {
        {"Pizza", 250.00, 4.5},
        {"Burger", 150.00, 4.2},
        {"Biryani", 220.00, 4.6}
    };

    for (int i = 0; i < 3; i++)
    {
        printf("\nFood Item: %s\n", food[i].itemName);
        printf("Price: %.2f\n", food[i].price);
        printf("Rating: %.1f\n", food[i].rating);
    }

    return 0;
}
```

Easy logic:

- food[3] stores details of **3 food items**.
- The for loop prints each item's details.

3. Define a nested structure called MovieShow for a BookMyShow-style app: Movie (string), Screen (integer), and a nested structure Time with hours and minutes (integers). Create and initialize a MovieShow variable for any movie and print its details in the format 'Movie: X, Screen: Y, Time: HH:MM'.

```
#include <stdio.h>
```

```
struct MovieShow
```

```
{
```

```
    char Movie[50];
```

```
    int Screen;
```

```
    struct Time
```

```
    {
```

```
        int hours;
```

```
        int minutes;
```

```
    } time;
```

```
};
```

```
int main()
```

```
{
```

```
    struct MovieShow show =
```

```
    {
```

```
        "Pushpa 2",
```

```
        3,
```

```

        {18, 30}
    };

    printf("Movie: %s, Screen: %d, Time: %02d:%02d",
        show.Movie,
        show.Screen,
        show.time.hours,
        show.time.minutes);

    return 0;
}

```

Output:

Movie: Pushpa 2, Screen: 3, Time: 18:30

Easy logic:

Here, Time is a **structure inside another structure** called MovieShow.

4. Build a structure called InstaProfile with fields: username (string), followers (integer), and a nested structure Bio with fields: description (string) and age (integer). Initialize an InstaProfile variable with your own details and display all fields.

```

#include <stdio.h>

struct InstaProfile
{
    char username[50];
    int followers;

    struct Bio

```

```
{
    char description[100];
    int age;
} bio;
};

int main()
{
    struct InstaProfile profile =
    {
        "dhruv_patel",
        1500,
        {"C Programming Student", 20}
    };

    printf("Username: %s\n", profile.username);
    printf("Followers: %d\n", profile.followers);
    printf("Bio: %s\n", profile.bio.description);
    printf("Age: %d\n", profile.bio.age);

    return 0;
}
```