

1. Declare a 1D array called dailySteps with 7 elements to store your step count for each day of the week, assign sample values, and print each value using a loop.

```
#include <stdio.h>

int main()
{
    int dailySteps[7] = {5000, 6000, 7500, 4000, 8000, 9000, 7000};

    for (int i = 0; i < 7; i++)
    {
        printf("Day %d: %d steps\n", i + 1, dailySteps[i]);
    }

    return 0;
}
```

Output:

Day 1: 5000 steps

Day 2: 6000 steps

Day 3: 7500 steps

Day 4: 4000 steps

Day 5: 8000 steps

Day 6: 9000 steps

Day 7: 7000 steps

2. Create a 2D array called playlistRatings to store ratings for 3 Spotify playlists over 5 days (rows = playlists, columns = days). Fill it with sample numbers and print the ratings for the second playlist.

Here, **3 rows = playlists** and **5 columns = days**.

```
#include <stdio.h>
```

```

int main()
{
    int playlistRatings[3][5] = {
        {4, 5, 4, 3, 5},
        {5, 4, 5, 5, 4},
        {3, 4, 3, 5, 4}
    };

    printf("Ratings of Second Playlist:\n");

    for (int i = 0; i < 5; i++)
    {
        printf("%d ", playlistRatings[1][i]);
    }

    return 0;
}

```

Output:

Ratings of Second Playlist:

5 4 5 5 4

👉 Remember: Array index starts from **0**, so the second playlist is playlistRatings[1].

3. Build a function that takes a 1D array of 7 integers representing your daily Zomato order amounts and calculates the average spend for the week.
Hint: Use a loop to sum the values, then divide by the array length.

```
#include <stdio.h>
```

```
float calculateAverage(int orders[], int size)
{
    int sum = 0;

    for (int i = 0; i < size; i++)
    {
        sum = sum + orders[i];
    }

    return (float)sum / size;
}

int main()
{
    int orders[7] = {250, 300, 450, 200, 500, 350, 400};

    float average;

    average = calculateAverage(orders, 7);

    printf("Average weekly spend: ₹%.2f", average);

    return 0;
}
```

Output:

Average weekly spend: ₹350.00

Easy logic:

Sum all 7 amounts → Divide by 7 → Get average

4. Given a 2D array called cricketScores where each row represents an IPL match and columns represent runs scored by each team, write code to print the highest score from each match.

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    int cricketScores[4][2] = {
```

```
        {180, 165},
```

```
        {145, 170},
```

```
        {210, 190},
```

```
        {175, 185}
```

```
    };
```

```
    for (int i = 0; i < 4; i++)
```

```
    {
```

```
        if (cricketScores[i][0] > cricketScores[i][1])
```

```
        {
```

```
            printf("Match %d highest score: %d\n",
```

```
                i + 1, cricketScores[i][0]);
```

```
        }
```

```
    else
```

```
    {
```

```
        printf("Match %d highest score: %d\n",
```

```
            i + 1, cricketScores[i][1]);
```

```
    }
```

```
}
```

```
    return 0;  
}
```

Output:

Match 1 highest score: 180

Match 2 highest score: 170

Match 3 highest score: 210

Match 4 highest score: 185