

Pile Turner SFZ1300LA



1. Machine Performance: Function for pile turner is: turner the paper; blowing; remove impurities; drying; alignment; stack jogger.

1.1. Use before the print:

1. clear paper and other impurities, improve the surface quality of the paper to be printed and reduce the double feed
2. due to improvement of the quality of the surface of the paper, printing machine speed can increase 3-5%, improve productivity.
3. greatly reduced the impurities and others into the printing machine, extend the life of the printing machine.
4. because the impurities abused by the decline, improve the yield 2-3%

This is an electronic message, hence signature not required.

Hyderabad

Pune

Vizag

Nairobi-kenya

1.2 After printing; secondary stations, paper cutter and die-cutting before use:

- 1.remove spray, clears dusting, accelerate ink drying, reducing the smell of ink solvent
- 2.prevent sticking, rub dirty and other quality problems
- 3.save a lot of labour

2.Design features:

- 1.Very stable steel frame design
- 2.Attractive design
- 3.Option for pallet truck
- 4.Closed, single part, strong vibrating table pallet
- 5.Maintenance-free slewing ring and cylinder bearing
- 6.Double air nozzles with overload slipping clutch can be controlled at operating console continuously
- 7.Stop-forward, reverse run of the air nozzle for removing single bow
- 8.Strong radial blowers with large air quantity
- 9.Powerful slipping device with direct drive
- 10.Stable collision and maintenance-free side stop with very large travel
- 11.Impact-free dropping of the ventilated stack through damped swivel cylinder
- 12.Hydraulic unlocking of the lifting frame
- 13.Optimal working height through relocation of pivot point
- 14.Highest operating comfort through two operating consoles

This is an electronic message, hence signature not required.

Hyderabad

Pune

Vizag

Nairobi-kenya

4.2 Configuration Listing

No	Name	Brand, specification & model	Origin of brand
1	Vibration Motor	GEFEG-NECKAR – DS 9060-2AY-RLT	Germany
2	PLC	Siemens S7-200CN	Germany
3	Air switch	(TE)-OSMC32N3C10	France
4	AC contactor	(TE)-LC1D09	France
5	Button	(TE)-ZB2	France
6	Photoelectric sensor	Autonics	Korea
7	Frequency Converter	E550	China
8	Power switch	(TE)-ABL 2REM24045H	France
9	Miniature Relay	(TE)-RXM2AB2BD	France
10	Hydraulic gear pump	Honor-HGP-1A-F2R-X	Taiwan
11	Cylinder	D90/d40-L230	China
12	Air pump	Geling-2RB720N-7HH47	Taiwan
13	Oil pump motor	ZLM-90L-4	China

4.3. Technical Parameter:

Model		SFZ1300LA
Plate Width	mm	1300
Max. Paper Size	mm	1200 x 900
Min. Paper Size	mm	500 x 400
Max. Layer Height	mm	1600
Min. Layer Height	mm	700
Max. Layer Weight	kg	2000
Gross Power	kw	12
Net Weight	kg	3400
Gross Weight	kg	3600
Machine Size (L x W x H)	mm	2920x2020x2220
Packing Size (L x W x H)	mm	3100x2200x2100

This is an electronic message, hence signature not required.

Hyderabad

Pune

Vizag

Nairobi-kenya