

Automatic Case Make Active Dual



All the Operations are Executed by the operator seated in front of the machine. The Operator passes the cover material into the gluing unit where it receives an even coating of hot gelatin glue. Utilizing foot switches, the operator controls the air suction plate for perfect registering of the cover material and to activate the board register bars. This allows accurate manual placement of the board places by the operator.

Turning in of the cover material on all four edges takes places in only two passes of the case by the operator. This process is enhanced by the use of brush rollers & pressing rollers an added benefit is that the 'active' model can also handle cases with a central window cut-out for photo album production. At this point the working process is completed and the final product is delivered to the rear of the machine on an inclined delivery table.

Technical Data: -

Min. case Size	100mm x 160mm
Max. Cse Size	450mm x 800mm
Paper Thickness	60gsm-170gsm
Board Thickness	1.5mm-5mm
Tuming-in Width	15mm-30mm
Production	350cases/hr.
Glue	Hot/cold (Optional)
Power	4.5 HP, 3 Phase, 415V
Dimensions	H1025mm X L2500mm X W1000mm
Weight	650Kgs.
Gluing system	Bottom
Man Power	One
Material	Paper, Laminated Paper, Plastic, Coated Paper, Clothe, etc.

This is an electronic message, hence signature not required.

Hyderabad

Pune

Vizag

Nairobi-kenya