

Automatic Spiral Binding and forming Machine



Advantages:

Forming different wires to spiral and binding into the book at the same time. Changing mould and tooth pitch can bind different specification of wire. Book binding and wire forming spiral finished at the same time. Convenience and efficiency after book binding completely, both ends can cut off and close up automatically. Books automatically drop into the collection tank after binding completely.

This is an electronic message, hence signature

Hyderabad

Pune

Vizag

Nairobi-kenya

Technical Parameters

Wire specifications	1/4"—1"
★ Running size over 5/8" diameter machine needed special order.	
Max.Binding Width	450×530mm
Min.Binding Width	130×85mm
Max.Binding Thickness	16mm
Working Speed	800—1300books/hour
Power Source	220V 1ph 50Hz
Machine Dimension	900×1400×1200mm
Weight	0.25T

Wire Chart

* Continuously steady tensile strength
* Eco-friendly coating offers excellent environmental protection;

DIAMETER	TOLERANCE	PACKAGES (KGS/ROLL)	TENSILE STRENGTH (N/mm ²)	METRE PER KG
0.70MM	+/-0.02MM	500+/-5%	710-780	394
0.80MM	+/-0.02MM	500+/-5%	710-780	294
0.90MM	+/-0.02MM	500+/-5%	710-780	228
1.00MM	+/-0.02MM	500+/-5%	680-750	182
1.05MM	+/-0.02MM	500+/-5%	680-750	168
1.10MM	+/-0.02MM	500+/-5%	660-750	149
1.15MM	+/-0.02MM	500+/-5%	660-750	136
1.20MM	+/-0.02MM	500+/-5%	630-750	124
1.25MM	+/-0.02MM	500+/-5%	630-750	110
1.30MM	+/-0.02MM	500+/-5%	610-680	105
1.40MM	+/-0.02MM	500+/-5%	600-680	86
1.50MM	+/-0.02MM	500+/-5%	570-590	78
2.00MM	+/-0.02MM	500+/-5%	680-800	40

This is an electronic message, hence signature

Hyderabad

Pune

Vizag

Nairobi-kenya