



PUBLIC

Document Version: 2511 – 2025-11

Operational Reporting API for Strategic Sourcing

Content

Operational Reporting API for Strategic Sourcing.	3
Usages of the Operational Reporting API for Strategic Sourcing.	4
Endpoints Included in the Operational Reporting API for Strategic Sourcing.	4
Query Parameters for the Operational Reporting API for Strategic Sourcing.	6
Date and Status Filters for the Operational Reporting API for Strategic Sourcing.	7
Workflow for Operational Reporting API for Strategic Sourcing.	7
Use of View Templates for the Operational Reporting API for Strategic Sourcing.	8
Creating a Client Application Using the Asynchronous Operational Reporting API for Strategic Sourcing.	16
Creating a Client Application Using the Synchronous Operational Reporting API for Strategic Sourcing.	20
Error Messages Returned by Reporting APIs.	21
API-Specific Disclaimers and Legal Information.	24

Operational Reporting API for Strategic Sourcing

This guide is for a customer developer who wants to extract and report on the transactional sourcing data you need to make operational decisions, using the Operational Reporting API for Strategic Sourcing.

Your client application filters the particular type of data you wish to extract by specifying transaction type, time-span, transaction status, and other considerations. These filters are included in reporting view templates. A particular view template is created only once, and persists in the system. The client application must specify the view by name with each API call.

You can request details including supported document types and attributes using the `/metadata` endpoint. For details about using `/metadata`, see [Use of the /Metadata Endpoint \[page 9\]](#).

This guide applies to:

- SAP Ariba APIs
- SAP Ariba Developer Portal
- SAP Ariba Sourcing

Restrictions

This API feature is available for customer use only. It is not available for partners.

You cannot modify a system view template; only custom view templates can be modified.

A valid API request for the Operational reporting API for strategic sourcing is always limited in the following ways:

- The maximum number of records returned is 10,000
- The maximum timespan for records returned is one year

Any API request attempting to exceed these restrictions will be rejected, and the response will include an error message. See [Error Messages Returned by Reporting APIs \[page 21\]](#) for the list of possible error messages.

Related Guides

[Help for the SAP Ariba Developer Portal](#)

[Usages of the Operational Reporting API for Strategic Sourcing \[page 4\]](#)

[Endpoints Included in the Operational Reporting API for Strategic Sourcing \[page 4\]](#)

[Query Parameters for the Operational Reporting API for Strategic Sourcing \[page 6\]](#)

[Date and Status Filters for the Operational Reporting API for Strategic Sourcing \[page 7\]](#)

[Workflow for Operational Reporting API for Strategic Sourcing \[page 7\]](#)

Usages of the Operational Reporting API for Strategic Sourcing

The Operational Reporting API for Strategic Sourcing can be used synchronously or asynchronously, and should not be confused with the Analytical Reporting API; the analytical API reports on facts and dimensions, while the Operational Reporting API for Strategic Sourcing reports on transactional data from sourcing documents.

The Operational reporting API for strategic sourcing enables you to extract and report on the transactional sourcing data that you need to make operational decisions, such as events scheduled to close in the next day, tasks due to be completed, documents awaiting approval, etc.

Asynchronous Versus Synchronous Usage

This API can be used synchronously to retrieve smaller data sets, or asynchronously to retrieve larger data sets.

In the asynchronous usage, requested output is batched into ZIP files containing 1000 records per file, and these files can be downloaded one at a time. The maximum number of records returned is 10,000, or 10 files containing 1000 records per file. Files created when submitting asynchronous requests expire after 48 hours.

In the synchronous usage, requested output is batched and paginated, and results are returned one page at a time in JSON format. The maximum number of records returned is 10,000. The maximum number of records per page is 50.

Endpoints Included in the Operational Reporting API for Strategic Sourcing

The Operational Reporting API for Strategic Sourcing includes endpoints for view template management and for asynchronous and synchronous reporting.

The Operational Reporting API for Strategic Sourcing includes the following sets of endpoints, each of which has its own discovery page on the SAP Ariba Developer Portal:

Operational Reporting for Sourcing - View Management API

Allows you to work with reporting view templates, which are used to specify the filters that determine what data will be returned in response to an API request using the Operational Reporting API for Strategic Sourcing. A reporting view template specifies the type of records to report on, the reporting fields to be included in the API response, and selection filters to select relevant records for inclusion.

Endpoint	Description
POST /viewTemplates/ {viewTemplateName}	Create a new view template.
GET /viewTemplates/ {viewTemplateName}	View the details of the specified view template.
GET /viewTemplates	View all view templates for a realm.
POST /viewTemplates/ {viewTemplateName}/patch	Update the specified view template.
GET /metadata	Request a list of all supported document types or a list of all filter and selection fields, either for a single document type or for all document types, that can be used to create custom view templates.

Operational Reporting for Sourcing - Job Submission API

Allows you to submit larger jobs for asynchronous processing, using reporting view templates.

Endpoint	Description
POST /jobs	Submit a job for asynchronous processing. To retrieve the output, use the Operational Reporting for Sourcing - Job Results API.

Operational Reporting for Sourcing - Job Results API

Allows you to request output from asynchronous jobs posted using the Operational Reporting for Sourcing - Job submission API. Requested output is batched into ZIP files containing 1000 records per file, and these can be downloaded one at a time.

Endpoint	Description
GET /jobs/{jobId}/files/{fileId}	Request ZIP files from the specified completed asynchronous operational reporting job, one ZIP file at a time.
GET /jobs/{jobId}	Request the status of the specified asynchronous operational reporting job.

Operational Reporting for Sourcing - Synchronous API

Allows you to submit smaller requests and receive results synchronously. In the synchronous usage, requested output is batched and paginated, and results are returned one page at a time.

Endpoint	Description
GET /views/{viewTemplateName}	Synchronously request output that satisfies the criteria in the specified view template. Output is batched and paginated, and JSON results are returned one page at a time.

Query Parameters for the Operational Reporting API for Strategic Sourcing

This topic lists supported query parameter for use with the Operational reporting API for strategic sourcing.

API requests can pass the following query parameters in the request URL:

Parameter	Description
<code>displayStateString</code>	Optional. By default, document status is returned as a numerical code. You can set this query parameter to <code>true</code> to receive a readable string status instead
<code>emitNull</code>	Optional. By default, API responses include NULL field values. You can set this query parameter to <code>false</code> to exclude NULL field values.
<code>filters</code>	Optional. The list of filters that determines what results to include in the response. Filters passed in the URL must be presented as a comma-separated list of key:value pairs. For example <pre>{"updatedAtFrom": "2017-06-19T00:00:00Z", "updatedAtTo": "2017-07-19T00:00:00Z"}</pre> Filters passed in the URL override filters passed in the JSON body of the request or in the view template. Note When specified in the URL, special characters in the filter list must be URL-encoded. The backslash character (\) must be double encoded, as follows: First, you must mark the character as literal by adding a second backslash character (\\). Then you must convert both characters to the URL code for a backslash, %5C. For example, URL encoding for <code>Directory2\Document2</code> would be <code>Directory2%5C%5CDocument2</code>.
<code>includeInactive</code>	Optional. By default, API responses do not include inactive transactions. You can set this query parameter to <code>true</code> to include inactive transactions in the responses.
<code>realm</code>	Required. The realm name.

Date and Status Filters for the Operational Reporting API for Strategic Sourcing

This topic lists date and status parameters used to filter the output returned in response to API requests to the Operational reporting API for strategic sourcing.

The following filter parameters can be used in view templates, passed in the request body, or included as part of the query URL:

Parameter	Description
<code>createdDateFrom</code>	Specify the document creation date range
<code>createdDateTo</code>	Dates for this parameter must be provided in the following format: <code>YYYY-MM-DDThh:mm:ssZ</code> . For example: <code>2016-07-07T00:00:00Z</code>
<code>status</code>	Status of the document. Permissible values vary based on document type. You can request a list of permissible values using the <code>/metadata</code> endpoint. See Use of /Metadata to Request a List of Selection Fields and Attributes for a Particular Document Type [page 11] .

Note

When specified in the URL, special characters in the filter list must be URL-encoded. The backslash character (\) must be double encoded, as follows: First, you must mark the character as literal by adding a second backslash character (\\). Then you must convert both characters to the URL code for a backslash, %53C. For example, URL encoding for `Directory2\Document2` would be `Directory2%53C%53CDocument2`.

Workflow for Operational Reporting API for Strategic Sourcing

Asynchronous Usage

1. Optional. If desired, a custom reporting view template is created or modified using web service calls.
2. The client application posts a job to the job queue, specifying a view template.
3. The client application polls the job status until the job is complete.
4. When the job is complete, output is batched into ZIP files containing up to the maximum records permitted by the system limit. If the number of records should exceed the system limit records are broken into pages containing up to the system maximum records. In this case, the response includes a page token that can be passed in the next query to retrieve the next page of records, and fields to help navigate and enumerate the results set.
5. The client application requests one file at a time.
6. Downloaded ZIP files are extracted and report data is processed as desired.

Note

This step is not executed using APIs.

Synchronous Usage

1. Optional. If desired, a custom view template is created or modified using web service calls.
2. The client application requests the first batch of report data, specifying a view template.
3. the client application requests subsequent batches of report data, as needed.
4. Report data is processed as desired.

Note

This step is not executed using APIs.

[Use of View Templates for the Operational Reporting API for Strategic Sourcing \[page 8\]](#)

[Creating a Client Application Using the Asynchronous Operational Reporting API for Strategic Sourcing \[page 16\]](#)

[Creating a Client Application Using the Synchronous Operational Reporting API for Strategic Sourcing \[page 20\]](#)

Use of View Templates for the Operational Reporting API for Strategic Sourcing

Reporting view templates are used to specify the filters that determine what data will be returned in response to an API request using the Operational reporting API for strategic sourcing. A reporting view template specifies the type of transaction to report on, the reporting fields to be included in the API response, and selection filters to select relevant transactions for inclusion.

For example, a view template for RFx documents could specify filters like `updatedAtFrom > 2017-10-01T00:00:00Z` to report on RFx documents updated after October 1, 2017. The response to a reporting API call would include the fields specified in the view template from RFx documents updated after October 1, 2017.

Note

In the sample URLs in this topic, replace `{{runtime_url}}` with the desired runtime URL from the **Environment Details** table on the SAP Ariba Developer Portal discovery page for this API.

Possible View Template Actions

- List the names and details of reporting views currently in the system for a particular document type using the `GET /viewTemplates` endpoint of the **Operational Reporting for Sourcing - View Management API**. You can specify the desired document type and status in the URL using the optional `documentType` and `status` parameters.

```
GET {{runtime_url}}/viewTemplates?
  realm={realm}&documentType={documentType}&status={status}
```

- Create a custom reporting view template using the `POST /viewTemplates/{viewTemplateName}` endpoint of the **Operational Reporting for Sourcing - View Management API**. Name the custom view template in the

URL and provide field and filter data in the request body. For a detailed example, see [Sample API Request to Create a Custom View Template \[page 14\]](#).

```
POST {{runtime_url}}/viewTemplates/{viewTemplateName}?realm={realm}
```

- Modify an existing custom view template using the POST `/viewTemplates/{viewTemplateName}/patch` endpoint of the **Operational Reporting for Sourcing - View Management API**. Provide the name of the custom view template to be modified in the URL, and provide fields and filter modifications in the request body.

```
POST {{runtime_url}}/viewTemplates/{viewTemplateName}/patch?realm={realm}
```

Note

You can only modify custom view templates. It is not possible to modify the default system view template.

To change the status of a custom reporting view template using this endpoint, pass the `status` parameter in the request body.

```
POST {{runtime_url}}/viewTemplates/{viewTemplateName}/patch?realm={realm}
Request body
{
  "status": "deactivated"
}
```

- View the details of a particular reporting view template using the GET `/viewTemplates/{template_name}` endpoint of the **Operational Reporting for Sourcing - View Management API**.

```
GET {{runtime_url}}/viewTemplates/{viewTemplateName}?realm={realm}
```

[Use of the /Metadata Endpoint \[page 9\]](#)

[View Template Structure \[page 12\]](#)

[Sample API Request to Create a Custom View Template \[page 14\]](#)

[Override of the Filter Values Passed in a View Template \[page 15\]](#)

Use of the /Metadata Endpoint

You can use the `/metadata` endpoint of the **Operational Reporting for Sourcing - View Management API** to request a list of all supported document types or a list of all filter and selection fields, either for a single document type or for all document types, that can be used to create custom view templates.

[Query Parameters for the /Metadata Endpoint \[page 10\]](#)

[Use of /Metadata to Request a List of Document Types \[page 11\]](#)

[Use of /Metadata to Request a List of Selection Fields and Attributes for a Particular Document Type \[page 11\]](#)

Query Parameters for the /Metadata Endpoint

Lists query parameters for the /metadata endpoint in the Operational reporting API for strategic sourcing.

This API supports the following query parameters:

Parameter	Description
realm	Required. The realm name.
documentType	Optional. If specified, the response contains only fields for the specified document type. If not specified, the response contains fields for all document types.
includeCustomFields	Optional. Default value is false . When true , the response to the /metadata query includes custom fields.
product	Required. Set value equal to ACM to limit results to fields relevant to the Operational reporting API for strategic sourcing.
select	Optional. Specifies which fields in the output will be populated and which will be null. Relevant fields are documentType, filterFields, and selectFields. Possible values of the select parameter are as follows: documentType returns a list of all supported document types. These are the supported values of the documentType parameter. filterFields returns a list of supported filter fields for the document type specified in the documentType parameter, or for all document types if documentType is not specified. selectFields returns a list of supported filter fields for the document type specified in the documentType parameter, or for all document types if documentType is not specified.
viewTemplateName	Optional. Restricts the output to include exactly the subset of the document schema that would be returned for the specified view template.

Note

You can specify more than one of these values by passing them in a comma-separated list. For example if you pass **select=documentType,selectFields**, both the **documentType** field and the **selectFields** field will be populated, but the **filterFields** field will have value **null**.

Use of /Metadata to Request a List of Document Types

Describes how to use /metadata to request a list of document types supported for use in the Operational reporting API for strategic sourcing.

Note

In the sample URLs in this topic, replace `{{runtime_url}}` with the desired runtime URL from the **Environment Details** table on the SAP Ariba Developer Portal discovery page for this API.

To request a list of document types construct a query according to the following model:

```
{{runtime_url}}/metadata?realm=myRealm&product=ACM&select=documentType
```

The query response is returned in JSON format, and it includes a complete list of document types in the `documentType` fields. These can be passed back in to the /metadata endpoint as values of the `documentType` query parameter.

-

Use of /Metadata to Request a List of Selection Fields and Attributes for a Particular Document Type

Describes how to use /metadata to request a list of selection fields and attributes for a particular document type, supported for use in the Operational reporting API for strategic sourcing.

Note

In the sample URLs in this topic, replace `{{runtime_url}}` with the desired runtime URL from the **Environment Details** table on the SAP Ariba Developer Portal discovery page for this API.

To request a list of selection fields and attributes for the Task document type, construct a query according to the following model:

```
{{runtime_url}}/metadata?realm=myRealm&documentType=Task&product=ACM
```

The query response is returned in JSON format, and it includes a list of all selection attributes, a list of all filter attributes, and the specified document type.

Note

If no document type is specified, the response includes all supported selection fields and attributes of all supported document types.

For each returned field, the response specifies its name and data type. For string fields, it includes the maximum length of the string in characters. For fields that accept only specific values, permissible values are specified in the `AllowedValues` section.

View Template Structure

View Template Elements

A view template has the following elements:

Element	Format	Description
viewTemplateName	String	The name of the view
type	Enum	system Predefined system view template
		custom Custom view template
status	Enum	published View templates in this status can be used for queries
		draft For use when designing the view template, before publication. Queries cannot be made against view templates in this status
		deactivated Queries cannot be made against view templates in this status
documentType	String	The type of transaction data this view template queries. Possible values are: • User • Organization • SourcingProject • Task • RFXItemValue • DocumentTask • RFXDocument • AuditEntry • ProjectAuditInfo • DynamicFormDocument_<templateName>

Note

The name of the DForms document type varies from company to company. To find the document name your company has assigned to DForms, use the GET /metadata endpoint to retrieve a list of document types. See [Use of /Metadata to Request a List of Document Types \[page 11\]](#) for instructions. In the response you can find the JSON block for DForms by searching for the prefix **DynamicFormDocument_**. The value of the **documentType** field in this block is the document type your company uses for DForms.

Element	Format	Description
selectAttributes	Collection<String>	The fields that will be included in the response to queries using this view template. Custom fields are supported. To specify a custom field, concatenate the prefix cus_ and the field name, as follows: cus_<fieldname>. For example, cus_mycustomfield.
filterExpressions	Collection<Object>	A collection of objects that defines filters for the view template. Each object contains name, field, op, and defaultValue elements. For example: <pre> { "filterExpressions": [{ "name": "createdDateFrom", "field": "TimeCreated", "op": ">=", "defaultValue": "2017-01-01T00:00:00Z" }, { "name": "createdDateTo", "field": "TimeCreated", "op": "<=", "defaultValue": "2017-01-10T00:00:00Z" }] }</pre>  Note At least one date filter (that is, a FROM filter and a TO filter, specifying a date range) is required in this parameter.
name	String	Element of a filter expression. A name given to this filter expression
field	String	Element of a filter expression. Specifies the field to which this filter expression applies
op	Enum	Element of a filter expression. The operator for the comparison to be performed in this filter expression. For a list of supported operators, see next table
defaultValue	Object	Element of a filter expression. A value to be applied to the filter expression in the absence of a request override

View Template Filter Operators

Filter expressions can use the following operators:

Operator	Description
AND	The logical intersection operator. Documents must meet both specified criteria to be included in the results set.
=	Arithmetic equality.
!=	Arithmetic inequality.

Operator	Description
<>	Arithmetic inequality.
>	Greater than.
<	Less than.
>=	Greater than or equal.
<=	Less than or equal.
LIKE	Has pattern.
NOT LIKE	Does not have pattern.
IN	Similar to the SQL IN operator. The value must be included in a set of values.
NOT IN	Similar to the SQL NOT IN operator. The value must not be included in a set of values.
IS NULL	The field is null.
IS NOT NULL	The field is not null.

Sample API Request to Create a Custom View Template

Include the fields and filters for a custom view template within the request body. The following example shows a request to create a custom view template, but you can use similar request body syntax with the `POST /viewTemplates/{template_name}/patch` endpoint of the **Operational Reporting for Sourcing - View Management API** for modification requests as well.

📌 Note

In the sample URLs in this topic, replace `{{runtime_url}}` with the desired runtime URL from the **Environment Details** table on the SAP Ariba Developer Portal discovery page for this API.

```
POST /viewTemplates/{template_name}?realm={realm}
```

Example

```
POST {{runtime_url}}/viewTemplates/myTaskView?realm=myRealm345
```

Request
body syn-
tax

```
{
  "viewTemplateName": "{template_name}"
  "type": "{system | custom}"
  "documentType": "{document type}"
  "status": "{draft | published | deactivated}"
  "selectAttributes": ["{field1}", "{field2}", {...}],
  "filterExpressions": [
    {
      "field": "{field name}",
      "op": "{operator}",
      "defaultValue": "{value}",
      "name": "{name}"
    },
    ...
  ]
}
```

Request
body ex-
ample

```
{
  "viewTemplateName": "myTaskView"
  "type": "custom"
  "documentType": "Task"
  "status": "draft"
  "selectAttributes": ["UniqueName", "StatusString", "TimeUpdated"],
  "filterExpressions": [
    {
      "field": "TimeUpdated",
      "op": "<=",
      "defaultValue": "2017-08-31T00:00:00Z",
      "name": "updatedAtTo"
    },
    {
      "field": "TimeUpdated",
      "op": ">",
      "defaultValue": "2017-08-01T00:00:00Z",
      "name": "updatedAtFrom"
    },
    {
      "field": "StatusString",
      "op": "IN",
      "defaultValue": ["Submitted", "Approved"],
      "name": "StatusInList"
    }
  ]
}
```

Override of the Filter Values Passed in a View Template

ⓘ Note

In the sample URLs in this topic, replace `{{runtime_url}}` with the desired runtime URL from the **Environment Details** table on the SAP Ariba Developer Portal discovery page for this API.

The API request can override the filter values specified in the view template by passing the `filters={filter_list}` parameter to the `/views/{viewTemplateName}` endpoint of the **Operational Reporting for Sourcing - Synchronous API**, as follows:

```
GET {{runtime_URL}}/views/{viewTemplateName}?realm={realm}&filters={filter_list}
```

Filter overrides should be presented as a comma-separated list of key:value pairs in JSON format. For example:

```
{"updatedAtFrom": "2017-06-19T00:00:00Z", "updatedAtTo": "2017-07-19T00:00:00Z"}
```

📌 Note

When specified in the URL, special characters in the filter list must be URL-encoded. The backslash character (\) must be double encoded, as follows: First, you must mark the character as literal by adding a second backslash character (\\). Then you must convert both characters to the URL code for a backslash, %5C. For example, URL encoding for `Directory2\Document2` would be `Directory2%5C%5CDocument2`.

Creating a Client Application Using the Asynchronous Operational Reporting API for Strategic Sourcing

Use this procedure to create a client application using the asynchronous Operational Reporting API for Strategic Sourcing. Choose the asynchronous usage for larger projects.

Context

📌 Note

In the sample URLs in this topic, replace `{{runtime_url}}` with the desired runtime URL from the **Environment Details** table on the SAP Ariba Developer Portal discovery page for this API.

📌 Note

When specified in the URL, special characters in the filter list must be URL-encoded. The backslash character (\) must be double encoded, as follows: First, you must mark the character as literal by adding a second backslash character (\\). Then you must convert both characters to the URL code for a backslash, %5C. For example, URL encoding for `Directory2\Document2` would be `Directory2%5C%5CDocument2`.

Follow these steps to create a client application using the asynchronous Operational reporting API:

Procedure

For the first page of results, follow these steps:

1. Choose a view template. If necessary, you can browse existing view templates using the `/viewTemplate/{template_name}` endpoint of the **Operational Reporting for Sourcing - View Management API**.

```
GET {{runtime_url}}/viewTemplate/{viewTemplateName}?realm={realm}
```

2. Optional. You can find out how many records will be included in the results set for a query using the specified view template and filters using the `GET /views/{viewTemplateName}/count` endpoint of the **Operational Reporting for Sourcing - Synchronous API**.

```
GET {{runtime_url}}/views/{template_name}/count?
realm={realm}&filters={filter_list}
```

Note

The record count returned represents the number of relevant records at the time of the call. In the unlikely case that your asynchronous workflow takes long enough for records to be generated or deleted, this count could change.

The response includes the following fields:

count	The total number of records that would be included in the results set using the specified view template and filters.
MaxRecordsInEachPage	The maximum number of records that can be returned in a single page of results. Note that a page might contain fewer records than this maximum.
TotalPages	The total number of pages in the results set.

3. Post the initial request to the jobs queue, using the `POST /jobs` endpoint of the **Operational Reporting for Sourcing - Job Submission API**, specifying the desired view and request ID.

```
POST {{runtime_url}}/jobs?realm={realm}

Request body: {
  "viewTemplateName": "ChosenViewName",
  "filters": {filter_list},
  "requestID": "myRequestID"
}
```

Note

Request filters must specify at least one timespan of 31 or fewer days.

The response includes the following fields:

requestID	The request ID you specified in the <code>requestID</code> parameter.
jobID	A system-generated job ID.

4. Query the status of your job using the `GET /jobs/{job_id}` endpoint of the **Operational Reporting for Sourcing - Job Results API**.

```
GET {{runtime_url}}/jobs/{job_id}?realm={realm}
```

This returns the job status, which can be one of the following:

- pending
- processing
- completed
- errorMaxReached
- errorInternal
- completedZeroRecords
- errorInvalidDateRange

When the status is **completed**, the job is complete, and output is batched into files. The response body includes the following fields:

files	A list of file IDs for the first page of files in your results set. Use these as the value of the fileID parameter in queries to download each file.
pageToken	A token you can pass as the value of the pageToken parameter in a subsequent query to request the next page of results.
requestID	The request ID you specified in the requestID parameter when you posted this job.
TotalNumOfRecords	The approximate total number of records in the response set, including records in the current response and all other responses that belong to the current results set.
TotalNumOfRecordsProcessed	The total number of records processed in the response set.
CurrentPageRecordsCount	The number of records included in the current page.
TotalNumOfPages	The total number of pages associated with the current results set.
CurrentPageNum	The number of the current page in the sequence of pages associated with the current results set. The response to the initial POST /jobs query is 1.
TotalNumOfFiles	Records are returned in the form of links to ZIP files, with each ZIP file containing up to the maximum permitted number of records. This field indicates the total number of ZIP file links in the results set.
FilesInCurrentPage	This field indicates the total number of ZIP file links in the current page.

5. Request files one at a time using the **GET /jobs/{job_id}/files/{file_id}** endpoint of the **Operational Reporting for Sourcing - Job Submission API**.

```
GET {{runtime_url}}/jobs/{job_id}/files/{file_id}?realm={realm}
```

Files are returned in ZIP format. Repeat this step for all desired file IDs.

For subsequent pages, follow these steps:

6. Post the request for the next page of results to the jobs queue, using the **POST /jobs** endpoint of the **Operational Reporting for Sourcing - Job Submission API**, adding the page token returned in the response to the previous **GET /jobs/{jobID}** query:

```
POST {{runtime_url}}/jobs?pageToken={pageToken}&realm={realm}
Request body:{
  "viewTemplateName":"ChosenViewName",
  "filters":{filter_list},
  "requestID":"myRequestID"
}
```

7. Request the status of your job, using the GET /jobs/{jobID} of the **Operational Reporting for Sourcing - Job Results API**:

```
GET {{runtime_url}}/jobs/{jobID}?realm={realm}
```

Note

Passing the value of the jobID from your POST /jobs response as the value of the jobID parameter in this query informs the system what page of results you want, because the POST /jobs query specified that information in the pageToken parameter.

The response includes the file IDs for the specified page in the files block, and the page token for the next page of results in the pageToken field. The response also includes the lastModified attribute when sourcing events' timings are modified.

8. Request files one at a time using the /jobs/{jobID}/files/{fileID} endpoint of the **Operational Reporting for Sourcing - Job Results API**:

```
GET {{runtime_url}}/jobs/{jobID}/files/{fileID}?realm={realm}
```

Repeat this step for all desired file IDs.

The response includes the lastModified attribute when sourcing events' timings are modified.

9. Repeat this procedure until you reach the final page of results. When you reach the last page of results, the value of the pageToken field returned by the GET /jobs/{jobID} query is NULL because there are no subsequent pages in the response set.

Results

You can extract retrieved files and process the data as desired. Extraction and data processing are not executed using the APIs.

Creating a Client Application Using the Synchronous Operational Reporting API for Strategic Sourcing

Use this procedure to create a client application using the synchronous Operational Reporting API for Strategic Sourcing. Choose the synchronous usage for smaller projects.

Context

Note

In the sample URLs in this topic, replace `{{runtime_url}}` with the desired runtime URL from the **Environment Details** table on the SAP Ariba Developer Portal discovery page for this API.

Note

When specified in the URL, special characters in the filter list must be URL-encoded. The backslash character (`\`) must be double encoded, as follows: First, you must mark the character as literal by adding a second backslash character (`\\`). Then you must convert both characters to the URL code for a backslash, `%5C`. For example, URL encoding for `Directory2\Document2` would be `Directory2%5C%5CDocument2`.

Follow these steps to create a client application using the synchronous Operational reporting API for strategic sourcing:

Procedure

1. Choose a view template. If necessary, you can browse existing view templates using the `/viewTemplates/{viewTemplateName}` endpoint of the *Operational Reporting for Sourcing - View Management API*.

```
GET {{runtime_url}}/viewTemplate/{viewTemplateName}?realm={realm}
```

2. Optional. You can find out how many records will be included in the results set for a query using the specified view template and filters using the `GET /views/{viewTemplateName}/count` endpoint of the **Operational Reporting for Sourcing - Synchronous API**.

```
GET {{runtime_url}}/views/{template_name}/count?
realm={realm}&filter={filter_list}
```

The response includes the following fields:

count	The total number of records that would be included in the results set using the specified view template and filters.
MaxRecordsInEachPage	The maximum number of records that can be returned in a single page of results. Note that a page might contain fewer records than this maximum.
TotalPages	The total number of pages in the results set.

3. Request the first batch of report data, using the `/views/{viewTemplateName}` endpoint of the *Operational Reporting for Sourcing - Synchronous API*. If desired, you can override the default filters in the URL.

```
GET {{runtime_url}}/views/{viewTemplateName}?realm={realm}&filters={filter_list}
```

Note

Request filters must specify at least one timespan of 31 or fewer days.

The response includes the `lastModified` attribute when sourcing events' timings are modified.

4. To request subsequent batches of report data, pass the `pageToken` parameter to the `/views/{viewTemplateName}` endpoint of the *Operational Reporting for Sourcing - Synchronous API*. Use the `pageToken` value returned in the previous request.

```
GET {{runtime_url}}/views/{viewTemplateName}?  
realm={realm}&filters={filter_list}&pageToken={page_token}
```

5. Process report data as desired.

Note

This step is not performed using the APIs.

Error Messages Returned by Reporting APIs

If a submitted API query fails, the response body contains one of the error codes in this topic.

HTTP Code	Error Code	Error Message
400	The API key passed in the request is not valid.	The API key passed in the query headers does not match the API key in the OAuth token.
400	containsEmptyRecord	Contains empty record.
400	containsLargeNumberOfRecords	Number of records exceeds maximum allowed.
400	DuplicateFilterExpressionName	Duplicate filter expression name.
400	featureNoteEnabled	The Reporting Data feature is not enabled.
400	filtersInvalidForView	Filters are invalid for the view provided.
400	fromDateGreater	From date is greater than to date for date filter key.
400	fromValueGreater	From date is greater than to date for date filter key: <filter key>.
400	invalidAttachmentId	Invalid attachment ID
400	invalidBodyFormat	Invalid body format

HTTP Code	Error Code	Error Message
400	invalidDateFormat	Invalid date format. Valid date format is YYYY-MM-DDThh:mm:ssZ
400	invalidDocumentType	Invalid documentType.
400	invalidEnumValue	Invalid enum value.
400	invalidFilter	Invalid filter for the view passed.
400	invalidFilterExpr	Invalid filter expression.
400	invalidFilterStructure	Invalid filter structure.
400	invalidFilterValue	Invalid default value/over-riding value.
400	invalidSelectAttr	Invalid select attributes.
400	invalidViewStatus	Invalid view status.
400	invalidViewTemplateName	Only alphanumeric and '_' characters are allowed in viewName.
400	jobNotCompleted	Job status not completed.
400	missingDateFilter	No valid date filter found.
400	missingDocumentType	Missing required parameter: documentType.
400	missingField	Missing required parameter: field.
400	missingFilterExpr	Missing required parameter: filter expression.
400	missingJobId	Missing required parameter: JobId.
400	missingOneDate	Date range incomplete
400	missingSelectAttr	Missing required parameter: select attributes.
400	missingValueForDateFilter	Missing value for date filter key: <filter key>/ key>/
400	missingViewTemplateName	viewTemplateName is required.
400	quotaExceeded	Reached maximum records that can be imported.
400	realmInvalid	Realm invalid
400	requiredParamNotProvided	One or more required parameters not provided.
400	unsupportedFilter	One or more filters are not supported.
400	viewAlreadyExists	View already exists.
401	unauthorized	Request unauthorized.
404	fileNotFound	File not found.
404	jobNotFound	Job not found.

HTTP Code	Error Code	Error Message
404	viewNotFound	View not found.
404	viewTemplateNotFound	viewTemplate not found.
500	failedToCreateView	Failed to create reporting view.

API-Specific Disclaimers and Legal Information

The SAP Ariba Developer Portal included in the SAP Ariba APIs product and the APIs made available on this site are provided solely at the discretion of SAP without warranty of any kind, and SAP may change, suspend, or cancel any or all features or functions of the SAP Ariba APIs product or revise the website at any time. Any production use of or commercialization of applications containing any APIs provided on this website is prohibited without a written agreement between your company and SAP governing such activities.

Access to this API is available to you as a subscriber to this solution as part of the SAP Cloud Service Level Agreement. However, it is not considered part of the solution. Use of this API is purely optional and is subject to restrictions stated in the documentation, including the Terms of Use and the documentation found at the SAP Ariba Developer Portal (see <https://developer.ariba.com/api>). If you wish to connect a third-party service using this API, first confirm that the company is participating in the SAP partner program and is authorized to provide a connection to this solution using this API. You will be required to submit written consent to SAP to authorize the exchange of data with the third-party service.

Important Disclaimers and Legal Information

Hyperlinks

Some links are classified by an icon and/or a mouseover text. These links provide additional information.

About the icons:

- Links with the icon  : You are entering a Web site that is not hosted by SAP. By using such links, you agree (unless expressly stated otherwise in your agreements with SAP) to this:
 - The content of the linked-to site is not SAP documentation. You may not infer any product claims against SAP based on this information.
 - SAP does not agree or disagree with the content on the linked-to site, nor does SAP warrant the availability and correctness. SAP shall not be liable for any damages caused by the use of such content unless damages have been caused by SAP's gross negligence or willful misconduct.
- Links with the icon  : You are leaving the documentation for that particular SAP product or service and are entering an SAP-hosted Web site. By using such links, you agree that (unless expressly stated otherwise in your agreements with SAP) you may not infer any product claims against SAP based on this information.

Videos Hosted on External Platforms

Some videos may point to third-party video hosting platforms. SAP cannot guarantee the future availability of videos stored on these platforms. Furthermore, any advertisements or other content hosted on these platforms (for example, suggested videos or by navigating to other videos hosted on the same site), are not within the control or responsibility of SAP.

Beta and Other Experimental Features

Experimental features are not part of the officially delivered scope that SAP guarantees for future releases. This means that experimental features may be changed by SAP at any time for any reason without notice. Experimental features are not for productive use. You may not demonstrate, test, examine, evaluate or otherwise use the experimental features in a live operating environment or with data that has not been sufficiently backed up.

The purpose of experimental features is to get feedback early on, allowing customers and partners to influence the future product accordingly. By providing your feedback (e.g. in the SAP Community), you accept that intellectual property rights of the contributions or derivative works shall remain the exclusive property of SAP.

Example Code

Any software coding and/or code snippets are examples. They are not for productive use. The example code is only intended to better explain and visualize the syntax and phrasing rules. SAP does not warrant the correctness and completeness of the example code. SAP shall not be liable for errors or damages caused by the use of example code unless damages have been caused by SAP's gross negligence or willful misconduct.

Bias-Free Language

SAP supports a culture of diversity and inclusion. Whenever possible, we use unbiased language in our documentation to refer to people of all cultures, ethnicities, genders, and abilities.

Copyright © 2025 Ariba, Inc. All rights reserved.

This documentation, as well as the Ariba solutions, software and/or services described in it, contain proprietary information. They are provided under a license or other agreement containing restrictions on use and disclosure and are also protected by copyright, patent and/or other intellectual property laws. Except as permitted by such agreement, no part of the document may be reproduced or transmitted in any form by any means, electronic, mechanical or otherwise, without the prior written permission of Ariba, Inc.

Ariba, Inc. assumes no responsibility or liability for any errors or inaccuracies that may appear in the documentation. The information contained in the documentation is subject to change without notice.

Ariba and Ariba products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of Ariba, Inc. in the United States and other countries. Please see <http://www.ariba.com/legal/trademarks> for additional trademark information and notices.

Ariba Sourcing solutions (On Demand and software) are protected by one or more of the following patents, including without limitation: U.S. Patent Nos. 6,199,050; 6,216,114; 6,223,167; 6,230,146; 6,230,147; 6,285,989; 6,408,283; 6,499,018; 6,564,192; 6,871,191; 6,952,682; 7,010,511; 7,072,061; 7,130,815; 7,146,331; 7,152,043; 7,225,152; 7,277,878; 7,249,085; 7,283,979; 7,283,980; 7,296,001; 7,346,574; 7,383,206; 7,395,238; 7,401,035; 7,407,035; 7,444,299; 7,483,852; 7,499,876; 7,536,362; 7,558,746; 7,558,752; 7,571,137; 7,599,878; 7,634,439; 7,657,461; 7,693,747; 8,364,577; and 8,392,317. Patents pending.

Other Ariba product solutions are protected by one or more of the following patents:

U.S. Patent Nos. 6,199,050, 6,216,114, 6,223,167, 6,230,146, 6,230,147, 6,285,989, 6,408,283, 6,499,018, 6,564,192, 6,584,451, 6,606,603, 6,714,939, 6,871,191, 6,952,682, 7,010,511, 7,047,318, 7,072,061, 7,084,998; 7,117,165; 7,225,145; 7,324,936; 7,536,362; 8,364,577; and 8,392,317. Patents pending.

Certain Ariba products may include third party software or other intellectual property licensed from a third party. For information regarding software or other intellectual property licensed from a third party, go to <http://www.ariba.com/copyrights.cfm>.

