

# # Enterprise Java #

## Stateful Session Bean & Stateless Session Bean

### How to create :-

- ⇒ Java with maven -> EJB module -> Finish
- ⇒ In Source Packages -> new package -> named(ejbStates)-> New -> Other -> Enterprise JavaBeans ->Session Bean -> named (StatefulBean)
- ⇒ If Session Bean make Stateless or Stateful according option select -> Local (if want Local Bean creation)
- ⇒ StatefulLocalBean , StatefulBean , StatelessBean , StatelessLocalBean
- ⇒ Make Servlet -> (package)ejbStatesServlets -> Client1Servlet and Client2Servlet

### What is a Session Bean (EJB)?

- A Session Bean is a business logic component.
- It does not handle HTTP requests directly.
- **Types:**
  - **Stateless** → No client-specific state; shared by all clients.
  - **Stateful** → Keeps state per client (like shopping cart).
  - **Singleton** → One instance per application.

### What is a Servlet?

- A **Servlet** is a **web component** that **handles HTTP requests and responses**.
- It sits in the **web layer** and talks directly with the client (browser, Postman, etc.).

- It can call **EJBs** to perform business logic.

⇒ **Servlet** = deals with HTTP request, prepares response (HTML, JSON, etc.).

⇒ **EJB** = performs the logic (calculation, DB access, transaction).

## Why do we need both?

Think in **layers**:

- **Servlets (Web Layer):**
  - Entry point for HTTP clients.
  - Handles GET, POST, query parameters, cookies, sessions, etc.
  - Responsible for presentation/output.
- **EJBs (Business Layer):**
  - Encapsulate reusable **business logic**.
  - Manage transactions, concurrency, security, pooling, etc.
  - Can be reused from Servlets, REST endpoints, other EJBs, or even remote clients.

**EJB** = business logic, no HTTP knowledge

**Servlet** = web interface, talks HTTP, calls EJBs

- You need both:
- Servlet = “front desk”
- EJB = “back office”