

Mechanical Assembly and Retention Record

A synthetic controlled-drawing extract for testing design-intent retrieval. It is not an actual engineering drawing and contains no fabrication dimensions.

Document ID	Incident	Record type	Status
R3-EV-003	R3 carrier beam - 10/14/2024	Application test evidence	Synthetic / controlled

Synthetic drawing notes

Feature	Test-scenario design statement	Evidence role	Status
Carrier beam / link connection	The carrier beam remains connected to the link by a pinned joint. The keeper retains that pin.	Explains why beam, link, and keeper could be recovered together.	Synthetic scenario fact
Link / yoke interface	The upper link surface rests in an open yoke pocket during the normal supported position.	Defines a possible lift-out or unseating path that must be evaluated from geometry and marks.	Synthetic scenario fact
Keeper function	The keeper is not a positive hold-down over the yoke pocket.	Separates 'keeper present' from 'link positively retained in yoke.'	Synthetic scenario fact
Outage position	When rolls are absent and the balance is raised, the carrier-beam assembly requires either the specified supported state or a rated temporary restraint before hydraulic pressure is removed.	Creates a procedure/design requirement to compare with field execution.	Synthetic scenario fact
Permitted clearances	No acceptance dimensions are included in this extract.	Full drawing and OEM tolerances remain necessary for dimensional conclusions.	Open / request full drawing

Revision and authority

Drawing reference	Revision	Approval	Limitation
R3-RB-ASM-SYN-001	Test Rev A	Synthetic evidence author	For application evaluation only; not valid for field work.