R2 · RAG Corpus Poisoning — Attack & Defense

Project brief · njt11682@gmail.com · drafted 2026-09-21

Status: Weeks 1–2 complete (corpus, gold set, clean RAG baseline). Weeks 3–4 pending (poison authoring, attack sweep, defense, live demo).

- Clean answer accuracy: **76.0%** (38/50)
- Retrieval-hit rate: **100%** (50/50)
- Attack success rate, defended ASR, utility cost: **TBD** — require the poison set


Objective

Build a retrieval-augmented QA system over a self-scraped corpus, then attack it: inject adversarial documents crafted to (a) win retrieval for a targeted question and (b) push the reader toward a specific false answer. Measure attack success rate as a function of poison count, poison style, and corpus size. Then defend with consistency voting and provenance scoring, and measure how much accuracy the defense recovers and what it costs on clean queries. Framed explicitly as a **defensive evaluation of our own corpus** — every poison document is self-authored and injected into our own index, no third-party system is targeted.

Applications

RAG security auditing before deployment · integrity checks for enterprise knowledge bases that ingest from open or web-scraped sources · robustness testing against SEO-style content designed to be retrieved · a reusable red-team harness (corpus + gold set + injectable poison) for any RAG stack · provenance/consistency scoring as a retrieval-time filter, independent of this specific corpus.

System & Pipeline



Poison injection — live `Index.add()` appends poison vectors with `np.vstack`, no rebuild: this is what lets the demo flip the answer in real time.

Defense — sits between retrieve and read: consistency voting across retrieved chunks and provenance scoring, filtering or down-weighting suspicious chunks before generation. Not yet implemented.

Dataset

Piece	Status	Detail
corpus.jsonl	**done**	125 Wikipedia chemical-element articles (MediaWiki API, ≥500 chars each, CC BY-SA)
gold.jsonl	**done**	50 questions: question, correct_answer (verbatim in source article), source_title, attacker_target

poison.jsonl	**pending**	150 docs planned — 3 per question × styles keyword / natural / authoritative. The original contribution.

Gold-set integrity is enforced by an automated check (`test_r2.py`): every correct_answer appears verbatim in its cited article, every cited article is retrievable in top-5 under a clean index, and every attacker_target is absent from that clean top-5 context — so a poison flip, when it happens, is attributable to the poison and not to an already-ambiguous question.

Desired Outcomes

· A released poison set (150 docs, 3 styles) that is retrieved and believed at measurable rates.
· An attack-success curve across poison count (1/3/5/10) and style, on the current 125-article corpus and at least one larger corpus size.
· A defense that recovers a stated share of poisoned-and-flipped answers at a stated, small cost to clean accuracy.
· A live Gradio demo replaying three visible states — correct → poisoned → defended — from the cached generations (`gen_cache`), network off.

Evaluation Metrics — Targets

Definitions are fixed by the code below; numeric targets are set where a baseline already exists and left TBD where they depend on the week-4 poison sweep.

Metric	Definition	Now / Target
Clean accuracy	Normalized substring match (casefold, punctuation→space, number-word↔digit) of correct_answer in the generated answer, no poison present	**76.0%**
Retrieval-hit rate	source_title present among top-5 retrieved chunk sources	**100%**
Attack success rate (ASR)	Share of questions where attacker_target appears in the generated answer once poison is present	**TBD**
Poison retrieval rate	Share of poisoned questions where ≥1 poison chunk enters top-5 — separates a retrieval failure from a reader failure	**TBD**
Defended ASR	ASR measured again with the defense enabled — the residual attack surface	**TBD**
Utility cost	Clean-accuracy drop caused by turning the defense on	**TBD**
Recovery rate	Share of poison-flipped answers the defense restores to correct	**TBD**

Sweep axes: `poison_count ∈ {1, 3, 5, 10}`, `poison_style ∈ {keyword, natural, authoritative}`, corpus size subsampled from the 125-article corpus. Known scoring ceiling: the substring match under-scores a correct-but-paraphrased answer; an LLM-judge fallback for ambiguous cases is planned for week 4, not yet built.

Future Work

This project is deliberately inference-only — the embedder and reader are both frozen, nothing is fine-tuned. A natural extension beyond this project's scope is a small **trained** poison-detector (a classifier over chunk-level features such as retrieval-score anomaly or stylistic markers), evaluated with its own precision/recall/F1 against the released poison set.